



CUDA API REFERENCE MANUAL

November 2011

Version 4.1



Contents

1	Deprecated List	1
2	Module Index	7
2.1	Modules	7
3	Data Structure Index	9
3.1	Data Structures	9
4	Module Documentation	11
4.1	CUDA Runtime API	11
4.1.1	Detailed Description	12
4.1.2	Define Documentation	12
4.1.2.1	CUDART_VERSION	12
4.2	Device Management	13
4.2.1	Detailed Description	14
4.2.2	Function Documentation	14
4.2.2.1	cudaChooseDevice	14
4.2.2.2	cudaDeviceGetByPCIBusId	14
4.2.2.3	cudaDeviceGetCacheConfig	15
4.2.2.4	cudaDeviceGetLimit	15
4.2.2.5	cudaDeviceGetPCIBusId	16
4.2.2.6	cudaDeviceReset	16
4.2.2.7	cudaDeviceSetCacheConfig	17
4.2.2.8	cudaDeviceSetLimit	17
4.2.2.9	cudaDeviceSynchronize	18
4.2.2.10	cudaGetDevice	18
4.2.2.11	cudaGetDeviceCount	19
4.2.2.12	cudaGetDeviceProperties	19
4.2.2.13	cudaIpcCloseMemHandle	22

4.2.2.14	cudaIpcGetEventHandle	23
4.2.2.15	cudaIpcGetMemHandle	23
4.2.2.16	cudaIpcOpenEventHandle	23
4.2.2.17	cudaIpcOpenMemHandle	24
4.2.2.18	cudaSetDevice	24
4.2.2.19	cudaSetDeviceFlags	25
4.2.2.20	cudaSetValidDevices	26
4.3	Thread Management [DEPRECATED]	27
4.3.1	Detailed Description	27
4.3.2	Function Documentation	27
4.3.2.1	cudaThreadExit	27
4.3.2.2	cudaThreadGetCacheConfig	28
4.3.2.3	cudaThreadGetLimit	28
4.3.2.4	cudaThreadSetCacheConfig	29
4.3.2.5	cudaThreadSetLimit	30
4.3.2.6	cudaThreadSynchronize	31
4.4	Error Handling	32
4.4.1	Detailed Description	32
4.4.2	Function Documentation	32
4.4.2.1	cudaGetErrorString	32
4.4.2.2	cudaGetLastError	32
4.4.2.3	cudaPeekAtLastError	33
4.5	Stream Management	34
4.5.1	Detailed Description	34
4.5.2	Function Documentation	34
4.5.2.1	cudaStreamCreate	34
4.5.2.2	cudaStreamDestroy	34
4.5.2.3	cudaStreamQuery	35
4.5.2.4	cudaStreamSynchronize	35
4.5.2.5	cudaStreamWaitEvent	36
4.6	Event Management	37
4.6.1	Detailed Description	37
4.6.2	Function Documentation	37
4.6.2.1	cudaEventCreate	37
4.6.2.2	cudaEventCreateWithFlags	38
4.6.2.3	cudaEventDestroy	38
4.6.2.4	cudaEventElapsedTime	39

4.6.2.5	cudaEventQuery	39
4.6.2.6	cudaEventRecord	40
4.6.2.7	cudaEventSynchronize	40
4.7	Execution Control	41
4.7.1	Detailed Description	41
4.7.2	Function Documentation	41
4.7.2.1	cudaConfigureCall	41
4.7.2.2	cudaFuncGetAttributes	42
4.7.2.3	cudaFuncSetCacheConfig	42
4.7.2.4	cudaLaunch	43
4.7.2.5	cudaSetDoubleForDevice	43
4.7.2.6	cudaSetDoubleForHost	44
4.7.2.7	cudaSetupArgument	44
4.8	Memory Management	45
4.8.1	Detailed Description	48
4.8.2	Function Documentation	48
4.8.2.1	cudaFree	48
4.8.2.2	cudaFreeArray	49
4.8.2.3	cudaFreeHost	49
4.8.2.4	cudaGetSymbolAddress	50
4.8.2.5	cudaGetSymbolSize	50
4.8.2.6	cudaHostAlloc	50
4.8.2.7	cudaHostGetDevicePointer	51
4.8.2.8	cudaHostGetFlags	52
4.8.2.9	cudaHostRegister	52
4.8.2.10	cudaHostUnregister	53
4.8.2.11	cudaMalloc	54
4.8.2.12	cudaMalloc3D	54
4.8.2.13	cudaMalloc3DArray	55
4.8.2.14	cudaMallocArray	56
4.8.2.15	cudaMallocHost	57
4.8.2.16	cudaMallocPitch	58
4.8.2.17	cudaMemcpy	58
4.8.2.18	cudaMemcpy2D	59
4.8.2.19	cudaMemcpy2DArrayToArray	60
4.8.2.20	cudaMemcpy2DAsync	60
4.8.2.21	cudaMemcpy2DFromArray	61

4.8.2.22	cudaMemcpy2DFromArrayAsync	62
4.8.2.23	cudaMemcpy2DToArray	63
4.8.2.24	cudaMemcpy2DToArrayAsync	64
4.8.2.25	cudaMemcpy3D	64
4.8.2.26	cudaMemcpy3DAsync	66
4.8.2.27	cudaMemcpy3DPeer	67
4.8.2.28	cudaMemcpy3DPeerAsync	68
4.8.2.29	cudaMemcpyArrayToArray	68
4.8.2.30	cudaMemcpyAsync	69
4.8.2.31	cudaMemcpyFromArray	69
4.8.2.32	cudaMemcpyFromArrayAsync	70
4.8.2.33	cudaMemcpyFromSymbol	71
4.8.2.34	cudaMemcpyFromSymbolAsync	71
4.8.2.35	cudaMemcpyPeer	72
4.8.2.36	cudaMemcpyPeerAsync	73
4.8.2.37	cudaMemcpyToArray	73
4.8.2.38	cudaMemcpyToArrayAsync	74
4.8.2.39	cudaMemcpyToSymbol	75
4.8.2.40	cudaMemcpyToSymbolAsync	75
4.8.2.41	cudaMemGetInfo	76
4.8.2.42	cudaMemset	76
4.8.2.43	cudaMemset2D	77
4.8.2.44	cudaMemset2DAsync	77
4.8.2.45	cudaMemset3D	78
4.8.2.46	cudaMemset3DAsync	78
4.8.2.47	cudaMemsetAsync	79
4.8.2.48	make_cudaExtent	79
4.8.2.49	make_cudaPitchedPtr	80
4.8.2.50	make_cudaPos	80
4.9	Unified Addressing	81
4.9.1	Detailed Description	81
4.9.2	Overview	81
4.9.3	Supported Platforms	81
4.9.4	Looking Up Information from Pointer Values	81
4.9.5	Automatic Mapping of Host Allocated Host Memory	81
4.9.6	Direct Access of	82
4.9.7	Exceptions, Disjoint Addressing	82

4.9.8	Function Documentation	82
4.9.8.1	cudaPointerGetAttributes	82
4.10	Peer Device Memory Access	84
4.10.1	Detailed Description	84
4.10.2	Function Documentation	84
4.10.2.1	cudaDeviceCanAccessPeer	84
4.10.2.2	cudaDeviceDisablePeerAccess	84
4.10.2.3	cudaDeviceEnablePeerAccess	85
4.11	OpenGL Interoperability	86
4.11.1	Detailed Description	86
4.11.2	Enumeration Type Documentation	86
4.11.2.1	cudaGLDeviceList	86
4.11.3	Function Documentation	87
4.11.3.1	cudaGLGetDevices	87
4.11.3.2	cudaGLSetGLDevice	87
4.11.3.3	cudaGraphicsGLRegisterBuffer	88
4.11.3.4	cudaGraphicsGLRegisterImage	88
4.11.3.5	cudaWGLGetDevice	89
4.12	Direct3D 9 Interoperability	91
4.12.1	Detailed Description	91
4.12.2	Enumeration Type Documentation	91
4.12.2.1	cudaD3D9DeviceList	91
4.12.3	Function Documentation	92
4.12.3.1	cudaD3D9GetDevice	92
4.12.3.2	cudaD3D9GetDevices	92
4.12.3.3	cudaD3D9GetDirect3DDevice	93
4.12.3.4	cudaD3D9SetDirect3DDevice	93
4.12.3.5	cudaGraphicsD3D9RegisterResource	94
4.13	Direct3D 10 Interoperability	96
4.13.1	Detailed Description	96
4.13.2	Enumeration Type Documentation	96
4.13.2.1	cudaD3D10DeviceList	96
4.13.3	Function Documentation	97
4.13.3.1	cudaD3D10GetDevice	97
4.13.3.2	cudaD3D10GetDevices	97
4.13.3.3	cudaD3D10GetDirect3DDevice	98
4.13.3.4	cudaD3D10SetDirect3DDevice	98

4.13.3.5	cudaGraphicsD3D10RegisterResource	99
4.14	Direct3D 11 Interoperability	101
4.14.1	Detailed Description	101
4.14.2	Enumeration Type Documentation	101
4.14.2.1	cudaD3D11DeviceList	101
4.14.3	Function Documentation	102
4.14.3.1	cudaD3D11GetDevice	102
4.14.3.2	cudaD3D11GetDevices	102
4.14.3.3	cudaD3D11GetDirect3DDevice	103
4.14.3.4	cudaD3D11SetDirect3DDevice	103
4.14.3.5	cudaGraphicsD3D11RegisterResource	104
4.15	VDPAU Interoperability	106
4.15.1	Detailed Description	106
4.15.2	Function Documentation	106
4.15.2.1	cudaGraphicsVDPAURegisterOutputSurface	106
4.15.2.2	cudaGraphicsVDPAURegisterVideoSurface	107
4.15.2.3	cudaVDPAUGetDevice	107
4.15.2.4	cudaVDPAUSetVDPAUDevice	108
4.16	Graphics Interoperability	109
4.16.1	Detailed Description	109
4.16.2	Function Documentation	109
4.16.2.1	cudaGraphicsMapResources	109
4.16.2.2	cudaGraphicsResourceGetMappedPointer	110
4.16.2.3	cudaGraphicsResourceSetMapFlags	110
4.16.2.4	cudaGraphicsSubResourceGetMappedArray	111
4.16.2.5	cudaGraphicsUnmapResources	112
4.16.2.6	cudaGraphicsUnregisterResource	112
4.17	Texture Reference Management	113
4.17.1	Detailed Description	113
4.17.2	Function Documentation	113
4.17.2.1	cudaBindTexture	113
4.17.2.2	cudaBindTexture2D	114
4.17.2.3	cudaBindTextureToArray	115
4.17.2.4	cudaCreateChannelDesc	115
4.17.2.5	cudaGetChannelDesc	116
4.17.2.6	cudaGetTextureAlignmentOffset	116
4.17.2.7	cudaGetTextureReference	117

4.17.2.8	cudaUnbindTexture	117
4.18	Surface Reference Management	118
4.18.1	Detailed Description	118
4.18.2	Function Documentation	118
4.18.2.1	cudaBindSurfaceToArray	118
4.18.2.2	cudaGetSurfaceReference	118
4.19	Version Management	120
4.19.1	Function Documentation	120
4.19.1.1	cudaDriverGetVersion	120
4.19.1.2	cudaRuntimeGetVersion	120
4.20	C++ API Routines	121
4.20.1	Detailed Description	122
4.20.2	Function Documentation	122
4.20.2.1	cudaBindSurfaceToArray	122
4.20.2.2	cudaBindSurfaceToArray	123
4.20.2.3	cudaBindTexture	123
4.20.2.4	cudaBindTexture	124
4.20.2.5	cudaBindTexture2D	125
4.20.2.6	cudaBindTexture2D	125
4.20.2.7	cudaBindTextureToArray	126
4.20.2.8	cudaBindTextureToArray	127
4.20.2.9	cudaCreateChannelDesc	127
4.20.2.10	cudaEventCreate	128
4.20.2.11	cudaFuncGetAttributes	128
4.20.2.12	cudaFuncSetCacheConfig	129
4.20.2.13	cudaGetSymbolAddress	129
4.20.2.14	cudaGetSymbolSize	130
4.20.2.15	cudaGetTextureAlignmentOffset	130
4.20.2.16	cudaLaunch	131
4.20.2.17	cudaMallocHost	131
4.20.2.18	cudaSetupArgument	132
4.20.2.19	cudaUnbindTexture	133
4.21	Interactions with the CUDA Driver API	134
4.21.1	Primary Contexts	134
4.21.2	Initialization and Tear-Down	134
4.21.3	Context Interoperability	134
4.21.4	Interactions between CUstream and cudaStream_t	135

4.21.5	Interactions between CUevent and cudaEvent_t	135
4.21.6	Interactions between CUarray and struct cudaArray *	135
4.21.7	Interactions between CUgraphicsResource and cudaGraphicsResource_t	135
4.22	Profiler Control	136
4.22.1	Detailed Description	136
4.22.2	Function Documentation	136
4.22.2.1	cudaProfilerInitialize	136
4.22.2.2	cudaProfilerStart	137
4.22.2.3	cudaProfilerStop	137
4.23	Direct3D 9 Interoperability [DEPRECATED]	138
4.23.1	Detailed Description	139
4.23.2	Enumeration Type Documentation	139
4.23.2.1	cudaD3D9MapFlags	139
4.23.2.2	cudaD3D9RegisterFlags	139
4.23.3	Function Documentation	139
4.23.3.1	cudaD3D9MapResources	139
4.23.3.2	cudaD3D9RegisterResource	140
4.23.3.3	cudaD3D9ResourceGetMappedArray	141
4.23.3.4	cudaD3D9ResourceGetMappedPitch	142
4.23.3.5	cudaD3D9ResourceGetMappedPointer	142
4.23.3.6	cudaD3D9ResourceGetMappedSize	143
4.23.3.7	cudaD3D9ResourceGetSurfaceDimensions	144
4.23.3.8	cudaD3D9ResourceSetMapFlags	145
4.23.3.9	cudaD3D9UnmapResources	145
4.23.3.10	cudaD3D9UnregisterResource	146
4.24	Direct3D 10 Interoperability [DEPRECATED]	147
4.24.1	Detailed Description	148
4.24.2	Enumeration Type Documentation	148
4.24.2.1	cudaD3D10MapFlags	148
4.24.2.2	cudaD3D10RegisterFlags	148
4.24.3	Function Documentation	148
4.24.3.1	cudaD3D10MapResources	148
4.24.3.2	cudaD3D10RegisterResource	149
4.24.3.3	cudaD3D10ResourceGetMappedArray	150
4.24.3.4	cudaD3D10ResourceGetMappedPitch	151
4.24.3.5	cudaD3D10ResourceGetMappedPointer	151
4.24.3.6	cudaD3D10ResourceGetMappedSize	152

4.24.3.7	cudaD3D10ResourceGetSurfaceDimensions	153
4.24.3.8	cudaD3D10ResourceSetMapFlags	153
4.24.3.9	cudaD3D10UnmapResources	154
4.24.3.10	cudaD3D10UnregisterResource	155
4.25	OpenGL Interoperability [DEPRECATED]	156
4.25.1	Detailed Description	156
4.25.2	Enumeration Type Documentation	156
4.25.2.1	cudaGLMapFlags	156
4.25.3	Function Documentation	157
4.25.3.1	cudaGLMapBufferObject	157
4.25.3.2	cudaGLMapBufferObjectAsync	157
4.25.3.3	cudaGLRegisterBufferObject	158
4.25.3.4	cudaGLSetBufferObjectMapFlags	158
4.25.3.5	cudaGLUnmapBufferObject	159
4.25.3.6	cudaGLUnmapBufferObjectAsync	159
4.25.3.7	cudaGLUnregisterBufferObject	160
4.26	Data types used by CUDA Runtime	161
4.26.1	Define Documentation	165
4.26.1.1	CUDA_IPC_HANDLE_SIZE	165
4.26.1.2	cudaArrayCubemap	165
4.26.1.3	cudaArrayDefault	165
4.26.1.4	cudaArrayLayered	165
4.26.1.5	cudaArraySurfaceLoadStore	165
4.26.1.6	cudaArrayTextureGather	166
4.26.1.7	cudaDeviceBlockingSync	166
4.26.1.8	cudaDeviceLmemResizeToMax	166
4.26.1.9	cudaDeviceMapHost	166
4.26.1.10	cudaDeviceMask	166
4.26.1.11	cudaDevicePropDontCare	166
4.26.1.12	cudaDeviceScheduleAuto	166
4.26.1.13	cudaDeviceScheduleBlockingSync	166
4.26.1.14	cudaDeviceScheduleMask	166
4.26.1.15	cudaDeviceScheduleSpin	166
4.26.1.16	cudaDeviceScheduleYield	167
4.26.1.17	cudaEventBlockingSync	167
4.26.1.18	cudaEventDefault	167
4.26.1.19	cudaEventDisableTiming	167

4.26.1.20	<code>cudaEventInterprocess</code>	167
4.26.1.21	<code>cudaHostAllocDefault</code>	167
4.26.1.22	<code>cudaHostAllocMapped</code>	167
4.26.1.23	<code>cudaHostAllocPortable</code>	167
4.26.1.24	<code>cudaHostAllocWriteCombined</code>	167
4.26.1.25	<code>cudaHostRegisterDefault</code>	167
4.26.1.26	<code>cudaHostRegisterMapped</code>	167
4.26.1.27	<code>cudaHostRegisterPortable</code>	167
4.26.1.28	<code>cudaPeerAccessDefault</code>	168
4.26.2	Typedef Documentation	168
4.26.2.1	<code>cudaError_t</code>	168
4.26.2.2	<code>cudaEvent_t</code>	168
4.26.2.3	<code>cudaGraphicsResource_t</code>	168
4.26.2.4	<code>cudaIpcEventHandle_t</code>	168
4.26.2.5	<code>cudaOutputMode_t</code>	168
4.26.2.6	<code>cudaStream_t</code>	168
4.26.2.7	<code>cudaUUID_t</code>	168
4.26.3	Enumeration Type Documentation	168
4.26.3.1	<code>cudaChannelFormatKind</code>	168
4.26.3.2	<code>cudaComputeMode</code>	169
4.26.3.3	<code>cudaError</code>	169
4.26.3.4	<code>cudaFuncCache</code>	173
4.26.3.5	<code>cudaGraphicsCubeFace</code>	173
4.26.3.6	<code>cudaGraphicsMapFlags</code>	173
4.26.3.7	<code>cudaGraphicsRegisterFlags</code>	173
4.26.3.8	<code>cudaLimit</code>	174
4.26.3.9	<code>cudaMemcpyKind</code>	174
4.26.3.10	<code>cudaMemoryType</code>	174
4.26.3.11	<code>cudaOutputMode</code>	174
4.26.3.12	<code>cudaSurfaceBoundaryMode</code>	174
4.26.3.13	<code>cudaSurfaceFormatMode</code>	175
4.26.3.14	<code>cudaTextureAddressMode</code>	175
4.26.3.15	<code>cudaTextureFilterMode</code>	175
4.26.3.16	<code>cudaTextureReadMode</code>	175
4.27	CUDA Driver API	176
4.27.1	Detailed Description	176
4.28	Data types used by CUDA driver	177

4.28.1	Define Documentation	183
4.28.1.1	CU_IPC_HANDLE_SIZE	183
4.28.1.2	CU_LAUNCH_PARAM_BUFFER_POINTER	184
4.28.1.3	CU_LAUNCH_PARAM_BUFFER_SIZE	184
4.28.1.4	CU_LAUNCH_PARAM_END	184
4.28.1.5	CU_MEMHOSTALLOC_DEVICEMAP	184
4.28.1.6	CU_MEMHOSTALLOC_PORTABLE	184
4.28.1.7	CU_MEMHOSTALLOC_WRITECOMBINED	184
4.28.1.8	CU_MEMHOSTREGISTER_DEVICEMAP	184
4.28.1.9	CU_MEMHOSTREGISTER_PORTABLE	184
4.28.1.10	CU_PARAM_TR_DEFAULT	184
4.28.1.11	CU_TRSA_OVERRIDE_FORMAT	184
4.28.1.12	CU_TRSF_NORMALIZED_COORDINATES	185
4.28.1.13	CU_TRSF_READ_AS_INTEGER	185
4.28.1.14	CU_TRSF_SRGB	185
4.28.1.15	CUDA_ARRAY3D_2DARRAY	185
4.28.1.16	CUDA_ARRAY3D_CUBEMAP	185
4.28.1.17	CUDA_ARRAY3D_LAYERED	185
4.28.1.18	CUDA_ARRAY3D_SURFACE_LDST	185
4.28.1.19	CUDA_ARRAY3D_TEXTURE_GATHER	185
4.28.1.20	CUDA_VERSION	185
4.28.2	Typedef Documentation	185
4.28.2.1	CUaddress_mode	185
4.28.2.2	CUarray	186
4.28.2.3	CUarray_cubemap_face	186
4.28.2.4	CUarray_format	186
4.28.2.5	CUcomputemode	186
4.28.2.6	CUcontext	186
4.28.2.7	CUctx_flags	186
4.28.2.8	CUDA_ARRAY3D_DESCRIPTOR	186
4.28.2.9	CUDA_ARRAY_DESCRIPTOR	186
4.28.2.10	CUDA_MEMCPY2D	186
4.28.2.11	CUDA_MEMCPY3D	186
4.28.2.12	CUDA_MEMCPY3D_PEER	186
4.28.2.13	CUdevice	186
4.28.2.14	CUdevice_attribute	187
4.28.2.15	CUdeviceptr	187

4.28.2.16	CUdevprop	187
4.28.2.17	CUevent	187
4.28.2.18	CUevent_flags	187
4.28.2.19	CUfilter_mode	187
4.28.2.20	CUfunc_cache	187
4.28.2.21	CUfunction	187
4.28.2.22	CUfunction_attribute	187
4.28.2.23	CUgraphicsMapResourceFlags	187
4.28.2.24	CUgraphicsRegisterFlags	187
4.28.2.25	CUgraphicsResource	187
4.28.2.26	CUjit_fallback	188
4.28.2.27	CUjit_option	188
4.28.2.28	CUjit_target	188
4.28.2.29	CUlimit	188
4.28.2.30	CUmemorytype	188
4.28.2.31	CUmodule	188
4.28.2.32	CUpointer_attribute	188
4.28.2.33	CUresult	188
4.28.2.34	CUstream	188
4.28.2.35	CUsurfref	188
4.28.2.36	CUtexref	188
4.28.3	Enumeration Type Documentation	189
4.28.3.1	CUaddress_mode_enum	189
4.28.3.2	CUarray_cubemap_face_enum	189
4.28.3.3	CUarray_format_enum	189
4.28.3.4	CUcomputemode_enum	189
4.28.3.5	CUctx_flags_enum	190
4.28.3.6	cudaError_enum	190
4.28.3.7	CUdevice_attribute_enum	192
4.28.3.8	CUevent_flags_enum	195
4.28.3.9	CUfilter_mode_enum	195
4.28.3.10	CUfunc_cache_enum	196
4.28.3.11	CUfunction_attribute_enum	196
4.28.3.12	CUgraphicsMapResourceFlags_enum	196
4.28.3.13	CUgraphicsRegisterFlags_enum	196
4.28.3.14	CUjit_fallback_enum	197
4.28.3.15	CUjit_option_enum	197

4.28.3.16 CUjit_target_enum	198
4.28.3.17 CUlimit_enum	198
4.28.3.18 CUmemorytype_enum	198
4.28.3.19 CUpointer_attribute_enum	198
4.29 Initialization	200
4.29.1 Detailed Description	200
4.29.2 Function Documentation	200
4.29.2.1 cuInit	200
4.30 Version Management	201
4.30.1 Detailed Description	201
4.30.2 Function Documentation	201
4.30.2.1 cuDriverGetVersion	201
4.31 Device Management	202
4.31.1 Detailed Description	202
4.31.2 Function Documentation	202
4.31.2.1 cuDeviceComputeCapability	202
4.31.2.2 cuDeviceGet	203
4.31.2.3 cuDeviceGetAttribute	203
4.31.2.4 cuDeviceGetCount	207
4.31.2.5 cuDeviceGetName	207
4.31.2.6 cuDeviceGetProperties	207
4.31.2.7 cuDeviceTotalMem	209
4.32 Context Management	210
4.32.1 Detailed Description	211
4.32.2 Function Documentation	211
4.32.2.1 cuCtxCreate	211
4.32.2.2 cuCtxDestroy	212
4.32.2.3 cuCtxGetApiVersion	212
4.32.2.4 cuCtxGetCacheConfig	213
4.32.2.5 cuCtxGetCurrent	214
4.32.2.6 cuCtxGetDevice	214
4.32.2.7 cuCtxGetLimit	214
4.32.2.8 cuCtxPopCurrent	215
4.32.2.9 cuCtxPushCurrent	215
4.32.2.10 cuCtxSetCacheConfig	216
4.32.2.11 cuCtxSetCurrent	216
4.32.2.12 cuCtxSetLimit	217

4.32.2.13	cuCtxSynchronize	218
4.33	Context Management [DEPRECATED]	219
4.33.1	Detailed Description	219
4.33.2	Function Documentation	219
4.33.2.1	cuCtxAttach	219
4.33.2.2	cuCtxDetach	220
4.34	Module Management	221
4.34.1	Detailed Description	221
4.34.2	Function Documentation	221
4.34.2.1	cuModuleGetFunction	221
4.34.2.2	cuModuleGetGlobal	222
4.34.2.3	cuModuleGetSurfRef	222
4.34.2.4	cuModuleGetTexRef	223
4.34.2.5	cuModuleLoad	223
4.34.2.6	cuModuleLoadData	224
4.34.2.7	cuModuleLoadDataEx	224
4.34.2.8	cuModuleLoadFatBinary	226
4.34.2.9	cuModuleUnload	226
4.35	Memory Management	228
4.35.1	Detailed Description	231
4.35.2	Function Documentation	232
4.35.2.1	cuArray3DCreate	232
4.35.2.2	cuArray3DGetDescriptor	234
4.35.2.3	cuArrayCreate	235
4.35.2.4	cuArrayDestroy	237
4.35.2.5	cuArrayGetDescriptor	237
4.35.2.6	cuDeviceGetByPCIBusId	238
4.35.2.7	cuDeviceGetPCIBusId	238
4.35.2.8	cuIpcCloseMemHandle	238
4.35.2.9	cuIpcGetEventHandle	239
4.35.2.10	cuIpcGetMemHandle	239
4.35.2.11	cuIpcOpenEventHandle	240
4.35.2.12	cuIpcOpenMemHandle	240
4.35.2.13	cuMemAlloc	241
4.35.2.14	cuMemAllocHost	241
4.35.2.15	cuMemAllocPitch	242
4.35.2.16	cuMemcpy	243

4.35.2.17 cuMemcpy2D	243
4.35.2.18 cuMemcpy2DAsync	246
4.35.2.19 cuMemcpy2DUnaligned	248
4.35.2.20 cuMemcpy3D	251
4.35.2.21 cuMemcpy3DAsync	253
4.35.2.22 cuMemcpy3DPeer	256
4.35.2.23 cuMemcpy3DPeerAsync	256
4.35.2.24 cuMemcpyAsync	256
4.35.2.25 cuMemcpyAtoA	257
4.35.2.26 cuMemcpyAtoD	258
4.35.2.27 cuMemcpyAtoH	258
4.35.2.28 cuMemcpyAtoHAsync	259
4.35.2.29 cuMemcpyDtoA	260
4.35.2.30 cuMemcpyDtoD	260
4.35.2.31 cuMemcpyDtoDAsync	261
4.35.2.32 cuMemcpyDtoH	262
4.35.2.33 cuMemcpyDtoHAsync	262
4.35.2.34 cuMemcpyHtoA	263
4.35.2.35 cuMemcpyHtoAAsync	263
4.35.2.36 cuMemcpyHtoD	264
4.35.2.37 cuMemcpyHtoDAsync	265
4.35.2.38 cuMemcpyPeer	265
4.35.2.39 cuMemcpyPeerAsync	266
4.35.2.40 cuMemFree	266
4.35.2.41 cuMemFreeHost	267
4.35.2.42 cuMemGetAddressRange	267
4.35.2.43 cuMemGetInfo	268
4.35.2.44 cuMemHostAlloc	269
4.35.2.45 cuMemHostGetDevicePointer	270
4.35.2.46 cuMemHostGetFlags	270
4.35.2.47 cuMemHostRegister	271
4.35.2.48 cuMemHostUnregister	272
4.35.2.49 cuMemsetD16	272
4.35.2.50 cuMemsetD16Async	273
4.35.2.51 cuMemsetD2D16	273
4.35.2.52 cuMemsetD2D16Async	274
4.35.2.53 cuMemsetD2D32	275

4.35.2.54	cuMemsetD2D32Async	275
4.35.2.55	cuMemsetD2D8	276
4.35.2.56	cuMemsetD2D8Async	277
4.35.2.57	cuMemsetD32	278
4.35.2.58	cuMemsetD32Async	278
4.35.2.59	cuMemsetD8	279
4.35.2.60	cuMemsetD8Async	279
4.36	Unified Addressing	281
4.36.1	Detailed Description	281
4.36.2	Overview	281
4.36.3	Supported Platforms	281
4.36.4	Looking Up Information from Pointer Values	281
4.36.5	Automatic Mapping of Host Allocated Host Memory	281
4.36.6	Automatic Registration of Peer Memory	282
4.36.7	Exceptions, Disjoint Addressing	282
4.36.8	Function Documentation	282
4.36.8.1	cuPointerGetAttribute	282
4.37	Stream Management	285
4.37.1	Detailed Description	285
4.37.2	Function Documentation	285
4.37.2.1	cuStreamCreate	285
4.37.2.2	cuStreamDestroy	286
4.37.2.3	cuStreamQuery	286
4.37.2.4	cuStreamSynchronize	286
4.37.2.5	cuStreamWaitEvent	287
4.38	Event Management	288
4.38.1	Detailed Description	288
4.38.2	Function Documentation	288
4.38.2.1	cuEventCreate	288
4.38.2.2	cuEventDestroy	289
4.38.2.3	cuEventElapsedTime	289
4.38.2.4	cuEventQuery	290
4.38.2.5	cuEventRecord	290
4.38.2.6	cuEventSynchronize	291
4.39	Execution Control	292
4.39.1	Detailed Description	292
4.39.2	Function Documentation	292

4.39.2.1	cuFuncGetAttribute	292
4.39.2.2	cuFuncSetCacheConfig	293
4.39.2.3	cuLaunchKernel	294
4.40	Execution Control [DEPRECATED]	296
4.40.1	Detailed Description	296
4.40.2	Function Documentation	296
4.40.2.1	cuFuncSetBlockShape	296
4.40.2.2	cuFuncSetSharedSize	297
4.40.2.3	cuLaunch	297
4.40.2.4	cuLaunchGrid	298
4.40.2.5	cuLaunchGridAsync	299
4.40.2.6	cuParamSetf	299
4.40.2.7	cuParamSeti	300
4.40.2.8	cuParamSetSize	300
4.40.2.9	cuParamSetTexRef	301
4.40.2.10	cuParamSetv	301
4.41	Texture Reference Management	303
4.41.1	Detailed Description	304
4.41.2	Function Documentation	304
4.41.2.1	cuTexRefGetAddress	304
4.41.2.2	cuTexRefGetAddressMode	304
4.41.2.3	cuTexRefGetArray	305
4.41.2.4	cuTexRefGetFilterMode	305
4.41.2.5	cuTexRefGetFlags	305
4.41.2.6	cuTexRefGetFormat	306
4.41.2.7	cuTexRefSetAddress	306
4.41.2.8	cuTexRefSetAddress2D	307
4.41.2.9	cuTexRefSetAddressMode	307
4.41.2.10	cuTexRefSetArray	308
4.41.2.11	cuTexRefSetFilterMode	309
4.41.2.12	cuTexRefSetFlags	309
4.41.2.13	cuTexRefSetFormat	310
4.42	Texture Reference Management [DEPRECATED]	311
4.42.1	Detailed Description	311
4.42.2	Function Documentation	311
4.42.2.1	cuTexRefCreate	311
4.42.2.2	cuTexRefDestroy	311

4.43	Surface Reference Management	313
4.43.1	Detailed Description	313
4.43.2	Function Documentation	313
4.43.2.1	cuSurfRefGetArray	313
4.43.2.2	cuSurfRefSetArray	313
4.44	Peer Context Memory Access	315
4.44.1	Detailed Description	315
4.44.2	Function Documentation	315
4.44.2.1	cuCtxDisablePeerAccess	315
4.44.2.2	cuCtxEnablePeerAccess	315
4.44.2.3	cuDeviceCanAccessPeer	316
4.45	Graphics Interoperability	317
4.45.1	Detailed Description	317
4.45.2	Function Documentation	317
4.45.2.1	cuGraphicsMapResources	317
4.45.2.2	cuGraphicsResourceGetMappedPointer	318
4.45.2.3	cuGraphicsResourceSetMapFlags	318
4.45.2.4	cuGraphicsSubResourceGetMappedArray	319
4.45.2.5	cuGraphicsUnmapResources	320
4.45.2.6	cuGraphicsUnregisterResource	320
4.46	Profiler Control	322
4.46.1	Detailed Description	322
4.46.2	Function Documentation	322
4.46.2.1	cuProfilerInitialize	322
4.46.2.2	cuProfilerStart	323
4.46.2.3	cuProfilerStop	323
4.47	OpenGL Interoperability	324
4.47.1	Detailed Description	324
4.47.2	Typedef Documentation	324
4.47.2.1	CUGLDeviceList	324
4.47.3	Enumeration Type Documentation	325
4.47.3.1	CUGLDeviceList_enum	325
4.47.4	Function Documentation	325
4.47.4.1	cuGLCtxCreate	325
4.47.4.2	cuGLGetDevices	325
4.47.4.3	cuGraphicsGLRegisterBuffer	326
4.47.4.4	cuGraphicsGLRegisterImage	327

4.47.4.5	cuWGLGetDevice	328
4.48	OpenGL Interoperability [DEPRECATED]	329
4.48.1	Detailed Description	329
4.48.2	Typedef Documentation	329
4.48.2.1	CUGLmap_flags	329
4.48.3	Enumeration Type Documentation	330
4.48.3.1	CUGLmap_flags_enum	330
4.48.4	Function Documentation	330
4.48.4.1	cuGLInit	330
4.48.4.2	cuGLMapBufferObject	330
4.48.4.3	cuGLMapBufferObjectAsync	331
4.48.4.4	cuGLRegisterBufferObject	331
4.48.4.5	cuGLSetBufferObjectMapFlags	332
4.48.4.6	cuGLUnmapBufferObject	333
4.48.4.7	cuGLUnmapBufferObjectAsync	333
4.48.4.8	cuGLUnregisterBufferObject	334
4.49	Direct3D 9 Interoperability	335
4.49.1	Detailed Description	335
4.49.2	Typedef Documentation	336
4.49.2.1	CUD3d9DeviceList	336
4.49.3	Enumeration Type Documentation	336
4.49.3.1	CUD3d9DeviceList_enum	336
4.49.4	Function Documentation	336
4.49.4.1	cuD3D9CtxCreate	336
4.49.4.2	cuD3D9CtxCreateOnDevice	337
4.49.4.3	cuD3D9GetDevice	337
4.49.4.4	cuD3D9GetDevices	338
4.49.4.5	cuD3D9GetDirect3DDevice	338
4.49.4.6	cuGraphicsD3D9RegisterResource	339
4.50	Direct3D 9 Interoperability [DEPRECATED]	341
4.50.1	Detailed Description	342
4.50.2	Typedef Documentation	342
4.50.2.1	CUD3d9map_flags	342
4.50.2.2	CUD3d9register_flags	342
4.50.3	Enumeration Type Documentation	342
4.50.3.1	CUD3d9map_flags_enum	342
4.50.3.2	CUD3d9register_flags_enum	342

4.50.4	Function Documentation	342
4.50.4.1	cuD3D9MapResources	342
4.50.4.2	cuD3D9RegisterResource	343
4.50.4.3	cuD3D9ResourceGetMappedArray	344
4.50.4.4	cuD3D9ResourceGetMappedPitch	345
4.50.4.5	cuD3D9ResourceGetMappedPointer	346
4.50.4.6	cuD3D9ResourceGetMappedSize	346
4.50.4.7	cuD3D9ResourceGetSurfaceDimensions	347
4.50.4.8	cuD3D9ResourceSetMapFlags	348
4.50.4.9	cuD3D9UnmapResources	349
4.50.4.10	cuD3D9UnregisterResource	349
4.51	Direct3D 10 Interoperability	350
4.51.1	Detailed Description	350
4.51.2	Typedef Documentation	351
4.51.2.1	CuD3d10DeviceList	351
4.51.3	Enumeration Type Documentation	351
4.51.3.1	CuD3d10DeviceList_enum	351
4.51.4	Function Documentation	351
4.51.4.1	cuD3D10CtxCreate	351
4.51.4.2	cuD3D10CtxCreateOnDevice	352
4.51.4.3	cuD3D10GetDevice	352
4.51.4.4	cuD3D10GetDevices	353
4.51.4.5	cuD3D10GetDirect3DDevice	353
4.51.4.6	cuGraphicsD3D10RegisterResource	354
4.52	Direct3D 10 Interoperability [DEPRECATED]	356
4.52.1	Detailed Description	357
4.52.2	Typedef Documentation	357
4.52.2.1	CUD3D10map_flags	357
4.52.2.2	CUD3D10register_flags	357
4.52.3	Enumeration Type Documentation	357
4.52.3.1	CUD3D10map_flags_enum	357
4.52.3.2	CUD3D10register_flags_enum	357
4.52.4	Function Documentation	357
4.52.4.1	cuD3D10MapResources	357
4.52.4.2	cuD3D10RegisterResource	358
4.52.4.3	cuD3D10ResourceGetMappedArray	359
4.52.4.4	cuD3D10ResourceGetMappedPitch	360

4.52.4.5	cuD3D10ResourceGetMappedPointer	361
4.52.4.6	cuD3D10ResourceGetMappedSize	361
4.52.4.7	cuD3D10ResourceGetSurfaceDimensions	362
4.52.4.8	cuD3D10ResourceSetMapFlags	363
4.52.4.9	cuD3D10UnmapResources	363
4.52.4.10	cuD3D10UnregisterResource	364
4.53	Direct3D 11 Interoperability	365
4.53.1	Detailed Description	365
4.53.2	Typedef Documentation	365
4.53.2.1	CUd3d11DeviceList	365
4.53.3	Enumeration Type Documentation	366
4.53.3.1	CUd3d11DeviceList_enum	366
4.53.4	Function Documentation	366
4.53.4.1	cuD3D11CtxCreate	366
4.53.4.2	cuD3D11CtxCreateOnDevice	366
4.53.4.3	cuD3D11GetDevice	367
4.53.4.4	cuD3D11GetDevices	368
4.53.4.5	cuD3D11GetDirect3DDevice	368
4.53.4.6	cuGraphicsD3D11RegisterResource	369
4.54	VDPAU Interoperability	371
4.54.1	Detailed Description	371
4.54.2	Function Documentation	371
4.54.2.1	cuGraphicsVDPAURegisterOutputSurface	371
4.54.2.2	cuGraphicsVDPAURegisterVideoSurface	372
4.54.2.3	cuVDPAUCtxCreate	373
4.54.2.4	cuVDPAUGetDevice	373
4.55	Mathematical Functions	375
4.55.1	Detailed Description	375
4.56	Single Precision Mathematical Functions	376
4.56.1	Detailed Description	380
4.56.2	Function Documentation	380
4.56.2.1	acosf	380
4.56.2.2	acoshf	381
4.56.2.3	asinf	381
4.56.2.4	asinhf	381
4.56.2.5	atan2f	381
4.56.2.6	atanf	382

4.56.2.7	atanhf	382
4.56.2.8	cbrtf	382
4.56.2.9	ceilf	382
4.56.2.10	copysignf	383
4.56.2.11	cosf	383
4.56.2.12	coshf	383
4.56.2.13	cospif	383
4.56.2.14	erfcf	384
4.56.2.15	erfcinvf	384
4.56.2.16	erfcxf	384
4.56.2.17	erff	384
4.56.2.18	erfinvf	385
4.56.2.19	exp10f	385
4.56.2.20	exp2f	385
4.56.2.21	expf	385
4.56.2.22	expm1f	386
4.56.2.23	fabsf	386
4.56.2.24	fdimf	386
4.56.2.25	fdividf	386
4.56.2.26	floorf	387
4.56.2.27	fmaf	387
4.56.2.28	fmaxf	387
4.56.2.29	fminf	388
4.56.2.30	fmodf	388
4.56.2.31	frexpf	388
4.56.2.32	hypotf	389
4.56.2.33	ilogbf	389
4.56.2.34	isfinite	389
4.56.2.35	isinf	389
4.56.2.36	isnan	389
4.56.2.37	j0f	390
4.56.2.38	j1f	390
4.56.2.39	jnf	390
4.56.2.40	ldexpf	390
4.56.2.41	lgammaf	391
4.56.2.42	llrintf	391
4.56.2.43	llroundf	391

4.56.2.44	log10f	391
4.56.2.45	log1pf	392
4.56.2.46	log2f	392
4.56.2.47	logbf	392
4.56.2.48	logf	393
4.56.2.49	lrintf	393
4.56.2.50	lroundf	393
4.56.2.51	modff	393
4.56.2.52	nanf	394
4.56.2.53	nearbyintf	394
4.56.2.54	nextafterf	394
4.56.2.55	powf	394
4.56.2.56	rcbrtf	395
4.56.2.57	remainderf	395
4.56.2.58	remquof	396
4.56.2.59	rintf	396
4.56.2.60	roundf	396
4.56.2.61	rsqrtf	396
4.56.2.62	scalblnf	397
4.56.2.63	scalbnf	397
4.56.2.64	signbit	397
4.56.2.65	sincosf	397
4.56.2.66	sinf	398
4.56.2.67	sinhf	398
4.56.2.68	sinpif	398
4.56.2.69	sqrtf	398
4.56.2.70	tanf	399
4.56.2.71	tanhf	399
4.56.2.72	tgammaf	399
4.56.2.73	truncf	399
4.56.2.74	y0f	400
4.56.2.75	y1f	400
4.56.2.76	ynf	400
4.57	Double Precision Mathematical Functions	401
4.57.1	Detailed Description	405
4.57.2	Function Documentation	405
4.57.2.1	acos	405

4.57.2.2	acosh	406
4.57.2.3	asin	406
4.57.2.4	asinh	406
4.57.2.5	atan	406
4.57.2.6	atan2	407
4.57.2.7	atanh	407
4.57.2.8	cbrt	407
4.57.2.9	ceil	407
4.57.2.10	copysign	408
4.57.2.11	cos	408
4.57.2.12	cosh	408
4.57.2.13	cospi	408
4.57.2.14	erf	409
4.57.2.15	erfc	409
4.57.2.16	erfcinv	409
4.57.2.17	erfcx	409
4.57.2.18	erfinv	410
4.57.2.19	exp	410
4.57.2.20	exp10	410
4.57.2.21	exp2	410
4.57.2.22	expm1	411
4.57.2.23	fabs	411
4.57.2.24	fdim	411
4.57.2.25	floor	411
4.57.2.26	fma	412
4.57.2.27	fmax	412
4.57.2.28	fmin	412
4.57.2.29	fmod	413
4.57.2.30	frexp	413
4.57.2.31	hypot	413
4.57.2.32	ilogb	414
4.57.2.33	isfinite	414
4.57.2.34	isinf	414
4.57.2.35	isnan	414
4.57.2.36	j0	414
4.57.2.37	j1	415
4.57.2.38	jn	415

4.57.2.39 ldexp	415
4.57.2.40 lgamma	415
4.57.2.41 llrint	416
4.57.2.42 llround	416
4.57.2.43 log	416
4.57.2.44 log10	417
4.57.2.45 loglp	417
4.57.2.46 log2	417
4.57.2.47 logb	418
4.57.2.48 lrint	418
4.57.2.49 lround	418
4.57.2.50 modf	418
4.57.2.51 nan	419
4.57.2.52 nearbyint	419
4.57.2.53 nextafter	419
4.57.2.54 pow	419
4.57.2.55 rcbrt	420
4.57.2.56 remainder	420
4.57.2.57 remquo	421
4.57.2.58 rint	421
4.57.2.59 round	421
4.57.2.60 rsqrt	421
4.57.2.61 scalbln	422
4.57.2.62 scalbn	422
4.57.2.63 signbit	422
4.57.2.64 sin	422
4.57.2.65 sincos	423
4.57.2.66 sinh	423
4.57.2.67 sinpi	423
4.57.2.68 sqrt	423
4.57.2.69 tan	424
4.57.2.70 tanh	424
4.57.2.71 tgamma	424
4.57.2.72 trunc	424
4.57.2.73 y0	425
4.57.2.74 y1	425
4.57.2.75 yn	425

4.58 Single Precision Intrinsics	426
4.58.1 Detailed Description	428
4.58.2 Function Documentation	428
4.58.2.1 __cosf	428
4.58.2.2 __exp10f	428
4.58.2.3 __expf	428
4.58.2.4 __fadd_rd	429
4.58.2.5 __fadd_rn	429
4.58.2.6 __fadd_ru	429
4.58.2.7 __fadd_rz	430
4.58.2.8 __fdiv_rd	430
4.58.2.9 __fdiv_rn	430
4.58.2.10 __fdiv_ru	430
4.58.2.11 __fdiv_rz	431
4.58.2.12 __fdividef	431
4.58.2.13 __fmaf_rd	431
4.58.2.14 __fmaf_rn	431
4.58.2.15 __fmaf_ru	432
4.58.2.16 __fmaf_rz	432
4.58.2.17 __fmul_rd	432
4.58.2.18 __fmul_rn	433
4.58.2.19 __fmul_ru	433
4.58.2.20 __fmul_rz	433
4.58.2.21 __frcp_rd	433
4.58.2.22 __frcp_rn	434
4.58.2.23 __frcp_ru	434
4.58.2.24 __frcp_rz	434
4.58.2.25 __fsqrt_rd	434
4.58.2.26 __fsqrt_rn	435
4.58.2.27 __fsqrt_ru	435
4.58.2.28 __fsqrt_rz	435
4.58.2.29 __log10f	435
4.58.2.30 __log2f	436
4.58.2.31 __logf	436
4.58.2.32 __powf	436
4.58.2.33 __saturatef	436
4.58.2.34 __sincosf	437

4.58.2.35	<code>__sinf</code>	437
4.58.2.36	<code>__tanf</code>	437
4.59	Double Precision Intrinsics	438
4.59.1	Detailed Description	439
4.59.2	Function Documentation	439
4.59.2.1	<code>__dadd_rd</code>	439
4.59.2.2	<code>__dadd_rn</code>	440
4.59.2.3	<code>__dadd_ru</code>	440
4.59.2.4	<code>__dadd_rz</code>	440
4.59.2.5	<code>__ddiv_rd</code>	440
4.59.2.6	<code>__ddiv_rn</code>	441
4.59.2.7	<code>__ddiv_ru</code>	441
4.59.2.8	<code>__ddiv_rz</code>	441
4.59.2.9	<code>__dmul_rd</code>	441
4.59.2.10	<code>__dmul_rn</code>	442
4.59.2.11	<code>__dmul_ru</code>	442
4.59.2.12	<code>__dmul_rz</code>	442
4.59.2.13	<code>__drecp_rd</code>	442
4.59.2.14	<code>__drecp_rn</code>	443
4.59.2.15	<code>__drecp_ru</code>	443
4.59.2.16	<code>__drecp_rz</code>	443
4.59.2.17	<code>__dsqrt_rd</code>	443
4.59.2.18	<code>__dsqrt_rn</code>	444
4.59.2.19	<code>__dsqrt_ru</code>	444
4.59.2.20	<code>__dsqrt_rz</code>	444
4.59.2.21	<code>__fma_rd</code>	444
4.59.2.22	<code>__fma_rn</code>	445
4.59.2.23	<code>__fma_ru</code>	445
4.59.2.24	<code>__fma_rz</code>	445
4.60	Integer Intrinsics	446
4.60.1	Detailed Description	447
4.60.2	Function Documentation	447
4.60.2.1	<code>__brev</code>	447
4.60.2.2	<code>__brevll</code>	447
4.60.2.3	<code>__byte_perm</code>	447
4.60.2.4	<code>__clz</code>	448
4.60.2.5	<code>__clzll</code>	448

4.60.2.6	<code>__ffs</code>	448
4.60.2.7	<code>__ffsll</code>	448
4.60.2.8	<code>__mul24</code>	448
4.60.2.9	<code>__mul64hi</code>	448
4.60.2.10	<code>__mulhi</code>	449
4.60.2.11	<code>__popc</code>	449
4.60.2.12	<code>__popcll</code>	449
4.60.2.13	<code>__sad</code>	449
4.60.2.14	<code>__umul24</code>	449
4.60.2.15	<code>__umul64hi</code>	449
4.60.2.16	<code>__umulhi</code>	450
4.60.2.17	<code>__usad</code>	450
4.61	Type Casting Intrinsics	451
4.61.1	Detailed Description	455
4.61.2	Function Documentation	455
4.61.2.1	<code>__double2float_rd</code>	455
4.61.2.2	<code>__double2float_rn</code>	455
4.61.2.3	<code>__double2float_ru</code>	455
4.61.2.4	<code>__double2float_rz</code>	456
4.61.2.5	<code>__double2hiint</code>	456
4.61.2.6	<code>__double2int_rd</code>	456
4.61.2.7	<code>__double2int_rn</code>	456
4.61.2.8	<code>__double2int_ru</code>	456
4.61.2.9	<code>__double2int_rz</code>	456
4.61.2.10	<code>__double2ll_rd</code>	457
4.61.2.11	<code>__double2ll_rn</code>	457
4.61.2.12	<code>__double2ll_ru</code>	457
4.61.2.13	<code>__double2ll_rz</code>	457
4.61.2.14	<code>__double2loint</code>	457
4.61.2.15	<code>__double2uint_rd</code>	457
4.61.2.16	<code>__double2uint_rn</code>	458
4.61.2.17	<code>__double2uint_ru</code>	458
4.61.2.18	<code>__double2uint_rz</code>	458
4.61.2.19	<code>__double2ull_rd</code>	458
4.61.2.20	<code>__double2ull_rn</code>	458
4.61.2.21	<code>__double2ull_ru</code>	458
4.61.2.22	<code>__double2ull_rz</code>	459

4.61.2.23	__double_as_longlong	459
4.61.2.24	__float2half_rn	459
4.61.2.25	__float2int_rd	459
4.61.2.26	__float2int_rn	459
4.61.2.27	__float2int_ru	459
4.61.2.28	__float2int_rz	460
4.61.2.29	__float2ll_rd	460
4.61.2.30	__float2ll_rn	460
4.61.2.31	__float2ll_ru	460
4.61.2.32	__float2ll_rz	460
4.61.2.33	__float2uint_rd	460
4.61.2.34	__float2uint_rn	461
4.61.2.35	__float2uint_ru	461
4.61.2.36	__float2uint_rz	461
4.61.2.37	__float2ull_rd	461
4.61.2.38	__float2ull_rn	461
4.61.2.39	__float2ull_ru	461
4.61.2.40	__float2ull_rz	462
4.61.2.41	__float_as_int	462
4.61.2.42	__half2float	462
4.61.2.43	__hiloint2double	462
4.61.2.44	__int2double_rn	462
4.61.2.45	__int2float_rd	462
4.61.2.46	__int2float_rn	463
4.61.2.47	__int2float_ru	463
4.61.2.48	__int2float_rz	463
4.61.2.49	__int_as_float	463
4.61.2.50	__ll2double_rd	463
4.61.2.51	__ll2double_rn	463
4.61.2.52	__ll2double_ru	464
4.61.2.53	__ll2double_rz	464
4.61.2.54	__ll2float_rd	464
4.61.2.55	__ll2float_rn	464
4.61.2.56	__ll2float_ru	464
4.61.2.57	__ll2float_rz	464
4.61.2.58	__longlong_as_double	465
4.61.2.59	__uint2double_rn	465

4.61.2.60	<code>__uint2float_rd</code>	465
4.61.2.61	<code>__uint2float_rn</code>	465
4.61.2.62	<code>__uint2float_ru</code>	465
4.61.2.63	<code>__uint2float_rz</code>	465
4.61.2.64	<code>__ull2double_rd</code>	466
4.61.2.65	<code>__ull2double_rn</code>	466
4.61.2.66	<code>__ull2double_ru</code>	466
4.61.2.67	<code>__ull2double_rz</code>	466
4.61.2.68	<code>__ull2float_rd</code>	466
4.61.2.69	<code>__ull2float_rn</code>	466
4.61.2.70	<code>__ull2float_ru</code>	467
4.61.2.71	<code>__ull2float_rz</code>	467
5	Data Structure Documentation	469
5.1	<code>CUDA_ARRAY3D_DESCRIPTOR_st</code> Struct Reference	469
5.1.1	Detailed Description	469
5.1.2	Field Documentation	469
5.1.2.1	Depth	469
5.1.2.2	Flags	469
5.1.2.3	Format	469
5.1.2.4	Height	469
5.1.2.5	NumChannels	470
5.1.2.6	Width	470
5.2	<code>CUDA_ARRAY_DESCRIPTOR_st</code> Struct Reference	471
5.2.1	Detailed Description	471
5.2.2	Field Documentation	471
5.2.2.1	Format	471
5.2.2.2	Height	471
5.2.2.3	NumChannels	471
5.2.2.4	Width	471
5.3	<code>CUDA_MEMCPY2D_st</code> Struct Reference	472
5.3.1	Detailed Description	472
5.3.2	Field Documentation	472
5.3.2.1	<code>dstArray</code>	472
5.3.2.2	<code>dstDevice</code>	472
5.3.2.3	<code>dstHost</code>	472
5.3.2.4	<code>dstMemoryType</code>	472

5.3.2.5	dstPitch	472
5.3.2.6	dstXInBytes	473
5.3.2.7	dstY	473
5.3.2.8	Height	473
5.3.2.9	srcArray	473
5.3.2.10	srcDevice	473
5.3.2.11	srcHost	473
5.3.2.12	srcMemoryType	473
5.3.2.13	srcPitch	473
5.3.2.14	srcXInBytes	473
5.3.2.15	srcY	473
5.3.2.16	WidthInBytes	473
5.4	CUDA_MEMCPY3D_PEER_st Struct Reference	474
5.4.1	Detailed Description	474
5.4.2	Field Documentation	474
5.4.2.1	Depth	474
5.4.2.2	dstArray	474
5.4.2.3	dstContext	474
5.4.2.4	dstDevice	475
5.4.2.5	dstHeight	475
5.4.2.6	dstHost	475
5.4.2.7	dstLOD	475
5.4.2.8	dstMemoryType	475
5.4.2.9	dstPitch	475
5.4.2.10	dstXInBytes	475
5.4.2.11	dstY	475
5.4.2.12	dstZ	475
5.4.2.13	Height	475
5.4.2.14	srcArray	475
5.4.2.15	srcContext	475
5.4.2.16	srcDevice	476
5.4.2.17	srcHeight	476
5.4.2.18	srcHost	476
5.4.2.19	srcLOD	476
5.4.2.20	srcMemoryType	476
5.4.2.21	srcPitch	476
5.4.2.22	srcXInBytes	476

5.4.2.23	srcY	476
5.4.2.24	srcZ	476
5.4.2.25	WidthInBytes	476
5.5	CUDA_MEMCPY3D_st Struct Reference	477
5.5.1	Detailed Description	477
5.5.2	Field Documentation	477
5.5.2.1	Depth	477
5.5.2.2	dstArray	477
5.5.2.3	dstDevice	477
5.5.2.4	dstHeight	478
5.5.2.5	dstHost	478
5.5.2.6	dstLOD	478
5.5.2.7	dstMemoryType	478
5.5.2.8	dstPitch	478
5.5.2.9	dstXInBytes	478
5.5.2.10	dstY	478
5.5.2.11	dstZ	478
5.5.2.12	Height	478
5.5.2.13	reserved0	478
5.5.2.14	reserved1	478
5.5.2.15	srcArray	478
5.5.2.16	srcDevice	479
5.5.2.17	srcHeight	479
5.5.2.18	srcHost	479
5.5.2.19	srcLOD	479
5.5.2.20	srcMemoryType	479
5.5.2.21	srcPitch	479
5.5.2.22	srcXInBytes	479
5.5.2.23	srcY	479
5.5.2.24	srcZ	479
5.5.2.25	WidthInBytes	479
5.6	cudaChannelFormatDesc Struct Reference	480
5.6.1	Detailed Description	480
5.6.2	Field Documentation	480
5.6.2.1	f	480
5.6.2.2	w	480
5.6.2.3	x	480

5.6.2.4	y	480
5.6.2.5	z	480
5.7	cudaDeviceProp Struct Reference	481
5.7.1	Detailed Description	482
5.7.2	Field Documentation	482
5.7.2.1	asyncEngineCount	482
5.7.2.2	canMapHostMemory	482
5.7.2.3	clockRate	482
5.7.2.4	computeMode	482
5.7.2.5	concurrentKernels	482
5.7.2.6	deviceOverlap	482
5.7.2.7	ECCEnabled	482
5.7.2.8	integrated	482
5.7.2.9	kernelExecTimeoutEnabled	482
5.7.2.10	l2CacheSize	483
5.7.2.11	major	483
5.7.2.12	maxGridSize	483
5.7.2.13	maxSurface1D	483
5.7.2.14	maxSurface1DLayered	483
5.7.2.15	maxSurface2D	483
5.7.2.16	maxSurface2DLayered	483
5.7.2.17	maxSurface3D	483
5.7.2.18	maxSurfaceCubemap	483
5.7.2.19	maxSurfaceCubemapLayered	483
5.7.2.20	maxTexture1D	483
5.7.2.21	maxTexture1DLayered	483
5.7.2.22	maxTexture1DLinear	484
5.7.2.23	maxTexture2D	484
5.7.2.24	maxTexture2DGather	484
5.7.2.25	maxTexture2DLayered	484
5.7.2.26	maxTexture2DLinear	484
5.7.2.27	maxTexture3D	484
5.7.2.28	maxTextureCubemap	484
5.7.2.29	maxTextureCubemapLayered	484
5.7.2.30	maxThreadsDim	484
5.7.2.31	maxThreadsPerBlock	484
5.7.2.32	maxThreadsPerMultiProcessor	484

5.7.2.33	memoryBusWidth	484
5.7.2.34	memoryClockRate	485
5.7.2.35	memPitch	485
5.7.2.36	minor	485
5.7.2.37	multiProcessorCount	485
5.7.2.38	name	485
5.7.2.39	pciBusID	485
5.7.2.40	pciDeviceID	485
5.7.2.41	pciDomainID	485
5.7.2.42	regsPerBlock	485
5.7.2.43	sharedMemPerBlock	485
5.7.2.44	surfaceAlignment	485
5.7.2.45	tccDriver	485
5.7.2.46	textureAlignment	486
5.7.2.47	texturePitchAlignment	486
5.7.2.48	totalConstMem	486
5.7.2.49	totalGlobalMem	486
5.7.2.50	unifiedAddressing	486
5.7.2.51	warpSize	486
5.8	cudaExtent Struct Reference	487
5.8.1	Detailed Description	487
5.8.2	Field Documentation	487
5.8.2.1	depth	487
5.8.2.2	height	487
5.8.2.3	width	487
5.9	cudaFuncAttributes Struct Reference	488
5.9.1	Detailed Description	488
5.9.2	Field Documentation	488
5.9.2.1	binaryVersion	488
5.9.2.2	constSizeBytes	488
5.9.2.3	localSizeBytes	488
5.9.2.4	maxThreadsPerBlock	488
5.9.2.5	numRegs	488
5.9.2.6	ptxVersion	488
5.9.2.7	sharedSizeBytes	489
5.10	cudaMemcpy3DParms Struct Reference	490
5.10.1	Detailed Description	490

5.10.2	Field Documentation	490
5.10.2.1	dstArray	490
5.10.2.2	dstPos	490
5.10.2.3	dstPtr	490
5.10.2.4	extent	490
5.10.2.5	kind	490
5.10.2.6	srcArray	490
5.10.2.7	srcPos	490
5.10.2.8	srcPtr	491
5.11	cudaMemcpy3DPeerParms Struct Reference	492
5.11.1	Detailed Description	492
5.11.2	Field Documentation	492
5.11.2.1	dstArray	492
5.11.2.2	dstDevice	492
5.11.2.3	dstPos	492
5.11.2.4	dstPtr	492
5.11.2.5	extent	492
5.11.2.6	srcArray	492
5.11.2.7	srcDevice	492
5.11.2.8	srcPos	493
5.11.2.9	srcPtr	493
5.12	cudaPitchedPtr Struct Reference	494
5.12.1	Detailed Description	494
5.12.2	Field Documentation	494
5.12.2.1	pitch	494
5.12.2.2	ptr	494
5.12.2.3	xsize	494
5.12.2.4	ysize	494
5.13	cudaPointerAttributes Struct Reference	495
5.13.1	Detailed Description	495
5.13.2	Field Documentation	495
5.13.2.1	device	495
5.13.2.2	devicePointer	495
5.13.2.3	hostPointer	495
5.13.2.4	memoryType	495
5.14	cudaPos Struct Reference	496
5.14.1	Detailed Description	496

5.14.2	Field Documentation	496
5.14.2.1	x	496
5.14.2.2	y	496
5.14.2.3	z	496
5.15	CUdevprop_st Struct Reference	497
5.15.1	Detailed Description	497
5.15.2	Field Documentation	497
5.15.2.1	clockRate	497
5.15.2.2	maxGridSize	497
5.15.2.3	maxThreadsDim	497
5.15.2.4	maxThreadsPerBlock	497
5.15.2.5	memPitch	497
5.15.2.6	regsPerBlock	497
5.15.2.7	sharedMemPerBlock	497
5.15.2.8	SIMDWidth	498
5.15.2.9	textureAlign	498
5.15.2.10	totalConstantMemory	498
5.16	surfaceReference Struct Reference	499
5.16.1	Detailed Description	499
5.16.2	Field Documentation	499
5.16.2.1	channelDesc	499
5.17	textureReference Struct Reference	500
5.17.1	Detailed Description	500
5.17.2	Field Documentation	500
5.17.2.1	addressMode	500
5.17.2.2	channelDesc	500
5.17.2.3	filterMode	500
5.17.2.4	normalized	500
5.17.2.5	sRGB	500

Chapter 1

Deprecated List

Global [cudaThreadExit](#)

Global [cudaThreadGetCacheConfig](#)

Global [cudaThreadGetLimit](#)

Global [cudaThreadSetCacheConfig](#)

Global [cudaThreadSetLimit](#)

Global [cudaThreadSynchronize](#)

Global [cudaD3D9MapResources](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D9RegisterResource](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D9ResourceGetMappedArray](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D9ResourceGetMappedPitch](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D9ResourceGetMappedPointer](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D9ResourceGetMappedSize](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D9ResourceGetSurfaceDimensions](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D9ResourceSetMapFlags](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D9UnmapResources](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D9UnregisterResource](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D10MapResources](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D10RegisterResource](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D10ResourceGetMappedArray](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D10ResourceGetMappedPitch](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D10ResourceGetMappedPointer](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D10ResourceGetMappedSize](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D10ResourceGetSurfaceDimensions](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D10ResourceSetMapFlags](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D10UnmapResources](#) This function is deprecated as of Cuda 3.0.

Global [cudaD3D10UnregisterResource](#) This function is deprecated as of Cuda 3.0.

Global [cudaGLMapBufferObject](#) This function is deprecated as of Cuda 3.0.

Global [cudaGLMapBufferObjectAsync](#) This function is deprecated as of Cuda 3.0.

Global [cudaGLRegisterBufferObject](#) This function is deprecated as of Cuda 3.0.

Global [cudaGLSetBufferObjectMapFlags](#) This function is deprecated as of Cuda 3.0.

Global [cudaGLUnmapBufferObject](#) This function is deprecated as of Cuda 3.0.

Global [cudaGLUnmapBufferObjectAsync](#) This function is deprecated as of Cuda 3.0.

Global [cudaGLUnregisterBufferObject](#) This function is deprecated as of Cuda 3.0.

Global [cudaErrorPriorLaunchFailure](#) This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

Global [cudaErrorAddressOfConstant](#) This error return is deprecated as of CUDA 3.1. Variables in constant memory may now have their address taken by the runtime via [cudaGetSymbolAddress\(\)](#).

Global [cudaErrorTextureFetchFailed](#) This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

Global [cudaErrorTextureNotBound](#) This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

Global [cudaErrorSynchronizationError](#) This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

Global [cudaErrorMixedDeviceExecution](#) This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

Global [cudaErrorNotYetImplemented](#) This error return is deprecated as of CUDA 4.1.

Global [cudaErrorMemoryValueTooLarge](#) This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

Global [cudaErrorApiFailureBase](#) This error return is deprecated as of CUDA 4.1.

Global [cudaDeviceBlockingSync](#) This flag was deprecated as of CUDA 4.0 and replaced with [cudaDeviceScheduleBlockingSync](#).

Global [CU_CTX_BLOCKING_SYNC](#) This flag was deprecated as of CUDA 4.0 and was replaced with [CU_CTX_SCHED_BLOCKING_SYNC](#).

Global [CUDA_ERROR_CONTEXT_ALREADY_CURRENT](#) This error return is deprecated as of CUDA 3.2. It is no longer an error to attempt to push the active context via [cuCtxPushCurrent\(\)](#).

Global [cuCtxAttach](#)

Global [cuCtxDetach](#)

Global [cuFuncSetBlockShape](#)

Global [cuFuncSetSharedSize](#)

Global [cuLaunch](#)

Global [cuLaunchGrid](#)

Global [cuLaunchGridAsync](#)

Global [cuParamSetf](#)

Global [cuParamSeti](#)

Global [cuParamSetSize](#)

Global [cuParamSetTexRef](#)

Global [cuParamSetv](#)

Global [cuTexRefCreate](#)

Global [cuTexRefDestroy](#)

Global [cuGLInit](#) This function is deprecated as of Cuda 3.0.

Global [cuGLMapBufferObject](#) This function is deprecated as of Cuda 3.0.

Global [cuGLMapBufferObjectAsync](#) This function is deprecated as of Cuda 3.0.

Global [cuGLRegisterBufferObject](#) This function is deprecated as of Cuda 3.0.

Global [cuGLSetBufferObjectMapFlags](#) This function is deprecated as of Cuda 3.0.

Global [cuGLUnmapBufferObject](#) This function is deprecated as of Cuda 3.0.

Global [cuGLUnmapBufferObjectAsync](#) This function is deprecated as of Cuda 3.0.

Global [cuGLUnregisterBufferObject](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D9MapResources](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D9RegisterResource](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D9ResourceGetMappedArray](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D9ResourceGetMappedPitch](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D9ResourceGetMappedPointer](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D9ResourceGetMappedSize](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D9ResourceGetSurfaceDimensions](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D9ResourceSetMapFlags](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D9UnmapResources](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D9UnregisterResource](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D10MapResources](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D10RegisterResource](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D10ResourceGetMappedArray](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D10ResourceGetMappedPitch](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D10ResourceGetMappedPointer](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D10ResourceGetMappedSize](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D10ResourceGetSurfaceDimensions](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D10ResourceSetMapFlags](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D10UnmapResources](#) This function is deprecated as of Cuda 3.0.

Global [cuD3D10UnregisterResource](#) This function is deprecated as of Cuda 3.0.

Chapter 2

Module Index

2.1 Modules

Here is a list of all modules:

CUDA Runtime API	11
Device Management	13
Thread Management [DEPRECATED]	27
Error Handling	32
Stream Management	34
Event Management	37
Execution Control	41
Memory Management	45
Unified Addressing	81
Peer Device Memory Access	84
OpenGL Interoperability	86
OpenGL Interoperability [DEPRECATED]	156
Direct3D 9 Interoperability	91
Direct3D 9 Interoperability [DEPRECATED]	138
Direct3D 10 Interoperability	96
Direct3D 10 Interoperability [DEPRECATED]	147
Direct3D 11 Interoperability	101
VDPAU Interoperability	106
Graphics Interoperability	109
Texture Reference Management	113
Surface Reference Management	118
Version Management	120
C++ API Routines	121
Interactions with the CUDA Driver API	134
Profiler Control	136
Data types used by CUDA Runtime	161
CUDA Driver API	176
Data types used by CUDA driver	177
Initialization	200
Version Management	201
Device Management	202
Context Management	210
Context Management [DEPRECATED]	219

Module Management	221
Memory Management	228
Unified Addressing	281
Stream Management	285
Event Management	288
Execution Control	292
Execution Control [DEPRECATED]	296
Texture Reference Management	303
Texture Reference Management [DEPRECATED]	311
Surface Reference Management	313
Peer Context Memory Access	315
Graphics Interoperability	317
Profiler Control	322
OpenGL Interoperability	324
OpenGL Interoperability [DEPRECATED]	329
Direct3D 9 Interoperability	335
Direct3D 9 Interoperability [DEPRECATED]	341
Direct3D 10 Interoperability	350
Direct3D 10 Interoperability [DEPRECATED]	356
Direct3D 11 Interoperability	365
VDPAU Interoperability	371
Mathematical Functions	375
Single Precision Mathematical Functions	376
Double Precision Mathematical Functions	401
Single Precision Intrinsics	426
Double Precision Intrinsics	438
Integer Intrinsics	446
Type Casting Intrinsics	451

Chapter 3

Data Structure Index

3.1 Data Structures

Here are the data structures with brief descriptions:

CUDA_ARRAY3D_DESCRIPTOR_st	469
CUDA_ARRAY_DESCRIPTOR_st	471
CUDA_MEMCPY2D_st	472
CUDA_MEMCPY3D_PEER_st	474
CUDA_MEMCPY3D_st	477
cudaChannelFormatDesc	480
cudaDeviceProp	481
cudaExtent	487
cudaFuncAttributes	488
cudaMemcpy3DParms	490
cudaMemcpy3DPeerParms	492
cudaPitchedPtr	494
cudaPointerAttributes	495
cudaPos	496
CUdevprop_st	497
surfaceReference	499
textureReference	500

Chapter 4

Module Documentation

4.1 CUDA Runtime API

Modules

- [Device Management](#)
- [Error Handling](#)
- [Stream Management](#)
- [Event Management](#)
- [Execution Control](#)
- [Memory Management](#)
- [Unified Addressing](#)
- [Peer Device Memory Access](#)
- [OpenGL Interoperability](#)
- [Direct3D 9 Interoperability](#)
- [Direct3D 10 Interoperability](#)
- [Direct3D 11 Interoperability](#)
- [VDPAU Interoperability](#)
- [Graphics Interoperability](#)
- [Texture Reference Management](#)
- [Surface Reference Management](#)
- [Version Management](#)
- [C++ API Routines](#)

C++-style interface built on top of CUDA runtime API.

- [Interactions with the CUDA Driver API](#)

Interactions between the CUDA Driver API and the CUDA Runtime API.

- [Profiler Control](#)
- [Data types used by CUDA Runtime](#)

Defines

- `#define CUDART_VERSION 4010`

4.1.1 Detailed Description

There are two levels for the runtime API.

The C API (*cuda_runtime_api.h*) is a C-style interface that does not require compiling with `nvcc`.

The **C++ API** (*cuda_runtime.h*) is a C++-style interface built on top of the C API. It wraps some of the C API routines, using overloading, references and default arguments. These wrappers can be used from C++ code and can be compiled with any C++ compiler. The C++ API also has some CUDA-specific wrappers that wrap C API routines that deal with symbols, textures, and device functions. These wrappers require the use of `nvcc` because they depend on code being generated by the compiler. For example, the execution configuration syntax to invoke kernels is only available in source code compiled with `nvcc`.

4.1.2 Define Documentation

4.1.2.1 `#define CUDART_VERSION 4010`

CUDA Runtime API Version 4.1

4.2 Device Management

Modules

- [Thread Management \[DEPRECATED\]](#)

Functions

- [cudaError_t cudaChooseDevice](#) (int *device, const struct [cudaDeviceProp](#) *prop)
Select compute-device which best matches criteria.
- [cudaError_t cudaDeviceGetByPCIBusId](#) (int *device, char *pciBusId)
Returns a handle to a compute device.
- [cudaError_t cudaDeviceGetCacheConfig](#) (enum [cudaFuncCache](#) *pCacheConfig)
Returns the preferred cache configuration for the current device.
- [cudaError_t cudaDeviceGetLimit](#) (size_t *pValue, enum [cudaLimit](#) limit)
Returns resource limits.
- [cudaError_t cudaDeviceGetPCIBusId](#) (char *pciBusId, int len, int device)
Returns a PCI Bus Id string for the device.
- [cudaError_t cudaDeviceReset](#) (void)
Destroy all allocations and reset all state on the current device in the current process.
- [cudaError_t cudaDeviceSetCacheConfig](#) (enum [cudaFuncCache](#) cacheConfig)
Sets the preferred cache configuration for the current device.
- [cudaError_t cudaDeviceSetLimit](#) (enum [cudaLimit](#) limit, size_t value)
Set resource limits.
- [cudaError_t cudaDeviceSynchronize](#) (void)
Wait for compute device to finish.
- [cudaError_t cudaGetDevice](#) (int *device)
Returns which device is currently being used.
- [cudaError_t cudaGetDeviceCount](#) (int *count)
Returns the number of compute-capable devices.
- [cudaError_t cudaGetDeviceProperties](#) (struct [cudaDeviceProp](#) *prop, int device)
Returns information about the compute-device.
- [cudaError_t cudaIpcCloseMemHandle](#) (void *devPtr)
- [cudaError_t cudaIpcGetEventHandle](#) ([cudaIpcEventHandle_t](#) *handle, [cudaEvent_t](#) event)
Gets an interprocess handle for a previously allocated event.
- [cudaError_t cudaIpcGetMemHandle](#) ([cudaIpcMemHandle_t](#) *handle, void *devPtr)
- [cudaError_t cudaIpcOpenEventHandle](#) ([cudaEvent_t](#) *event, [cudaIpcEventHandle_t](#) handle)

Opens an interprocess event handle for use in the current process.

- [cudaError_t cudaIpcOpenMemHandle](#) (void **devPtr, cudaIpcMemHandle_t handle)
- [cudaError_t cudaSetDevice](#) (int device)

Set device to be used for GPU executions.

- [cudaError_t cudaSetDeviceFlags](#) (unsigned int flags)

Sets flags to be used for device executions.

- [cudaError_t cudaSetValidDevices](#) (int *device_arr, int len)

Set a list of devices that can be used for CUDA.

4.2.1 Detailed Description

This section describes the device management functions of the CUDA runtime application programming interface.

4.2.2 Function Documentation

4.2.2.1 [cudaError_t cudaChooseDevice](#) (int *device, const struct cudaDeviceProp *prop)

Returns in *device the device which has properties that best match *prop.

Parameters:

device - Device with best match

prop - Desired device properties

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGetDeviceCount](#), [cudaGetDevice](#), [cudaSetDevice](#), [cudaGetDeviceProperties](#)

4.2.2.2 [cudaError_t cudaDeviceGetByPCIBusId](#) (int *device, char *pciBusId)

Returns in *device a device ordinal given a PCI bus ID string.

Parameters:

device - Returned device ordinal

pciBusId - String in one of the following forms: [domain]:[bus]:[device].[function] [domain]:[bus]:[device]
[bus]:[device].[function] where domain, bus, device, and function are all hexadecimal values

Returns:

[cudaSuccess](#) [cudaErrorInvalidValue](#), [cudaErrorInvalidDevice](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceGetPCIBusId](#)

4.2.2.3 `cudaError_t cudaDeviceGetCacheConfig (enum cudaFuncCache * pCacheConfig)`

On devices where the L1 cache and shared memory use the same hardware resources, this returns through `pCacheConfig` the preferred cache configuration for the current device. This is only a preference. The runtime will use the requested configuration if possible, but it is free to choose a different configuration if required to execute functions.

This will return a `pCacheConfig` of [cudaFuncCachePreferNone](#) on devices where the size of the L1 cache and shared memory are fixed.

The supported cache configurations are:

- [cudaFuncCachePreferNone](#): no preference for shared memory or L1 (default)
- [cudaFuncCachePreferShared](#): prefer larger shared memory and smaller L1 cache
- [cudaFuncCachePreferL1](#): prefer larger L1 cache and smaller shared memory

Parameters:

pCacheConfig - Returned cache configuration

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceSetCacheConfig](#), [cudaFuncSetCacheConfig \(C API\)](#), [cudaFuncSetCacheConfig \(C++ API\)](#)

4.2.2.4 `cudaError_t cudaDeviceGetLimit (size_t * pValue, enum cudaLimit limit)`

Returns in `*pValue` the current size of `limit`. The supported [cudaLimit](#) values are:

- [cudaLimitStackSize](#): stack size of each GPU thread;
- [cudaLimitPrintfFifoSize](#): size of the shared FIFO used by the `printf()` and `fprintf()` device system calls.
- [cudaLimitMallocHeapSize](#): size of the heap used by the `malloc()` and `free()` device system calls;

Parameters:

limit - Limit to query

pValue - Returned size in bytes of limit

Returns:

[cudaSuccess](#), [cudaErrorUnsupportedLimit](#), [cudaErrorInvalidValue](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceSetLimit](#)

4.2.2.5 `cudaError_t cudaDeviceGetPCIBusId (char *pciBusId, int len, int device)`

Returns an ASCII string identifying the device `dev` in the NULL-terminated string pointed to by `pciBusId`. `len` specifies the maximum length of the string that may be returned.

Parameters:

pciBusId - Returned identifier string for the device in the following format `[domain]:[bus]:[device].[function]` where `domain`, `bus`, `device`, and `function` are all hexadecimal values. `pciBusId` should be large enough to store 13 characters including the NULL-terminator.

len - Maximum length of string to store in `name`

device - Device to get identifier string for

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevice](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceGetByPCIBusId](#)

4.2.2.6 `cudaError_t cudaDeviceReset (void)`

Explicitly destroys and cleans up all resources associated with the current device in the current process. Any subsequent API call to this device will reinitialize the device.

Note that this function will reset the device immediately. It is the caller's responsibility to ensure that the device is not being accessed by any other host threads from the process when this function is called.

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceSynchronize](#)

4.2.2.7 `cudaError_t cudaDeviceSetCacheConfig (enum cudaFuncCache cacheConfig)`

On devices where the L1 cache and shared memory use the same hardware resources, this sets through `cacheConfig` the preferred cache configuration for the current device. This is only a preference. The runtime will use the requested configuration if possible, but it is free to choose a different configuration if required to execute the function. Any function preference set via `cudaFuncSetCacheConfig` (C API) or `cudaFuncSetCacheConfig` (C++ API) will be preferred over this device-wide setting. Setting the device-wide cache configuration to `cudaFuncCachePreferNone` will cause subsequent kernel launches to prefer to not change the cache configuration unless required to launch the kernel.

This setting does nothing on devices where the size of the L1 cache and shared memory are fixed.

Launching a kernel with a different preference than the most recent preference setting may insert a device-side synchronization point.

The supported cache configurations are:

- `cudaFuncCachePreferNone`: no preference for shared memory or L1 (default)
- `cudaFuncCachePreferShared`: prefer larger shared memory and smaller L1 cache
- `cudaFuncCachePreferL1`: prefer larger L1 cache and smaller shared memory

Parameters:

cacheConfig - Requested cache configuration

Returns:

`cudaSuccess`, `cudaErrorInitializationError`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaDeviceGetCacheConfig`, `cudaFuncSetCacheConfig` (C API), `cudaFuncSetCacheConfig` (C++ API)

4.2.2.8 `cudaError_t cudaDeviceSetLimit (enum cudaLimit limit, size_t value)`

Setting `limit` to `value` is a request by the application to update the current limit maintained by the device. The driver is free to modify the requested value to meet h/w requirements (this could be clamping to minimum or maximum values, rounding up to nearest element size, etc). The application can use `cudaDeviceGetLimit()` to find out exactly what the limit has been set to.

Setting each `cudaLimit` has its own specific restrictions, so each is discussed here.

- `cudaLimitStackSize` controls the stack size of each GPU thread. This limit is only applicable to devices of compute capability 2.0 and higher. Attempting to set this limit on devices of compute capability less than 2.0 will result in the error `cudaErrorUnsupportedLimit` being returned.
- `cudaLimitPrintfFifoSize` controls the size of the shared FIFO used by the `printf()` and `fprintf()` device system calls. Setting `cudaLimitPrintfFifoSize` must be performed before launching any kernel that uses the `printf()` or `fprintf()` device system calls, otherwise `cudaErrorInvalidValue` will be returned. This limit is only applicable to devices of compute capability 2.0 and higher. Attempting to set this limit on devices of compute capability less than 2.0 will result in the error `cudaErrorUnsupportedLimit` being returned.

- [cudaLimitMallocHeapSize](#) controls the size of the heap used by the `malloc()` and `free()` device system calls. Setting [cudaLimitMallocHeapSize](#) must be performed before launching any kernel that uses the `malloc()` or `free()` device system calls, otherwise [cudaErrorInvalidValue](#) will be returned. This limit is only applicable to devices of compute capability 2.0 and higher. Attempting to set this limit on devices of compute capability less than 2.0 will result in the error [cudaErrorUnsupportedLimit](#) being returned.

Parameters:

limit - Limit to set

value - Size in bytes of limit

Returns:

[cudaSuccess](#), [cudaErrorUnsupportedLimit](#), [cudaErrorInvalidValue](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceGetLimit](#)

4.2.2.9 [cudaError_t](#) `cudaDeviceSynchronize` (void)

Blocks until the device has completed all preceding requested tasks. [cudaDeviceSynchronize\(\)](#) returns an error if one of the preceding tasks has failed. If the [cudaDeviceScheduleBlockingSync](#) flag was set for this device, the host thread will block until the device has finished its work.

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceSynchronize](#)

4.2.2.10 [cudaError_t](#) `cudaGetDevice` (int * *device*)

Returns in `*device` the current device for the calling host thread.

Parameters:

device - Returns the device on which the active host thread executes the device code.

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGetDeviceCount](#), [cudaSetDevice](#), [cudaGetDeviceProperties](#), [cudaChooseDevice](#)

4.2.2.11 `cudaError_t cudaGetDeviceCount (int * count)`

Returns in **count* the number of devices with compute capability greater or equal to 1.0 that are available for execution. If there is no such device then `cudaGetDeviceCount()` will return `cudaErrorNoDevice`. If no driver can be loaded to determine if any such devices exist then `cudaGetDeviceCount()` will return `cudaErrorInsufficientDriver`.

Parameters:

count - Returns the number of devices with compute capability greater or equal to 1.0

Returns:

`cudaSuccess`, `cudaErrorNoDevice`, `cudaErrorInsufficientDriver`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaGetDevice`, `cudaSetDevice`, `cudaGetDeviceProperties`, `cudaChooseDevice`

4.2.2.12 `cudaError_t cudaGetDeviceProperties (struct cudaDeviceProp * prop, int device)`

Returns in **prop* the properties of device dev. The `cudaDeviceProp` structure is defined as:

```
struct cudaDeviceProp {
    char name[256];
    size_t totalGlobalMem;
    size_t sharedMemPerBlock;
    int regsPerBlock;
    int warpSize;
    size_t memPitch;
    int maxThreadsPerBlock;
    int maxThreadsDim[3];
    int maxGridSize[3];
    int clockRate;
    size_t totalConstMem;
    int major;
    int minor;
    size_t textureAlignment;
    size_t texturePitchAlignment;
    int deviceOverlap;
    int multiProcessorCount;
    int kernelExecTimeoutEnabled;
    int integrated;
    int canMapHostMemory;
    int computeMode;
    int maxTexture1D;
    int maxTexture1DLinear;
    int maxTexture2D[2];
    int maxTexture2DLinear[3];
    int maxTexture2DGather[2];
    int maxTexture3D[3];
    int maxTextureCubemap;
    int maxTexture1DLayered[2];
    int maxTexture2DLayered[3];
    int maxTextureCubemapLayered[2];
    int maxSurface1D;
    int maxSurface2D[2];
    int maxSurface3D[3];
}
```

```

    int maxSurface1DLayered[2];
    int maxSurface2DLayered[3];
    int maxSurfaceCubemap;
    int maxSurfaceCubemapLayered[2];
    size_t surfaceAlignment;
    int concurrentKernels;
    int ECCEnabled;
    int pciBusID;
    int pciDeviceID;
    int pciDomainID;
    int tccDriver;
    int asyncEngineCount;
    int unifiedAddressing;
    int memoryClockRate;
    int memoryBusWidth;
    int l2CacheSize;
    int maxThreadsPerMultiProcessor;
}

```

where:

- [name\[256\]](#) is an ASCII string identifying the device;
- [totalGlobalMem](#) is the total amount of global memory available on the device in bytes;
- [sharedMemPerBlock](#) is the maximum amount of shared memory available to a thread block in bytes; this amount is shared by all thread blocks simultaneously resident on a multiprocessor;
- [regsPerBlock](#) is the maximum number of 32-bit registers available to a thread block; this number is shared by all thread blocks simultaneously resident on a multiprocessor;
- [warpSize](#) is the warp size in threads;
- [memPitch](#) is the maximum pitch in bytes allowed by the memory copy functions that involve memory regions allocated through [cudaMallocPitch\(\)](#);
- [maxThreadsPerBlock](#) is the maximum number of threads per block;
- [maxThreadsDim\[3\]](#) contains the maximum size of each dimension of a block;
- [maxGridSize\[3\]](#) contains the maximum size of each dimension of a grid;
- [clockRate](#) is the clock frequency in kilohertz;
- [totalConstMem](#) is the total amount of constant memory available on the device in bytes;
- [major](#), [minor](#) are the major and minor revision numbers defining the device's compute capability;
- [textureAlignment](#) is the alignment requirement; texture base addresses that are aligned to [textureAlignment](#) bytes do not need an offset applied to texture fetches;
- [texturePitchAlignment](#) is the pitch alignment requirement for 2D texture references that are bound to pitched memory;
- [deviceOverlap](#) is 1 if the device can concurrently copy memory between host and device while executing a kernel, or 0 if not. Deprecated, use instead [asyncEngineCount](#).
- [multiProcessorCount](#) is the number of multiprocessors on the device;
- [kernelExecTimeoutEnabled](#) is 1 if there is a run time limit for kernels executed on the device, or 0 if not.
- [integrated](#) is 1 if the device is an integrated (motherboard) GPU and 0 if it is a discrete (card) component.

- `canMapHostMemory` is 1 if the device can map host memory into the CUDA address space for use with `cudaHostAlloc()/cudaHostGetDevicePointer()`, or 0 if not;
- `computeMode` is the compute mode that the device is currently in. Available modes are as follows:
 - `cudaComputeModeDefault`: Default mode - Device is not restricted and multiple threads can use `cudaSetDevice()` with this device.
 - `cudaComputeModeExclusive`: Compute-exclusive mode - Only one thread will be able to use `cudaSetDevice()` with this device.
 - `cudaComputeModeProhibited`: Compute-prohibited mode - No threads can use `cudaSetDevice()` with this device.
 - `cudaComputeModeExclusiveProcess`: Compute-exclusive-process mode - Many threads in one process will be able to use `cudaSetDevice()` with this device.

If `cudaSetDevice()` is called on an already occupied device with computeMode `cudaComputeModeExclusive`, `cudaErrorDeviceAlreadyInUse` will be immediately returned indicating the device cannot be used. When an occupied exclusive mode device is chosen with `cudaSetDevice`, all subsequent non-device management runtime functions will return `cudaErrorDevicesUnavailable`.
- `maxTexture1D` is the maximum 1D texture size.
- `maxTexture1DLinear` is the maximum 1D texture size for textures bound to linear memory.
- `maxTexture2D[2]` contains the maximum 2D texture dimensions.
- `maxTexture2DLinear[3]` contains the maximum 2D texture dimensions for 2D textures bound to pitch linear memory.
- `maxTexture2DGather[2]` contains the maximum 2D texture dimensions if texture gather operations have to be performed.
- `maxTexture3D[3]` contains the maximum 3D texture dimensions.
- `maxTextureCubemap` is the maximum cubemap texture width or height.
- `maxTexture1DLayered[2]` contains the maximum 1D layered texture dimensions.
- `maxTexture2DLayered[3]` contains the maximum 2D layered texture dimensions.
- `maxTextureCubemapLayered[2]` contains the maximum cubemap layered texture dimensions.
- `maxSurface1D` is the maximum 1D surface size.
- `maxSurface2D[2]` contains the maximum 2D surface dimensions.
- `maxSurface3D[3]` contains the maximum 3D surface dimensions.
- `maxSurface1DLayered[2]` contains the maximum 1D layered surface dimensions.
- `maxSurface2DLayered[3]` contains the maximum 2D layered surface dimensions.
- `maxSurfaceCubemap` is the maximum cubemap surface width or height.
- `maxSurfaceCubemapLayered[2]` contains the maximum cubemap layered surface dimensions.
- `surfaceAlignment` specifies the alignment requirements for surfaces.
- `concurrentKernels` is 1 if the device supports executing multiple kernels within the same context simultaneously, or 0 if not. It is not guaranteed that multiple kernels will be resident on the device concurrently so this feature should not be relied upon for correctness;
- `ECCEnabled` is 1 if the device has ECC support turned on, or 0 if not.

- [pciBusID](#) is the PCI bus identifier of the device.
- [pciDeviceID](#) is the PCI device (sometimes called slot) identifier of the device.
- [pciDomainID](#) is the PCI domain identifier of the device.
- [tccDriver](#) is 1 if the device is using a TCC driver or 0 if not.
- [asyncEngineCount](#) is 1 when the device can concurrently copy memory between host and device while executing a kernel. It is 2 when the device can concurrently copy memory between host and device in both directions and execute a kernel at the same time. It is 0 if neither of these is supported.
- [unifiedAddressing](#) is 1 if the device shares a unified address space with the host and 0 otherwise.
- [memoryClockRate](#) is the peak memory clock frequency in kilohertz.
- [memoryBusWidth](#) is the memory bus width in bits.
- [l2CacheSize](#) is L2 cache size in bytes.
- [maxThreadsPerMultiProcessor](#) is the number of maximum resident threads per multiprocessor.

Parameters:

prop - Properties for the specified device

device - Device number to get properties for

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#)

See also:

[cudaGetDeviceCount](#), [cudaGetDevice](#), [cudaSetDevice](#), [cudaChooseDevice](#)

4.2.2.13 [cudaError_t cudaIpcCloseMemHandle \(void * devPtr\)](#)

/brief Close memory mapped with [cudaIpcOpenMemHandle](#)

Unmaps memory returned by [cudaIpcOpenMemHandle](#). The original allocation in the exporting process as well as imported mappings in other processes will be unaffected.

Any resources used to enable peer access will be freed if this is the last mapping using them.

Parameters:

devPtr - Device pointer returned by [cudaIpcOpenMemHandle](#)

Returns:

[cudaSuccess](#), [cudaErrorMapBufferObjectFailed](#), [cudaErrorInvalidResourceHandle](#),

See also:

[cudaMemAlloc](#), [cudaMemFree](#), [cudaIpcGetEventHandle](#), [cudaIpcOpenEventHandle](#), [cudaIpcGetMemHandle](#), [cudaIpcOpenMemHandle](#),

4.2.2.14 `cudaError_t cudaIpcGetEventHandle (cudaIpcEventHandle_t * handle, cudaEvent_t event)`

Takes as input a previously allocated event. This event must have been created with the [cudaEventInterprocess](#) and [cudaEventDisableTiming](#) flags set. This opaque handle may be copied into other processes and opened with [cudaIpcOpenEventHandle](#) to allow efficient hardware synchronization between GPU work in different processes.

After the event has been opened in the importing process, [cudaEventRecord](#), [cudaEventSynchronize](#), [cudaStreamWaitEvent](#) and [cudaEventQuery](#) may be used in either process. Performing operations on the imported event after the exported event has been freed with [cudaEventDestroy](#) will result in undefined behavior.

Parameters:

- handle* - Pointer to a user allocated `cudaIpcEventHandle` in which to return the opaque event handle
- event* - Event allocated with [cudaEventInterprocess](#) and [cudaEventDisableTiming](#) flags.

Returns:

[cudaSuccess](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorMemoryAllocation](#), [cudaErrorMapBufferObjectFailed](#)

See also:

[cudaEventCreate](#), [cudaEventDestroy](#), [cudaEventSynchronize](#), [cudaEventQuery](#), [cudaStreamWaitEvent](#), [cudaIpcOpenEventHandle](#), [cudaIpcGetMemHandle](#), [cudaIpcOpenMemHandle](#), [cudaIpcCloseMemHandle](#)

4.2.2.15 `cudaError_t cudaIpcGetMemHandle (cudaIpcMemHandle_t * handle, void * devPtr)`

/brief Gets an interprocess memory handle for an existing device memory allocation

Takes a pointer to the base of an existing device memory allocation created with `cudaMemAlloc` and exports it for use in another process. This is a lightweight operation and may be called multiple times on an allocation without adverse effects.

If a region of memory is freed with `cudaMemFree` and a subsequent call to `cudaMemAlloc` returns memory with the same device address, [cudaIpcGetMemHandle](#) will return a unique handle for the new memory.

Parameters:

- handle* - Pointer to user allocated `cudaIpcMemHandle` to return the handle in.
- devPtr* - Base pointer to previously allocated device memory

Returns:

[cudaSuccess](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorMemoryAllocation](#), [cudaErrorMapBufferObjectFailed](#),

See also:

[cudaMemAlloc](#), [cudaMemFree](#), [cudaIpcGetEventHandle](#), [cudaIpcOpenEventHandle](#), [cudaIpcOpenMemHandle](#), [cudaIpcCloseMemHandle](#)

4.2.2.16 `cudaError_t cudaIpcOpenEventHandle (cudaEvent_t * event, cudaIpcEventHandle_t handle)`

Opens an interprocess event handle exported from another process with [cudaIpcGetEventHandle](#). This function returns a `cudaEvent_t` that behaves like a locally created event with the [cudaEventDisableTiming](#) flag specified. This event must be freed with [cudaEventDestroy](#).

Performing operations on the imported event after the exported event has been freed with [cudaEventDestroy](#) will result in undefined behavior.

Parameters:

event - Returns the imported event
handle - Interprocess handle to open

Returns:

[cudaSuccess](#), [cudaErrorMapBufferObjectFailed](#), [cudaErrorInvalidResourceHandle](#)

See also:

[cudaEventCreate](#), [cudaEventDestroy](#), [cudaEventSynchronize](#), [cudaEventQuery](#), [cudaStreamWaitEvent](#), [cudaIpcGetEventHandle](#), [cudaIpcGetMemHandle](#), [cudaIpcOpenMemHandle](#), [cudaIpcCloseMemHandle](#)

4.2.2.17 [cudaError_t](#) [cudaIpcOpenMemHandle](#) (void ** *devPtr*, [cudaIpcMemHandle_t](#) *handle*)

/brief Opens an interprocess memory handle exported from another process and returns a device pointer usable in the local process.

Maps memory exported from another process with [cudaIpcGetMemHandle](#) into the current device address space. For contexts on different devices [cudaIpcOpenMemHandle](#) will attempt to enable peer access between the devices as if the user called [cudaDeviceEnablePeerAccess](#). Calling [cudaDeviceCanAccessPeer](#) can determine if this mapping is possible.

Calling [cudaMemFree](#) on an exported memory region before calling [cudaIpcCloseMemHandle](#) in the importing context will result in undefined behavior.

Memory returned from [cudaIpcOpenMemHandle](#) must be freed with [cudaIpcCloseMemHandle](#).

Parameters:

devPtr - Returned device pointer
handle - [cudaIpcMemHandle](#) to open

Returns:

[cudaSuccess](#), [cudaErrorMapBufferObjectFailed](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorTooManyPeers](#)

See also:

[cudaMemAlloc](#), [cudaMemFree](#), [cudaIpcGetEventHandle](#), [cudaIpcOpenEventHandle](#), [cudaIpcGetMemHandle](#), [cudaIpcCloseMemHandle](#), [cudaDeviceEnablePeerAccess](#), [cudaDeviceCanAccessPeer](#),

4.2.2.18 [cudaError_t](#) [cudaSetDevice](#) (int *device*)

Sets *device* as the current device for the calling host thread.

Any device memory subsequently allocated from this host thread using [cudaMalloc\(\)](#), [cudaMallocPitch\(\)](#) or [cudaMallocArray\(\)](#) will be physically resident on *device*. Any host memory allocated from this host thread using [cudaMallocHost\(\)](#) or [cudaHostAlloc\(\)](#) or [cudaHostRegister\(\)](#) will have its lifetime associated with *device*. Any streams or events created from this host thread will be associated with *device*. Any kernels launched from this host thread using the <<<>>> operator or [cudaLaunch\(\)](#) will be executed on *device*.

This call may be made from any host thread, to any device, and at any time. This function will do no synchronization with the previous or new device, and should be considered a very low overhead call.

Parameters:

device - Device on which the active host thread should execute the device code.

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#), [cudaErrorDeviceAlreadyInUse](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGetDeviceCount](#), [cudaGetDevice](#), [cudaGetDeviceProperties](#), [cudaChooseDevice](#)

4.2.2.19 `cudaError_t cudaSetDeviceFlags (unsigned int flags)`

Records *flags* as the flags to use when initializing the current device. If no device has been made current to the calling thread then *flags* will be applied to the initialization of any device initialized by the calling host thread, unless that device has had its initialization flags set explicitly by this or any host thread.

If the current device has been set and that device has already been initialized then this call will fail with the error [cudaErrorSetOnActiveProcess](#). In this case it is necessary to reset *device* using [cudaDeviceReset\(\)](#) before the device's initialization flags may be set.

The two LSBs of the *flags* parameter can be used to control how the CPU thread interacts with the OS scheduler when waiting for results from the device.

- [cudaDeviceScheduleAuto](#): The default value if the *flags* parameter is zero, uses a heuristic based on the number of active CUDA contexts in the process *C* and the number of logical processors in the system *P*. If $C > P$, then CUDA will yield to other OS threads when waiting for the device, otherwise CUDA will not yield while waiting for results and actively spin on the processor.
- [cudaDeviceScheduleSpin](#): Instruct CUDA to actively spin when waiting for results from the device. This can decrease latency when waiting for the device, but may lower the performance of CPU threads if they are performing work in parallel with the CUDA thread.
- [cudaDeviceScheduleYield](#): Instruct CUDA to yield its thread when waiting for results from the device. This can increase latency when waiting for the device, but can increase the performance of CPU threads performing work in parallel with the device.
- [cudaDeviceScheduleBlockingSync](#): Instruct CUDA to block the CPU thread on a synchronization primitive when waiting for the device to finish work.
- [cudaDeviceBlockingSync](#): Instruct CUDA to block the CPU thread on a synchronization primitive when waiting for the device to finish work.
Deprecated: This flag was deprecated as of CUDA 4.0 and replaced with [cudaDeviceScheduleBlockingSync](#).
- [cudaDeviceMapHost](#): This flag must be set in order to allocate pinned host memory that is accessible to the device. If this flag is not set, [cudaHostGetDevicePointer\(\)](#) will always return a failure code.
- [cudaDeviceLmemResizeToMax](#): Instruct CUDA to not reduce local memory after resizing local memory for a kernel. This can prevent thrashing by local memory allocations when launching many kernels with high local memory usage at the cost of potentially increased memory usage.

Parameters:

flags - Parameters for device operation

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#), [cudaErrorSetOnActiveProcess](#)

See also:

[cudaGetDeviceCount](#), [cudaGetDevice](#), [cudaGetDeviceProperties](#), [cudaSetDevice](#), [cudaSetValidDevices](#), [cudaChooseDevice](#)

4.2.2.20 `cudaError_t cudaSetValidDevices (int * device_arr, int len)`

Sets a list of devices for CUDA execution in priority order using `device_arr`. The parameter `len` specifies the number of elements in the list. CUDA will try devices from the list sequentially until it finds one that works. If this function is not called, or if it is called with a `len` of 0, then CUDA will go back to its default behavior of trying devices sequentially from a default list containing all of the available CUDA devices in the system. If a specified device ID in the list does not exist, this function will return [cudaErrorInvalidDevice](#). If `len` is not 0 and `device_arr` is NULL or if `len` exceeds the number of devices in the system, then [cudaErrorInvalidValue](#) is returned.

Parameters:

device_arr - List of devices to try

len - Number of devices in specified list

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevice](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGetDeviceCount](#), [cudaSetDevice](#), [cudaGetDeviceProperties](#), [cudaSetDeviceFlags](#), [cudaChooseDevice](#)

4.3 Thread Management [DEPRECATED]

Functions

- `cudaError_t cudaThreadExit` (void)
Exit and clean up from CUDA launches.
- `cudaError_t cudaThreadGetCacheConfig` (enum `cudaFuncCache` *pCacheConfig)
Returns the preferred cache configuration for the current device.
- `cudaError_t cudaThreadGetLimit` (size_t *pValue, enum `cudaLimit` limit)
Returns resource limits.
- `cudaError_t cudaThreadSetCacheConfig` (enum `cudaFuncCache` cacheConfig)
Sets the preferred cache configuration for the current device.
- `cudaError_t cudaThreadSetLimit` (enum `cudaLimit` limit, size_t value)
Set resource limits.
- `cudaError_t cudaThreadSynchronize` (void)
Wait for compute device to finish.

4.3.1 Detailed Description

This section describes deprecated thread management functions of the CUDA runtime application programming interface.

4.3.2 Function Documentation

4.3.2.1 `cudaError_t cudaThreadExit` (void)

Deprecated

Note that this function is deprecated because its name does not reflect its behavior. Its functionality is identical to the non-deprecated function `cudaDeviceReset()`, which should be used instead.

Explicitly destroys all cleans up all resources associated with the current device in the current process. Any subsequent API call to this device will reinitialize the device.

Note that this function will reset the device immediately. It is the caller's responsibility to ensure that the device is not being accessed by any other host threads from the process when this function is called.

Returns:

`cudaSuccess`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceReset](#)

4.3.2.2 `cudaError_t cudaThreadGetCacheConfig (enum cudaFuncCache * pCacheConfig)`

Deprecated

Note that this function is deprecated because its name does not reflect its behavior. Its functionality is identical to the non-deprecated function [cudaDeviceGetCacheConfig\(\)](#), which should be used instead.

On devices where the L1 cache and shared memory use the same hardware resources, this returns through `pCacheConfig` the preferred cache configuration for the current device. This is only a preference. The runtime will use the requested configuration if possible, but it is free to choose a different configuration if required to execute functions.

This will return a `pCacheConfig` of [cudaFuncCachePreferNone](#) on devices where the size of the L1 cache and shared memory are fixed.

The supported cache configurations are:

- [cudaFuncCachePreferNone](#): no preference for shared memory or L1 (default)
- [cudaFuncCachePreferShared](#): prefer larger shared memory and smaller L1 cache
- [cudaFuncCachePreferL1](#): prefer larger L1 cache and smaller shared memory

Parameters:

pCacheConfig - Returned cache configuration

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceGetCacheConfig](#)

4.3.2.3 `cudaError_t cudaThreadGetLimit (size_t * pValue, enum cudaLimit limit)`

Deprecated

Note that this function is deprecated because its name does not reflect its behavior. Its functionality is identical to the non-deprecated function [cudaDeviceGetLimit\(\)](#), which should be used instead.

Returns in `*pValue` the current size of `limit`. The supported [cudaLimit](#) values are:

- [cudaLimitStackSize](#): stack size of each GPU thread;

- [cudaLimitPrintfFifoSize](#): size of the shared FIFO used by the `printf()` and `fprintf()` device system calls.
- [cudaLimitMallocHeapSize](#): size of the heap used by the `malloc()` and `free()` device system calls;

Parameters:

limit - Limit to query

pValue - Returned size in bytes of limit

Returns:

[cudaSuccess](#), [cudaErrorUnsupportedLimit](#), [cudaErrorInvalidValue](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceGetLimit](#)

4.3.2.4 `cudaError_t cudaThreadSetCacheConfig (enum cudaFuncCache cacheConfig)`

Deprecated

Note that this function is deprecated because its name does not reflect its behavior. Its functionality is identical to the non-deprecated function [cudaDeviceSetCacheConfig\(\)](#), which should be used instead.

On devices where the L1 cache and shared memory use the same hardware resources, this sets through `cacheConfig` the preferred cache configuration for the current device. This is only a preference. The runtime will use the requested configuration if possible, but it is free to choose a different configuration if required to execute the function. Any function preference set via [cudaFuncSetCacheConfig \(C API\)](#) or [cudaFuncSetCacheConfig \(C++ API\)](#) will be preferred over this device-wide setting. Setting the device-wide cache configuration to [cudaFuncCachePreferNone](#) will cause subsequent kernel launches to prefer to not change the cache configuration unless required to launch the kernel.

This setting does nothing on devices where the size of the L1 cache and shared memory are fixed.

Launching a kernel with a different preference than the most recent preference setting may insert a device-side synchronization point.

The supported cache configurations are:

- [cudaFuncCachePreferNone](#): no preference for shared memory or L1 (default)
- [cudaFuncCachePreferShared](#): prefer larger shared memory and smaller L1 cache
- [cudaFuncCachePreferL1](#): prefer larger L1 cache and smaller shared memory

Parameters:

cacheConfig - Requested cache configuration

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceSetCacheConfig](#)

4.3.2.5 `cudaError_t cudaThreadSetLimit (enum cudaLimit limit, size_t value)`**Deprecated**

Note that this function is deprecated because its name does not reflect its behavior. Its functionality is identical to the non-deprecated function [cudaDeviceSetLimit\(\)](#), which should be used instead.

Setting `limit` to `value` is a request by the application to update the current limit maintained by the device. The driver is free to modify the requested value to meet h/w requirements (this could be clamping to minimum or maximum values, rounding up to nearest element size, etc). The application can use [cudaThreadGetLimit\(\)](#) to find out exactly what the limit has been set to.

Setting each [cudaLimit](#) has its own specific restrictions, so each is discussed here.

- [cudaLimitStackSize](#) controls the stack size of each GPU thread. This limit is only applicable to devices of compute capability 2.0 and higher. Attempting to set this limit on devices of compute capability less than 2.0 will result in the error [cudaErrorUnsupportedLimit](#) being returned.
- [cudaLimitPrintfFifoSize](#) controls the size of the shared FIFO used by the `printf()` and `fprintf()` device system calls. Setting [cudaLimitPrintfFifoSize](#) must be performed before launching any kernel that uses the `printf()` or `fprintf()` device system calls, otherwise [cudaErrorInvalidValue](#) will be returned. This limit is only applicable to devices of compute capability 2.0 and higher. Attempting to set this limit on devices of compute capability less than 2.0 will result in the error [cudaErrorUnsupportedLimit](#) being returned.
- [cudaLimitMallocHeapSize](#) controls the size of the heap used by the `malloc()` and `free()` device system calls. Setting [cudaLimitMallocHeapSize](#) must be performed before launching any kernel that uses the `malloc()` or `free()` device system calls, otherwise [cudaErrorInvalidValue](#) will be returned. This limit is only applicable to devices of compute capability 2.0 and higher. Attempting to set this limit on devices of compute capability less than 2.0 will result in the error [cudaErrorUnsupportedLimit](#) being returned.

Parameters:

limit - Limit to set

value - Size in bytes of limit

Returns:

[cudaSuccess](#), [cudaErrorUnsupportedLimit](#), [cudaErrorInvalidValue](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceSetLimit](#)

4.3.2.6 `cudaError_t cudaThreadSynchronize (void)`

Deprecated

Note that this function is deprecated because its name does not reflect its behavior. Its functionality is similar to the non-deprecated function [cudaDeviceSynchronize\(\)](#), which should be used instead.

Blocks until the device has completed all preceding requested tasks. [cudaThreadSynchronize\(\)](#) returns an error if one of the preceding tasks has failed. If the [cudaDeviceScheduleBlockingSync](#) flag was set for this device, the host thread will block until the device has finished its work.

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceSynchronize](#)

4.4 Error Handling

Functions

- `const char * cudaGetErrorString (cudaError_t error)`
Returns the message string from an error code.
- `cudaError_t cudaGetLastError (void)`
Returns the last error from a runtime call.
- `cudaError_t cudaPeekAtLastError (void)`
Returns the last error from a runtime call.

4.4.1 Detailed Description

This section describes the error handling functions of the CUDA runtime application programming interface.

4.4.2 Function Documentation

4.4.2.1 `const char* cudaGetErrorString (cudaError_t error)`

Returns the message string from an error code.

Parameters:

error - Error code to convert to string

Returns:

char* pointer to a NULL-terminated string

See also:

[cudaGetLastError](#), [cudaPeekAtLastError](#), [cudaError](#)

4.4.2.2 `cudaError_t cudaGetLastError (void)`

Returns the last error that has been produced by any of the runtime calls in the same host thread and resets it to [cudaSuccess](#).

Returns:

[cudaSuccess](#), [cudaErrorMissingConfiguration](#), [cudaErrorMemoryAllocation](#), [cudaErrorInitializationError](#), [cudaErrorLaunchFailure](#), [cudaErrorLaunchTimeout](#), [cudaErrorLaunchOutOfResources](#), [cudaErrorInvalidDeviceFunction](#), [cudaErrorInvalidConfiguration](#), [cudaErrorInvalidDevice](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidPitchValue](#), [cudaErrorInvalidSymbol](#), [cudaErrorUnmapBufferObjectFailed](#), [cudaErrorInvalidHostPointer](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidTexture](#), [cudaErrorInvalidTextureBinding](#), [cudaErrorInvalidChannelDescriptor](#), [cudaErrorInvalidMemcpyDirection](#), [cudaErrorInvalidFilterSetting](#), [cudaErrorInvalidNormSetting](#), [cudaErrorUnknown](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorInsufficientDriver](#), [cudaErrorSetOnActiveProcess](#), [cudaErrorStartupFailure](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaPeekAtLastError](#), [cudaGetErrorString](#), [cudaError](#)

4.4.2.3 `cudaError_t cudaPeekAtLastError (void)`

Returns the last error that has been produced by any of the runtime calls in the same host thread. Note that this call does not reset the error to [cudaSuccess](#) like [cudaGetLastError\(\)](#).

Returns:

[cudaSuccess](#), [cudaErrorMissingConfiguration](#), [cudaErrorMemoryAllocation](#), [cudaErrorInitializationError](#), [cudaErrorLaunchFailure](#), [cudaErrorLaunchTimeout](#), [cudaErrorLaunchOutOfResources](#), [cudaErrorInvalidDeviceFunction](#), [cudaErrorInvalidConfiguration](#), [cudaErrorInvalidDevice](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidPitchValue](#), [cudaErrorInvalidSymbol](#), [cudaErrorUnmapBufferObjectFailed](#), [cudaErrorInvalidHostPointer](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidTexture](#), [cudaErrorInvalidTextureBinding](#), [cudaErrorInvalidChannelDescriptor](#), [cudaErrorInvalidMemcpyDirection](#), [cudaErrorInvalidFilterSetting](#), [cudaErrorInvalidNormSetting](#), [cudaErrorUnknown](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorInsufficientDriver](#), [cudaErrorSetOnActiveProcess](#), [cudaErrorStartupFailure](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGetLastError](#), [cudaGetErrorString](#), [cudaError](#)

4.5 Stream Management

Functions

- [cudaError_t cudaStreamCreate \(cudaStream_t *pStream\)](#)
Create an asynchronous stream.
- [cudaError_t cudaStreamDestroy \(cudaStream_t stream\)](#)
Destroys and cleans up an asynchronous stream.
- [cudaError_t cudaStreamQuery \(cudaStream_t stream\)](#)
Queries an asynchronous stream for completion status.
- [cudaError_t cudaStreamSynchronize \(cudaStream_t stream\)](#)
Waits for stream tasks to complete.
- [cudaError_t cudaStreamWaitEvent \(cudaStream_t stream, cudaEvent_t event, unsigned int flags\)](#)
Make a compute stream wait on an event.

4.5.1 Detailed Description

This section describes the stream management functions of the CUDA runtime application programming interface.

4.5.2 Function Documentation

4.5.2.1 [cudaError_t cudaStreamCreate \(cudaStream_t *pStream\)](#)

Creates a new asynchronous stream.

Parameters:

pStream - Pointer to new stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaStreamQuery](#), [cudaStreamSynchronize](#), [cudaStreamWaitEvent](#), [cudaStreamDestroy](#)

4.5.2.2 [cudaError_t cudaStreamDestroy \(cudaStream_t stream\)](#)

Destroys and cleans up the asynchronous stream specified by `stream`.

In the case that the device is still doing work in the stream `stream` when [cudaStreamDestroy\(\)](#) is called, the function will return immediately and the resources associated with `stream` will be released automatically once the device has completed all work in `stream`.

Parameters:

stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidResourceHandle](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaStreamCreate](#), [cudaStreamQuery](#), [cudaStreamWaitEvent](#), [cudaStreamSynchronize](#)

4.5.2.3 [cudaError_t cudaStreamQuery \(cudaStream_t stream\)](#)

Returns [cudaSuccess](#) if all operations in `stream` have completed, or [cudaErrorNotReady](#) if not.

Parameters:

stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorNotReady](#), [cudaErrorInvalidResourceHandle](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaStreamCreate](#), [cudaStreamWaitEvent](#), [cudaStreamSynchronize](#), [cudaStreamDestroy](#)

4.5.2.4 [cudaError_t cudaStreamSynchronize \(cudaStream_t stream\)](#)

Blocks until `stream` has completed all operations. If the [cudaDeviceScheduleBlockingSync](#) flag was set for this device, the host thread will block until the stream is finished with all of its tasks.

Parameters:

stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidResourceHandle](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaStreamCreate](#), [cudaStreamQuery](#), [cudaStreamWaitEvent](#), [cudaStreamDestroy](#)

4.5.2.5 `cudaError_t cudaStreamWaitEvent(cudaStream_t stream, cudaEvent_t event, unsigned int flags)`

Makes all future work submitted to `stream` wait until `event` reports completion before beginning execution. This synchronization will be performed efficiently on the device. The event `event` may be from a different context than `stream`, in which case this function will perform cross-device synchronization.

The stream `stream` will wait only for the completion of the most recent host call to [cudaEventRecord\(\)](#) on `event`. Once this call has returned, any functions (including [cudaEventRecord\(\)](#) and [cudaEventDestroy\(\)](#)) may be called on `event` again, and the subsequent calls will not have any effect on `stream`.

If `stream` is NULL, any future work submitted in any stream will wait for `event` to complete before beginning execution. This effectively creates a barrier for all future work submitted to the device on this thread.

If [cudaEventRecord\(\)](#) has not been called on `event`, this call acts as if the record has already completed, and so is a functional no-op.

Parameters:

stream - Stream to wait

event - Event to wait on

flags - Parameters for the operation (must be 0)

Returns:

[cudaSuccess](#), [cudaErrorInvalidResourceHandle](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaStreamCreate](#), [cudaStreamQuery](#), [cudaStreamSynchronize](#), [cudaStreamDestroy](#)

4.6 Event Management

Functions

- [cudaError_t cudaEventCreate](#) ([cudaEvent_t](#) *event)
Creates an event object.
- [cudaError_t cudaEventCreateWithFlags](#) ([cudaEvent_t](#) *event, unsigned int flags)
Creates an event object with the specified flags.
- [cudaError_t cudaEventDestroy](#) ([cudaEvent_t](#) event)
Destroys an event object.
- [cudaError_t cudaEventElapsedTime](#) (float *ms, [cudaEvent_t](#) start, [cudaEvent_t](#) end)
Computes the elapsed time between events.
- [cudaError_t cudaEventQuery](#) ([cudaEvent_t](#) event)
Queries an event's status.
- [cudaError_t cudaEventRecord](#) ([cudaEvent_t](#) event, [cudaStream_t](#) stream=0)
Records an event.
- [cudaError_t cudaEventSynchronize](#) ([cudaEvent_t](#) event)
Waits for an event to complete.

4.6.1 Detailed Description

This section describes the event management functions of the CUDA runtime application programming interface.

4.6.2 Function Documentation

4.6.2.1 [cudaError_t cudaEventCreate](#) ([cudaEvent_t](#) * event)

Creates an event object using [cudaEventDefault](#).

Parameters:

event - Newly created event

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#), [cudaErrorInvalidValue](#), [cudaErrorLaunchFailure](#), [cudaErrorMemoryAllocation](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaEventCreate](#) (C++ API), [cudaEventCreateWithFlags](#), [cudaEventRecord](#), [cudaEventQuery](#), [cudaEventSynchronize](#), [cudaEventDestroy](#), [cudaEventElapsedTime](#), [cudaStreamWaitEvent](#)

4.6.2.2 `cudaError_t cudaEventCreateWithFlags(cudaEvent_t * event, unsigned int flags)`

Creates an event object with the specified flags. Valid flags include:

- `cudaEventDefault`: Default event creation flag.
- `cudaEventBlockingSync`: Specifies that event should use blocking synchronization. A host thread that uses `cudaEventSynchronize()` to wait on an event created with this flag will block until the event actually completes.
- `cudaEventDisableTiming`: Specifies that the created event does not need to record timing data. Events created with this flag specified and the `cudaEventBlockingSync` flag not specified will provide the best performance when used with `cudaStreamWaitEvent()` and `cudaEventQuery()`.

Parameters:

event - Newly created event

flags - Flags for new event

Returns:

`cudaSuccess`, `cudaErrorInitializationError`, `cudaErrorInvalidValue`, `cudaErrorLaunchFailure`, `cudaErrorMemoryAllocation`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaEventCreate` (C API), `cudaEventSynchronize`, `cudaEventDestroy`, `cudaEventElapsedTime`, `cudaStreamWaitEvent`

4.6.2.3 `cudaError_t cudaEventDestroy(cudaEvent_t event)`

Destroys the event specified by `event`.

In the case that `event` has been recorded but has not yet been completed when `cudaEventDestroy()` is called, the function will return immediately and the resources associated with `event` will be released automatically once the device has completed `event`.

Parameters:

event - Event to destroy

Returns:

`cudaSuccess`, `cudaErrorInitializationError`, `cudaErrorInvalidValue`, `cudaErrorLaunchFailure`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaEventCreate` (C API), `cudaEventCreateWithFlags`, `cudaEventQuery`, `cudaEventSynchronize`, `cudaEventRecord`, `cudaEventElapsedTime`

4.6.2.4 `cudaError_t cudaEventElapsedTime (float * ms, cudaEvent_t start, cudaEvent_t end)`

Computes the elapsed time between two events (in milliseconds with a resolution of around 0.5 microseconds).

If either event was last recorded in a non-NULL stream, the resulting time may be greater than expected (even if both used the same stream handle). This happens because the `cudaEventRecord()` operation takes place asynchronously and there is no guarantee that the measured latency is actually just between the two events. Any number of other different stream operations could execute in between the two measured events, thus altering the timing in a significant way.

If `cudaEventRecord()` has not been called on either event, then `cudaErrorInvalidResourceHandle` is returned. If `cudaEventRecord()` has been called on both events but one or both of them has not yet been completed (that is, `cudaEventQuery()` would return `cudaErrorNotReady` on at least one of the events), `cudaErrorNotReady` is returned. If either event was created with the `cudaEventDisableTiming` flag, then this function will return `cudaErrorInvalidResourceHandle`.

Parameters:

ms - Time between *start* and *end* in ms
start - Starting event
end - Ending event

Returns:

`cudaSuccess`, `cudaErrorNotReady`, `cudaErrorInvalidValue`, `cudaErrorInitializationError`, `cudaErrorInvalidResourceHandle`, `cudaErrorLaunchFailure`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaEventCreate` (C API), `cudaEventCreateWithFlags`, `cudaEventQuery`, `cudaEventSynchronize`, `cudaEventDestroy`, `cudaEventRecord`

4.6.2.5 `cudaError_t cudaEventQuery (cudaEvent_t event)`

Query the status of all device work preceding the most recent call to `cudaEventRecord()` (in the appropriate compute streams, as specified by the arguments to `cudaEventRecord()`).

If this work has successfully been completed by the device, or if `cudaEventRecord()` has not been called on *event*, then `cudaSuccess` is returned. If this work has not yet been completed by the device then `cudaErrorNotReady` is returned.

Parameters:

event - Event to query

Returns:

`cudaSuccess`, `cudaErrorNotReady`, `cudaErrorInitializationError`, `cudaErrorInvalidValue`, `cudaErrorInvalidResourceHandle`, `cudaErrorLaunchFailure`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaEventCreate` (C API), `cudaEventCreateWithFlags`, `cudaEventRecord`, `cudaEventSynchronize`, `cudaEventDestroy`, `cudaEventElapsedTime`

4.6.2.6 `cudaError_t cudaEventRecord(cudaEvent_t event, cudaStream_t stream = 0)`

Records an event. If `stream` is non-zero, the event is recorded after all preceding operations in `stream` have been completed; otherwise, it is recorded after all preceding operations in the CUDA context have been completed. Since operation is asynchronous, [cudaEventQuery\(\)](#) and/or [cudaEventSynchronize\(\)](#) must be used to determine when the event has actually been recorded.

If [cudaEventRecord\(\)](#) has previously been called on `event`, then this call will overwrite any existing state in `event`. Any subsequent calls which examine the status of `event` will only examine the completion of this most recent call to [cudaEventRecord\(\)](#).

Parameters:

event - Event to record
stream - Stream in which to record event

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInitializationError](#), [cudaErrorInvalidResourceHandle](#), [cudaError-LaunchFailure](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaEventCreate](#) (C API), [cudaEventCreateWithFlags](#), [cudaEventQuery](#), [cudaEventSynchronize](#), [cudaEventDestroy](#), [cudaEventElapsedTime](#), [cudaStreamWaitEvent](#)

4.6.2.7 `cudaError_t cudaEventSynchronize(cudaEvent_t event)`

Wait until the completion of all device work preceding the most recent call to [cudaEventRecord\(\)](#) (in the appropriate compute streams, as specified by the arguments to [cudaEventRecord\(\)](#)).

If [cudaEventRecord\(\)](#) has not been called on `event`, [cudaSuccess](#) is returned immediately.

Waiting for an event that was created with the [cudaEventBlockingSync](#) flag will cause the calling CPU thread to block until the event has been completed by the device. If the [cudaEventBlockingSync](#) flag has not been set, then the CPU thread will busy-wait until the event has been completed by the device.

Parameters:

event - Event to wait for

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaError-LaunchFailure](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaEventCreate](#) (C API), [cudaEventCreateWithFlags](#), [cudaEventRecord](#), [cudaEventQuery](#), [cudaEventDestroy](#), [cudaEventElapsedTime](#)

4.7 Execution Control

Functions

- `cudaError_t cudaConfigureCall` (`dim3 gridDim`, `dim3 blockDim`, `size_t sharedMem=0`, `cudaStream_t stream=0`)
Configure a device-launch.
- `cudaError_t cudaFuncGetAttributes` (`struct cudaFuncAttributes *attr`, `const char *func`)
Find out attributes for a given function.
- `cudaError_t cudaFuncSetCacheConfig` (`const char *func`, `enum cudaFuncCache cacheConfig`)
Sets the preferred cache configuration for a device function.
- `cudaError_t cudaLaunch` (`const char *entry`)
Launches a device function.
- `cudaError_t cudaSetDoubleForDevice` (`double *d`)
Converts a double argument to be executed on a device.
- `cudaError_t cudaSetDoubleForHost` (`double *d`)
Converts a double argument after execution on a device.
- `cudaError_t cudaSetupArgument` (`const void *arg`, `size_t size`, `size_t offset`)
Configure a device launch.

4.7.1 Detailed Description

This section describes the execution control functions of the CUDA runtime application programming interface.

4.7.2 Function Documentation

4.7.2.1 `cudaError_t cudaConfigureCall` (`dim3 gridDim`, `dim3 blockDim`, `size_t sharedMem = 0`, `cudaStream_t stream = 0`)

Specifies the grid and block dimensions for the device call to be executed similar to the execution configuration syntax. `cudaConfigureCall()` is stack based. Each call pushes data on top of an execution stack. This data contains the dimension for the grid and thread blocks, together with any arguments for the call.

Parameters:

gridDim - Grid dimensions
blockDim - Block dimensions
sharedMem - Shared memory
stream - Stream identifier

Returns:

`cudaSuccess`, `cudaErrorInvalidConfiguration`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaFuncSetCacheConfig \(C API\)](#), [cudaFuncGetAttributes \(C API\)](#), [cudaLaunch \(C API\)](#), [cudaSetDoubleForDevice](#), [cudaSetDoubleForHost](#), [cudaSetupArgument \(C API\)](#),

4.7.2.2 `cudaError_t cudaFuncGetAttributes (struct cudaFuncAttributes * attr, const char * func)`

This function obtains the attributes of a function specified via `func`, which is a character string that specifies the fully-decorated (C++) name for a function that executes on the device. The parameter specified by `func` must be declared as a `__global__` function. The fetched attributes are placed in `attr`. If the specified function does not exist, then [cudaErrorInvalidDeviceFunction](#) is returned.

Note that some function attributes such as [maxThreadsPerBlock](#) may vary based on the device that is currently being used.

Parameters:

attr - Return pointer to function's attributes

func - Function to get attributes of

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#), [cudaErrorInvalidDeviceFunction](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaConfigureCall](#), [cudaFuncSetCacheConfig \(C API\)](#), [cudaFuncGetAttributes \(C++ API\)](#), [cudaLaunch \(C API\)](#), [cudaSetDoubleForDevice](#), [cudaSetDoubleForHost](#), [cudaSetupArgument \(C API\)](#)

4.7.2.3 `cudaError_t cudaFuncSetCacheConfig (const char * func, enum cudaFuncCache cacheConfig)`

On devices where the L1 cache and shared memory use the same hardware resources, this sets through `cacheConfig` the preferred cache configuration for the function specified via `func`. This is only a preference. The runtime will use the requested configuration if possible, but it is free to choose a different configuration if required to execute `func`.

`func` is a character string that specifies the fully-decorated (C++) name for a function that executes on the device. The parameter specified by `func` must be declared as a `__global__` function. If the specified function does not exist, then [cudaErrorInvalidDeviceFunction](#) is returned.

This setting does nothing on devices where the size of the L1 cache and shared memory are fixed.

Launching a kernel with a different preference than the most recent preference setting may insert a device-side synchronization point.

The supported cache configurations are:

- [cudaFuncCachePreferNone](#): no preference for shared memory or L1 (default)
- [cudaFuncCachePreferShared](#): prefer larger shared memory and smaller L1 cache

- [cudaFuncCachePreferL1](#): prefer larger L1 cache and smaller shared memory

Parameters:

func - Char string naming device function

cacheConfig - Requested cache configuration

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#), [cudaErrorInvalidDeviceFunction](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaConfigureCall](#), [cudaFuncSetCacheConfig](#) (C++ API), [cudaFuncGetAttributes](#) (C API), [cudaLaunch](#) (C API), [cudaSetDoubleForDevice](#), [cudaSetDoubleForHost](#), [cudaSetupArgument](#) (C API), [cudaThreadGetCacheConfig](#), [cudaThreadSetCacheConfig](#)

4.7.2.4 [cudaError_t](#) [cudaLaunch](#) (const char * *entry*)

Launches the function *entry* on the device. The parameter *entry* must be a character string naming a function that executes on the device. The parameter specified by *entry* must be declared as a `__global__` function. [cudaLaunch\(\)](#) must be preceded by a call to [cudaConfigureCall\(\)](#) since it pops the data that was pushed by [cudaConfigureCall\(\)](#) from the execution stack.

Parameters:

entry - Device char string naming device function to execute

Returns:

[cudaSuccess](#), [cudaErrorInvalidDeviceFunction](#), [cudaErrorInvalidConfiguration](#), [cudaErrorLaunchFailure](#), [cudaErrorLaunchTimeout](#), [cudaErrorLaunchOutOfResources](#), [cudaErrorSharedObjectInitFailed](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaConfigureCall](#), [cudaFuncSetCacheConfig](#) (C API), [cudaFuncGetAttributes](#) (C API), [cudaLaunch](#) (C++ API), [cudaSetDoubleForDevice](#), [cudaSetDoubleForHost](#), [cudaSetupArgument](#) (C API), [cudaThreadGetCacheConfig](#), [cudaThreadSetCacheConfig](#)

4.7.2.5 [cudaError_t](#) [cudaSetDoubleForDevice](#) (double * *d*)**Parameters:**

d - Double to convert

Converts the double value of *d* to an internal float representation if the device does not support double arithmetic. If the device does natively support doubles, then this function does nothing.

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaConfigureCall](#), [cudaFuncSetCacheConfig](#) (C API), [cudaFuncGetAttributes](#) (C API), [cudaLaunch](#) (C API), [cudaSetDoubleForHost](#), [cudaSetupArgument](#) (C API)

4.7.2.6 `cudaError_t cudaSetDoubleForHost (double * d)`

Converts the double value of `d` from a potentially internal float representation if the device does not support double arithmetic. If the device does natively support doubles, then this function does nothing.

Parameters:

d - Double to convert

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaConfigureCall](#), [cudaFuncSetCacheConfig](#) (C API), [cudaFuncGetAttributes](#) (C API), [cudaLaunch](#) (C API), [cudaSetDoubleForDevice](#), [cudaSetupArgument](#) (C API)

4.7.2.7 `cudaError_t cudaSetupArgument (const void * arg, size_t size, size_t offset)`

Pushes `size` bytes of the argument pointed to by `arg` at `offset` bytes from the start of the parameter passing area, which starts at offset 0. The arguments are stored in the top of the execution stack. [cudaSetupArgument\(\)](#) must be preceded by a call to [cudaConfigureCall\(\)](#).

Parameters:

arg - Argument to push for a kernel launch

size - Size of argument

offset - Offset in argument stack to push new arg

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaConfigureCall](#), [cudaFuncSetCacheConfig](#) (C API), [cudaFuncGetAttributes](#) (C API), [cudaLaunch](#) (C API), [cudaSetDoubleForDevice](#), [cudaSetDoubleForHost](#), [cudaSetupArgument](#) (C++ API),

4.8 Memory Management

Functions

- [cudaError_t cudaFree](#) (void *devPtr)
Frees memory on the device.
- [cudaError_t cudaFreeArray](#) (struct cudaArray *array)
Frees an array on the device.
- [cudaError_t cudaFreeHost](#) (void *ptr)
Frees page-locked memory.
- [cudaError_t cudaGetSymbolAddress](#) (void **devPtr, const char *symbol)
Finds the address associated with a CUDA symbol.
- [cudaError_t cudaGetSymbolSize](#) (size_t *size, const char *symbol)
Finds the size of the object associated with a CUDA symbol.
- [cudaError_t cudaHostAlloc](#) (void **pHost, size_t size, unsigned int flags)
Allocates page-locked memory on the host.
- [cudaError_t cudaHostGetDevicePointer](#) (void **pDevice, void *pHost, unsigned int flags)
Passes back device pointer of mapped host memory allocated by [cudaHostAlloc\(\)](#) or registered by [cudaHostRegister\(\)](#).
- [cudaError_t cudaHostGetFlags](#) (unsigned int *pFlags, void *pHost)
Passes back flags used to allocate pinned host memory allocated by [cudaHostAlloc\(\)](#).
- [cudaError_t cudaHostRegister](#) (void *ptr, size_t size, unsigned int flags)
Registers an existing host memory range for use by CUDA.
- [cudaError_t cudaHostUnregister](#) (void *ptr)
Unregisters a memory range that was registered with [cudaHostRegister\(\)](#).
- [cudaError_t cudaMalloc](#) (void **devPtr, size_t size)
Allocate memory on the device.
- [cudaError_t cudaMalloc3D](#) (struct [cudaPitchedPtr](#) *pitchedDevPtr, struct [cudaExtent](#) extent)
Allocates logical 1D, 2D, or 3D memory objects on the device.
- [cudaError_t cudaMalloc3DArray](#) (struct cudaArray **array, const struct [cudaChannelFormatDesc](#) *desc, struct [cudaExtent](#) extent, unsigned int flags=0)
Allocate an array on the device.
- [cudaError_t cudaMallocArray](#) (struct cudaArray **array, const struct [cudaChannelFormatDesc](#) *desc, size_t width, size_t height=0, unsigned int flags=0)
Allocate an array on the device.
- [cudaError_t cudaMallocHost](#) (void **ptr, size_t size)
Allocates page-locked memory on the host.

- [cudaError_t cudaMallocPitch](#) (void **devPtr, size_t *pitch, size_t width, size_t height)
Allocates pitched memory on the device.
- [cudaError_t cudaMemcpy](#) (void *dst, const void *src, size_t count, enum [cudaMemcpyKind](#) kind)
Copies data between host and device.
- [cudaError_t cudaMemcpy2D](#) (void *dst, size_t dpitch, const void *src, size_t spitch, size_t width, size_t height, enum [cudaMemcpyKind](#) kind)
Copies data between host and device.
- [cudaError_t cudaMemcpy2DArrayToArray](#) (struct [cudaArray](#) *dst, size_t wOffsetDst, size_t hOffsetDst, const struct [cudaArray](#) *src, size_t wOffsetSrc, size_t hOffsetSrc, size_t width, size_t height, enum [cudaMemcpyKind](#) kind=[cudaMemcpyDeviceToDevice](#))
Copies data between host and device.
- [cudaError_t cudaMemcpy2DAsync](#) (void *dst, size_t dpitch, const void *src, size_t spitch, size_t width, size_t height, enum [cudaMemcpyKind](#) kind, [cudaStream_t](#) stream=0)
Copies data between host and device.
- [cudaError_t cudaMemcpy2DFromArray](#) (void *dst, size_t dpitch, const struct [cudaArray](#) *src, size_t wOffset, size_t hOffset, size_t width, size_t height, enum [cudaMemcpyKind](#) kind)
Copies data between host and device.
- [cudaError_t cudaMemcpy2DFromArrayAsync](#) (void *dst, size_t dpitch, const struct [cudaArray](#) *src, size_t wOffset, size_t hOffset, size_t width, size_t height, enum [cudaMemcpyKind](#) kind, [cudaStream_t](#) stream=0)
Copies data between host and device.
- [cudaError_t cudaMemcpy2DToArray](#) (struct [cudaArray](#) *dst, size_t wOffset, size_t hOffset, const void *src, size_t spitch, size_t width, size_t height, enum [cudaMemcpyKind](#) kind)
Copies data between host and device.
- [cudaError_t cudaMemcpy2DToArrayAsync](#) (struct [cudaArray](#) *dst, size_t wOffset, size_t hOffset, const void *src, size_t spitch, size_t width, size_t height, enum [cudaMemcpyKind](#) kind, [cudaStream_t](#) stream=0)
Copies data between host and device.
- [cudaError_t cudaMemcpy3D](#) (const struct [cudaMemcpy3DParms](#) *p)
Copies data between 3D objects.
- [cudaError_t cudaMemcpy3DAsync](#) (const struct [cudaMemcpy3DParms](#) *p, [cudaStream_t](#) stream=0)
Copies data between 3D objects.
- [cudaError_t cudaMemcpy3DPeer](#) (const struct [cudaMemcpy3DPeerParms](#) *p)
Copies memory between devices.
- [cudaError_t cudaMemcpy3DPeerAsync](#) (const struct [cudaMemcpy3DPeerParms](#) *p, [cudaStream_t](#) stream=0)
Copies memory between devices asynchronously.
- [cudaError_t cudaMemcpyArrayToArray](#) (struct [cudaArray](#) *dst, size_t wOffsetDst, size_t hOffsetDst, const struct [cudaArray](#) *src, size_t wOffsetSrc, size_t hOffsetSrc, size_t count, enum [cudaMemcpyKind](#) kind=[cudaMemcpyDeviceToDevice](#))

Copies data between host and device.

- `cudaError_t cudaMemcpyAsync` (void *dst, const void *src, size_t count, enum `cudaMemcpyKind` kind, `cudaStream_t` stream=0)

Copies data between host and device.

- `cudaError_t cudaMemcpyFromArray` (void *dst, const struct `cudaArray` *src, size_t wOffset, size_t hOffset, size_t count, enum `cudaMemcpyKind` kind)

Copies data between host and device.

- `cudaError_t cudaMemcpyFromArrayAsync` (void *dst, const struct `cudaArray` *src, size_t wOffset, size_t hOffset, size_t count, enum `cudaMemcpyKind` kind, `cudaStream_t` stream=0)

Copies data between host and device.

- `cudaError_t cudaMemcpyFromSymbol` (void *dst, const char *symbol, size_t count, size_t offset=0, enum `cudaMemcpyKind` kind=`cudaMemcpyDeviceToHost`)

Copies data from the given symbol on the device.

- `cudaError_t cudaMemcpyFromSymbolAsync` (void *dst, const char *symbol, size_t count, size_t offset, enum `cudaMemcpyKind` kind, `cudaStream_t` stream=0)

Copies data from the given symbol on the device.

- `cudaError_t cudaMemcpyPeer` (void *dst, int dstDevice, const void *src, int srcDevice, size_t count)

Copies memory between two devices.

- `cudaError_t cudaMemcpyPeerAsync` (void *dst, int dstDevice, const void *src, int srcDevice, size_t count, `cudaStream_t` stream=0)

Copies memory between two devices asynchronously.

- `cudaError_t cudaMemcpyToArray` (struct `cudaArray` *dst, size_t wOffset, size_t hOffset, const void *src, size_t count, enum `cudaMemcpyKind` kind)

Copies data between host and device.

- `cudaError_t cudaMemcpyToArrayAsync` (struct `cudaArray` *dst, size_t wOffset, size_t hOffset, const void *src, size_t count, enum `cudaMemcpyKind` kind, `cudaStream_t` stream=0)

Copies data between host and device.

- `cudaError_t cudaMemcpyToSymbol` (const char *symbol, const void *src, size_t count, size_t offset=0, enum `cudaMemcpyKind` kind=`cudaMemcpyHostToDevice`)

Copies data to the given symbol on the device.

- `cudaError_t cudaMemcpyToSymbolAsync` (const char *symbol, const void *src, size_t count, size_t offset, enum `cudaMemcpyKind` kind, `cudaStream_t` stream=0)

Copies data to the given symbol on the device.

- `cudaError_t cudaMemGetInfo` (size_t *free, size_t *total)

Gets free and total device memory.

- `cudaError_t cudaMemset` (void *devPtr, int value, size_t count)

Initializes or sets device memory to a value.

- [cudaError_t cudaMemset2D](#) (void *devPtr, size_t pitch, int value, size_t width, size_t height)
Initializes or sets device memory to a value.
- [cudaError_t cudaMemset2DAsync](#) (void *devPtr, size_t pitch, int value, size_t width, size_t height, [cudaStream_t](#) stream=0)
Initializes or sets device memory to a value.
- [cudaError_t cudaMemset3D](#) (struct [cudaPitchedPtr](#) pitchedDevPtr, int value, struct [cudaExtent](#) extent)
Initializes or sets device memory to a value.
- [cudaError_t cudaMemset3DAsync](#) (struct [cudaPitchedPtr](#) pitchedDevPtr, int value, struct [cudaExtent](#) extent, [cudaStream_t](#) stream=0)
Initializes or sets device memory to a value.
- [cudaError_t cudaMemsetAsync](#) (void *devPtr, int value, size_t count, [cudaStream_t](#) stream=0)
Initializes or sets device memory to a value.
- struct [cudaExtent](#) [make_cudaExtent](#) (size_t w, size_t h, size_t d)
Returns a [cudaExtent](#) based on input parameters.
- struct [cudaPitchedPtr](#) [make_cudaPitchedPtr](#) (void *d, size_t p, size_t xsz, size_t ysz)
Returns a [cudaPitchedPtr](#) based on input parameters.
- struct [cudaPos](#) [make_cudaPos](#) (size_t x, size_t y, size_t z)
Returns a [cudaPos](#) based on input parameters.

4.8.1 Detailed Description

This section describes the memory management functions of the CUDA runtime application programming interface.

4.8.2 Function Documentation

4.8.2.1 [cudaError_t cudaFree](#) (void * devPtr)

Frees the memory space pointed to by `devPtr`, which must have been returned by a previous call to [cudaMalloc\(\)](#) or [cudaMallocPitch\(\)](#). Otherwise, or if [cudaFree\(devPtr\)](#) has already been called before, an error is returned. If `devPtr` is 0, no operation is performed. [cudaFree\(\)](#) returns [cudaErrorInvalidDevicePointer](#) in case of failure.

Parameters:

devPtr - Device pointer to memory to free

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInitializationError](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMalloc](#), [cudaMallocPitch](#), [cudaMallocArray](#), [cudaFreeArray](#), [cudaMallocHost \(C API\)](#), [cudaFreeHost](#), [cudaMalloc3D](#), [cudaMalloc3DArray](#), [cudaHostAlloc](#)

4.8.2.2 `cudaError_t cudaFreeArray (struct cudaArray * array)`

Frees the CUDA array `array`, which must have been * returned by a previous call to [cudaMallocArray\(\)](#). If [cudaFreeArray\(array\)](#) has already been called before, [cudaErrorInvalidValue](#) is returned. If `devPtr` is 0, no operation is performed.

Parameters:

array - Pointer to array to free

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInitializationError](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMalloc](#), [cudaMallocPitch](#), [cudaFree](#), [cudaMallocArray](#), [cudaMallocHost \(C API\)](#), [cudaFreeHost](#), [cudaHostAlloc](#)

4.8.2.3 `cudaError_t cudaFreeHost (void * ptr)`

Frees the memory space pointed to by `hostPtr`, which must have been returned by a previous call to [cudaMallocHost\(\)](#) or [cudaHostAlloc\(\)](#).

Parameters:

ptr - Pointer to memory to free

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMalloc](#), [cudaMallocPitch](#), [cudaFree](#), [cudaMallocArray](#), [cudaFreeArray](#), [cudaMallocHost \(C API\)](#), [cudaMalloc3D](#), [cudaMalloc3DArray](#), [cudaHostAlloc](#)

4.8.2.4 `cudaError_t cudaGetSymbolAddress (void ** devPtr, const char * symbol)`

Returns in `*devPtr` the address of symbol `symbol` on the device. `symbol` can either be a variable that resides in global or constant memory space, or it can be a character string, naming a variable that resides in global or constant memory space. If `symbol` cannot be found, or if `symbol` is not declared in the global or constant memory space, `*devPtr` is unchanged and the error `cudaErrorInvalidSymbol` is returned. If there are multiple global or constant variables with the same string name (from separate files) and the lookup is done via character string, `cudaErrorDuplicateVariableName` is returned.

Parameters:

devPtr - Return device pointer associated with symbol

symbol - Global variable or string symbol to search for

Returns:

`cudaSuccess`, `cudaErrorInvalidSymbol`, `cudaErrorDuplicateVariableName`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaGetSymbolAddress` (C++ API) `cudaGetSymbolSize` (C API)

4.8.2.5 `cudaError_t cudaGetSymbolSize (size_t * size, const char * symbol)`

Returns in `*size` the size of symbol `symbol`. `symbol` can either be a variable that resides in global or constant memory space, or it can be a character string, naming a variable that resides in global or constant memory space. If `symbol` cannot be found, or if `symbol` is not declared in global or constant memory space, `*size` is unchanged and the error `cudaErrorInvalidSymbol` is returned.

Parameters:

size - Size of object associated with symbol

symbol - Global variable or string symbol to find size of

Returns:

`cudaSuccess`, `cudaErrorInvalidSymbol`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaGetSymbolAddress` (C API) `cudaGetSymbolSize` (C++ API)

4.8.2.6 `cudaError_t cudaHostAlloc (void ** pHost, size_t size, unsigned int flags)`

Allocates `size` bytes of host memory that is page-locked and accessible to the device. The driver tracks the virtual memory ranges allocated with this function and automatically accelerates calls to functions such as `cudaMemcpy()`.

Since the memory can be accessed directly by the device, it can be read or written with much higher bandwidth than pageable memory obtained with functions such as `malloc()`. Allocating excessive amounts of pinned memory may degrade system performance, since it reduces the amount of memory available to the system for paging. As a result, this function is best used sparingly to allocate staging areas for data exchange between host and device.

The `flags` parameter enables different options to be specified that affect the allocation, as follows.

- **`cudaHostAllocDefault`**: This flag's value is defined to be 0 and causes `cudaHostAlloc()` to emulate `cudaMallocHost()`.
- **`cudaHostAllocPortable`**: The memory returned by this call will be considered as pinned memory by all CUDA contexts, not just the one that performed the allocation.
- **`cudaHostAllocMapped`**: Maps the allocation into the CUDA address space. The device pointer to the memory may be obtained by calling `cudaHostGetDevicePointer()`.
- **`cudaHostAllocWriteCombined`**: Allocates the memory as write-combined (WC). WC memory can be transferred across the PCI Express bus more quickly on some system configurations, but cannot be read efficiently by most CPUs. WC memory is a good option for buffers that will be written by the CPU and read by the device via mapped pinned memory or host->device transfers.

All of these flags are orthogonal to one another: a developer may allocate memory that is portable, mapped and/or write-combined with no restrictions.

`cudaSetDeviceFlags()` must have been called with the `cudaDeviceMapHost` flag in order for the `cudaHostAllocMapped` flag to have any effect.

The `cudaHostAllocMapped` flag may be specified on CUDA contexts for devices that do not support mapped pinned memory. The failure is deferred to `cudaHostGetDevicePointer()` because the memory may be mapped into other CUDA contexts via the `cudaHostAllocPortable` flag.

Memory allocated by this function must be freed with `cudaFreeHost()`.

Parameters:

- pHost* - Device pointer to allocated memory
- size* - Requested allocation size in bytes
- flags* - Requested properties of allocated memory

Returns:

`cudaSuccess`, `cudaErrorMemoryAllocation`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaSetDeviceFlags`, `cudaMallocHost` (C API), `cudaFreeHost`

4.8.2.7 `cudaError_t cudaHostGetDevicePointer (void **pDevice, void *pHost, unsigned int flags)`

Passes back the device pointer corresponding to the mapped, pinned host buffer allocated by `cudaHostAlloc()` or registered by `cudaHostRegister()`.

`cudaHostGetDevicePointer()` will fail if the `cudaDeviceMapHost` flag was not specified before deferred context creation occurred, or if called on a device that does not support mapped, pinned memory.

`flags` provides for future releases. For now, it must be set to 0.

Parameters:

pDevice - Returned device pointer for mapped memory

pHost - Requested host pointer mapping

flags - Flags for extensions (must be 0 for now)

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorMemoryAllocation](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaSetDeviceFlags](#), [cudaHostAlloc](#)

4.8.2.8 `cudaError_t cudaHostGetFlags (unsigned int * pFlags, void * pHost)`

[cudaHostGetFlags\(\)](#) will fail if the input pointer does not reside in an address range allocated by [cudaHostAlloc\(\)](#).

Parameters:

pFlags - Returned flags word

pHost - Host pointer

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaHostAlloc](#)

4.8.2.9 `cudaError_t cudaHostRegister (void * ptr, size_t size, unsigned int flags)`

Page-locks the memory range specified by `ptr` and `size` and maps it for the device(s) as specified by `flags`. This memory range also is added to the same tracking mechanism as [cudaHostAlloc\(\)](#) to automatically accelerate calls to functions such as [cudaMemcpy\(\)](#). Since the memory can be accessed directly by the device, it can be read or written with much higher bandwidth than pageable memory that has not been registered. Page-locking excessive amounts of memory may degrade system performance, since it reduces the amount of memory available to the system for paging. As a result, this function is best used sparingly to register staging areas for data exchange between host and device.

The `flags` parameter enables different options to be specified that affect the allocation, as follows.

- [cudaHostRegisterPortable](#): The memory returned by this call will be considered as pinned memory by all CUDA contexts, not just the one that performed the allocation.

- [cudaHostRegisterMapped](#): Maps the allocation into the CUDA address space. The device pointer to the memory may be obtained by calling [cudaHostGetDevicePointer\(\)](#). This feature is available only on GPUs with compute capability greater than or equal to 1.1.

All of these flags are orthogonal to one another: a developer may page-lock memory that is portable or mapped with no restrictions.

The CUDA context must have been created with the `cudaMapHost` flag in order for the [cudaHostRegisterMapped](#) flag to have any effect.

The [cudaHostRegisterMapped](#) flag may be specified on CUDA contexts for devices that do not support mapped pinned memory. The failure is deferred to [cudaHostGetDevicePointer\(\)](#) because the memory may be mapped into other CUDA contexts via the [cudaHostRegisterPortable](#) flag.

The pointer `ptr` and size `size` must be aligned to the host page size (4 KB).

The memory page-locked by this function must be unregistered with [cudaHostUnregister\(\)](#).

Parameters:

- ptr* - Host pointer to memory to page-lock
- size* - Size in bytes of the address range to page-lock in bytes
- flags* - Flags for allocation request

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorMemoryAllocation](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaHostUnregister](#), [cudaHostGetFlags](#), [cudaHostGetDevicePointer](#)

4.8.2.10 `cudaError_t cudaHostUnregister (void * ptr)`

Unmaps the memory range whose base address is specified by `ptr`, and makes it pageable again.

The base address must be the same one specified to [cudaHostRegister\(\)](#).

Parameters:

- ptr* - Host pointer to memory to unregister

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaHostUnregister](#)

4.8.2.11 `cudaError_t cudaMalloc (void ** devPtr, size_t size)`

Allocates `size` bytes of linear memory on the device and returns in `*devPtr` a pointer to the allocated memory. The allocated memory is suitably aligned for any kind of variable. The memory is not cleared. `cudaMalloc()` returns `cudaErrorMemoryAllocation` in case of failure.

Parameters:

devPtr - Pointer to allocated device memory

size - Requested allocation size in bytes

Returns:

`cudaSuccess`, `cudaErrorMemoryAllocation`

See also:

`cudaMallocPitch`, `cudaFree`, `cudaMallocArray`, `cudaFreeArray`, `cudaMalloc3D`, `cudaMalloc3DArray`, `cudaMallocHost` (C API), `cudaFreeHost`, `cudaHostAlloc`

4.8.2.12 `cudaError_t cudaMalloc3D (struct cudaPitchedPtr * pitchedDevPtr, struct cudaExtent extent)`

Allocates at least `width * height * depth` bytes of linear memory on the device and returns a `cudaPitchedPtr` in which `ptr` is a pointer to the allocated memory. The function may pad the allocation to ensure hardware alignment requirements are met. The pitch returned in the `pitch` field of `pitchedDevPtr` is the width in bytes of the allocation.

The returned `cudaPitchedPtr` contains additional fields `xsize` and `ysize`, the logical width and height of the allocation, which are equivalent to the `width` and `height` `extent` parameters provided by the programmer during allocation.

For allocations of 2D and 3D objects, it is highly recommended that programmers perform allocations using `cudaMalloc3D()` or `cudaMallocPitch()`. Due to alignment restrictions in the hardware, this is especially true if the application will be performing memory copies involving 2D or 3D objects (whether linear memory or CUDA arrays).

Parameters:

pitchedDevPtr - Pointer to allocated pitched device memory

extent - Requested allocation size (`width` field in bytes)

Returns:

`cudaSuccess`, `cudaErrorMemoryAllocation`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaMallocPitch`, `cudaFree`, `cudaMemcpy3D`, `cudaMemset3D`, `cudaMalloc3DArray`, `cudaMallocArray`, `cudaFreeArray`, `cudaMallocHost` (C API), `cudaFreeHost`, `cudaHostAlloc`, `make_cudaPitchedPtr`, `make_cudaExtent`

4.8.2.13 `cudaError_t cudaMalloc3DArray (struct cudaArray ** array, const struct cudaChannelFormatDesc * desc, struct cudaExtent extent, unsigned int flags = 0)`

Allocates a CUDA array according to the `cudaChannelFormatDesc` structure `desc` and returns a handle to the new CUDA array in `*array`.

The `cudaChannelFormatDesc` is defined as:

```
struct cudaChannelFormatDesc {
    int x, y, z, w;
    enum cudaChannelFormatKind f;
};
```

where `cudaChannelFormatKind` is one of `cudaChannelFormatKindSigned`, `cudaChannelFormatKindUnsigned`, or `cudaChannelFormatKindFloat`.

`cudaMalloc3DArray()` can allocate the following:

- A 1D array is allocated if the height and depth extents are both zero.
- A 2D array is allocated if only the depth extent is zero.
- A 3D array is allocated if all three extents are non-zero.
- A 1D layered CUDA array is allocated if only the height extent is zero and the `cudaArrayLayered` flag is set. Each layer is a 1D array. The number of layers is determined by the depth extent.
- A 2D layered CUDA array is allocated if all three extents are non-zero and the `cudaArrayLayered` flag is set. Each layer is a 2D array. The number of layers is determined by the depth extent.
- A cubemap CUDA array is allocated if all three extents are non-zero and the `cudaArrayCubemap` flag is set. Width must be equal to height, and depth must be six. A cubemap is a special type of 2D layered CUDA array, where the six layers represent the six faces of a cube. The order of the six layers in memory is the same as that listed in `cudaGraphicsCubeFace`.
- A cubemap layered CUDA array is allocated if all three extents are non-zero, and both, `cudaArrayCubemap` and `cudaArrayLayered` flags are set. Width must be equal to height, and depth must be a multiple of six. A cubemap layered CUDA array is a special type of 2D layered CUDA array that consists of a collection of cubemaps. The first six layers represent the first cubemap, the next six layers form the second cubemap, and so on.

The `flags` parameter enables different options to be specified that affect the allocation, as follows.

- `cudaArrayDefault`: This flag's value is defined to be 0 and provides default array allocation
- `cudaArrayLayered`: Allocates a layered CUDA array, with the depth extent indicating the number of layers
- `cudaArrayCubemap`: Allocates a cubemap CUDA array. Width must be equal to height, and depth must be six. If the `cudaArrayLayered` flag is also set, depth must be a multiple of six.
- `cudaArraySurfaceLoadStore`: Allocates a CUDA array that could be read from or written to using a surface reference.
- `cudaArrayTextureGather`: This flag indicates that texture gather operations will be performed on the CUDA array. Texture gather can only be performed on 2D CUDA arrays.

The width, height and depth extents must meet certain size requirements as listed in the following table. All values are specified in elements.

Note that 2D CUDA arrays have different size requirements if the [cudaArrayTextureGather](#) flag is set. In that case, the valid range for (width, height, depth) is ((1,maxTexture2DGather[0]), (1,maxTexture2DGather[1]), 0).

CUDA array type	Valid extents that must always be met {(width range in elements), (height range), (depth range)}	Valid extents with cudaArraySurfaceLoadStore set {(width range in elements), (height range), (depth range)}
1D	{ (1,maxTexture1D), 0, 0 }	{ (1,maxSurface1D), 0, 0 }
2D	{ (1,maxTexture2D[0]), (1,maxTexture2D[1]), 0 }	{ (1,maxSurface2D[0]), (1,maxSurface2D[1]), 0 }
3D	{ (1,maxTexture3D[0]), (1,maxTexture3D[1]), (1,maxTexture3D[2]) }	{ (1,maxSurface3D[0]), (1,maxSurface3D[1]), (1,maxSurface3D[2]) }
1D Layered	{ (1,maxTexture1DLayered[0]), 0, (1,maxTexture1DLayered[1]) }	{ (1,maxSurface1DLayered[0]), 0, (1,maxSurface1DLayered[1]) }
2D Layered	{ (1,maxTexture2DLayered[0]), (1,maxTexture2DLayered[1]), (1,maxTexture2DLayered[2]) }	{ (1,maxSurface2DLayered[0]), (1,maxSurface2DLayered[1]), (1,maxSurface2DLayered[2]) }
Cubemap	{ (1,maxTextureCubemap), (1,maxTextureCubemap), 6 }	{ (1,maxSurfaceCubemap), (1,maxSurfaceCubemap), 6 }
Cubemap Layered	{ (1,maxTextureCubemapLayered[0]), (1,maxTextureCubemapLayered[0]), (1,maxTextureCubemapLayered[1]) }	{ (1,maxSurfaceCubemapLayered[0]), (1,maxSurfaceCubemapLayered[0]), (1,maxSurfaceCubemapLayered[1]) }

Parameters:

array - Pointer to allocated array in device memory
desc - Requested channel format
extent - Requested allocation size (width field in elements)
flags - Flags for extensions

Returns:

[cudaSuccess](#), [cudaErrorMemoryAllocation](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMalloc3D](#), [cudaMalloc](#), [cudaMallocPitch](#), [cudaFree](#), [cudaFreeArray](#), [cudaMallocHost](#) (C API), [cudaFreeHost](#), [cudaHostAlloc](#), [make_cudaExtent](#)

4.8.2.14 `cudaError_t cudaMallocArray (struct cudaArray ** array, const struct cudaChannelFormatDesc * desc, size_t width, size_t height = 0, unsigned int flags = 0)`

Allocates a CUDA array according to the [cudaChannelFormatDesc](#) structure *desc* and returns a handle to the new CUDA array in **array*.

The [cudaChannelFormatDesc](#) is defined as:

```
struct cudaChannelFormatDesc {
    int x, y, z, w;
    enum cudaChannelFormatKind f;
};
```

where `cudaChannelFormatKind` is one of `cudaChannelFormatKindSigned`, `cudaChannelFormatKindUnsigned`, or `cudaChannelFormatKindFloat`.

The `flags` parameter enables different options to be specified that affect the allocation, as follows.

- `cudaArrayDefault`: This flag's value is defined to be 0 and provides default array allocation
- `cudaArraySurfaceLoadStore`: Allocates an array that can be read from or written to using a surface reference
- `cudaArrayTextureGather`: This flag indicates that texture gather operations will be performed on the array.

`width` and `height` must meet certain size requirements. See `cudaMalloc3DArray()` for more details.

Parameters:

array - Pointer to allocated array in device memory
desc - Requested channel format
width - Requested array allocation width
height - Requested array allocation height
flags - Requested properties of allocated array

Returns:

`cudaSuccess`, `cudaErrorMemoryAllocation`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaMalloc`, `cudaMallocPitch`, `cudaFree`, `cudaFreeArray`, `cudaMallocHost` (C API), `cudaFreeHost`, `cudaMalloc3D`, `cudaMalloc3DArray`, `cudaHostAlloc`

4.8.2.15 `cudaError_t cudaMallocHost (void **ptr, size_t size)`

Allocates `size` bytes of host memory that is page-locked and accessible to the device. The driver tracks the virtual memory ranges allocated with this function and automatically accelerates calls to functions such as `cudaMemcpy*()`. Since the memory can be accessed directly by the device, it can be read or written with much higher bandwidth than pageable memory obtained with functions such as `malloc()`. Allocating excessive amounts of memory with `cudaMallocHost()` may degrade system performance, since it reduces the amount of memory available to the system for paging. As a result, this function is best used sparingly to allocate staging areas for data exchange between host and device.

Parameters:

ptr - Pointer to allocated host memory
size - Requested allocation size in bytes

Returns:

`cudaSuccess`, `cudaErrorMemoryAllocation`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMalloc](#), [cudaMallocPitch](#), [cudaMallocArray](#), [cudaMalloc3D](#), [cudaMalloc3DArray](#), [cudaHostAlloc](#), [cudaFree](#), [cudaFreeArray](#), [cudaMallocHost](#) (C++ API), [cudaFreeHost](#), [cudaHostAlloc](#)

4.8.2.16 `cudaError_t cudaMallocPitch (void **devPtr, size_t *pitch, size_t width, size_t height)`

Allocates at least `width` (in bytes) * `height` bytes of linear memory on the device and returns in `*devPtr` a pointer to the allocated memory. The function may pad the allocation to ensure that corresponding pointers in any given row will continue to meet the alignment requirements for coalescing as the address is updated from row to row. The pitch returned in `*pitch` by [cudaMallocPitch\(\)](#) is the width in bytes of the allocation. The intended usage of `pitch` is as a separate parameter of the allocation, used to compute addresses within the 2D array. Given the row and column of an array element of type `T`, the address is computed as:

```
T* pElement = (T*)((char*)BaseAddress + Row * pitch) + Column;
```

For allocations of 2D arrays, it is recommended that programmers consider performing pitch allocations using [cudaMallocPitch\(\)](#). Due to pitch alignment restrictions in the hardware, this is especially true if the application will be performing 2D memory copies between different regions of device memory (whether linear memory or CUDA arrays).

Parameters:

devPtr - Pointer to allocated pitched device memory
pitch - Pitch for allocation
width - Requested pitched allocation width (in bytes)
height - Requested pitched allocation height

Returns:

[cudaSuccess](#), [cudaErrorMemoryAllocation](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMalloc](#), [cudaFree](#), [cudaMallocArray](#), [cudaFreeArray](#), [cudaMallocHost](#) (C API), [cudaFreeHost](#), [cudaMalloc3D](#), [cudaMalloc3DArray](#), [cudaHostAlloc](#)

4.8.2.17 `cudaError_t cudaMemcpy (void *dst, const void *src, size_t count, enum cudaMemcpyKind kind)`

Copies `count` bytes from the memory area pointed to by `src` to the memory area pointed to by `dst`, where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy. The memory areas may not overlap. Calling [cudaMemcpy\(\)](#) with `dst` and `src` pointers that do not match the direction of the copy results in an undefined behavior.

Parameters:

dst - Destination memory address
src - Source memory address
count - Size in bytes to copy

kind - Type of transfer

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.18 `cudaError_t cudaMemcpy2D (void *dst, size_t dpitch, const void *src, size_t spitch, size_t width, size_t height, enum cudaMemcpyKind kind)`

Copies a matrix (height rows of width bytes each) from the memory area pointed to by `src` to the memory area pointed to by `dst`, where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy. `dpitch` and `spitch` are the widths in memory in bytes of the 2D arrays pointed to by `dst` and `src`, including any padding added to the end of each row. The memory areas may not overlap. `width` must not exceed either `dpitch` or `spitch`. Calling [cudaMemcpy2D\(\)](#) with `dst` and `src` pointers that do not match the direction of the copy results in an undefined behavior. [cudaMemcpy2D\(\)](#) returns an error if `dpitch` or `spitch` exceeds the maximum allowed.

Parameters:

dst - Destination memory address
dpitch - Pitch of destination memory
src - Source memory address
spitch - Pitch of source memory
width - Width of matrix transfer (columns in bytes)
height - Height of matrix transfer (rows)
kind - Type of transfer

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidPitchValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.19 `cudaError_t cudaMemcpy2DArrayToArray (struct cudaArray * dst, size_t wOffsetDst, size_t hOffsetDst, const struct cudaArray * src, size_t wOffsetSrc, size_t hOffsetSrc, size_t width, size_t height, enum cudaMemcpyKind kind = cudaMemcpyDeviceToDevice)`

Copies a matrix (height rows of width bytes each) from the CUDA array `srcArray` starting at the upper left corner (`wOffsetSrc`, `hOffsetSrc`) to the CUDA array `dst` starting at the upper left corner (`wOffsetDst`, `hOffsetDst`), where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy. `wOffsetDst + width` must not exceed the width of the CUDA array `dst`. `wOffsetSrc + width` must not exceed the width of the CUDA array `src`.

Parameters:

dst - Destination memory address
wOffsetDst - Destination starting X offset
hOffsetDst - Destination starting Y offset
src - Source memory address
wOffsetSrc - Source starting X offset
hOffsetSrc - Source starting Y offset
width - Width of matrix transfer (columns in bytes)
height - Height of matrix transfer (rows)
kind - Type of transfer

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.20 `cudaError_t cudaMemcpy2DAsync (void * dst, size_t dpitch, const void * src, size_t spitch, size_t width, size_t height, enum cudaMemcpyKind kind, cudaStream_t stream = 0)`

Copies a matrix (height rows of width bytes each) from the memory area pointed to by `src` to the memory area pointed to by `dst`, where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy. `dpitch` and `spitch` are the widths in memory in bytes of the 2D arrays pointed to by `dst` and `src`, including any padding added to the end of each row. The memory areas may not overlap. `width` must not exceed either `dpitch` or `spitch`. Calling [cudaMemcpy2DAsync\(\)](#) with `dst` and `src` pointers that do not match the direction of the copy results in an undefined behavior. [cudaMemcpy2DAsync\(\)](#) returns an error if `dpitch` or `spitch` is greater than the maximum allowed.

[cudaMemcpy2DAsync\(\)](#) is asynchronous with respect to the host, so the call may return before the copy is complete. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input.

The copy can optionally be associated to a stream by passing a non-zero `stream` argument. If `kind` is [cudaMemcpyHostToDevice](#) or [cudaMemcpyDeviceToHost](#) and `stream` is non-zero, the copy may overlap with operations in other streams.

Parameters:

dst - Destination memory address
dpitch - Pitch of destination memory
src - Source memory address
spitch - Pitch of source memory
width - Width of matrix transfer (columns in bytes)
height - Height of matrix transfer (rows)
kind - Type of transfer
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidPitchValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.21 `cudaError_t cudaMemcpy2DFromArray (void *dst, size_t dpitch, const struct cudaArray *src, size_t wOffset, size_t hOffset, size_t width, size_t height, enum cudaMemcpyKind kind)`

Copies a matrix (height rows of width bytes each) from the CUDA array `srcArray` starting at the upper left corner (`wOffset`, `hOffset`) to the memory area pointed to by `dst`, where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy. `dpitch` is the width in memory in bytes of the 2D array pointed to by `dst`, including any padding added to the end of each row. `wOffset` + `width` must not exceed the width of the CUDA array `src`. `width` must not exceed `dpitch`. [cudaMemcpy2DFromArray\(\)](#) returns an error if `dpitch` exceeds the maximum allowed.

Parameters:

dst - Destination memory address
dpitch - Pitch of destination memory
src - Source memory address
wOffset - Source starting X offset
hOffset - Source starting Y offset
width - Width of matrix transfer (columns in bytes)
height - Height of matrix transfer (rows)

kind - Type of transfer

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidPitchValue](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.22 `cudaError_t cudaMemcpy2DFromArrayAsync(void *dst, size_t dpitch, const struct cudaArray *src, size_t wOffset, size_t hOffset, size_t width, size_t height, enum cudaMemcpyKind kind, cudaStream_t stream = 0)`

Copies a matrix (height rows of width bytes each) from the CUDA array `srcArray` starting at the upper left corner (`wOffset`, `hOffset`) to the memory area pointed to by `dst`, where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy. `dpitch` is the width in memory in bytes of the 2D array pointed to by `dst`, including any padding added to the end of each row. `wOffset` + `width` must not exceed the width of the CUDA array `src`. `width` must not exceed `dpitch`. [cudaMemcpy2DFromArrayAsync\(\)](#) returns an error if `dpitch` exceeds the maximum allowed.

[cudaMemcpy2DFromArrayAsync\(\)](#) is asynchronous with respect to the host, so the call may return before the copy is complete. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input. The copy can optionally be associated to a stream by passing a non-zero `stream` argument. If `kind` is [cudaMemcpyHostToDevice](#) or [cudaMemcpyDeviceToHost](#) and `stream` is non-zero, the copy may overlap with operations in other streams.

Parameters:

dst - Destination memory address
dpitch - Pitch of destination memory
src - Source memory address
wOffset - Source starting X offset
hOffset - Source starting Y offset
width - Width of matrix transfer (columns in bytes)
height - Height of matrix transfer (rows)
kind - Type of transfer
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidPitchValue](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.23 `cudaError_t cudaMemcpy2DToArray` (`struct cudaArray *dst`, `size_t wOffset`, `size_t hOffset`, `const void *src`, `size_t spitch`, `size_t width`, `size_t height`, `enum cudaMemcpyKind kind`)

Copies a matrix (height rows of width bytes each) from the memory area pointed to by `src` to the CUDA array `dst` starting at the upper left corner (`wOffset`, `hOffset`) where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy. `spitch` is the width in memory in bytes of the 2D array pointed to by `src`, including any padding added to the end of each row. `wOffset + width` must not exceed the width of the CUDA array `dst`. `width` must not exceed `spitch`. [cudaMemcpy2DToArray\(\)](#) returns an error if `spitch` exceeds the maximum allowed.

Parameters:

dst - Destination memory address
wOffset - Destination starting X offset
hOffset - Destination starting Y offset
src - Source memory address
spitch - Pitch of source memory
width - Width of matrix transfer (columns in bytes)
height - Height of matrix transfer (rows)
kind - Type of transfer

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidPitchValue](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.24 `cudaError_t cudaMemcpy2DToArrayAsync (struct cudaArray * dst, size_t wOffset, size_t hOffset, const void * src, size_t spitch, size_t width, size_t height, enum cudaMemcpyKind kind, cudaStream_t stream = 0)`

Copies a matrix (height rows of width bytes each) from the memory area pointed to by `src` to the CUDA array `dst` starting at the upper left corner (`wOffset`, `hOffset`) where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy. `spitch` is the width in memory in bytes of the 2D array pointed to by `src`, including any padding added to the end of each row. `wOffset + width` must not exceed the width of the CUDA array `dst`. `width` must not exceed `spitch`. [cudaMemcpy2DToArrayAsync\(\)](#) returns an error if `spitch` exceeds the maximum allowed.

[cudaMemcpy2DToArrayAsync\(\)](#) is asynchronous with respect to the host, so the call may return before the copy is complete. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input. The copy can optionally be associated to a stream by passing a non-zero `stream` argument. If `kind` is [cudaMemcpyHostToDevice](#) or [cudaMemcpyDeviceToHost](#) and `stream` is non-zero, the copy may overlap with operations in other streams.

Parameters:

dst - Destination memory address
wOffset - Destination starting X offset
hOffset - Destination starting Y offset
src - Source memory address
spitch - Pitch of source memory
width - Width of matrix transfer (columns in bytes)
height - Height of matrix transfer (rows)
kind - Type of transfer
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidPitchValue](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.25 `cudaError_t cudaMemcpy3D (const struct cudaMemcpy3DParms * p)`

```
struct cudaExtent {
    size_t width;
    size_t height;
    size_t depth;
};
struct cudaExtent make_cudaExtent(size_t w, size_t h, size_t d);
```

```

struct cudaPos {
    size_t x;
    size_t y;
    size_t z;
};

struct cudaPos make_cudaPos(size_t x, size_t y, size_t z);

struct cudaMemcpy3DParms {
    struct cudaArray    *srcArray;
    struct cudaPos      srcPos;
    struct cudaPitchedPtr srcPtr;
    struct cudaArray    *dstArray;
    struct cudaPos      dstPos;
    struct cudaPitchedPtr dstPtr;
    struct cudaExtent    extent;
    enum cudaMemcpyKind  kind;
};

```

[cudaMemcpy3D\(\)](#) copies data between two 3D objects. The source and destination objects may be in either host memory, device memory, or a CUDA array. The source, destination, extent, and kind of copy performed is specified by the [cudaMemcpy3DParms](#) struct which should be initialized to zero before use:

```
cudaMemcpy3DParms myParms = {0};
```

The struct passed to [cudaMemcpy3D\(\)](#) must specify one of `srcArray` or `srcPtr` and one of `dstArray` or `dstPtr`. Passing more than one non-zero source or destination will cause [cudaMemcpy3D\(\)](#) to return an error.

The `srcPos` and `dstPos` fields are optional offsets into the source and destination objects and are defined in units of each object's elements. The element for a host or device pointer is assumed to be **unsigned char**. For CUDA arrays, positions must be in the range [0, 2048) for any dimension.

The `extent` field defines the dimensions of the transferred area in elements. If a CUDA array is participating in the copy, the extent is defined in terms of that array's elements. If no CUDA array is participating in the copy then the extents are defined in elements of **unsigned char**.

The `kind` field defines the direction of the copy. It must be one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#).

If the source and destination are both arrays, [cudaMemcpy3D\(\)](#) will return an error if they do not have the same element size.

The source and destination object may not overlap. If overlapping source and destination objects are specified, undefined behavior will result.

The source object must lie entirely within the region defined by `srcPos` and `extent`. The destination object must lie entirely within the region defined by `dstPos` and `extent`.

[cudaMemcpy3D\(\)](#) returns an error if the pitch of `srcPtr` or `dstPtr` exceeds the maximum allowed. The pitch of a [cudaPitchedPtr](#) allocated with [cudaMalloc3D\(\)](#) will always be valid.

Parameters:

p - 3D memory copy parameters

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidPitchValue](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMalloc3D](#), [cudaMalloc3DArray](#), [cudaMemset3D](#), [cudaMemcpy3DAsync](#), [cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#), [make_cudaExtent](#), [make_cudaPos](#)

4.8.2.26 `cudaError_t cudaMemcpy3DAsync(const struct cudaMemcpy3DParms *p, cudaStream_t stream = 0)`

```
struct cudaExtent {
    size_t width;
    size_t height;
    size_t depth;
};
struct cudaExtent make_cudaExtent(size_t w, size_t h, size_t d);

struct cudaPos {
    size_t x;
    size_t y;
    size_t z;
};
struct cudaPos make_cudaPos(size_t x, size_t y, size_t z);

struct cudaMemcpy3DParms {
    struct cudaArray    *srcArray;
    struct cudaPos      srcPos;
    struct cudaPitchedPtr srcPtr;
    struct cudaArray    *dstArray;
    struct cudaPos      dstPos;
    struct cudaPitchedPtr dstPtr;
    struct cudaExtent    extent;
    enum cudaMemcpyKind  kind;
};
```

[cudaMemcpy3DAsync\(\)](#) copies data between two 3D objects. The source and destination objects may be in either host memory, device memory, or a CUDA array. The source, destination, extent, and kind of copy performed is specified by the [cudaMemcpy3DParms](#) struct which should be initialized to zero before use:

```
cudaMemcpy3DParms myParms = {0};
```

The struct passed to [cudaMemcpy3DAsync\(\)](#) must specify one of `srcArray` or `srcPtr` and one of `dstArray` or `dstPtr`. Passing more than one non-zero source or destination will cause [cudaMemcpy3DAsync\(\)](#) to return an error.

The `srcPos` and `dstPos` fields are optional offsets into the source and destination objects and are defined in units of each object's elements. The element for a host or device pointer is assumed to be **unsigned char**. For CUDA arrays, positions must be in the range [0, 2048) for any dimension.

The `extent` field defines the dimensions of the transferred area in elements. If a CUDA array is participating in the copy, the extent is defined in terms of that array's elements. If no CUDA array is participating in the copy then the extents are defined in elements of **unsigned char**.

The `kind` field defines the direction of the copy. It must be one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#).

If the source and destination are both arrays, [cudaMemcpy3DAsync\(\)](#) will return an error if they do not have the same element size.

The source and destination object may not overlap. If overlapping source and destination objects are specified, undefined behavior will result.

The source object must lie entirely within the region defined by `srcPos` and `extent`. The destination object must lie entirely within the region defined by `dstPos` and `extent`.

`cudaMemcpy3DAsync()` returns an error if the pitch of `srcPtr` or `dstPtr` exceeds the maximum allowed. The pitch of a `cudaPitchedPtr` allocated with `cudaMalloc3D()` will always be valid.

`cudaMemcpy3DAsync()` is asynchronous with respect to the host, so the call may return before the copy is complete. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input. The copy can optionally be associated to a stream by passing a non-zero `stream` argument. If `kind` is `cudaMemcpyHostToDevice` or `cudaMemcpyDeviceToHost` and `stream` is non-zero, the copy may overlap with operations in other streams.

Parameters:

p - 3D memory copy parameters
stream - Stream identifier

Returns:

`cudaSuccess`, `cudaErrorInvalidValue`, `cudaErrorInvalidDevicePointer`, `cudaErrorInvalidPitchValue`, `cudaErrorInvalidMemcpyDirection`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaMalloc3D`, `cudaMalloc3DArray`, `cudaMemset3D`, `cudaMemcpy3D`, `cudaMemcpy`, `cudaMemcpy2D`, `cudaMemcpyToArray`, `cudaMemcpy2DToArray`, `cudaMemcpyFromArray`, `cudaMemcpy2DFromArray`, `cudaMemcpyArrayToArray`, `cudaMemcpy2DArrayToArray`, `cudaMemcpyToSymbol`, `cudaMemcpyFromSymbol`, `cudaMemcpyAsync`, `cudaMemcpy2DAsync`, `cudaMemcpyToArrayAsync`, `cudaMemcpy2DToArrayAsync`, `cudaMemcpyFromArrayAsync`, `cudaMemcpy2DFromArrayAsync`, `cudaMemcpyToSymbolAsync`, `cudaMemcpyFromSymbolAsync`, `make_cudaExtent`, `make_cudaPos`

4.8.2.27 `cudaError_t cudaMemcpy3DPeer (const struct cudaMemcpy3DPeerParms * p)`

Perform a 3D memory copy according to the parameters specified in `p`. See the definition of the `cudaMemcpy3DPeerParms` structure for documentation of its parameters.

Note that this function is synchronous with respect to the host only if the source or destination of the transfer is host memory. Note also that this copy is serialized with respect to all pending and future asynchronous work in to the current device, the copy's source device, and the copy's destination device (use `cudaMemcpy3DPeerAsync` to avoid this synchronization).

Parameters:

p - Parameters for the memory copy

Returns:

`cudaSuccess`, `cudaErrorInvalidValue`, `cudaErrorInvalidDevice`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpyPeer](#), [cudaMemcpyAsync](#), [cudaMemcpyPeerAsync](#), [cudaMemcpy3DPeerAsync](#)

4.8.2.28 `cudaError_t cudaMemcpy3DPeerAsync (const struct cudaMemcpy3DPeerParms *p, cudaStream_t stream = 0)`

Perform a 3D memory copy according to the parameters specified in `p`. See the definition of the [cudaMemcpy3DPeerParms](#) structure for documentation of its parameters.

Parameters:

p - Parameters for the memory copy
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevice](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpyPeer](#), [cudaMemcpyAsync](#), [cudaMemcpyPeerAsync](#), [cudaMemcpy3DPeerAsync](#)

4.8.2.29 `cudaError_t cudaMemcpyArrayToArray (struct cudaArray *dst, size_t wOffsetDst, size_t hOffsetDst, const struct cudaArray *src, size_t wOffsetSrc, size_t hOffsetSrc, size_t count, enum cudaMemcpyKind kind = cudaMemcpyDeviceToDevice)`

Copies `count` bytes from the CUDA array `src` starting at the upper left corner (`wOffsetSrc`, `hOffsetSrc`) to the CUDA array `dst` starting at the upper left corner (`wOffsetDst`, `hOffsetDst`) where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy.

Parameters:

dst - Destination memory address
wOffsetDst - Destination starting X offset
hOffsetDst - Destination starting Y offset
src - Source memory address
wOffsetSrc - Source starting X offset
hOffsetSrc - Source starting Y offset
count - Size in bytes to copy
kind - Type of transfer

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.30 `cudaError_t cudaMemcpyAsync(void *dst, const void *src, size_t count, enum cudaMemcpyKind kind, cudaStream_t stream = 0)`

Copies `count` bytes from the memory area pointed to by `src` to the memory area pointed to by `dst`, where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy. The memory areas may not overlap. Calling [cudaMemcpyAsync\(\)](#) with `dst` and `src` pointers that do not match the direction of the copy results in an undefined behavior.

[cudaMemcpyAsync\(\)](#) is asynchronous with respect to the host, so the call may return before the copy is complete. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input. The copy can optionally be associated to a stream by passing a non-zero `stream` argument. If `kind` is [cudaMemcpyHostToDevice](#) or [cudaMemcpyDeviceToHost](#) and the `stream` is non-zero, the copy may overlap with operations in other streams.

Parameters:

dst - Destination memory address
src - Source memory address
count - Size in bytes to copy
kind - Type of transfer
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.31 `cudaError_t cudaMemcpyFromArray(void *dst, const struct cudaArray *src, size_t wOffset, size_t hOffset, size_t count, enum cudaMemcpyKind kind)`

Copies `count` bytes from the CUDA array `src` starting at the upper left corner (`wOffset`, `hOffset`) to the memory area pointed to by `dst`, where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy.

Parameters:

dst - Destination memory address
src - Source memory address
wOffset - Source starting X offset
hOffset - Source starting Y offset
count - Size in bytes to copy
kind - Type of transfer

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.32 `cudaError_t cudaMemcpyFromArrayAsync(void *dst, const struct cudaArray *src, size_t wOffset, size_t hOffset, size_t count, enum cudaMemcpyKind kind, cudaStream_t stream = 0)`

Copies `count` bytes from the CUDA array `src` starting at the upper left corner (`wOffset`, `hOffset`) to the memory area pointed to by `dst`, where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy.

[cudaMemcpyFromArrayAsync\(\)](#) is asynchronous with respect to the host, so the call may return before the copy is complete. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input. The copy can optionally be associated to a stream by passing a non-zero `stream` argument. If `kind` is [cudaMemcpyHostToDevice](#) or [cudaMemcpyDeviceToHost](#) and `stream` is non-zero, the copy may overlap with operations in other streams.

Parameters:

dst - Destination memory address
src - Source memory address
wOffset - Source starting X offset
hOffset - Source starting Y offset
count - Size in bytes to copy
kind - Type of transfer
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.33 `cudaError_t cudaMemcpyFromSymbol(void *dst, const char *symbol, size_t count, size_t offset = 0, enum cudaMemcpyKind kind = cudaMemcpyDeviceToHost)`

Copies `count` bytes from the memory area pointed to by `offset` bytes from the start of symbol `symbol` to the memory area pointed to by `dst`. The memory areas may not overlap. `symbol` can either be a variable that resides in global or constant memory space, or it can be a character string, naming a variable that resides in global or constant memory space. `kind` can be either [cudaMemcpyDeviceToHost](#) or [cudaMemcpyDeviceToDevice](#).

Parameters:

dst - Destination memory address
symbol - Symbol source from device
count - Size in bytes to copy
offset - Offset from start of symbol in bytes
kind - Type of transfer

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidSymbol](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromSymbolAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.34 `cudaError_t cudaMemcpyFromSymbolAsync(void *dst, const char *symbol, size_t count, size_t offset, enum cudaMemcpyKind kind, cudaStream_t stream = 0)`

Copies `count` bytes from the memory area pointed to by `offset` bytes from the start of symbol `symbol` to the memory area pointed to by `dst`. The memory areas may not overlap. `symbol` can either be a variable that resides in global or constant memory space, or it can be a character string, naming a variable that resides in global or constant memory space. `kind` can be either [cudaMemcpyDeviceToHost](#) or [cudaMemcpyDeviceToDevice](#).

[cudaMemcpyFromSymbolAsync\(\)](#) is asynchronous with respect to the host, so the call may return before the copy is complete. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input. The copy can optionally be associated to a stream by passing a non-zero `stream` argument. If `kind` is [cudaMemcpyDeviceToHost](#) and `stream` is non-zero, the copy may overlap with operations in other streams.

Parameters:

dst - Destination memory address
symbol - Symbol source from device
count - Size in bytes to copy
offset - Offset from start of symbol in bytes
kind - Type of transfer
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidSymbol](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#)

4.8.2.35 `cudaError_t cudaMemcpyPeer (void *dst, int dstDevice, const void *src, int srcDevice, size_t count)`

Copies memory from one device to memory on another device. `dst` is the base device pointer of the destination memory and `dstDevice` is the destination device. `src` is the base device pointer of the source memory and `srcDevice` is the source device. `count` specifies the number of bytes to copy.

Note that this function is asynchronous with respect to the host, but serialized with respect all pending and future asynchronous work in to the current device, `srcDevice`, and `dstDevice` (use [cudaMemcpyPeerAsync](#) to avoid this synchronization).

Parameters:

dst - Destination device pointer
dstDevice - Destination device
src - Source device pointer
srcDevice - Source device
count - Size of memory copy in bytes

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevice](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpyPeer3D](#), [cudaMemcpyAsync](#), [cudaMemcpyPeerAsync](#), [cudaMemcpy3DPeerAsync](#)

4.8.2.36 `cudaError_t cudaMemcpyPeerAsync(void *dst, int dstDevice, const void *src, int srcDevice, size_t count, cudaStream_t stream = 0)`

Copies memory from one device to memory on another device. `dst` is the base device pointer of the destination memory and `dstDevice` is the destination device. `src` is the base device pointer of the source memory and `srcDevice` is the source device. `count` specifies the number of bytes to copy.

Note that this function is asynchronous with respect to the host and all work in other streams and other devices.

Parameters:

dst - Destination device pointer
dstDevice - Destination device
src - Source device pointer
srcDevice - Source device
count - Size of memory copy in bytes
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevice](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpyPeer](#), [cudaMemcpyPeer3D](#), [cudaMemcpyAsync](#), [cudaMemcpy3DPeerAsync](#)

4.8.2.37 `cudaError_t cudaMemcpyToArray(struct cudaArray *dst, size_t wOffset, size_t hOffset, const void *src, size_t count, enum cudaMemcpyKind kind)`

Copies `count` bytes from the memory area pointed to by `src` to the CUDA array `dst` starting at the upper left corner (`wOffset`, `hOffset`), where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy.

Parameters:

dst - Destination memory address
wOffset - Destination starting X offset
hOffset - Destination starting Y offset
src - Source memory address
count - Size in bytes to copy

kind - Type of transfer

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.38 `cudaError_t cudaMemcpyToArrayAsync(struct cudaArray *dst, size_t wOffset, size_t hOffset, const void *src, size_t count, enum cudaMemcpyKind kind, cudaStream_t stream = 0)`

Copies `count` bytes from the memory area pointed to by `src` to the CUDA array `dst` starting at the upper left corner (`wOffset`, `hOffset`), where `kind` is one of [cudaMemcpyHostToHost](#), [cudaMemcpyHostToDevice](#), [cudaMemcpyDeviceToHost](#), or [cudaMemcpyDeviceToDevice](#), and specifies the direction of the copy.

[cudaMemcpyToArrayAsync\(\)](#) is asynchronous with respect to the host, so the call may return before the copy is complete. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input. The copy can optionally be associated to a stream by passing a non-zero `stream` argument. If `kind` is [cudaMemcpyHostToDevice](#) or [cudaMemcpyDeviceToHost](#) and `stream` is non-zero, the copy may overlap with operations in other streams.

Parameters:

dst - Destination memory address
wOffset - Destination starting X offset
hOffset - Destination starting Y offset
src - Source memory address
count - Size in bytes to copy
kind - Type of transfer
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyToSymbolAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.39 `cudaError_t cudaMemcpyToSymbol (const char * symbol, const void * src, size_t count, size_t offset = 0, enum cudaMemcpyKind kind = cudaMemcpyHostToDevice)`

Copies `count` bytes from the memory area pointed to by `src` to the memory area pointed to by `offset` bytes from the start of symbol `symbol`. The memory areas may not overlap. `symbol` can either be a variable that resides in global or constant memory space, or it can be a character string, naming a variable that resides in global or constant memory space. `kind` can be either `cudaMemcpyHostToDevice` or `cudaMemcpyDeviceToDevice`.

Parameters:

symbol - Symbol destination on device
src - Source memory address
count - Size in bytes to copy
offset - Offset from start of symbol in bytes
kind - Type of transfer

Returns:

`cudaSuccess`, `cudaErrorInvalidValue`, `cudaErrorInvalidSymbol`, `cudaErrorInvalidDevicePointer`, `cudaErrorInvalidMemcpyDirection`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaMemcpy`, `cudaMemcpy2D`, `cudaMemcpyToArray`, `cudaMemcpy2DToArray`, `cudaMemcpyFromArray`, `cudaMemcpy2DFromArray`, `cudaMemcpyArrayToArray`, `cudaMemcpy2DArrayToArray`, `cudaMemcpyFromSymbol`, `cudaMemcpyAsync`, `cudaMemcpy2DAsync`, `cudaMemcpyToArrayAsync`, `cudaMemcpy2DToArrayAsync`, `cudaMemcpyFromArrayAsync`, `cudaMemcpy2DFromArrayAsync`, `cudaMemcpyToSymbolAsync`, `cudaMemcpyFromSymbolAsync`

4.8.2.40 `cudaError_t cudaMemcpyToSymbolAsync (const char * symbol, const void * src, size_t count, size_t offset, enum cudaMemcpyKind kind, cudaStream_t stream = 0)`

Copies `count` bytes from the memory area pointed to by `src` to the memory area pointed to by `offset` bytes from the start of symbol `symbol`. The memory areas may not overlap. `symbol` can either be a variable that resides in global or constant memory space, or it can be a character string, naming a variable that resides in global or constant memory space. `kind` can be either `cudaMemcpyHostToDevice` or `cudaMemcpyDeviceToDevice`.

`cudaMemcpyToSymbolAsync()` is asynchronous with respect to the host, so the call may return before the copy is complete. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input. The copy can optionally be associated to a stream by passing a non-zero `stream` argument. If `kind` is `cudaMemcpyHostToDevice` and `stream` is non-zero, the copy may overlap with operations in other streams.

Parameters:

symbol - Symbol destination on device
src - Source memory address
count - Size in bytes to copy
offset - Offset from start of symbol in bytes
kind - Type of transfer

stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidSymbol](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidMemcpyDirection](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemcpy](#), [cudaMemcpy2D](#), [cudaMemcpyToArray](#), [cudaMemcpy2DToArray](#), [cudaMemcpyFromArray](#), [cudaMemcpy2DFromArray](#), [cudaMemcpyArrayToArray](#), [cudaMemcpy2DArrayToArray](#), [cudaMemcpyToSymbol](#), [cudaMemcpyFromSymbol](#), [cudaMemcpyAsync](#), [cudaMemcpy2DAsync](#), [cudaMemcpyToArrayAsync](#), [cudaMemcpy2DToArrayAsync](#), [cudaMemcpyFromArrayAsync](#), [cudaMemcpy2DFromArrayAsync](#), [cudaMemcpyFromSymbolAsync](#)

4.8.2.41 `cudaError_t cudaMemGetInfo (size_t *free, size_t *total)`

Returns in **free* and **total* respectively, the free and total amount of memory available for allocation by the device in bytes.

Parameters:

free - Returned free memory in bytes

total - Returned total memory in bytes

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#), [cudaErrorInvalidValue](#), [cudaErrorLaunchFailure](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

4.8.2.42 `cudaError_t cudaMemset (void *devPtr, int value, size_t count)`

Fills the first *count* bytes of the memory area pointed to by *devPtr* with the constant byte value *value*.

Parameters:

devPtr - Pointer to device memory

value - Value to set for each byte of specified memory

count - Size in bytes to set

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemset2D](#), [cudaMemset3D](#), [cudaMemsetAsync](#), [cudaMemset2DAsync](#), [cudaMemset3DAsync](#)

4.8.2.43 `cudaError_t cudaMemset2D (void * devPtr, size_t pitch, int value, size_t width, size_t height)`

Sets to the specified value `value` a matrix (`height` rows of `width` bytes each) pointed to by `dstPtr`. `pitch` is the width in bytes of the 2D array pointed to by `dstPtr`, including any padding added to the end of each row. This function performs fastest when the pitch is one that has been passed back by `cudaMallocPitch()`.

Parameters:

devPtr - Pointer to 2D device memory
pitch - Pitch in bytes of 2D device memory
value - Value to set for each byte of specified memory
width - Width of matrix set (columns in bytes)
height - Height of matrix set (rows)

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemset](#), [cudaMemset3D](#), [cudaMemsetAsync](#), [cudaMemset2DAsync](#), [cudaMemset3DAsync](#)

4.8.2.44 `cudaError_t cudaMemset2DAsync (void * devPtr, size_t pitch, int value, size_t width, size_t height, cudaStream_t stream = 0)`

Sets to the specified value `value` a matrix (`height` rows of `width` bytes each) pointed to by `dstPtr`. `pitch` is the width in bytes of the 2D array pointed to by `dstPtr`, including any padding added to the end of each row. This function performs fastest when the pitch is one that has been passed back by `cudaMallocPitch()`.

`cudaMemset2DAsync()` is asynchronous with respect to the host, so the call may return before the memset is complete. The operation can optionally be associated to a stream by passing a non-zero `stream` argument. If `stream` is non-zero, the operation may overlap with operations in other streams.

Parameters:

devPtr - Pointer to 2D device memory
pitch - Pitch in bytes of 2D device memory
value - Value to set for each byte of specified memory
width - Width of matrix set (columns in bytes)
height - Height of matrix set (rows)
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemset](#), [cudaMemset2D](#), [cudaMemset3D](#), [cudaMemsetAsync](#), [cudaMemset3DAsync](#)

4.8.2.45 `cudaError_t cudaMemset3D (struct cudaPitchedPtr pitchedDevPtr, int value, struct cudaExtent extent)`

Initializes each element of a 3D array to the specified value *value*. The object to initialize is defined by *pitchedDevPtr*. The *pitch* field of *pitchedDevPtr* is the width in memory in bytes of the 3D array pointed to by *pitchedDevPtr*, including any padding added to the end of each row. The *xsize* field specifies the logical width of each row in bytes, while the *ysize* field specifies the height of each 2D slice in rows.

The extents of the initialized region are specified as a *width* in bytes, a *height* in rows, and a *depth* in slices.

Extents with *width* greater than or equal to the *xsize* of *pitchedDevPtr* may perform significantly faster than extents narrower than the *xsize*. Secondly, extents with *height* equal to the *ysize* of *pitchedDevPtr* will perform faster than when the *height* is shorter than the *ysize*.

This function performs fastest when the *pitchedDevPtr* has been allocated by [cudaMalloc3D\(\)](#).

Parameters:

pitchedDevPtr - Pointer to pitched device memory

value - Value to set for each byte of specified memory

extent - Size parameters for where to set device memory (*width* field in bytes)

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemset](#), [cudaMemset2D](#), [cudaMemsetAsync](#), [cudaMemset2DAsync](#), [cudaMemset3DAsync](#), [cudaMalloc3D](#), [make_cudaPitchedPtr](#), [make_cudaExtent](#)

4.8.2.46 `cudaError_t cudaMemset3DAsync (struct cudaPitchedPtr pitchedDevPtr, int value, struct cudaExtent extent, cudaStream_t stream = 0)`

Initializes each element of a 3D array to the specified value *value*. The object to initialize is defined by *pitchedDevPtr*. The *pitch* field of *pitchedDevPtr* is the width in memory in bytes of the 3D array pointed to by *pitchedDevPtr*, including any padding added to the end of each row. The *xsize* field specifies the logical width of each row in bytes, while the *ysize* field specifies the height of each 2D slice in rows.

The extents of the initialized region are specified as a *width* in bytes, a *height* in rows, and a *depth* in slices.

Extents with *width* greater than or equal to the *xsize* of *pitchedDevPtr* may perform significantly faster than extents narrower than the *xsize*. Secondly, extents with *height* equal to the *ysize* of *pitchedDevPtr* will perform faster than when the *height* is shorter than the *ysize*.

This function performs fastest when the *pitchedDevPtr* has been allocated by [cudaMalloc3D\(\)](#).

[cudaMemset3DAsync\(\)](#) is asynchronous with respect to the host, so the call may return before the memset is complete. The operation can optionally be associated to a stream by passing a non-zero *stream* argument. If *stream* is non-zero, the operation may overlap with operations in other streams.

Parameters:

pitchedDevPtr - Pointer to pitched device memory

value - Value to set for each byte of specified memory
extent - Size parameters for where to set device memory (*width* field in bytes)
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemset](#), [cudaMemset2D](#), [cudaMemset3D](#), [cudaMemsetAsync](#), [cudaMemset2DAsync](#), [cudaMalloc3D](#), [make_cudaPitchedPtr](#), [make_cudaExtent](#)

4.8.2.47 `cudaError_t cudaMemsetAsync (void * devPtr, int value, size_t count, cudaStream_t stream = 0)`

Fills the first *count* bytes of the memory area pointed to by *devPtr* with the constant byte value *value*.

[cudaMemsetAsync\(\)](#) is asynchronous with respect to the host, so the call may return before the memset is complete. The operation can optionally be associated to a stream by passing a non-zero *stream* argument. If *stream* is non-zero, the operation may overlap with operations in other streams.

Parameters:

devPtr - Pointer to device memory
value - Value to set for each byte of specified memory
count - Size in bytes to set
stream - Stream identifier

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaMemset](#), [cudaMemset2D](#), [cudaMemset3D](#), [cudaMemset2DAsync](#), [cudaMemset3DAsync](#)

4.8.2.48 `struct cudaExtent make_cudaExtent (size_t w, size_t h, size_t d) [read]`

Returns a [cudaExtent](#) based on the specified input parameters *w*, *h*, and *d*.

Parameters:

w - Width in bytes
h - Height in elements
d - Depth in elements

Returns:

[cudaExtent](#) specified by *w*, *h*, and *d*

See also:

[make_cudaPitchedPtr](#), [make_cudaPos](#)

4.8.2.49 struct cudaPitchedPtr make_cudaPitchedPtr (void * *d*, size_t *p*, size_t *xsz*, size_t *ysz*) [read]

Returns a [cudaPitchedPtr](#) based on the specified input parameters *d*, *p*, *xsz*, and *ysz*.

Parameters:

d - Pointer to allocated memory

p - Pitch of allocated memory in bytes

xsz - Logical width of allocation in elements

ysz - Logical height of allocation in elements

Returns:

[cudaPitchedPtr](#) specified by *d*, *p*, *xsz*, and *ysz*

See also:

[make_cudaExtent](#), [make_cudaPos](#)

4.8.2.50 struct cudaPos make_cudaPos (size_t *x*, size_t *y*, size_t *z*) [read]

Returns a [cudaPos](#) based on the specified input parameters *x*, *y*, and *z*.

Parameters:

x - X position

y - Y position

z - Z position

Returns:

[cudaPos](#) specified by *x*, *y*, and *z*

See also:

[make_cudaExtent](#), [make_cudaPitchedPtr](#)

4.9 Unified Addressing

Functions

- [cudaError_t cudaPointerGetAttributes](#) (struct [cudaPointerAttributes](#) *attributes, void *ptr)

Returns attributes about a specified pointer.

4.9.1 Detailed Description

This section describes the unified addressing functions of the CUDA runtime application programming interface.

4.9.2 Overview

CUDA devices can share a unified address space with the host. For these devices there is no distinction between a device pointer and a host pointer – the same pointer value may be used to access memory from the host program and from a kernel running on the device (with exceptions enumerated below).

4.9.3 Supported Platforms

Whether or not a device supports unified addressing may be queried by calling [cudaGetDeviceProperties\(\)](#) with the device property [cudaDeviceProp::unifiedAddressing](#).

Unified addressing is automatically enabled in 64-bit processes on devices with compute capability greater than or equal to 2.0.

Unified addressing is not yet supported on Windows Vista or Windows 7 for devices that do not use the TCC driver model.

4.9.4 Looking Up Information from Pointer Values

It is possible to look up information about the memory which backs a pointer value. For instance, one may want to know if a pointer points to host or device memory. As another example, in the case of device memory, one may want to know on which CUDA device the memory resides. These properties may be queried using the function [cudaPointerGetAttributes\(\)](#)

Because pointers are unique, it is not necessary to specify information about the pointers specified to [cudaMemcpy\(\)](#) and other copy functions. The copy direction [cudaMemcpyDefault](#) may be used to specify that the CUDA runtime should infer the location of the pointer from its value.

4.9.5 Automatic Mapping of Host Allocated Host Memory

All host memory allocated through all devices using [cudaMallocHost\(\)](#) and [cudaHostAlloc\(\)](#) is always directly accessible from all devices that support unified addressing. This is the case regardless of whether or not the flags [cudaHostAllocPortable](#) and [cudaHostAllocMapped](#) are specified.

The pointer value through which allocated host memory may be accessed in kernels on all devices that support unified addressing is the same as the pointer value through which that memory is accessed on the host. It is not necessary to call [cudaHostGetDevicePointer\(\)](#) to get the device pointer for these allocations.

Note that this is not the case for memory allocated using the flag [cudaHostAllocWriteCombined](#), as discussed below.

4.9.6 Direct Access of

Peer Memory

Upon enabling direct access from a device that supports unified addressing to another peer device that supports unified addressing using `cudaDeviceEnablePeerAccess()` all memory allocated in the peer device using `cudaMalloc()` and `cudaMallocPitch()` will immediately be accessible by the current device. The device pointer value through which any peer's memory may be accessed in the current device is the same pointer value through which that memory may be accessed from the peer device.

4.9.7 Exceptions, Disjoint Addressing

Not all memory may be accessed on devices through the same pointer value through which they are accessed on the host. These exceptions are host memory registered using `cudaHostRegister()` and host memory allocated using the flag `cudaHostAllocWriteCombined`. For these exceptions, there exists a distinct host and device address for the memory. The device address is guaranteed to not overlap any valid host pointer range and is guaranteed to have the same value across all devices that support unified addressing.

This device address may be queried using `cudaHostGetDevicePointer()` when a device using unified addressing is current. Either the host or the unified device pointer value may be used to refer to this memory in `cudaMemcpy()` and similar functions using the `cudaMemcpyDefault` memory direction.

4.9.8 Function Documentation

4.9.8.1 `cudaError_t cudaPointerGetAttributes (struct cudaPointerAttributes * attributes, void * ptr)`

Returns in `*attributes` the attributes of the pointer `ptr`.

The `cudaPointerAttributes` structure is defined as:

```
struct cudaPointerAttributes {
    enum cudaMemoryType memoryType;
    int device;
    void *devicePointer;
    void *hostPointer;
}
```

In this structure, the individual fields mean

- `memoryType` identifies the physical location of the memory associated with pointer `ptr`. It can be `cudaMemoryTypeHost` for host memory or `cudaMemoryTypeDevice` for device memory.
- `device` is the device against which `ptr` was allocated. If `ptr` has memory type `cudaMemoryTypeDevice` then this identifies the device on which the memory referred to by `ptr` physically resides. If `ptr` has memory type `cudaMemoryTypeHost` then this identifies the device which was current when the allocation was made (and if that device is deinitialized then this allocation will vanish with that device's state).
- `devicePointer` is the device pointer alias through which the memory referred to by `ptr` may be accessed on the current device. If the memory referred to by `ptr` cannot be accessed directly by the current device then this is `NULL`.
- `hostPointer` is the host pointer alias through which the memory referred to by `ptr` may be accessed on the host. If the memory referred to by `ptr` cannot be accessed directly by the host then this is `NULL`.

Parameters:

attributes - Attributes for the specified pointer

ptr - Pointer to get attributes for

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#)

See also:

[cudaGetDeviceCount](#), [cudaGetDevice](#), [cudaSetDevice](#), [cudaChooseDevice](#)

4.10 Peer Device Memory Access

Functions

- [cudaError_t cudaDeviceCanAccessPeer](#) (int *canAccessPeer, int device, int peerDevice)
Queries if a device may directly access a peer device's memory.
- [cudaError_t cudaDeviceDisablePeerAccess](#) (int peerDevice)
Disables direct access to memory allocations on a peer device and unregisters any registered allocations from that device.
- [cudaError_t cudaDeviceEnablePeerAccess](#) (int peerDevice, unsigned int flags)
Enables direct access to memory allocations on a peer device.

4.10.1 Detailed Description

This section describes the peer device memory access functions of the CUDA runtime application programming interface.

4.10.2 Function Documentation

4.10.2.1 [cudaError_t cudaDeviceCanAccessPeer](#) (int *canAccessPeer, int device, int peerDevice)

Returns in *canAccessPeer a value of 1 if device device is capable of directly accessing memory from peerDevice and 0 otherwise. If direct access of peerDevice from device is possible, then access may be enabled by calling [cudaDeviceEnablePeerAccess\(\)](#).

Parameters:

canAccessPeer - Returned access capability

device - Device from which allocations on peerDevice are to be directly accessed.

peerDevice - Device on which the allocations to be directly accessed by device reside.

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceEnablePeerAccess](#), [cudaDeviceDisablePeerAccess](#)

4.10.2.2 [cudaError_t cudaDeviceDisablePeerAccess](#) (int peerDevice)

Disables registering memory on peerDevice for direct access from the current device. If there are any allocations on peerDevice which were registered in the current device using [cudaPeerRegister\(\)](#) then these allocations will be automatically unregistered.

Returns [cudaErrorPeerAccessNotEnabled](#) if direct access to memory on `peerDevice` has not yet been enabled from the current device.

Parameters:

peerDevice - Peer device to disable direct access to

Returns:

[cudaSuccess](#), [cudaErrorPeerAccessNotEnabled](#), [cudaErrorInvalidDevice](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceCanAccessPeer](#), [cudaDeviceEnablePeerAccess](#)

4.10.2.3 `cudaError_t cudaDeviceEnablePeerAccess (int peerDevice, unsigned int flags)`

Enables registering memory on `peerDevice` for direct access from the current device. On success, allocations on `peerDevice` may be registered for access from the current device using `cudaPeerRegister()`. Registering peer memory will be possible until it is explicitly disabled using [cudaDeviceDisablePeerAccess\(\)](#), or either the current device or `peerDevice` is reset using [cudaDeviceReset\(\)](#).

If both the current device and `peerDevice` support unified addressing then all allocations from `peerDevice` will immediately be accessible by the current device upon success. In this case, explicitly sharing allocations using `cudaPeerRegister()` is not necessary.

Note that access granted by this call is unidirectional and that in order to access memory on the current device from `peerDevice`, a separate symmetric call to [cudaDeviceEnablePeerAccess\(\)](#) is required.

Returns [cudaErrorInvalidDevice](#) if [cudaDeviceCanAccessPeer\(\)](#) indicates that the current device cannot directly access memory from `peerDevice`.

Returns [cudaErrorPeerAccessAlreadyEnabled](#) if direct access of `peerDevice` from the current device has already been enabled.

Returns [cudaErrorInvalidValue](#) if `flags` is not 0.

Parameters:

peerDevice - Peer device to enable direct access to from the current device

flags - Reserved for future use and must be set to 0

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#), [cudaErrorPeerAccessAlreadyEnabled](#), [cudaErrorInvalidValue](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaDeviceCanAccessPeer](#), [cudaDeviceDisablePeerAccess](#)

4.11 OpenGL Interoperability

Modules

- [OpenGL Interoperability \[DEPRECATED\]](#)

Enumerations

- enum [cudaGLDeviceList](#) {
[cudaGLDeviceListAll](#) = 1,
[cudaGLDeviceListCurrentFrame](#) = 2,
[cudaGLDeviceListNextFrame](#) = 3 }

Functions

- [cudaError_t cudaGLGetDevices](#) (unsigned int *pCudaDeviceCount, int *pCudaDevices, unsigned int cudaDeviceCount, enum [cudaGLDeviceList](#) deviceList)
Gets the CUDA devices associated with the current OpenGL context.
- [cudaError_t cudaGLSetGLDevice](#) (int device)
Sets a CUDA device to use OpenGL interoperability.
- [cudaError_t cudaGraphicsGLRegisterBuffer](#) (struct cudaGraphicsResource **resource, GLuint buffer, unsigned int flags)
Registers an OpenGL buffer object.
- [cudaError_t cudaGraphicsGLRegisterImage](#) (struct cudaGraphicsResource **resource, GLuint image, GLenum target, unsigned int flags)
Register an OpenGL texture or renderbuffer object.
- [cudaError_t cudaWGLGetDevice](#) (int *device, HGPUNV hGpu)
Gets the CUDA device associated with hGpu.

4.11.1 Detailed Description

This section describes the OpenGL interoperability functions of the CUDA runtime application programming interface. Note that mapping of OpenGL resources is performed with the graphics API agnostic, resource mapping interface described in [Graphics Interopability](#).

4.11.2 Enumeration Type Documentation

4.11.2.1 enum cudaGLDeviceList

CUDA devices corresponding to the current OpenGL context

Enumerator:

cudaGLDeviceListAll The CUDA devices for all GPUs used by the current OpenGL context

cudaGLDeviceListCurrentFrame The CUDA devices for the GPUs used by the current OpenGL context in its currently rendering frame

cudaGLDeviceListNextFrame The CUDA devices for the GPUs to be used by the current OpenGL context in the next frame

4.11.3 Function Documentation

4.11.3.1 `cudaError_t cudaGLGetDevices (unsigned int *pCudaDeviceCount, int *pCudaDevices, unsigned int cudaDeviceCount, enum cudaGLDeviceList deviceList)`

Returns in *pCudaDeviceCount* the number of CUDA-compatible devices corresponding to the current OpenGL context. Also returns in *pCudaDevices* at most *cudaDeviceCount* of the CUDA-compatible devices corresponding to the current OpenGL context. If any of the GPUs being used by the current OpenGL context are not CUDA capable then the call will return [cudaErrorNoDevice](#).

Parameters:

pCudaDeviceCount - Returned number of CUDA devices corresponding to the current OpenGL context

pCudaDevices - Returned CUDA devices corresponding to the current OpenGL context

cudaDeviceCount - The size of the output device array *pCudaDevices*

deviceList - The set of devices to return. This set may be [cudaGLDeviceListAll](#) for all devices, [cudaGLDeviceListCurrentFrame](#) for the devices used to render the current frame (in SLI), or [cudaGLDeviceListNextFrame](#) for the devices used to render the next frame (in SLI).

Returns:

[cudaSuccess](#), [cudaErrorNoDevice](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnregisterResource](#), [cudaGraphicsMapResources](#), [cudaGraphicsSubResourceGetMappedArray](#), [cudaGraphicsResourceGetMappedPointer](#)

4.11.3.2 `cudaError_t cudaGLSetGLDevice (int device)`

Records the calling thread's current OpenGL context as the OpenGL context to use for OpenGL interoperability with the CUDA device *device* and sets *device* as the current device for the calling host thread.

If *device* has already been initialized then this call will fail with the error [cudaErrorSetOnActiveProcess](#). In this case it is necessary to reset *device* using [cudaDeviceReset\(\)](#) before OpenGL interoperability on *device* may be enabled.

Parameters:

device - Device to use for OpenGL interoperability

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#), [cudaErrorSetOnActiveProcess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGLRegisterBufferObject](#), [cudaGLMapBufferObject](#), [cudaGLUnmapBufferObject](#), [cudaGLUnregisterBufferObject](#), [cudaGLMapBufferObjectAsync](#), [cudaGLUnmapBufferObjectAsync](#), [cudaDeviceReset](#)

4.11.3.3 `cudaError_t cudaGraphicsGLRegisterBuffer (struct cudaGraphicsResource ** resource, GLuint buffer, unsigned int flags)`

Registers the buffer object specified by `buffer` for access by CUDA. A handle to the registered object is returned as `resource`. The register flags `flags` specify the intended usage, as follows:

- [cudaGraphicsRegisterFlagsNone](#): Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA. This is the default value.
- [cudaGraphicsRegisterFlagsReadOnly](#): Specifies that CUDA will not write to this resource.
- [cudaGraphicsRegisterFlagsWriteDiscard](#): Specifies that CUDA will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

Parameters:

resource - Pointer to the returned object handle

buffer - name of buffer object to be registered

flags - Register flags

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGLSetGLDevice](#), [cudaGraphicsUnregisterResource](#), [cudaGraphicsMapResources](#), [cudaGraphicsResourceGetMappedPointer](#)

4.11.3.4 `cudaError_t cudaGraphicsGLRegisterImage (struct cudaGraphicsResource ** resource, GLuint image, GLenum target, unsigned int flags)`

Registers the texture or renderbuffer object specified by `image` for access by CUDA. A handle to the registered object is returned as `resource`.

`target` must match the type of the object, and must be one of `GL_TEXTURE_2D`, `GL_TEXTURE_RECTANGLE`, `GL_TEXTURE_CUBE_MAP`, `GL_TEXTURE_3D`, `GL_TEXTURE_2D_ARRAY`, or `GL_RENDERBUFFER`.

The register flags `flags` specify the intended usage, as follows:

- [cudaGraphicsRegisterFlagsNone](#): Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA. This is the default value.

- [cudaGraphicsRegisterFlagsReadOnly](#): Specifies that CUDA will not write to this resource.
- [cudaGraphicsRegisterFlagsWriteDiscard](#): Specifies that CUDA will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.
- [cudaGraphicsRegisterFlagsSurfaceLoadStore](#): Specifies that CUDA will bind this resource to a surface reference.
- [cudaGraphicsRegisterFlagsTextureGather](#): Specifies that CUDA will perform texture gather operations on this resource.

The following image formats are supported. For brevity's sake, the list is abbreviated. For ex., {GL_R, GL_RG} X {8, 16} would expand to the following 4 formats {GL_R8, GL_R16, GL_RG8, GL_RG16} :

- GL_RED, GL_RG, GL_RGBA, GL_LUMINANCE, GL_ALPHA, GL_LUMINANCE_ALPHA, GL_INTENSITY
- {GL_R, GL_RG, GL_RGBA} X {8, 16, 16F, 32F, 8UI, 16UI, 32UI, 8I, 16I, 32I}
- {GL_LUMINANCE, GL_ALPHA, GL_LUMINANCE_ALPHA, GL_INTENSITY} X {8, 16, 16F_ARB, 32F_ARB, 8UI_EXT, 16UI_EXT, 32UI_EXT, 8I_EXT, 16I_EXT, 32I_EXT}

The following image classes are currently disallowed:

- Textures with borders
- Multisampled renderbuffers

Parameters:

resource - Pointer to the returned object handle
image - name of texture or renderbuffer object to be registered
target - Identifies the type of object specified by *image*
flags - Register flags

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGLSetGLDevice](#), [cudaGraphicsUnregisterResource](#), [cudaGraphicsMapResources](#), [cudaGraphicsSubResourceGetMappedArray](#)

4.11.3.5 `cudaError_t cudaWGLGetDevice (int * device, HGPUNV hGpu)`

Returns the CUDA device associated with a hGpu, if applicable.

Parameters:

device - Returns the device associated with hGpu, or -1 if hGpu is not a compute device.

hGpu - Handle to a GPU, as queried via WGL_NV_gpu_affinity

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

WGL_NV_gpu_affinity, [cudaGLSetGLDevice](#)

4.12 Direct3D 9 Interoperability

Modules

- [Direct3D 9 Interoperability \[DEPRECATED\]](#)

Enumerations

- enum [cudaD3D9DeviceList](#) {
[cudaD3D9DeviceListAll](#) = 1,
[cudaD3D9DeviceListCurrentFrame](#) = 2,
[cudaD3D9DeviceListNextFrame](#) = 3 }

Functions

- [cudaError_t cudaD3D9GetDevice](#) (int *device, const char *pszAdapterName)
Gets the device number for an adapter.
- [cudaError_t cudaD3D9GetDevices](#) (unsigned int *pCudaDeviceCount, int *pCudaDevices, unsigned int cudaDeviceCount, IDirect3DDevice9 *pD3D9Device, enum [cudaD3D9DeviceList](#) deviceList)
Gets the CUDA devices corresponding to a Direct3D 9 device.
- [cudaError_t cudaD3D9GetDirect3DDevice](#) (IDirect3DDevice9 **ppD3D9Device)
Gets the Direct3D device against which the current CUDA context was created.
- [cudaError_t cudaD3D9SetDirect3DDevice](#) (IDirect3DDevice9 *pD3D9Device, int device=-1)
Sets the Direct3D 9 device to use for interoperability with a CUDA device.
- [cudaError_t cudaGraphicsD3D9RegisterResource](#) (struct [cudaGraphicsResource](#) **resource, IDirect3DResource9 *pD3DResource, unsigned int flags)
Register a Direct3D 9 resource for access by CUDA.

4.12.1 Detailed Description

This section describes the Direct3D 9 interoperability functions of the CUDA runtime application programming interface. Note that mapping of Direct3D 9 resources is performed with the graphics API agnostic, resource mapping interface described in [Graphics Interoperability](#).

4.12.2 Enumeration Type Documentation

4.12.2.1 enum [cudaD3D9DeviceList](#)

CUDA devices corresponding to a D3D9 device

Enumerator:

[cudaD3D9DeviceListAll](#) The CUDA devices for all GPUs used by a D3D9 device

cudaD3D9DeviceListCurrentFrame The CUDA devices for the GPUs used by a D3D9 device in its currently rendering frame

cudaD3D9DeviceListNextFrame The CUDA devices for the GPUs to be used by a D3D9 device in the next frame

4.12.3 Function Documentation

4.12.3.1 `cudaError_t cudaD3D9GetDevice (int * device, const char * pszAdapterName)`

Returns in *device* the CUDA-compatible device corresponding to the adapter name *pszAdapterName* obtained from EnumDisplayDevices or IDirect3D9::GetAdapterIdentifier(). If no device on the adapter with name *pszAdapterName* is CUDA-compatible then the call will fail.

Parameters:

device - Returns the device corresponding to *pszAdapterName*

pszAdapterName - D3D9 adapter to get device for

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaD3D9SetDirect3DDevice](#), [cudaGraphicsD3D9RegisterResource](#),

4.12.3.2 `cudaError_t cudaD3D9GetDevices (unsigned int * pCudaDeviceCount, int * pCudaDevices, unsigned int cudaDeviceCount, IDirect3DDevice9 * pD3D9Device, enum cudaD3D9DeviceList deviceList)`

Returns in *pCudaDeviceCount* the number of CUDA-compatible devices corresponding to the Direct3D 9 device *pD3D9Device*. Also returns in *pCudaDevices* at most *cudaDeviceCount* of the the CUDA-compatible devices corresponding to the Direct3D 9 device *pD3D9Device*.

If any of the GPUs being used to render *pDevice* are not CUDA capable then the call will return [cudaErrorNoDevice](#).

Parameters:

pCudaDeviceCount - Returned number of CUDA devices corresponding to *pD3D9Device*

pCudaDevices - Returned CUDA devices corresponding to *pD3D9Device*

cudaDeviceCount - The size of the output device array *pCudaDevices*

pD3D9Device - Direct3D 9 device to query for CUDA devices

deviceList - The set of devices to return. This set may be [cudaD3D9DeviceListAll](#) for all devices, [cudaD3D9DeviceListCurrentFrame](#) for the devices used to render the current frame (in SLI), or [cudaD3D9DeviceListNextFrame](#) for the devices used to render the next frame (in SLI).

Returns:

[cudaSuccess](#), [cudaErrorNoDevice](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnregisterResource](#), [cudaGraphicsMapResources](#), [cudaGraphicsSubResourceGetMappedArray](#), [cudaGraphicsResourceGetMappedPointer](#)

4.12.3.3 `cudaError_t cudaD3D9GetDirect3DDevice (IDirect3DDevice9 **ppD3D9Device)`

Returns in `*ppD3D9Device` the Direct3D device against which this CUDA context was created in [cu-daD3D9SetDirect3DDevice\(\)](#).

Parameters:

ppD3D9Device - Returns the Direct3D device for this thread

Returns:

[cudaSuccess](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaD3D9SetDirect3DDevice](#)

4.12.3.4 `cudaError_t cudaD3D9SetDirect3DDevice (IDirect3DDevice9 *pD3D9Device, int device = -1)`

Records `pD3D9Device` as the Direct3D 9 device to use for Direct3D 9 interoperability with the CUDA device `device` and sets `device` as the current device for the calling host thread.

If `device` has already been initialized then this call will fail with the error [cudaErrorSetOnActiveProcess](#). In this case it is necessary to reset `device` using [cudaDeviceReset\(\)](#) before Direct3D 9 interoperability on `device` may be enabled.

Successfully initializing CUDA interoperability with `pD3D9Device` will increase the internal reference count on `pD3D9Device`. This reference count will be decremented when `device` is reset using [cudaDeviceReset\(\)](#).

Parameters:

pD3D9Device - Direct3D device to use for this thread

device - The CUDA device to use. This device must be among the devices returned when querying [cu-daD3D9DeviceListAll](#) from [cudaD3D9GetDevices](#), may be set to -1 to automatically select an appropriate CUDA device.

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#), [cudaErrorInvalidValue](#), [cudaErrorSetOnActiveProcess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaD3D9GetDevice](#), [cudaGraphicsD3D9RegisterResource](#), [cudaDeviceReset](#)

4.12.3.5 `cudaError_t cudaGraphicsD3D9RegisterResource (struct cudaGraphicsResource ** resource, IDirect3DResource9 * pD3DResource, unsigned int flags)`

Registers the Direct3D 9 resource `pD3DResource` for access by CUDA.

If this call is successful then the application will be able to map and unmap this resource until it is unregistered through `cudaGraphicsUnregisterResource()`. Also on success, this call will increase the internal reference count on `pD3DResource`. This reference count will be decremented when this resource is unregistered through `cudaGraphicsUnregisterResource()`.

This call is potentially high-overhead and should not be called every frame in interactive applications.

The type of `pD3DResource` must be one of the following.

- `IDirect3DVertexBuffer9`: may be accessed through a device pointer
- `IDirect3DIndexBuffer9`: may be accessed through a device pointer
- `IDirect3DSurface9`: may be accessed through an array. Only stand-alone objects of type `IDirect3DSurface9` may be explicitly shared. In particular, individual mipmap levels and faces of cube maps may not be registered directly. To access individual surfaces associated with a texture, one must register the base texture object.
- `IDirect3DBaseTexture9`: individual surfaces on this texture may be accessed through an array.

The `flags` argument may be used to specify additional parameters at register time. The valid values for this parameter are

- `cudaGraphicsRegisterFlagsNone`: Specifies no hints about how this resource will be used.
- `cudaGraphicsRegisterFlagsSurfaceLoadStore`: Specifies that CUDA will bind this resource to a surface reference.
- `cudaGraphicsRegisterFlagsTextureGather`: Specifies that CUDA will perform texture gather operations on this resource.

Not all Direct3D resources of the above types may be used for interoperability with CUDA. The following are some limitations.

- The primary rendertarget may not be registered with CUDA.
- Resources allocated as shared may not be registered with CUDA.
- Textures which are not of a format which is 1, 2, or 4 channels of 8, 16, or 32-bit integer or floating-point data cannot be shared.
- Surfaces of depth or stencil formats cannot be shared.

If Direct3D interoperability is not initialized using `cudaD3D9SetDirect3DDevice` then `cudaErrorInvalidDevice` is returned. If `pD3DResource` is of incorrect type or is already registered, then `cudaErrorInvalidResourceHandle` is returned. If `pD3DResource` cannot be registered, then `cudaErrorUnknown` is returned.

Parameters:

- resource* - Pointer to returned resource handle
- pD3DResource* - Direct3D resource to register
- flags* - Parameters for resource registration

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaD3D9SetDirect3DDevice](#), [cudaGraphicsUnregisterResource](#), [cudaGraphicsMapResources](#), [cudaGraphicsSubResourceGetMappedArray](#), [cudaGraphicsResourceGetMappedPointer](#)

4.13 Direct3D 10 Interoperability

Modules

- [Direct3D 10 Interoperability \[DEPRECATED\]](#)

Enumerations

- enum [cudaD3D10DeviceList](#) {
[cudaD3D10DeviceListAll](#) = 1,
[cudaD3D10DeviceListCurrentFrame](#) = 2,
[cudaD3D10DeviceListNextFrame](#) = 3 }

Functions

- [cudaError_t cudaD3D10GetDevice](#) (int *device, IDXGIAdapter *pAdapter)
Gets the device number for an adapter.
- [cudaError_t cudaD3D10GetDevices](#) (unsigned int *pCudaDeviceCount, int *pCudaDevices, unsigned int cudaDeviceCount, ID3D10Device *pD3D10Device, enum [cudaD3D10DeviceList](#) deviceList)
Gets the CUDA devices corresponding to a Direct3D 10 device.
- [cudaError_t cudaD3D10GetDirect3DDevice](#) (ID3D10Device **ppD3D10Device)
Gets the Direct3D device against which the current CUDA context was created.
- [cudaError_t cudaD3D10SetDirect3DDevice](#) (ID3D10Device *pD3D10Device, int device=-1)
Sets the Direct3D 10 device to use for interoperability with a CUDA device.
- [cudaError_t cudaGraphicsD3D10RegisterResource](#) (struct [cudaGraphicsResource](#) **resource, ID3D10Resource *pD3DResource, unsigned int flags)
Register a Direct3D 10 resource for access by CUDA.

4.13.1 Detailed Description

This section describes the Direct3D 10 interoperability functions of the CUDA runtime application programming interface. Note that mapping of Direct3D 10 resources is performed with the graphics API agnostic, resource mapping interface described in [Graphics Interoperability](#).

4.13.2 Enumeration Type Documentation

4.13.2.1 enum cudaD3D10DeviceList

CUDA devices corresponding to a D3D10 device

Enumerator:

cudaD3D10DeviceListAll The CUDA devices for all GPUs used by a D3D10 device

cudaD3D10DeviceListCurrentFrame The CUDA devices for the GPUs used by a D3D10 device in its currently rendering frame

cudaD3D10DeviceListNextFrame The CUDA devices for the GPUs to be used by a D3D10 device in the next frame

4.13.3 Function Documentation

4.13.3.1 `cudaError_t cudaD3D10GetDevice (int * device, IDXGIAdapter * pAdapter)`

Returns in **device* the CUDA-compatible device corresponding to the adapter *pAdapter* obtained from IDXGIFactory::EnumAdapters. This call will succeed only if a device on adapter *pAdapter* is Cuda-compatible.

Parameters:

device - Returns the device corresponding to *pAdapter*

pAdapter - D3D10 adapter to get device for

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaD3D10SetDirect3DDevice](#), [cudaGraphicsD3D10RegisterResource](#),

4.13.3.2 `cudaError_t cudaD3D10GetDevices (unsigned int * pCudaDeviceCount, int * pCudaDevices, unsigned int cudaDeviceCount, ID3D10Device * pD3D10Device, enum cudaD3D10DeviceList deviceList)`

Returns in **pCudaDeviceCount* the number of CUDA-compatible devices corresponding to the Direct3D 10 device *pD3D10Device*. Also returns in **pCudaDevices* at most *cudaDeviceCount* of the the CUDA-compatible devices corresponding to the Direct3D 10 device *pD3D10Device*.

If any of the GPUs being used to render *pDevice* are not CUDA capable then the call will return [cudaErrorNoDevice](#).

Parameters:

pCudaDeviceCount - Returned number of CUDA devices corresponding to *pD3D10Device*

pCudaDevices - Returned CUDA devices corresponding to *pD3D10Device*

cudaDeviceCount - The size of the output device array *pCudaDevices*

pD3D10Device - Direct3D 10 device to query for CUDA devices

deviceList - The set of devices to return. This set may be [cudaD3D10DeviceListAll](#) for all devices, [cudaD3D10DeviceListCurrentFrame](#) for the devices used to render the current frame (in SLI), or [cudaD3D10DeviceListNextFrame](#) for the devices used to render the next frame (in SLI).

Returns:

[cudaSuccess](#), [cudaErrorNoDevice](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnregisterResource](#), [cudaGraphicsMapResources](#), [cudaGraphicsSubResourceGetMappedArray](#), [cudaGraphicsResourceGetMappedPointer](#)

4.13.3.3 `cudaError_t cudaD3D10GetDirect3DDevice (ID3D10Device ** ppD3D10Device)`

Returns in `*ppD3D10Device` the Direct3D device against which this CUDA context was created in [cudaD3D10SetDirect3DDevice\(\)](#).

Parameters:

ppD3D10Device - Returns the Direct3D device for this thread

Returns:

[cudaSuccess](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaD3D10SetDirect3DDevice](#)

4.13.3.4 `cudaError_t cudaD3D10SetDirect3DDevice (ID3D10Device * pD3D10Device, int device = -1)`

Records `pD3D10Device` as the Direct3D 10 device to use for Direct3D 10 interoperability with the CUDA device `device` and sets `device` as the current device for the calling host thread.

If `device` has already been initialized then this call will fail with the error [cudaErrorSetOnActiveProcess](#). In this case it is necessary to reset `device` using [cudaDeviceReset\(\)](#) before Direct3D 10 interoperability on `device` may be enabled.

Successfully initializing CUDA interoperability with `pD3D10Device` will increase the internal reference count on `pD3D10Device`. This reference count will be decremented when `device` is reset using [cudaDeviceReset\(\)](#).

Parameters:

pD3D10Device - Direct3D device to use for interoperability

device - The CUDA device to use. This device must be among the devices returned when querying [cudaD3D10DeviceListAll](#) from [cudaD3D10GetDevices](#), may be set to -1 to automatically select an appropriate CUDA device.

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#), [cudaErrorInvalidValue](#), [cudaErrorSetOnActiveProcess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaD3D10GetDevice](#), [cudaGraphicsD3D10RegisterResource](#), [cudaDeviceReset](#)

4.13.3.5 `cudaError_t cudaGraphicsD3D10RegisterResource` (struct `cudaGraphicsResource` ** *resource*, `ID3D10Resource` * *pD3DResource*, unsigned int *flags*)

Registers the Direct3D 10 resource `pD3DResource` for access by CUDA.

If this call is successful, then the application will be able to map and unmap this resource until it is unregistered through `cudaGraphicsUnregisterResource()`. Also on success, this call will increase the internal reference count on `pD3DResource`. This reference count will be decremented when this resource is unregistered through `cudaGraphicsUnregisterResource()`.

This call is potentially high-overhead and should not be called every frame in interactive applications.

The type of `pD3DResource` must be one of the following.

- `ID3D10Buffer`: may be accessed via a device pointer
- `ID3D10Texture1D`: individual subresources of the texture may be accessed via arrays
- `ID3D10Texture2D`: individual subresources of the texture may be accessed via arrays
- `ID3D10Texture3D`: individual subresources of the texture may be accessed via arrays

The `flags` argument may be used to specify additional parameters at register time. The valid values for this parameter are

- `cudaGraphicsRegisterFlagsNone`: Specifies no hints about how this resource will be used.
- `cudaGraphicsRegisterFlagsSurfaceLoadStore`: Specifies that CUDA will bind this resource to a surface reference.
- `cudaGraphicsRegisterFlagsTextureGather`: Specifies that CUDA will perform texture gather operations on this resource.

Not all Direct3D resources of the above types may be used for interoperability with CUDA. The following are some limitations.

- The primary rendertarget may not be registered with CUDA.
- Resources allocated as shared may not be registered with CUDA.
- Textures which are not of a format which is 1, 2, or 4 channels of 8, 16, or 32-bit integer or floating-point data cannot be shared.
- Surfaces of depth or stencil formats cannot be shared.

If Direct3D interoperability is not initialized using `cudaD3D10SetDirect3DDevice` then `cudaErrorInvalidDevice` is returned. If `pD3DResource` is of incorrect type or is already registered, then `cudaErrorInvalidResourceHandle` is returned. If `pD3DResource` cannot be registered, then `cudaErrorUnknown` is returned.

Parameters:

resource - Pointer to returned resource handle
pD3DResource - Direct3D resource to register
flags - Parameters for resource registration

Returns:

`cudaSuccess`, `cudaErrorInvalidDevice`, `cudaErrorInvalidValue`, `cudaErrorInvalidResourceHandle`, `cudaErrorUnknown`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaD3D10SetDirect3DDevice](#), [cudaGraphicsUnregisterResource](#), [cudaGraphicsMapResources](#), [cudaGraphicsResourceGetMappedArray](#), [cudaGraphicsResourceGetMappedPointer](#)

4.14 Direct3D 11 Interoperability

Enumerations

- enum `cudaD3D11DeviceList` {
`cudaD3D11DeviceListAll` = 1,
`cudaD3D11DeviceListCurrentFrame` = 2,
`cudaD3D11DeviceListNextFrame` = 3 }

Functions

- `cudaError_t cudaD3D11GetDevice` (int *device, IDXGIAdapter *pAdapter)
Gets the device number for an adapter.
- `cudaError_t cudaD3D11GetDevices` (unsigned int *pCudaDeviceCount, int *pCudaDevices, unsigned int cudaDeviceCount, ID3D11Device *pD3D11Device, enum `cudaD3D11DeviceList` deviceList)
Gets the CUDA devices corresponding to a Direct3D 11 device.
- `cudaError_t cudaD3D11GetDirect3DDevice` (ID3D11Device **ppD3D11Device)
Gets the Direct3D device against which the current CUDA context was created.
- `cudaError_t cudaD3D11SetDirect3DDevice` (ID3D11Device *pD3D11Device, int device=-1)
Sets the Direct3D 11 device to use for interoperability with a CUDA device.
- `cudaError_t cudaGraphicsD3D11RegisterResource` (struct `cudaGraphicsResource` **resource, ID3D11Resource *pD3DRResource, unsigned int flags)
Register a Direct3D 11 resource for access by CUDA.

4.14.1 Detailed Description

This section describes the Direct3D 11 interoperability functions of the CUDA runtime application programming interface. Note that mapping of Direct3D 11 resources is performed with the graphics API agnostic, resource mapping interface described in [Graphics Interoperability](#).

4.14.2 Enumeration Type Documentation

4.14.2.1 enum `cudaD3D11DeviceList`

CUDA devices corresponding to a D3D11 device

Enumerator:

`cudaD3D11DeviceListAll` The CUDA devices for all GPUs used by a D3D11 device

`cudaD3D11DeviceListCurrentFrame` The CUDA devices for the GPUs used by a D3D11 device in its currently rendering frame

`cudaD3D11DeviceListNextFrame` The CUDA devices for the GPUs to be used by a D3D11 device in the next frame

4.14.3 Function Documentation

4.14.3.1 `cudaError_t cudaD3D11GetDevice (int * device, IDXGIAdapter * pAdapter)`

Returns in **device* the CUDA-compatible device corresponding to the adapter *pAdapter* obtained from `IDXGI-Factory::EnumAdapters`. This call will succeed only if a device on adapter *pAdapter* is Cuda-compatible.

Parameters:

device - Returns the device corresponding to *pAdapter*
pAdapter - D3D11 adapter to get device for

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnregisterResource](#), [cudaGraphicsMapResources](#), [cudaGraphicsSubResourceGetMappedArray](#), [cudaGraphicsResourceGetMappedPointer](#)

4.14.3.2 `cudaError_t cudaD3D11GetDevices (unsigned int * pCudaDeviceCount, int * pCudaDevices, unsigned int cudaDeviceCount, ID3D11Device * pD3D11Device, enum cudaD3D11DeviceList deviceList)`

Returns in **pCudaDeviceCount* the number of CUDA-compatible devices corresponding to the Direct3D 11 device *pD3D11Device*. Also returns in **pCudaDevices* at most *cudaDeviceCount* of the the CUDA-compatible devices corresponding to the Direct3D 11 device *pD3D11Device*.

If any of the GPUs being used to render *pDevice* are not CUDA capable then the call will return [cudaErrorNoDevice](#).

Parameters:

pCudaDeviceCount - Returned number of CUDA devices corresponding to *pD3D11Device*
pCudaDevices - Returned CUDA devices corresponding to *pD3D11Device*
cudaDeviceCount - The size of the output device array *pCudaDevices*
pD3D11Device - Direct3D 11 device to query for CUDA devices
deviceList - The set of devices to return. This set may be [cudaD3D11DeviceListAll](#) for all devices, [cudaD3D11DeviceListCurrentFrame](#) for the devices used to render the current frame (in SLI), or [cudaD3D11DeviceListNextFrame](#) for the devices used to render the next frame (in SLI).

Returns:

[cudaSuccess](#), [cudaErrorNoDevice](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnregisterResource](#), [cudaGraphicsMapResources](#), [cudaGraphicsSubResourceGetMappedArray](#), [cudaGraphicsResourceGetMappedPointer](#)

4.14.3.3 `cudaError_t cudaD3D11GetDirect3DDevice (ID3D11Device ** ppD3D11Device)`

Returns in `*ppD3D11Device` the Direct3D device against which this CUDA context was created in `cudaD3D11SetDirect3DDevice()`.

Parameters:

ppD3D11Device - Returns the Direct3D device for this thread

Returns:

`cudaSuccess`, `cudaErrorUnknown`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaD3D11SetDirect3DDevice`

4.14.3.4 `cudaError_t cudaD3D11SetDirect3DDevice (ID3D11Device * pD3D11Device, int device = -1)`

Records `pD3D11Device` as the Direct3D 11 device to use for Direct3D 11 interoperability with the CUDA device `device` and sets `device` as the current device for the calling host thread.

If `device` has already been initialized then this call will fail with the error `cudaErrorSetActiveProcess`. In this case it is necessary to reset `device` using `cudaDeviceReset()` before Direct3D 11 interoperability on `device` may be enabled.

Successfully initializing CUDA interoperability with `pD3D11Device` will increase the internal reference count on `pD3D11Device`. This reference count will be decremented when `device` is reset using `cudaDeviceReset()`.

Parameters:

pD3D11Device - Direct3D device to use for interoperability

device - The CUDA device to use. This device must be among the devices returned when querying `cudaD3D11DeviceListAll` from `cudaD3D11GetDevices`, may be set to -1 to automatically select an appropriate CUDA device.

Returns:

`cudaSuccess`, `cudaErrorInitializationError`, `cudaErrorInvalidValue`, `cudaErrorSetActiveProcess`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaD3D11GetDevice`, `cudaGraphicsD3D11RegisterResource`, `cudaDeviceReset`

4.14.3.5 `cudaError_t cudaGraphicsD3D11RegisterResource` (struct `cudaGraphicsResource` ** *resource*, `ID3D11Resource` * *pD3DResource*, unsigned int *flags*)

Registers the Direct3D 11 resource `pD3DResource` for access by CUDA.

If this call is successful, then the application will be able to map and unmap this resource until it is unregistered through `cudaGraphicsUnregisterResource()`. Also on success, this call will increase the internal reference count on `pD3DResource`. This reference count will be decremented when this resource is unregistered through `cudaGraphicsUnregisterResource()`.

This call is potentially high-overhead and should not be called every frame in interactive applications.

The type of `pD3DResource` must be one of the following.

- `ID3D11Buffer`: may be accessed via a device pointer
- `ID3D11Texture1D`: individual subresources of the texture may be accessed via arrays
- `ID3D11Texture2D`: individual subresources of the texture may be accessed via arrays
- `ID3D11Texture3D`: individual subresources of the texture may be accessed via arrays

The `flags` argument may be used to specify additional parameters at register time. The valid values for this parameter are

- `cudaGraphicsRegisterFlagsNone`: Specifies no hints about how this resource will be used.
- `cudaGraphicsRegisterFlagsSurfaceLoadStore`: Specifies that CUDA will bind this resource to a surface reference.
- `cudaGraphicsRegisterFlagsTextureGather`: Specifies that CUDA will perform texture gather operations on this resource.

Not all Direct3D resources of the above types may be used for interoperability with CUDA. The following are some limitations.

- The primary rendertarget may not be registered with CUDA.
- Resources allocated as shared may not be registered with CUDA.
- Textures which are not of a format which is 1, 2, or 4 channels of 8, 16, or 32-bit integer or floating-point data cannot be shared.
- Surfaces of depth or stencil formats cannot be shared.

If Direct3D interoperability is not initialized using `cudaD3D11SetDirect3DDevice` then `cudaErrorInvalidDevice` is returned. If `pD3DResource` is of incorrect type or is already registered, then `cudaErrorInvalidResourceHandle` is returned. If `pD3DResource` cannot be registered, then `cudaErrorUnknown` is returned.

Parameters:

resource - Pointer to returned resource handle
pD3DResource - Direct3D resource to register
flags - Parameters for resource registration

Returns:

`cudaSuccess`, `cudaErrorInvalidDevice`, `cudaErrorInvalidValue`, `cudaErrorInvalidResourceHandle`, `cudaErrorUnknown`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaD3D11SetDirect3DDevice](#), [cudaGraphicsUnregisterResource](#), [cudaGraphicsMapResources](#), [cudaGraphicsResourceGetMappedArray](#), [cudaGraphicsResourceGetMappedPointer](#)

4.15 VDPAU Interoperability

Functions

- [cudaError_t cudaGraphicsVDPAURegisterOutputSurface](#) (struct cudaGraphicsResource **resource, VdpOutputSurface vdpSurface, unsigned int flags)
Register a VdpOutputSurface object.
- [cudaError_t cudaGraphicsVDPAURegisterVideoSurface](#) (struct cudaGraphicsResource **resource, VdpVideoSurface vdpSurface, unsigned int flags)
Register a VdpVideoSurface object.
- [cudaError_t cudaVDPAUGetDevice](#) (int *device, VdpDevice vdpDevice, VdpGetProcAddress *vdpGetProcAddress)
Gets the CUDA device associated with a VdpDevice.
- [cudaError_t cudaVDPAUSetVDPAUDevice](#) (int device, VdpDevice vdpDevice, VdpGetProcAddress *vdpGetProcAddress)
Sets a CUDA device to use VDPAU interoperability.

4.15.1 Detailed Description

This section describes the VDPAU interoperability functions of the CUDA runtime application programming interface.

4.15.2 Function Documentation

4.15.2.1 [cudaError_t cudaGraphicsVDPAURegisterOutputSurface](#) (struct cudaGraphicsResource **resource, VdpOutputSurface vdpSurface, unsigned int flags)

Registers the VdpOutputSurface specified by vdpSurface for access by CUDA. A handle to the registered object is returned as resource. The surface's intended usage is specified using flags, as follows:

- [cudaGraphicsMapFlagsNone](#): Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA. This is the default value.
- [cudaGraphicsMapFlagsReadOnly](#): Specifies that CUDA will not write to this resource.
- [cudaGraphicsMapFlagsWriteDiscard](#): Specifies that CUDA will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

Parameters:

resource - Pointer to the returned object handle
vdpSurface - VDPAU object to be registered
flags - Map flags

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaVDPAUSetVDPAUDevice](#) [cudaGraphicsUnregisterResource](#), [cudaGraphicsSubResourceGetMappedArray](#)

4.15.2.2 `cudaError_t cudaGraphicsVDPAURegisterVideoSurface (struct cudaGraphicsResource ** resource, VdpVideoSurface vdpSurface, unsigned int flags)`

Registers the `VdpVideoSurface` specified by `vdpSurface` for access by CUDA. A handle to the registered object is returned as `resource`. The surface's intended usage is specified using `flags`, as follows:

- [cudaGraphicsMapFlagsNone](#): Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA. This is the default value.
- [cudaGraphicsMapFlagsReadOnly](#): Specifies that CUDA will not write to this resource.
- [cudaGraphicsMapFlagsWriteDiscard](#): Specifies that CUDA will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

Parameters:

resource - Pointer to the returned object handle

vdpSurface - VDPAU object to be registered

flags - Map flags

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaVDPAUSetVDPAUDevice](#) [cudaGraphicsUnregisterResource](#), [cudaGraphicsSubResourceGetMappedArray](#)

4.15.2.3 `cudaError_t cudaVDPAUGetDevice (int * device, VdpDevice vdpDevice, VdpGetProcAddress * vdpGetProcAddress)`

Returns the CUDA device associated with a `VdpDevice`, if applicable.

Parameters:

device - Returns the device associated with `vdpDevice`, or -1 if the device associated with `vdpDevice` is not a compute device.

vdpDevice - A `VdpDevice` handle

vdpGetProcAddress - VDPAU's `VdpGetProcAddress` function pointer

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaVDPAUSetVDPAUDevice](#)

4.15.2.4 `cudaError_t cudaVDPAUSetVDPAUDevice (int device, VdpDevice vdpDevice, VdpGetProcAddress * vdpGetProcAddress)`

Records `vdpDevice` as the `VdpDevice` for VDPAU interoperability with the CUDA device `device` and sets `device` as the current device for the calling host thread.

If `device` has already been initialized then this call will fail with the error [cudaErrorSetOnActiveProcess](#). In this case it is necessary to reset `device` using [cudaDeviceReset\(\)](#) before VDPAU interoperability on `device` may be enabled.

Parameters:

device - Device to use for VDPAU interoperability

vdpDevice - The `VdpDevice` to interoperate with

vdpGetProcAddress - VDPAU's `VdpGetProcAddress` function pointer

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#), [cudaErrorSetOnActiveProcess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsVDPAURegisterVideoSurface](#), [cudaGraphicsVDPAURegisterOutputSurface](#), [cudaDeviceReset](#)

4.16 Graphics Interoperability

Functions

- `cudaError_t cudaGraphicsMapResources` (int count, `cudaGraphicsResource_t` *resources, `cudaStream_t` stream=0)
Map graphics resources for access by CUDA.
- `cudaError_t cudaGraphicsResourceGetMappedPointer` (void **devPtr, size_t *size, `cudaGraphicsResource_t` resource)
Get an device pointer through which to access a mapped graphics resource.
- `cudaError_t cudaGraphicsResourceSetMapFlags` (`cudaGraphicsResource_t` resource, unsigned int flags)
Set usage flags for mapping a graphics resource.
- `cudaError_t cudaGraphicsSubResourceGetMappedArray` (struct `cudaArray` **array, `cudaGraphicsResource_t` resource, unsigned int arrayIndex, unsigned int mipLevel)
Get an array through which to access a subresource of a mapped graphics resource.
- `cudaError_t cudaGraphicsUnmapResources` (int count, `cudaGraphicsResource_t` *resources, `cudaStream_t` stream=0)
Unmap graphics resources.
- `cudaError_t cudaGraphicsUnregisterResource` (`cudaGraphicsResource_t` resource)
Unregisters a graphics resource for access by CUDA.

4.16.1 Detailed Description

This section describes the graphics interoperability functions of the CUDA runtime application programming interface.

4.16.2 Function Documentation

4.16.2.1 `cudaError_t cudaGraphicsMapResources` (int count, `cudaGraphicsResource_t` *resources, `cudaStream_t` stream = 0)

Maps the count graphics resources in resources for access by CUDA.

The resources in resources may be accessed by CUDA until they are unmapped. The graphics API from which resources were registered should not access any resources while they are mapped by CUDA. If an application does so, the results are undefined.

This function provides the synchronization guarantee that any graphics calls issued before `cudaGraphicsMapResources()` will complete before any subsequent CUDA work issued in stream begins.

If resources contains any duplicate entries then `cudaErrorInvalidResourceHandle` is returned. If any of resources are presently mapped for access by CUDA then `cudaErrorUnknown` is returned.

Parameters:

count - Number of resources to map

resources - Resources to map for CUDA

stream - Stream for synchronization

Returns:

[cudaSuccess](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsResourceGetMappedPointer](#) [cudaGraphicsSubResourceGetMappedArray](#) [cudaGraphicsUnmapResources](#)

4.16.2.2 `cudaError_t cudaGraphicsResourceGetMappedPointer (void ** devPtr, size_t * size, cudaGraphicsResource_t resource)`

Returns in `*devPtr` a pointer through which the mapped graphics resource `resource` may be accessed. Returns in `*size` the size of the memory in bytes which may be accessed from that pointer. The value set in `devPtr` may change every time that `resource` is mapped.

If `resource` is not a buffer then it cannot be accessed via a pointer and [cudaErrorUnknown](#) is returned. If `resource` is not mapped then [cudaErrorUnknown](#) is returned. *

Parameters:

devPtr - Returned pointer through which `resource` may be accessed

size - Returned size of the buffer accessible starting at `*devPtr`

resource - Mapped resource to access

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsMapResources](#), [cudaGraphicsSubResourceGetMappedArray](#)

4.16.2.3 `cudaError_t cudaGraphicsResourceSetMapFlags (cudaGraphicsResource_t resource, unsigned int flags)`

Set `flags` for mapping the graphics resource `resource`.

Changes to `flags` will take effect the next time `resource` is mapped. The `flags` argument may be any of the following:

- [cudaGraphicsMapFlagsNone](#): Specifies no hints about how `resource` will be used. It is therefore assumed that CUDA may read from or write to `resource`.
- [cudaGraphicsMapFlagsReadOnly](#): Specifies that CUDA will not write to `resource`.

- [cudaGraphicsMapFlagsWriteDiscard](#): Specifies CUDA will not read from `resource` and will write over the entire contents of `resource`, so none of the data previously stored in `resource` will be preserved.

If `resource` is presently mapped for access by CUDA then [cudaErrorUnknown](#) is returned. If `flags` is not one of the above values then [cudaErrorInvalidValue](#) is returned.

Parameters:

resource - Registered resource to set flags for

flags - Parameters for resource mapping

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsMapResources](#)

4.16.2.4 [cudaError_t cudaGraphicsSubResourceGetMappedArray](#) (struct [cudaArray](#) ** *array*, [cudaGraphicsResource_t](#) *resource*, unsigned int *arrayIndex*, unsigned int *mipLevel*)

Returns in `*array` an array through which the subresource of the mapped graphics resource `resource` which corresponds to array index `arrayIndex` and mipmap level `mipLevel` may be accessed. The value set in `array` may change every time that `resource` is mapped.

If `resource` is not a texture then it cannot be accessed via an array and [cudaErrorUnknown](#) is returned. If `arrayIndex` is not a valid array index for `resource` then [cudaErrorInvalidValue](#) is returned. If `mipLevel` is not a valid mipmap level for `resource` then [cudaErrorInvalidValue](#) is returned. If `resource` is not mapped then [cudaErrorUnknown](#) is returned.

Parameters:

array - Returned array through which a subresource of `resource` may be accessed

resource - Mapped resource to access

arrayIndex - Array index for array textures or cubemap face index as defined by [cudaGraphicsCubeFace](#) for cubemap textures for the subresource to access

mipLevel - Mipmap level for the subresource to access

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsResourceGetMappedPointer](#)

4.16.2.5 `cudaError_t cudaGraphicsUnmapResources (int count, cudaGraphicsResource_t * resources, cudaStream_t stream = 0)`

Unmaps the `count` graphics resources in `resources`.

Once unmapped, the resources in `resources` may not be accessed by CUDA until they are mapped again.

This function provides the synchronization guarantee that any CUDA work issued in `stream` before `cudaGraphicsUnmapResources()` will complete before any subsequently issued graphics work begins.

If `resources` contains any duplicate entries then `cudaErrorInvalidResourceHandle` is returned. If any of `resources` are not presently mapped for access by Cuda then `cudaErrorUnknown` is returned.

Parameters:

count - Number of resources to unmap

resources - Resources to unmap

stream - Stream for synchronization

Returns:

`cudaSuccess`, `cudaErrorInvalidResourceHandle`, `cudaErrorUnknown`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaGraphicsMapResources`

4.16.2.6 `cudaError_t cudaGraphicsUnregisterResource (cudaGraphicsResource_t resource)`

Unregisters the graphics resource `resource` so it is not accessible by CUDA unless registered again.

If `resource` is invalid then `cudaErrorInvalidResourceHandle` is returned.

Parameters:

resource - Resource to unregister

Returns:

`cudaSuccess`, `cudaErrorInvalidResourceHandle`, `cudaErrorUnknown`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaGraphicsD3D9RegisterResource`, `cudaGraphicsD3D10RegisterResource`, `cudaGraphicsD3D11RegisterResource`, `cudaGraphicsGLRegisterBuffer`, `cudaGraphicsGLRegisterImage`

4.17 Texture Reference Management

Functions

- `cudaError_t cudaBindTexture` (`size_t *offset`, `const struct textureReference *texref`, `const void *devPtr`, `const struct cudaChannelFormatDesc *desc`, `size_t size=UINT_MAX`)
Binds a memory area to a texture.
- `cudaError_t cudaBindTexture2D` (`size_t *offset`, `const struct textureReference *texref`, `const void *devPtr`, `const struct cudaChannelFormatDesc *desc`, `size_t width`, `size_t height`, `size_t pitch`)
Binds a 2D memory area to a texture.
- `cudaError_t cudaBindTextureToArray` (`const struct textureReference *texref`, `const struct cudaArray *array`, `const struct cudaChannelFormatDesc *desc`)
Binds an array to a texture.
- `struct cudaChannelFormatDesc cudaCreateChannelDesc` (`int x`, `int y`, `int z`, `int w`, `enum cudaChannelFormatKind f`)
Returns a channel descriptor using the specified format.
- `cudaError_t cudaGetChannelDesc` (`struct cudaChannelFormatDesc *desc`, `const struct cudaArray *array`)
Get the channel descriptor of an array.
- `cudaError_t cudaGetTextureAlignmentOffset` (`size_t *offset`, `const struct textureReference *texref`)
Get the alignment offset of a texture.
- `cudaError_t cudaGetTextureReference` (`const struct textureReference **texref`, `const char *symbol`)
Get the texture reference associated with a symbol.
- `cudaError_t cudaUnbindTexture` (`const struct textureReference *texref`)
Unbinds a texture.

4.17.1 Detailed Description

This section describes the low level texture reference management functions of the CUDA runtime application programming interface.

4.17.2 Function Documentation

4.17.2.1 `cudaError_t cudaBindTexture` (`size_t *offset`, `const struct textureReference *texref`, `const void *devPtr`, `const struct cudaChannelFormatDesc *desc`, `size_t size = UINT_MAX`)

Binds `size` bytes of the memory area pointed to by `devPtr` to the texture reference `texref`. `desc` describes how the memory is interpreted when fetching values from the texture. Any memory previously bound to `texref` is unbound.

Since the hardware enforces an alignment requirement on texture base addresses, `cudaBindTexture()` returns in `*offset` a byte offset that must be applied to texture fetches in order to read from the desired memory. This offset must be divided by the texel size and passed to kernels that read from the texture so they can be applied to the

`tex1Dfetch()` function. If the device memory pointer was returned from `cudaMalloc()`, the offset is guaranteed to be 0 and NULL may be passed as the `offset` parameter.

The total number of elements (or texels) in the linear address range cannot exceed `cudaDeviceProp::maxTexture1DLinear[0]`. The number of elements is computed as $(size / elementSize)$, where `elementSize` is determined from `desc`.

Parameters:

offset - Offset in bytes
texref - Texture to bind
devPtr - Memory area on device
desc - Channel format
size - Size of the memory area pointed to by *devPtr*

Returns:

`cudaSuccess`, `cudaErrorInvalidValue`, `cudaErrorInvalidDevicePointer`, `cudaErrorInvalidTexture`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaCreateChannelDesc` (C API), `cudaGetChannelDesc`, `cudaGetTextureReference`, `cudaBindTexture` (C++ API), `cudaBindTexture2D` (C API), `cudaBindTextureToArray` (C API), `cudaUnbindTexture` (C API), `cudaGetTextureAlignmentOffset` (C API)

4.17.2.2 `cudaError_t cudaBindTexture2D (size_t * offset, const struct textureReference * texref, const void * devPtr, const struct cudaChannelFormatDesc * desc, size_t width, size_t height, size_t pitch)`

Binds the 2D memory area pointed to by *devPtr* to the texture reference *texref*. The size of the area is constrained by *width* in texel units, *height* in texel units, and *pitch* in byte units. *desc* describes how the memory is interpreted when fetching values from the texture. Any memory previously bound to *texref* is unbound.

Since the hardware enforces an alignment requirement on texture base addresses, `cudaBindTexture2D()` returns in **offset* a byte offset that must be applied to texture fetches in order to read from the desired memory. This offset must be divided by the texel size and passed to kernels that read from the texture so they can be applied to the `tex2D()` function. If the device memory pointer was returned from `cudaMalloc()`, the offset is guaranteed to be 0 and NULL may be passed as the `offset` parameter.

width and *height*, which are specified in elements (or texels), cannot exceed `cudaDeviceProp::maxTexture2DLinear[0]` and `cudaDeviceProp::maxTexture2DLinear[1]` respectively. *pitch*, which is specified in bytes, cannot exceed `cudaDeviceProp::maxTexture2DLinear[2]`.

The driver returns `cudaErrorInvalidValue` if *pitch* is not a multiple of `cudaDeviceProp::texturePitchAlignment`.

Parameters:

offset - Offset in bytes
texref - Texture reference to bind
devPtr - 2D memory area on device
desc - Channel format

width - Width in texel units

height - Height in texel units

pitch - Pitch in bytes

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidTexture](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C API), [cudaBindTexture2D](#) (C++ API), [cudaBindTexture2D](#) (C++ API, inherited channel descriptor), [cudaBindTextureToArray](#) (C API), [cudaBindTextureToArray](#) (C API), [cudaGetTextureAlignmentOffset](#) (C API)

4.17.2.3 `cudaError_t cudaBindTextureToArray (const struct textureReference * texref, const struct cudaArray * array, const struct cudaChannelFormatDesc * desc)`

Binds the CUDA array `array` to the texture reference `texref`. `desc` describes how the memory is interpreted when fetching values from the texture. Any CUDA array previously bound to `texref` is unbound.

Parameters:

texref - Texture to bind

array - Memory array on device

desc - Channel format

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidTexture](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C API), [cudaBindTexture2D](#) (C API), [cudaBindTextureToArray](#) (C++ API), [cudaUnbindTexture](#) (C API), [cudaGetTextureAlignmentOffset](#) (C API)

4.17.2.4 `struct cudaChannelFormatDesc cudaCreateChannelDesc (int x, int y, int z, int w, enum cudaChannelFormatKind f)` [read]

Returns a channel descriptor with format `f` and number of bits of each component `x`, `y`, `z`, and `w`. The [cudaChannelFormatDesc](#) is defined as:

```
struct cudaChannelFormatDesc {
    int x, y, z, w;
    enum cudaChannelFormatKind f;
};
```

where `cudaChannelFormatKind` is one of `cudaChannelFormatKindSigned`, `cudaChannelFormatKindUnsigned`, or `cudaChannelFormatKindFloat`.

Parameters:

x - X component
y - Y component
z - Z component
w - W component
f - Channel format

Returns:

Channel descriptor with format *f*

See also:

[cudaCreateChannelDesc](#) (C++ API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C API), [cudaBindTexture2D](#) (C API), [cudaBindTextureToArray](#) (C API), [cudaUnbindTexture](#) (C API), [cudaGetTextureAlignmentOffset](#) (C API)

4.17.2.5 `cudaError_t cudaGetChannelDesc (struct cudaChannelFormatDesc * desc, const struct cudaArray * array)`

Returns in **desc* the channel descriptor of the CUDA array *array*.

Parameters:

desc - Channel format
array - Memory array on device

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C API), [cudaGetTextureReference](#), [cudaBindTexture](#) (C API), [cudaBindTexture2D](#) (C API), [cudaBindTextureToArray](#) (C API), [cudaUnbindTexture](#) (C API), [cudaGetTextureAlignmentOffset](#) (C API)

4.17.2.6 `cudaError_t cudaGetTextureAlignmentOffset (size_t * offset, const struct textureReference * texref)`

Returns in **offset* the offset that was returned when texture reference *texref* was bound.

Parameters:

offset - Offset of texture reference in bytes
texref - Texture to get offset of

Returns:

[cudaSuccess](#), [cudaErrorInvalidTexture](#), [cudaErrorInvalidTextureBinding](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C API), [cudaBindTexture2D](#) (C API), [cudaBindTextureToArray](#) (C API), [cudaUnbindTexture](#) (C API), [cudaGetTextureAlignmentOffset](#) (C++ API)

4.17.2.7 `cudaError_t cudaGetTextureReference (const struct textureReference ** texref, const char * symbol)`

Returns in **texref* the structure associated to the texture reference defined by symbol *symbol*.

Parameters:

texref - Texture associated with symbol
symbol - Symbol to find texture reference for

Returns:

[cudaSuccess](#), [cudaErrorInvalidTexture](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C API), [cudaGetChannelDesc](#), [cudaGetTextureAlignmentOffset](#) (C API), [cudaBindTexture](#) (C API), [cudaBindTexture2D](#) (C API), [cudaBindTextureToArray](#) (C API), [cudaUnbindTexture](#) (C API)

4.17.2.8 `cudaError_t cudaUnbindTexture (const struct textureReference * texref)`

Unbinds the texture bound to *texref*.

Parameters:

texref - Texture to unbind

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C API), [cudaBindTexture2D](#) (C API), [cudaBindTextureToArray](#) (C API), [cudaUnbindTexture](#) (C++ API), [cudaGetTextureAlignmentOffset](#) (C API)

4.18 Surface Reference Management

Functions

- [cudaError_t cudaBindSurfaceToArray](#) (const struct [surfaceReference](#) *surfref, const struct cudaArray *array, const struct [cudaChannelFormatDesc](#) *desc)
Binds an array to a surface.
- [cudaError_t cudaGetSurfaceReference](#) (const struct [surfaceReference](#) **surfref, const char *symbol)
Get the surface reference associated with a symbol.

4.18.1 Detailed Description

This section describes the low level surface reference management functions of the CUDA runtime application programming interface.

4.18.2 Function Documentation

4.18.2.1 [cudaError_t cudaBindSurfaceToArray](#) (const struct [surfaceReference](#) * *surfref*, const struct [cudaArray](#) * *array*, const struct [cudaChannelFormatDesc](#) * *desc*)

Binds the CUDA array *array* to the surface reference *surfref*. *desc* describes how the memory is interpreted when fetching values from the surface. Any CUDA array previously bound to *surfref* is unbound.

Parameters:

surfref - Surface to bind
array - Memory array on device
desc - Channel format

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidSurface](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaBindSurfaceToArray](#) (C++ API), [cudaBindSurfaceToArray](#) (C++ API, inherited channel descriptor), [cudaGetSurfaceReference](#)

4.18.2.2 [cudaError_t cudaGetSurfaceReference](#) (const struct [surfaceReference](#) ** *surfref*, const char * *symbol*)

Returns in **surfref* the structure associated to the surface reference defined by symbol *symbol*.

Parameters:

surfref - Surface associated with symbol

symbol - Symbol to find surface reference for

Returns:

[cudaSuccess](#), [cudaErrorInvalidSurface](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaBindSurfaceToArray \(C API\)](#)

4.19 Version Management

Functions

- [cudaError_t cudaDriverGetVersion](#) (int *driverVersion)
Returns the CUDA driver version.
- [cudaError_t cudaRuntimeGetVersion](#) (int *runtimeVersion)
Returns the CUDA Runtime version.

4.19.1 Function Documentation

4.19.1.1 [cudaError_t cudaDriverGetVersion](#) (int * *driverVersion*)

Returns in *driverVersion the version number of the installed CUDA driver. If no driver is installed, then 0 is returned as the driver version (via driverVersion). This function automatically returns [cudaErrorInvalidValue](#) if the driverVersion argument is NULL.

Parameters:

driverVersion - Returns the CUDA driver version.

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaRuntimeGetVersion](#)

4.19.1.2 [cudaError_t cudaRuntimeGetVersion](#) (int * *runtimeVersion*)

Returns in *runtimeVersion the version number of the installed CUDA Runtime. This function automatically returns [cudaErrorInvalidValue](#) if the runtimeVersion argument is NULL.

Parameters:

runtimeVersion - Returns the CUDA Runtime version.

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#)

See also:

[cudaDriverGetVersion](#)

4.20 C++ API Routines

C++-style interface built on top of CUDA runtime API.

Functions

- `template<class T, int dim>`
`cudaError_t cudaBindSurfaceToArray` (const struct surface< T, dim > &surf, const struct cudaArray *array)
[C++ API] Binds an array to a surface
- `template<class T, int dim>`
`cudaError_t cudaBindSurfaceToArray` (const struct surface< T, dim > &surf, const struct cudaArray *array, const struct `cudaChannelFormatDesc` &desc)
[C++ API] Binds an array to a surface
- `template<class T, int dim, enum cudaTextureReadMode readMode>`
`cudaError_t cudaBindTexture` (size_t *offset, const struct texture< T, dim, readMode > &tex, const void *devPtr, size_t size=UINT_MAX)
[C++ API] Binds a memory area to a texture
- `template<class T, int dim, enum cudaTextureReadMode readMode>`
`cudaError_t cudaBindTexture` (size_t *offset, const struct texture< T, dim, readMode > &tex, const void *devPtr, const struct `cudaChannelFormatDesc` &desc, size_t size=UINT_MAX)
[C++ API] Binds a memory area to a texture
- `template<class T, int dim, enum cudaTextureReadMode readMode>`
`cudaError_t cudaBindTexture2D` (size_t *offset, const struct texture< T, dim, readMode > &tex, const void *devPtr, size_t width, size_t height, size_t pitch)
[C++ API] Binds a 2D memory area to a texture
- `template<class T, int dim, enum cudaTextureReadMode readMode>`
`cudaError_t cudaBindTexture2D` (size_t *offset, const struct texture< T, dim, readMode > &tex, const void *devPtr, const struct `cudaChannelFormatDesc` &desc, size_t width, size_t height, size_t pitch)
[C++ API] Binds a 2D memory area to a texture
- `template<class T, int dim, enum cudaTextureReadMode readMode>`
`cudaError_t cudaBindTextureToArray` (const struct texture< T, dim, readMode > &tex, const struct cudaArray *array)
[C++ API] Binds an array to a texture
- `template<class T, int dim, enum cudaTextureReadMode readMode>`
`cudaError_t cudaBindTextureToArray` (const struct texture< T, dim, readMode > &tex, const struct cudaArray *array, const struct `cudaChannelFormatDesc` &desc)
[C++ API] Binds an array to a texture
- `template<class T >`
`cudaChannelFormatDesc cudaCreateChannelDesc` (void)
[C++ API] Returns a channel descriptor using the specified format
- `cudaError_t cudaEventCreate` (`cudaEvent_t` *event, unsigned int flags)
[C++ API] Creates an event object with the specified flags

- `template<class T >`
`cudaError_t cudaFuncGetAttributes` (struct `cudaFuncAttributes` *attr, T *entry)
[C++ API] Find out attributes for a given function
- `template<class T >`
`cudaError_t cudaFuncSetCacheConfig` (T *func, enum `cudaFuncCache` cacheConfig)
Sets the preferred cache configuration for a device function.
- `template<class T >`
`cudaError_t cudaGetSymbolAddress` (void **devPtr, const T &symbol)
[C++ API] Finds the address associated with a CUDA symbol
- `template<class T >`
`cudaError_t cudaGetSymbolSize` (size_t *size, const T &symbol)
[C++ API] Finds the size of the object associated with a CUDA symbol
- `template<class T, int dim, enum cudaTextureReadMode readMode>`
`cudaError_t cudaGetTextureAlignmentOffset` (size_t *offset, const struct texture< T, dim, readMode > &tex)
[C++ API] Get the alignment offset of a texture
- `template<class T >`
`cudaError_t cudaLaunch` (T *entry)
[C++ API] Launches a device function
- `cudaError_t cudaMallocHost` (void **ptr, size_t size, unsigned int flags)
[C++ API] Allocates page-locked memory on the host
- `template<class T >`
`cudaError_t cudaSetupArgument` (T arg, size_t offset)
[C++ API] Configure a device launch
- `template<class T, int dim, enum cudaTextureReadMode readMode>`
`cudaError_t cudaUnbindTexture` (const struct texture< T, dim, readMode > &tex)
[C++ API] Unbinds a texture

4.20.1 Detailed Description

This section describes the C++ high level API functions of the CUDA runtime application programming interface. To use these functions, your application needs to be compiled with the `nvcc` compiler.

4.20.2 Function Documentation

4.20.2.1 `template<class T, int dim> cudaError_t cudaBindSurfaceToArray` (const struct surface< T, dim > &surf, const struct cudaArray *array)

Binds the CUDA array `array` to the surface reference `surf`. The channel descriptor is inherited from the CUDA array. Any CUDA array previously bound to `surf` is unbound.

Parameters:

surf - Surface to bind
array - Memory array on device

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidSurface](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaBindSurfaceToArray \(C API\)](#), [cudaBindSurfaceToArray \(C++ API\)](#)

4.20.2.2 `template<class T , int dim> cudaError_t cudaBindSurfaceToArray (const struct surface< T, dim > & surf, const struct cudaArray * array, const struct cudaChannelFormatDesc & desc)`

Binds the CUDA array *array* to the surface reference *surf*. *desc* describes how the memory is interpreted when dealing with the surface. Any CUDA array previously bound to *surf* is unbound.

Parameters:

surf - Surface to bind
array - Memory array on device
desc - Channel format

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidSurface](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaBindSurfaceToArray \(C API\)](#), [cudaBindSurfaceToArray \(C++ API, inherited channel descriptor\)](#)

4.20.2.3 `template<class T , int dim, enum cudaTextureReadMode readMode> cudaError_t cudaBindTexture (size_t * offset, const struct texture< T, dim, readMode > & tex, const void * devPtr, size_t size = UINT_MAX)`

Binds *size* bytes of the memory area pointed to by *devPtr* to texture reference *tex*. The channel descriptor is inherited from the texture reference type. The *offset* parameter is an optional byte offset as with the low-level [cudaBindTexture\(size_t*, const struct textureReference*, const void*, const struct cudaChannelFormatDesc*, size_t\)](#) function. Any memory previously bound to *tex* is unbound.

Parameters:

offset - Offset in bytes
tex - Texture to bind

devPtr - Memory area on device

size - Size of the memory area pointed to by devPtr

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidTexture](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C++ API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C API), [cudaBindTexture](#) (C++ API), [cudaBindTexture2D](#) (C++ API), [cudaBindTexture2D](#) (C++ API, inherited channel descriptor), [cudaBindTextureToArray](#) (C++ API), [cudaBindTextureToArray](#) (C++ API, inherited channel descriptor), [cudaUnbindTexture](#) (C++ API), [cudaGetTextureAlignmentOffset](#) (C++ API)

4.20.2.4 `template<class T, int dim, enum cudaTextureReadMode readMode> cudaError_t
cudaBindTexture(size_t * offset, const struct texture< T, dim, readMode > & tex, const void *
devPtr, const struct cudaChannelFormatDesc & desc, size_t size = UINT_MAX)`

Binds *size* bytes of the memory area pointed to by *devPtr* to texture reference *tex*. *desc* describes how the memory is interpreted when fetching values from the texture. The *offset* parameter is an optional byte offset as with the low-level [cudaBindTexture\(\)](#) function. Any memory previously bound to *tex* is unbound.

Parameters:

offset - Offset in bytes

tex - Texture to bind

devPtr - Memory area on device

desc - Channel format

size - Size of the memory area pointed to by devPtr

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidTexture](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C++ API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C API), [cudaBindTexture](#) (C++ API, inherited channel descriptor), [cudaBindTexture2D](#) (C++ API), [cudaBindTexture2D](#) (C++ API, inherited channel descriptor), [cudaBindTextureToArray](#) (C++ API), [cudaBindTextureToArray](#) (C++ API, inherited channel descriptor), [cudaUnbindTexture](#) (C++ API), [cudaGetTextureAlignmentOffset](#) (C++ API)

4.20.2.5 `template<class T , int dim, enum cudaTextureReadMode readMode> cudaError_t
 cudaBindTexture2D (size_t * offset, const struct texture< T, dim, readMode > & tex, const void *
devPtr, size_t width, size_t height, size_t pitch)`

Binds the 2D memory area pointed to by *devPtr* to the texture reference *tex*. The size of the area is constrained by *width* in texel units, *height* in texel units, and *pitch* in byte units. The channel descriptor is inherited from the texture reference type. Any memory previously bound to *tex* is unbound.

Since the hardware enforces an alignment requirement on texture base addresses, `cudaBindTexture2D()` returns in **offset* a byte offset that must be applied to texture fetches in order to read from the desired memory. This offset must be divided by the texel size and passed to kernels that read from the texture so they can be applied to the `tex2D()` function. If the device memory pointer was returned from `cudaMalloc()`, the offset is guaranteed to be 0 and NULL may be passed as the *offset* parameter.

Parameters:

offset - Offset in bytes
tex - Texture reference to bind
devPtr - 2D memory area on device
width - Width in texel units
height - Height in texel units
pitch - Pitch in bytes

Returns:

`cudaSuccess`, `cudaErrorInvalidValue`, `cudaErrorInvalidDevicePointer`, `cudaErrorInvalidTexture`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaCreateChannelDesc` (C++ API), `cudaGetChannelDesc`, `cudaGetTextureReference`, `cudaBindTexture` (C++ API), `cudaBindTexture` (C++ API, inherited channel descriptor), `cudaBindTexture2D` (C API), `cudaBindTexture2D` (C++ API), `cudaBindTextureToArray` (C++ API), `cudaBindTextureToArray` (C++ API, inherited channel descriptor), `cudaUnbindTexture` (C++ API), `cudaGetTextureAlignmentOffset` (C++ API)

4.20.2.6 `template<class T , int dim, enum cudaTextureReadMode readMode> cudaError_t
 cudaBindTexture2D (size_t * offset, const struct texture< T, dim, readMode > & tex, const void *
devPtr, const struct cudaChannelFormatDesc & desc, size_t width, size_t height, size_t pitch)`

Binds the 2D memory area pointed to by *devPtr* to the texture reference *tex*. The size of the area is constrained by *width* in texel units, *height* in texel units, and *pitch* in byte units. *desc* describes how the memory is interpreted when fetching values from the texture. Any memory previously bound to *tex* is unbound.

Since the hardware enforces an alignment requirement on texture base addresses, `cudaBindTexture2D()` returns in **offset* a byte offset that must be applied to texture fetches in order to read from the desired memory. This offset must be divided by the texel size and passed to kernels that read from the texture so they can be applied to the `tex2D()` function. If the device memory pointer was returned from `cudaMalloc()`, the offset is guaranteed to be 0 and NULL may be passed as the *offset* parameter.

Parameters:

offset - Offset in bytes

tex - Texture reference to bind
devPtr - 2D memory area on device
desc - Channel format
width - Width in texel units
height - Height in texel units
pitch - Pitch in bytes

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidTexture](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C++ API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C++ API), [cudaBindTexture](#) (C++ API, inherited channel descriptor), [cudaBindTexture2D](#) (C API), [cudaBindTexture2D](#) (C++ API, inherited channel descriptor), [cudaBindTextureToArray](#) (C++ API), [cudaBindTextureToArray](#) (C++ API, inherited channel descriptor), [cudaUnbindTexture](#) (C++ API), [cudaGetTextureAlignmentOffset](#) (C++ API)

4.20.2.7 `template<class T, int dim, enum cudaTextureReadMode readMode> cudaError_t
 cudaBindTextureToArray (const struct texture< T, dim, readMode > & tex, const struct cudaArray
 * array)`

Binds the CUDA array `array` to the texture reference `tex`. The channel descriptor is inherited from the CUDA array. Any CUDA array previously bound to `tex` is unbound.

Parameters:

tex - Texture to bind
array - Memory array on device

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidTexture](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C++ API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C++ API), [cudaBindTexture](#) (C++ API, inherited channel descriptor), [cudaBindTexture2D](#) (C++ API), [cudaBindTexture2D](#) (C++ API, inherited channel descriptor), [cudaBindTextureToArray](#) (C API), [cudaBindTextureToArray](#) (C++ API), [cudaUnbindTexture](#) (C++ API), [cudaGetTextureAlignmentOffset](#) (C++ API)

4.20.2.8 `template<class T, int dim, enum cudaTextureReadMode readMode> cudaError_t
 cudaBindTextureToArray (const struct texture< T, dim, readMode > & tex, const struct cudaArray
 * array, const struct cudaChannelFormatDesc & desc)`

Binds the CUDA array *array* to the texture reference *tex*. *desc* describes how the memory is interpreted when fetching values from the texture. Any CUDA array previously bound to *tex* is unbound.

Parameters:

tex - Texture to bind
array - Memory array on device
desc - Channel format

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorInvalidTexture](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C++ API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C++ API), [cudaBindTexture](#) (C++ API, inherited channel descriptor), [cudaBindTexture2D](#) (C++ API), [cudaBindTexture2D](#) (C++ API, inherited channel descriptor), [cudaBindTextureToArray](#) (C API), [cudaBindTextureToArray](#) (C++ API, inherited channel descriptor), [cudaUnbindTexture](#) (C++ API), [cudaGetTextureAlignmentOffset](#) (C++ API)

4.20.2.9 `template<class T> cudaChannelFormatDesc cudaCreateChannelDesc (void)`

Returns a channel descriptor with format *f* and number of bits of each component *x*, *y*, *z*, and *w*. The [cudaChannelFormatDesc](#) is defined as:

```
struct cudaChannelFormatDesc {
    int x, y, z, w;
    enum cudaChannelFormatKind f;
};
```

where [cudaChannelFormatKind](#) is one of [cudaChannelFormatKindSigned](#), [cudaChannelFormatKindUnsigned](#), or [cudaChannelFormatKindFloat](#).

Returns:

Channel descriptor with format *f*

See also:

[cudaCreateChannelDesc](#) (Low level), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (High level), [cudaBindTexture](#) (High level, inherited channel descriptor), [cudaBindTexture2D](#) (High level), [cudaBindTextureToArray](#) (High level), [cudaBindTextureToArray](#) (High level, inherited channel descriptor), [cudaUnbindTexture](#) (High level), [cudaGetTextureAlignmentOffset](#) (High level)

4.20.2.10 `cudaError_t cudaEventCreate (cudaEvent_t * event, unsigned int flags)`

Creates an event object with the specified flags. Valid flags include:

- [cudaEventDefault](#): Default event creation flag.
- [cudaEventBlockingSync](#): Specifies that event should use blocking synchronization. A host thread that uses [cudaEventSynchronize\(\)](#) to wait on an event created with this flag will block until the event actually completes.
- [cudaEventDisableTiming](#): Specifies that the created event does not need to record timing data. Events created with this flag specified and the [cudaEventBlockingSync](#) flag not specified will provide the best performance when used with [cudaStreamWaitEvent\(\)](#) and [cudaEventQuery\(\)](#).

Parameters:

event - Newly created event

flags - Flags for new event

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#), [cudaErrorInvalidValue](#), [cudaErrorLaunchFailure](#), [cudaErrorMemoryAllocation](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaEventCreate \(C API\)](#), [cudaEventCreateWithFlags](#), [cudaEventRecord](#), [cudaEventQuery](#), [cudaEventSynchronize](#), [cudaEventDestroy](#), [cudaEventElapsedTime](#), [cudaStreamWaitEvent](#)

4.20.2.11 `template<class T> cudaError_t cudaFuncGetAttributes (struct cudaFuncAttributes * attr, T * entry)`

This function obtains the attributes of a function specified via *entry*. The parameter *entry* can either be a pointer to a function that executes on the device, or it can be a character string specifying the fully-decorated (C++) name of a function that executes on the device. The parameter specified by *entry* must be declared as a `__global__` function. The fetched attributes are placed in *attr*. If the specified function does not exist, then [cudaErrorInvalidDeviceFunction](#) is returned.

Note that some function attributes such as [maxThreadsPerBlock](#) may vary based on the device that is currently being used.

Parameters:

attr - Return pointer to function's attributes

entry - Function to get attributes of

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#), [cudaErrorInvalidDeviceFunction](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaConfigureCall](#), [cudaFuncSetCacheConfig](#) (C++ API), [cudaFuncGetAttributes](#) (C API), [cudaLaunch](#) (C++ API), [cudaSetDoubleForDevice](#), [cudaSetDoubleForHost](#), [cudaSetupArgument](#) (C++ API)

4.20.2.12 `template<class T> cudaError_t cudaFuncSetCacheConfig (T *func, enum cudaFuncCache cacheConfig)`

On devices where the L1 cache and shared memory use the same hardware resources, this sets through `cacheConfig` the preferred cache configuration for the function specified via `func`. This is only a preference. The runtime will use the requested configuration if possible, but it is free to choose a different configuration if required to execute `func`.

`func` can either be a pointer to a function that executes on the device, or it can be a character string specifying the fully-decorated (C++) name for a function that executes on the device. The parameter specified by `func` must be declared as a `__global__` function. If the specified function does not exist, then [cudaErrorInvalidDeviceFunction](#) is returned.

This setting does nothing on devices where the size of the L1 cache and shared memory are fixed.

Launching a kernel with a different preference than the most recent preference setting may insert a device-side synchronization point.

The supported cache configurations are:

- [cudaFuncCachePreferNone](#): no preference for shared memory or L1 (default)
- [cudaFuncCachePreferShared](#): prefer larger shared memory and smaller L1 cache
- [cudaFuncCachePreferL1](#): prefer larger L1 cache and smaller shared memory

Parameters:

func - Char string naming device function

cacheConfig - Requested cache configuration

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#), [cudaErrorInvalidDeviceFunction](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaConfigureCall](#), [cudaFuncSetCacheConfig](#) (C API), [cudaFuncGetAttributes](#) (C++ API), [cudaLaunch](#) (C API), [cudaSetDoubleForDevice](#), [cudaSetDoubleForHost](#), [cudaSetupArgument](#) (C++ API), [cudaThreadGetCacheConfig](#), [cudaThreadSetCacheConfig](#)

4.20.2.13 `template<class T> cudaError_t cudaGetSymbolAddress (void **devPtr, const T & symbol)`

Returns in `*devPtr` the address of symbol `symbol` on the device. `symbol` can either be a variable that resides in global or constant memory space, or it can be a character string, naming a variable that resides in global or constant memory space. If `symbol` cannot be found, or if `symbol` is not declared in the global or constant memory space, `*devPtr` is unchanged and the error [cudaErrorInvalidSymbol](#) is returned. If there are multiple global or constant variables with the same string name (from separate files) and the lookup is done via character string, [cudaErrorDuplicateVariableName](#) is returned.

Parameters:

devPtr - Return device pointer associated with symbol
symbol - Global/constant variable or string symbol to search for

Returns:

[cudaSuccess](#), [cudaErrorInvalidSymbol](#), [cudaErrorDuplicateVariableName](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGetSymbolAddress](#) (C API) [cudaGetSymbolSize](#) (C++ API)

4.20.2.14 `template<class T > cudaError_t cudaGetSymbolSize (size_t * size, const T & symbol)`

Returns in **size* the size of symbol *symbol*. *symbol* can either be a variable that resides in global or constant memory space, or it can be a character string, naming a variable that resides in global or constant memory space. If *symbol* cannot be found, or if *symbol* is not declared in global or constant memory space, **size* is unchanged and the error [cudaErrorInvalidSymbol](#) is returned. If there are multiple global variables with the same string name (from separate files) and the lookup is done via character string, [cudaErrorDuplicateVariableName](#) is returned.

Parameters:

size - Size of object associated with symbol
symbol - Global variable or string symbol to find size of

Returns:

[cudaSuccess](#), [cudaErrorInvalidSymbol](#), [cudaErrorDuplicateVariableName](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGetSymbolAddress](#) (C++ API) [cudaGetSymbolSize](#) (C API)

**4.20.2.15 `template<class T , int dim, enum cudaTextureReadMode readMode> cudaError_t
cudaGetTextureAlignmentOffset (size_t * offset, const struct texture< T, dim, readMode > & tex)`**

Returns in **offset* the offset that was returned when texture reference *tex* was bound.

Parameters:

offset - Offset of texture reference in bytes
tex - Texture to get offset of

Returns:

[cudaSuccess](#), [cudaErrorInvalidTexture](#), [cudaErrorInvalidTextureBinding](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C++ API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C++ API), [cudaBindTexture](#) (C++ API, inherited channel descriptor), [cudaBindTexture2D](#) (C++ API), [cudaBindTexture2D](#) (C++ API, inherited channel descriptor), [cudaBindTextureToArray](#) (C++ API), [cudaBindTextureToArray](#) (C++ API, inherited channel descriptor), [cudaUnbindTexture](#) (C++ API), [cudaGetTextureAlignmentOffset](#) (C API)

4.20.2.16 `template<class T> cudaError_t cudaLaunch (T * entry)`

Launches the function `entry` on the device. The parameter `entry` can either be a function that executes on the device, or it can be a character string, naming a function that executes on the device. The parameter specified by `entry` must be declared as a `__global__` function. `cudaLaunch()` must be preceded by a call to `cudaConfigureCall()` since it pops the data that was pushed by `cudaConfigureCall()` from the execution stack.

Parameters:

entry - Device function pointer or char string naming device function to execute

Returns:

[cudaSuccess](#), [cudaErrorInvalidDeviceFunction](#), [cudaErrorInvalidConfiguration](#), [cudaErrorLaunchFailure](#), [cudaErrorLaunchTimeout](#), [cudaErrorLaunchOutOfResources](#), [cudaErrorSharedObjectSymbolNotFound](#), [cudaErrorSharedObjectInitFailed](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaConfigureCall](#), [cudaFuncSetCacheConfig](#) (C++ API), [cudaFuncGetAttributes](#) (C++ API), [cudaLaunch](#) (C API), [cudaSetDoubleForDevice](#), [cudaSetDoubleForHost](#), [cudaSetupArgument](#) (C++ API), [cudaThreadGetCacheConfig](#), [cudaThreadSetCacheConfig](#)

4.20.2.17 `cudaError_t cudaMallocHost (void **ptr, size_t size, unsigned int flags)`

Allocates `size` bytes of host memory that is page-locked and accessible to the device. The driver tracks the virtual memory ranges allocated with this function and automatically accelerates calls to functions such as [cudaMemcpy\(\)](#). Since the memory can be accessed directly by the device, it can be read or written with much higher bandwidth than pageable memory obtained with functions such as `malloc()`. Allocating excessive amounts of pinned memory may degrade system performance, since it reduces the amount of memory available to the system for paging. As a result, this function is best used sparingly to allocate staging areas for data exchange between host and device.

The `flags` parameter enables different options to be specified that affect the allocation, as follows.

- [cudaHostAllocDefault](#): This flag's value is defined to be 0.
- [cudaHostAllocPortable](#): The memory returned by this call will be considered as pinned memory by all CUDA contexts, not just the one that performed the allocation.

- [cudaHostAllocMapped](#): Maps the allocation into the CUDA address space. The device pointer to the memory may be obtained by calling [cudaHostGetDevicePointer\(\)](#).
- [cudaHostAllocWriteCombined](#): Allocates the memory as write-combined (WC). WC memory can be transferred across the PCI Express bus more quickly on some system configurations, but cannot be read efficiently by most CPUs. WC memory is a good option for buffers that will be written by the CPU and read by the device via mapped pinned memory or host->device transfers.

All of these flags are orthogonal to one another: a developer may allocate memory that is portable, mapped and/or write-combined with no restrictions.

[cudaSetDeviceFlags\(\)](#) must have been called with the [cudaDeviceMapHost](#) flag in order for the [cudaHostAllocMapped](#) flag to have any effect.

The [cudaHostAllocMapped](#) flag may be specified on CUDA contexts for devices that do not support mapped pinned memory. The failure is deferred to [cudaHostGetDevicePointer\(\)](#) because the memory may be mapped into other CUDA contexts via the [cudaHostAllocPortable](#) flag.

Memory allocated by this function must be freed with [cudaFreeHost\(\)](#).

Parameters:

- ptr* - Device pointer to allocated memory
- size* - Requested allocation size in bytes
- flags* - Requested properties of allocated memory

Returns:

[cudaSuccess](#), [cudaErrorMemoryAllocation](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaSetDeviceFlags](#), [cudaMallocHost](#) (C API), [cudaFreeHost](#), [cudaHostAlloc](#)

4.20.2.18 `template<class T> cudaError_t cudaSetupArgument (T arg, size_t offset)`

Pushes *size* bytes of the argument pointed to by *arg* at *offset* bytes from the start of the parameter passing area, which starts at offset 0. The arguments are stored in the top of the execution stack. [cudaSetupArgument\(\)](#) must be preceded by a call to [cudaConfigureCall\(\)](#).

Parameters:

- arg* - Argument to push for a kernel launch
- offset* - Offset in argument stack to push new arg

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaConfigureCall](#), [cudaFuncGetAttributes](#) (C++ API), [cudaLaunch](#) (C++ API), [cudaSetDoubleForDevice](#), [cudaSetDoubleForHost](#), [cudaSetupArgument](#) (C API)

4.20.2.19 `template<class T, int dim, enum cudaTextureReadMode readMode> cudaError_t
cudaUnbindTexture (const struct texture< T, dim, readMode > & tex)`

Unbinds the texture bound to `tex`.

Parameters:

tex - Texture to unbind

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaCreateChannelDesc](#) (C++ API), [cudaGetChannelDesc](#), [cudaGetTextureReference](#), [cudaBindTexture](#) (C++ API), [cudaBindTexture](#) (C++ API, inherited channel descriptor), [cudaBindTexture2D](#) (C++ API), [cudaBindTexture2D](#) (C++ API, inherited channel descriptor), [cudaBindTextureToArray](#) (C++ API), [cudaBindTextureToArray](#) (C++ API, inherited channel descriptor), [cudaUnbindTexture](#) (C API), [cudaGetTextureAlignmentOffset](#) (C++ API)

4.21 Interactions with the CUDA Driver API

Interactions between the CUDA Driver API and the CUDA Runtime API.

This section describes the interactions between the CUDA Driver API and the CUDA Runtime API

4.21.1 Primary Contexts

There exists a one to one relationship between CUDA devices in the CUDA Runtime API and [CUcontext](#) s in the CUDA Driver API within a process. The specific context which the CUDA Runtime API uses for a device is called the device's primary context. From the perspective of the CUDA Runtime API, a device and its primary context are synonymous.

4.21.2 Initialization and Tear-Down

CUDA Runtime API calls operate on the CUDA Driver API [CUcontext](#) which is current to the calling host thread.

The function [cudaSetDevice\(\)](#) makes the primary context for the specified device current to the calling thread by calling [cuCtxSetCurrent\(\)](#).

The CUDA Runtime API will automatically initialize the primary context for a device at the first CUDA Runtime API call which requires an active context. If no [CUcontext](#) is current to the calling thread when a CUDA Runtime API call which requires an active context is made, then the primary context for a device will be selected, made current to the calling thread, and initialized.

The context which the CUDA Runtime API initializes will be initialized using the parameters specified by the CUDA Runtime API functions [cudaSetDeviceFlags\(\)](#), [cudaD3D9SetDirect3DDevice\(\)](#), [cudaD3D10SetDirect3DDevice\(\)](#), [cudaD3D11SetDirect3DDevice\(\)](#), [cudaGLSetGLDevice\(\)](#), and [cudaVDPAUSetVDPAUDevice\(\)](#). Note that these functions will fail with [cudaErrorSetOnActiveProcess](#) if they are called when the primary context for the specified device has already been initialized. (or if the current device has already been initialized, in the case of [cudaSetDeviceFlags\(\)](#)).

Primary contexts will remain active until they are explicitly deinitialized using [cudaDeviceReset\(\)](#). The function [cudaDeviceReset\(\)](#) will deinitialize the primary context for the calling thread's current device immediately. The context will remain current to all of the threads that it was current to. The next CUDA Runtime API call on any thread which requires an active context will trigger the reinitialization of that device's primary context.

Note that there is no reference counting of the primary context's lifetime. It is recommended that the primary context not be deinitialized except just before exit or to recover from an unspecified launch failure.

4.21.3 Context Interoperability

Note that the use of multiple [CUcontext](#) s per device within a single process will substantially degrade performance and is strongly discouraged. Instead, it is highly recommended that the implicit one-to-one device-to-context mapping for the process provided by the CUDA Runtime API be used.

If a non-primary [CUcontext](#) created by the CUDA Driver API is current to a thread then the CUDA Runtime API calls to that thread will operate on that [CUcontext](#), with some exceptions listed below. Interoperability between data types is discussed in the following sections.

The function [cudaPointerGetAttributes\(\)](#) will return the error [cudaErrorIncompatibleDriverContext](#) if the pointer being queried was allocated by a non-primary context. The function [cudaDeviceEnablePeerAccess\(\)](#) and the rest of the peer access API may not be called when a non-primary [CUcontext](#) is current. To use the pointer query and peer access APIs with a context created using the CUDA Driver API, it is necessary that the CUDA Driver API be used to access these features.

All CUDA Runtime API state (e.g, global variables' addresses and values) travels with its underlying [CUcontext](#). In particular, if a [CUcontext](#) is moved from one thread to another then all CUDA Runtime API state will move to that thread as well.

Please note that attaching to legacy contexts (those with a version of 3010 as returned by [cuCtxGetApiVersion\(\)](#)) is not possible. The CUDA Runtime will return [cudaErrorIncompatibleDriverContext](#) in such cases.

4.21.4 Interactions between CUstream and cudaStream_t

The types [CUstream](#) and [cudaStream_t](#) are identical and may be used interchangeably.

4.21.5 Interactions between CUEvent and cudaEvent_t

The types [CUEvent](#) and [cudaEvent_t](#) are identical and may be used interchangeably.

4.21.6 Interactions between CUarray and struct cudaArray *

The types [CUarray](#) and struct `cudaArray *` represent the same data type and may be used interchangeably by casting the two types between each other.

In order to use a [CUarray](#) in a CUDA Runtime API function which takes a struct `cudaArray *`, it is necessary to explicitly cast the [CUarray](#) to a struct `cudaArray *`.

In order to use a struct `cudaArray *` in a CUDA Driver API function which takes a [CUarray](#), it is necessary to explicitly cast the struct `cudaArray *` to a [CUarray](#).

4.21.7 Interactions between CUgraphicsResource and cudaGraphicsResource_t

The types [CUgraphicsResource](#) and [cudaGraphicsResource_t](#) represent the same data type and may be used interchangeably by casting the two types between each other.

In order to use a [CUgraphicsResource](#) in a CUDA Runtime API function which takes a [cudaGraphicsResource_t](#), it is necessary to explicitly cast the [CUgraphicsResource](#) to a [cudaGraphicsResource_t](#).

In order to use a [cudaGraphicsResource_t](#) in a CUDA Driver API function which takes a [CUgraphicsResource](#), it is necessary to explicitly cast the [cudaGraphicsResource_t](#) to a [CUgraphicsResource](#).

4.22 Profiler Control

Functions

- [cudaError_t cudaProfilerInitialize](#) (const char *configFile, const char *outputFile, [cudaOutputMode_t](#) outputMode)
Initialize the profiling.
- [cudaError_t cudaProfilerStart](#) (void)
Start the profiling.
- [cudaError_t cudaProfilerStop](#) (void)
Stop the profiling.

4.22.1 Detailed Description

This section describes the profiler control functions of the CUDA runtime application programming interface.

4.22.2 Function Documentation

4.22.2.1 [cudaError_t cudaProfilerInitialize](#) (const char * *configFile*, const char * *outputFile*, [cudaOutputMode_t](#) *outputMode*)

Using this API user can specify the configuration file, output file and output file format. This API is generally used to profile different set of counters by looping the kernel launch. `configFile` parameter can be used to select profiling options including profiler counters. Refer the "Command Line Profiler" section in the "Compute Visual Profiler User Guide" for supported profiler options and counters.

Configurations defined initially by environment variable settings are overwritten by [cudaProfilerInitialize\(\)](#).

Limitation: Profiling APIs do not work when the application is running with any profiler tool such as Compute Visual Profiler. User must handle error [cudaErrorProfilerDisabled](#) returned by profiler APIs if application is likely to be used with any profiler tool.

Typical usage of the profiling APIs is as follows:

for each set of counters

```
{
cudaProfilerInitialize\(\); //Initialize profiling,set the counters/options in the config file
...
cudaProfilerStart\(\);
// code to be profiled
cudaProfilerStop\(\);
...
cudaProfilerStart\(\);
// code to be profiled
cudaProfilerStop\(\);
```

```
...  
}
```

Parameters:

configFile - Name of the config file that lists the counters for profiling.

outputFile - Name of the output file where the profiling results will be stored.

outputMode - outputMode, can be [cudaKeyValuePair](#) OR [cudaCSV](#).

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorProfilerDisabled](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaProfilerStart](#), [cudaProfilerStop](#)

4.22.2.2 [cudaError_t](#) [cudaProfilerStart](#) (void)

This API is used in conjunction with [cudaProfilerStop](#) to selectively profile subsets of the CUDA program. Profiler must be initialized using [cudaProfilerInitialize\(\)](#) before making a call to [cudaProfilerStart\(\)](#). API returns an error [cudaErrorProfilerNotInitialized](#) if it is called without initializing profiler.

Returns:

[cudaSuccess](#), [cudaErrorProfilerDisabled](#), [cudaErrorProfilerAlreadyStarted](#), [cudaErrorProfilerNotInitialized](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaProfilerInitialize](#), [cudaProfilerStop](#)

4.22.2.3 [cudaError_t](#) [cudaProfilerStop](#) (void)

This API is used in conjunction with [cudaProfilerStart](#) to selectively profile subsets of the CUDA program. Profiler must be initialized using [cudaProfilerInitialize\(\)](#) before making a call to [cudaProfilerStop\(\)](#). API returns an error [cudaErrorProfilerNotInitialized](#) if it is called without initializing profiler.

Returns:

[cudaSuccess](#), [cudaErrorProfilerDisabled](#), [cudaErrorProfilerAlreadyStopped](#), [cudaErrorProfilerNotInitialized](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaProfilerInitialize](#), [cudaProfilerStart](#)

4.23 Direct3D 9 Interoperability [DEPRECATED]

Enumerations

- enum `cudaD3D9MapFlags` {
`cudaD3D9MapFlagsNone` = 0,
`cudaD3D9MapFlagsReadOnly` = 1,
`cudaD3D9MapFlagsWriteDiscard` = 2 }
- enum `cudaD3D9RegisterFlags` {
`cudaD3D9RegisterFlagsNone` = 0,
`cudaD3D9RegisterFlagsArray` = 1 }

Functions

- `cudaError_t cudaD3D9MapResources` (int count, IDirect3DResource9 **ppResources)
Map Direct3D resources for access by CUDA.
- `cudaError_t cudaD3D9RegisterResource` (IDirect3DResource9 *pResource, unsigned int flags)
Registers a Direct3D resource for access by CUDA.
- `cudaError_t cudaD3D9ResourceGetMappedArray` (cudaArray **ppArray, IDirect3DResource9 *pResource, unsigned int face, unsigned int level)
Get an array through which to access a subresource of a Direct3D resource which has been mapped for access by CUDA.
- `cudaError_t cudaD3D9ResourceGetMappedPitch` (size_t *pPitch, size_t *pPitchSlice, IDirect3DResource9 *pResource, unsigned int face, unsigned int level)
Get the pitch of a subresource of a Direct3D resource which has been mapped for access by CUDA.
- `cudaError_t cudaD3D9ResourceGetMappedPointer` (void **pPointer, IDirect3DResource9 *pResource, unsigned int face, unsigned int level)
Get a pointer through which to access a subresource of a Direct3D resource which has been mapped for access by CUDA.
- `cudaError_t cudaD3D9ResourceGetMappedSize` (size_t *pSize, IDirect3DResource9 *pResource, unsigned int face, unsigned int level)
Get the size of a subresource of a Direct3D resource which has been mapped for access by CUDA.
- `cudaError_t cudaD3D9ResourceGetSurfaceDimensions` (size_t *pWidth, size_t *pHeight, size_t *pDepth, IDirect3DResource9 *pResource, unsigned int face, unsigned int level)
Get the dimensions of a registered Direct3D surface.
- `cudaError_t cudaD3D9ResourceSetMapFlags` (IDirect3DResource9 *pResource, unsigned int flags)
Set usage flags for mapping a Direct3D resource.
- `cudaError_t cudaD3D9UnmapResources` (int count, IDirect3DResource9 **ppResources)
Unmap Direct3D resources for access by CUDA.
- `cudaError_t cudaD3D9UnregisterResource` (IDirect3DResource9 *pResource)
Unregisters a Direct3D resource for access by CUDA.

4.23.1 Detailed Description

This section describes deprecated Direct3D 9 interoperability functions.

4.23.2 Enumeration Type Documentation

4.23.2.1 enum cudaD3D9MapFlags

CUDA D3D9 Map Flags

Enumerator:

cudaD3D9MapFlagsNone Default; Assume resource can be read/written

cudaD3D9MapFlagsReadOnly CUDA kernels will not write to this resource

cudaD3D9MapFlagsWriteDiscard CUDA kernels will only write to and will not read from this resource

4.23.2.2 enum cudaD3D9RegisterFlags

CUDA D3D9 Register Flags

Enumerator:

cudaD3D9RegisterFlagsNone Default; Resource can be accessed through a void*

cudaD3D9RegisterFlagsArray Resource can be accessed through a CUarray*

4.23.3 Function Documentation

4.23.3.1 cudaError_t cudaD3D9MapResources (int count, IDirect3DResource9 ** ppResources)

Deprecated

This function is deprecated as of Cuda 3.0.

Maps the `count` Direct3D resources in `ppResources` for access by CUDA.

The resources in `ppResources` may be accessed in CUDA kernels until they are unmapped. Direct3D should not access any resources while they are mapped by CUDA. If an application does so, the results are undefined.

This function provides the synchronization guarantee that any Direct3D calls issued before `cudaD3D9MapResources()` will complete before any CUDA kernels issued after `cudaD3D9MapResources()` begin.

If any of `ppResources` have not been registered for use with CUDA or if `ppResources` contains any duplicate entries then `cudaErrorInvalidResourceHandle` is returned. If any of `ppResources` are presently mapped for access by CUDA then `cudaErrorUnknown` is returned.

Parameters:

count - Number of resources to map for CUDA

ppResources - Resources to map for CUDA

Returns:

`cudaSuccess`, `cudaErrorInvalidResourceHandle`, `cudaErrorUnknown`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsMapResources](#)

4.23.3.2 `cudaError_t cudaD3D9RegisterResource (IDirect3DResource9 * pResource, unsigned int flags)`

Deprecated

This function is deprecated as of Cuda 3.0.

Registers the Direct3D resource `pResource` for access by CUDA.

If this call is successful, then the application will be able to map and unmap this resource until it is unregistered through [cudaD3D9UnregisterResource\(\)](#). Also on success, this call will increase the internal reference count on `pResource`. This reference count will be decremented when this resource is unregistered through [cudaD3D9UnregisterResource\(\)](#).

This call is potentially high-overhead and should not be called every frame in interactive applications.

The type of `pResource` must be one of the following.

- `IDirect3DVertexBuffer9`: No notes.
- `IDirect3DIndexBuffer9`: No notes.
- `IDirect3DSurface9`: Only stand-alone objects of type `IDirect3DSurface9` may be explicitly shared. In particular, individual mipmap levels and faces of cube maps may not be registered directly. To access individual surfaces associated with a texture, one must register the base texture object.
- `IDirect3DBaseTexture9`: When a texture is registered, all surfaces associated with all mipmap levels of all faces of the texture will be accessible to CUDA.

The `flags` argument specifies the mechanism through which CUDA will access the Direct3D resource. The following value is allowed:

- [cudaD3D9RegisterFlagsNone](#): Specifies that CUDA will access this resource through a `void*`. The pointer, size, and pitch for each subresource of this resource may be queried through [cudaD3D9ResourceGetMappedPointer\(\)](#), [cudaD3D9ResourceGetMappedSize\(\)](#), and [cudaD3D9ResourceGetMappedPitch\(\)](#) respectively. This option is valid for all resource types.

Not all Direct3D resources of the above types may be used for interoperability with CUDA. The following are some limitations:

- The primary rendertarget may not be registered with CUDA.
- Resources allocated as shared may not be registered with CUDA.
- Any resources allocated in `D3DPOOL_SYSTEMMEM` or `D3DPOOL_MANAGED` may not be registered with CUDA.
- Textures which are not of a format which is 1, 2, or 4 channels of 8, 16, or 32-bit integer or floating-point data cannot be shared.
- Surfaces of depth or stencil formats cannot be shared.

If Direct3D interoperability is not initialized on this context, then [cudaErrorInvalidDevice](#) is returned. If `pResource` is of incorrect type (e.g, is a non-stand-alone `IDirect3DSurface9`) or is already registered, then [cudaErrorInvalidResourceHandle](#) is returned. If `pResource` cannot be registered then [cudaErrorUnknown](#) is returned.

Parameters:

pResource - Resource to register
flags - Parameters for resource registration

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsD3D9RegisterResource](#)

4.23.3.3 `cudaError_t cudaD3D9ResourceGetMappedArray (cudaArray **ppArray, IDirect3DResource9 *pResource, unsigned int face, unsigned int level)`

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in `*ppArray` an array through which the subresource of the mapped Direct3D resource `pResource`, which corresponds to `face` and `level` may be accessed. The value set in `pArray` may change every time that `pResource` is mapped.

If `pResource` is not registered then [cudaErrorInvalidResourceHandle](#) is returned. If `pResource` was not registered with usage flags [cudaD3D9RegisterFlagsArray](#), then [cudaErrorInvalidResourceHandle](#) is returned. If `pResource` is not mapped, then [cudaErrorUnknown](#) is returned.

For usage requirements of `face` and `level` parameters, see [cudaD3D9ResourceGetMappedPointer\(\)](#).

Parameters:

ppArray - Returned array corresponding to subresource
pResource - Mapped resource to access
face - Face of resource to access
level - Level of resource to access

Returns:

[cudaSuccess](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsSubResourceGetMappedArray](#)

4.23.3.4 `cudaError_t cudaD3D9ResourceGetMappedPitch (size_t * pPitch, size_t * pPitchSlice, IDirect3DResource9 * pResource, unsigned int face, unsigned int level)`

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in *pPitch* and *pPitchSlice* the pitch and Z-slice pitch of the subresource of the mapped Direct3D resource *pResource*, which corresponds to *face* and *level*. The values set in *pPitch* and *pPitchSlice* may change every time that *pResource* is mapped.

The pitch and Z-slice pitch values may be used to compute the location of a sample on a surface as follows.

For a 2D surface, the byte offset of the sample at position *x*, *y* from the base pointer of the surface is:

$$y * \text{pitch} + (\text{bytes per pixel}) * x$$

For a 3D surface, the byte offset of the sample at position *x*, *y*, *z* from the base pointer of the surface is:

$$z * \text{slicePitch} + y * \text{pitch} + (\text{bytes per pixel}) * x$$

Both parameters *pPitch* and *pPitchSlice* are optional and may be set to NULL.

If *pResource* is not of type `IDirect3DBaseTexture9` or one of its sub-types or if *pResource* has not been registered for use with CUDA, then `cudaErrorInvalidResourceHandle` is returned. If *pResource* was not registered with usage flags `cudaD3D9RegisterFlagsNone`, then `cudaErrorInvalidResourceHandle` is returned. If *pResource* is not mapped for access by CUDA then `cudaErrorUnknown` is returned.

For usage requirements of *face* and *level* parameters, see `cudaD3D9ResourceGetMappedPointer()`.

Parameters:

pPitch - Returned pitch of subresource

pPitchSlice - Returned Z-slice pitch of subresource

pResource - Mapped resource to access

face - Face of resource to access

level - Level of resource to access

Returns:

`cudaSuccess`, `cudaErrorInvalidValue`, `cudaErrorInvalidResourceHandle`, `cudaErrorUnknown`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaGraphicsResourceGetMappedPointer`

4.23.3.5 `cudaError_t cudaD3D9ResourceGetMappedPointer (void ** pPointer, IDirect3DResource9 * pResource, unsigned int face, unsigned int level)`

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in *pPointer* the base pointer of the subresource of the mapped Direct3D resource *pResource*, which corresponds to *face* and *level*. The value set in *pPointer* may change every time that *pResource* is mapped.

If *pResource* is not registered, then [cudaErrorInvalidResourceHandle](#) is returned. If *pResource* was not registered with usage flags [cudaD3D9RegisterFlagsNone](#), then [cudaErrorInvalidResourceHandle](#) is returned. If *pResource* is not mapped, then [cudaErrorUnknown](#) is returned.

If *pResource* is of type `IDirect3DCubeTexture9`, then *face* must one of the values enumerated by type `D3DCUBEMAP_FACES`. For all other types, *face* must be 0. If *face* is invalid, then [cudaErrorInvalidValue](#) is returned.

If *pResource* is of type `IDirect3DBaseTexture9`, then *level* must correspond to a valid mipmap level. Only mipmap level 0 is supported for now. For all other types *level* must be 0. If *level* is invalid, then [cudaErrorInvalidValue](#) is returned.

Parameters:

pPointer - Returned pointer corresponding to subresource

pResource - Mapped resource to access

face - Face of resource to access

level - Level of resource to access

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsResourceGetMappedPointer](#)

4.23.3.6 `cudaError_t cudaD3D9ResourceGetMappedSize (size_t * pSize, IDirect3DResource9 * pResource, unsigned int face, unsigned int level)`

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in *pSize* the size of the subresource of the mapped Direct3D resource *pResource*, which corresponds to *face* and *level*. The value set in *pSize* may change every time that *pResource* is mapped.

If *pResource* has not been registered for use with CUDA then [cudaErrorInvalidResourceHandle](#) is returned. If *pResource* was not registered with usage flags [cudaD3D9RegisterFlagsNone](#), then [cudaErrorInvalidResourceHandle](#) is returned. If *pResource* is not mapped for access by CUDA then [cudaErrorUnknown](#) is returned.

For usage requirements of *face* and *level* parameters, see [cudaD3D9ResourceGetMappedPointer\(\)](#).

Parameters:

pSize - Returned size of subresource

pResource - Mapped resource to access

face - Face of resource to access

level - Level of resource to access

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsResourceGetMappedPointer](#)

4.23.3.7 `cudaError_t cudaD3D9ResourceGetSurfaceDimensions (size_t * pWidth, size_t * pHeight, size_t * pDepth, IDirect3DResource9 * pResource, unsigned int face, unsigned int level)`

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in *pWidth*, *pHeight*, and *pDepth* the dimensions of the subresource of the mapped Direct3D resource *pResource* which corresponds to *face* and *level*.

Because anti-aliased surfaces may have multiple samples per pixel, it is possible that the dimensions of a resource will be an integer factor larger than the dimensions reported by the Direct3D runtime.

The parameters *pWidth*, *pHeight*, and *pDepth* are optional. For 2D surfaces, the value returned in *pDepth* will be 0.

If *pResource* is not of type `IDirect3DBaseTexture9` or `IDirect3DSurface9` or if *pResource* has not been registered for use with CUDA, then [cudaErrorInvalidResourceHandle](#) is returned.

For usage requirements of *face* and *level* parameters, see [cudaD3D9ResourceGetMappedPointer](#).

Parameters:

pWidth - Returned width of surface

pHeight - Returned height of surface

pDepth - Returned depth of surface

pResource - Registered resource to access

face - Face of resource to access

level - Level of resource to access

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsSubResourceGetMappedArray](#)

4.23.3.8 `cudaError_t cudaD3D9ResourceSetMapFlags (IDirect3DResource9 * pResource, unsigned int flags)`**Deprecated**

This function is deprecated as of Cuda 3.0.

Set flags for mapping the Direct3D resource `pResource`.

Changes to flags will take effect the next time `pResource` is mapped. The `flags` argument may be any of the following:

- `cudaD3D9MapFlagsNone`: Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA kernels. This is the default value.
- `cudaD3D9MapFlagsReadOnly`: Specifies that CUDA kernels which access this resource will not write to this resource.
- `cudaD3D9MapFlagsWriteDiscard`: Specifies that CUDA kernels which access this resource will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

If `pResource` has not been registered for use with CUDA, then `cudaErrorInvalidResourceHandle` is returned. If `pResource` is presently mapped for access by CUDA, then `cudaErrorUnknown` is returned.

Parameters:

pResource - Registered resource to set flags for

flags - Parameters for resource mapping

Returns:

`cudaSuccess`, `cudaErrorInvalidValue`, `cudaErrorInvalidResourceHandle`, `cudaErrorUnknown`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaInteropResourceSetMapFlags`

4.23.3.9 `cudaError_t cudaD3D9UnmapResources (int count, IDirect3DResource9 ** ppResources)`**Deprecated**

This function is deprecated as of Cuda 3.0.

Unmaps the `count` Direct3D resources in `ppResources`.

This function provides the synchronization guarantee that any CUDA kernels issued before `cudaD3D9UnmapResources()` will complete before any Direct3D calls issued after `cudaD3D9UnmapResources()` begin.

If any of `ppResources` have not been registered for use with CUDA or if `ppResources` contains any duplicate entries, then `cudaErrorInvalidResourceHandle` is returned. If any of `ppResources` are not presently mapped for access by CUDA then `cudaErrorUnknown` is returned.

Parameters:

count - Number of resources to unmap for CUDA

ppResources - Resources to unmap for CUDA

Returns:

[cudaSuccess](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnmapResources](#)

4.23.3.10 `cudaError_t cudaD3D9UnregisterResource (IDirect3DResource9 * pResource)`**Deprecated**

This function is deprecated as of Cuda 3.0.

Unregisters the Direct3D resource `pResource` so it is not accessible by CUDA unless registered again.

If `pResource` is not registered, then [cudaErrorInvalidResourceHandle](#) is returned.

Parameters:

pResource - Resource to unregister

Returns:

[cudaSuccess](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnregisterResource](#)

4.24 Direct3D 10 Interoperability [DEPRECATED]

Enumerations

- enum `cudaD3D10MapFlags` {
`cudaD3D10MapFlagsNone` = 0,
`cudaD3D10MapFlagsReadOnly` = 1,
`cudaD3D10MapFlagsWriteDiscard` = 2 }
- enum `cudaD3D10RegisterFlags` {
`cudaD3D10RegisterFlagsNone` = 0,
`cudaD3D10RegisterFlagsArray` = 1 }

Functions

- `cudaError_t cudaD3D10MapResources` (int count, ID3D10Resource **ppResources)
Map Direct3D Resources for access by CUDA.
- `cudaError_t cudaD3D10RegisterResource` (ID3D10Resource *pResource, unsigned int flags)
Register a Direct3D 10 resource for access by CUDA.
- `cudaError_t cudaD3D10ResourceGetMappedArray` (cudaArray **ppArray, ID3D10Resource *pResource, unsigned int subResource)
Get an array through which to access a subresource of a Direct3D resource which has been mapped for access by CUDA.
- `cudaError_t cudaD3D10ResourceGetMappedPitch` (size_t *pPitch, size_t *pPitchSlice, ID3D10Resource *pResource, unsigned int subResource)
Get the pitch of a subresource of a Direct3D resource which has been mapped for access by CUDA.
- `cudaError_t cudaD3D10ResourceGetMappedPointer` (void **pPointer, ID3D10Resource *pResource, unsigned int subResource)
Get a pointer through which to access a subresource of a Direct3D resource which has been mapped for access by CUDA.
- `cudaError_t cudaD3D10ResourceGetMappedSize` (size_t *pSize, ID3D10Resource *pResource, unsigned int subResource)
Get the size of a subresource of a Direct3D resource which has been mapped for access by CUDA.
- `cudaError_t cudaD3D10ResourceGetSurfaceDimensions` (size_t *pWidth, size_t *pHeight, size_t *pDepth, ID3D10Resource *pResource, unsigned int subResource)
Get the dimensions of a registered Direct3D surface.
- `cudaError_t cudaD3D10ResourceSetMapFlags` (ID3D10Resource *pResource, unsigned int flags)
Set usage flags for mapping a Direct3D resource.
- `cudaError_t cudaD3D10UnmapResources` (int count, ID3D10Resource **ppResources)
Unmaps Direct3D resources.
- `cudaError_t cudaD3D10UnregisterResource` (ID3D10Resource *pResource)
Unregisters a Direct3D resource.

4.24.1 Detailed Description

This section describes deprecated Direct3D 10 interoperability functions.

4.24.2 Enumeration Type Documentation

4.24.2.1 enum cudaD3D10MapFlags

CUDA D3D10 Map Flags

Enumerator:

cudaD3D10MapFlagsNone Default; Assume resource can be read/written
cudaD3D10MapFlagsReadOnly CUDA kernels will not write to this resource
cudaD3D10MapFlagsWriteDiscard CUDA kernels will only write to and will not read from this resource

4.24.2.2 enum cudaD3D10RegisterFlags

CUDA D3D10 Register Flags

Enumerator:

cudaD3D10RegisterFlagsNone Default; Resource can be accessed through a void*
cudaD3D10RegisterFlagsArray Resource can be accessed through a CUarray*

4.24.3 Function Documentation

4.24.3.1 cudaError_t cudaD3D10MapResources (int count, ID3D10Resource ** ppResources)

Deprecated

This function is deprecated as of Cuda 3.0.

Maps the `count` Direct3D resources in `ppResources` for access by CUDA.

The resources in `ppResources` may be accessed in CUDA kernels until they are unmapped. Direct3D should not access any resources while they are mapped by CUDA. If an application does so, the results are undefined.

This function provides the synchronization guarantee that any Direct3D calls issued before `cudaD3D10MapResources()` will complete before any CUDA kernels issued after `cudaD3D10MapResources()` begin.

If any of `ppResources` have not been registered for use with CUDA or if `ppResources` contains any duplicate entries then `cudaErrorInvalidResourceHandle` is returned. If any of `ppResources` are presently mapped for access by CUDA then `cudaErrorUnknown` is returned.

Parameters:

count - Number of resources to map for CUDA
ppResources - Resources to map for CUDA

Returns:

`cudaSuccess`, `cudaErrorInvalidResourceHandle`, `cudaErrorUnknown`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsMapResources](#)

4.24.3.2 `cudaError_t cudaD3D10RegisterResource (ID3D10Resource *pResource, unsigned int flags)`**Deprecated**

This function is deprecated as of Cuda 3.0.

Registers the Direct3D resource `pResource` for access by CUDA.

If this call is successful, then the application will be able to map and unmap this resource until it is unregistered through [cudaD3D10UnregisterResource\(\)](#). Also on success, this call will increase the internal reference count on `pResource`. This reference count will be decremented when this resource is unregistered through [cudaD3D10UnregisterResource\(\)](#).

This call is potentially high-overhead and should not be called every frame in interactive applications.

The type of `pResource` must be one of the following:

- `ID3D10Buffer`: Cannot be used with `flags` set to `cudaD3D10RegisterFlagsArray`.
- `ID3D10Texture1D`: No restrictions.
- `ID3D10Texture2D`: No restrictions.
- `ID3D10Texture3D`: No restrictions.

The `flags` argument specifies the mechanism through which CUDA will access the Direct3D resource. The following values are allowed.

- [cudaD3D10RegisterFlagsNone](#): Specifies that CUDA will access this resource through a `void*`. The pointer, size, and pitch for each subresource of this resource may be queried through [cudaD3D10ResourceGetMappedPointer\(\)](#), [cudaD3D10ResourceGetMappedSize\(\)](#), and [cudaD3D10ResourceGetMappedPitch\(\)](#) respectively. This option is valid for all resource types.
- [cudaD3D10RegisterFlagsArray](#): Specifies that CUDA will access this resource through a `CUarray` queried on a sub-resource basis through [cudaD3D10ResourceGetMappedArray\(\)](#). This option is only valid for resources of type `ID3D10Texture1D`, `ID3D10Texture2D`, and `ID3D10Texture3D`.

Not all Direct3D resources of the above types may be used for interoperability with CUDA. The following are some limitations.

- The primary rendertarget may not be registered with CUDA.
- Resources allocated as shared may not be registered with CUDA.
- Textures which are not of a format which is 1, 2, or 4 channels of 8, 16, or 32-bit integer or floating-point data cannot be shared.
- Surfaces of depth or stencil formats cannot be shared.

If Direct3D interoperability is not initialized on this context then [cudaErrorInvalidDevice](#) is returned. If `pResource` is of incorrect type or is already registered then [cudaErrorInvalidResourceHandle](#) is returned. If `pResource` cannot be registered then [cudaErrorUnknown](#) is returned.

Parameters:

pResource - Resource to register
flags - Parameters for resource registration

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevice](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsD3D10RegisterResource](#)

4.24.3.3 `cudaError_t cudaD3D10ResourceGetMappedArray (cudaArray ** ppArray, ID3D10Resource * pResource, unsigned int subResource)`

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in `*ppArray` an array through which the subresource of the mapped Direct3D resource `pResource` which corresponds to `subResource` may be accessed. The value set in `ppArray` may change every time that `pResource` is mapped.

If `pResource` is not registered, then [cudaErrorInvalidResourceHandle](#) is returned. If `pResource` was not registered with usage flags [cudaD3D10RegisterFlagsArray](#), then [cudaErrorInvalidResourceHandle](#) is returned. If `pResource` is not mapped then [cudaErrorUnknown](#) is returned.

For usage requirements of the `subResource` parameter, see [cudaD3D10ResourceGetMappedPointer\(\)](#).

Parameters:

ppArray - Returned array corresponding to subresource
pResource - Mapped resource to access
subResource - Subresource of `pResource` to access

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsSubResourceGetMappedArray](#)

4.24.3.4 `cudaError_t cudaD3D10ResourceGetMappedPitch (size_t * pPitch, size_t * pPitchSlice, ID3D10Resource * pResource, unsigned int subResource)`

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in **pPitch* and **pPitchSlice* the pitch and Z-slice pitch of the subresource of the mapped Direct3D resource *pResource*, which corresponds to *subResource*. The values set in *pPitch* and *pPitchSlice* may change every time that *pResource* is mapped.

The pitch and Z-slice pitch values may be used to compute the location of a sample on a surface as follows.

For a 2D surface, the byte offset of the sample at position *x*, *y* from the base pointer of the surface is:

$$y * \text{pitch} + (\text{bytes per pixel}) * x$$

For a 3D surface, the byte offset of the sample at position *x*, *y*, *z* from the base pointer of the surface is:

$$z * \text{slicePitch} + y * \text{pitch} + (\text{bytes per pixel}) * x$$

Both parameters *pPitch* and *pPitchSlice* are optional and may be set to NULL.

If *pResource* is not of type ID3D10Texture1D, ID3D10Texture2D, or ID3D10Texture3D, or if *pResource* has not been registered for use with CUDA, then [cudaErrorInvalidResourceHandle](#) is returned. If *pResource* was not registered with usage flags [cudaD3D10RegisterFlagsNone](#), then [cudaErrorInvalidResourceHandle](#) is returned. If *pResource* is not mapped for access by CUDA then [cudaErrorUnknown](#) is returned.

For usage requirements of the *subResource* parameter see [cudaD3D10ResourceGetMappedPointer\(\)](#).

Parameters:

pPitch - Returned pitch of subresource

pPitchSlice - Returned Z-slice pitch of subresource

pResource - Mapped resource to access

subResource - Subresource of *pResource* to access

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsSubResourceGetMappedArray](#)

4.24.3.5 `cudaError_t cudaD3D10ResourceGetMappedPointer (void ** pPointer, ID3D10Resource * pResource, unsigned int subResource)`

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in **pPointer* the base pointer of the subresource of the mapped Direct3D resource *pResource* which corresponds to *subResource*. The value set in *pPointer* may change every time that *pResource* is mapped.

If `pResource` is not registered, then `cudaErrorInvalidResourceHandle` is returned. If `pResource` was not registered with usage flags `cudaD3D9RegisterFlagsNone`, then `cudaErrorInvalidResourceHandle` is returned. If `pResource` is not mapped then `cudaErrorUnknown` is returned.

If `pResource` is of type `ID3D10Buffer` then `subResource` must be 0. If `pResource` is of any other type, then the value of `subResource` must come from the subresource calculation in `D3D10CalcSubResource()`.

Parameters:

pPointer - Returned pointer corresponding to subresource
pResource - Mapped resource to access
subResource - Subresource of `pResource` to access

Returns:

`cudaSuccess`, `cudaErrorInvalidValue`, `cudaErrorInvalidResourceHandle`, `cudaErrorUnknown`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaGraphicsResourceGetMappedPointer`

4.24.3.6 `cudaError_t cudaD3D10ResourceGetMappedSize (size_t * pSize, ID3D10Resource * pResource, unsigned int subResource)`

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in `*pSize` the size of the subresource of the mapped Direct3D resource `pResource` which corresponds to `subResource`. The value set in `pSize` may change every time that `pResource` is mapped.

If `pResource` has not been registered for use with CUDA then `cudaErrorInvalidHandle` is returned. If `pResource` was not registered with usage flags `cudaD3D10RegisterFlagsNone`, then `cudaErrorInvalidResourceHandle` is returned. If `pResource` is not mapped for access by CUDA then `cudaErrorUnknown` is returned.

For usage requirements of the `subResource` parameter see `cudaD3D10ResourceGetMappedPointer()`.

Parameters:

pSize - Returned size of subresource
pResource - Mapped resource to access
subResource - Subresource of `pResource` to access

Returns:

`cudaSuccess`, `cudaErrorInvalidValue`, `cudaErrorInvalidResourceHandle`, `cudaErrorUnknown`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaGraphicsResourceGetMappedPointer`

4.24.3.7 `cudaError_t cudaD3D10ResourceGetSurfaceDimensions (size_t * pWidth, size_t * pHeight, size_t * pDepth, ID3D10Resource * pResource, unsigned int subResource)`

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in *pWidth*, *pHeight*, and *pDepth* the dimensions of the subresource of the mapped Direct3D resource *pResource* which corresponds to *subResource*.

Because anti-aliased surfaces may have multiple samples per pixel, it is possible that the dimensions of a resource will be an integer factor larger than the dimensions reported by the Direct3D runtime.

The parameters *pWidth*, *pHeight*, and *pDepth* are optional. For 2D surfaces, the value returned in *pDepth* will be 0.

If *pResource* is not of type `ID3D10Texture1D`, `ID3D10Texture2D`, or `ID3D10Texture3D`, or if *pResource* has not been registered for use with CUDA, then `cudaErrorInvalidHandle` is returned.

For usage requirements of *subResource* parameters see [cudaD3D10ResourceGetMappedPointer\(\)](#).

Parameters:

- pWidth* - Returned width of surface
- pHeight* - Returned height of surface
- pDepth* - Returned depth of surface
- pResource* - Registered resource to access
- subResource* - Subresource of *pResource* to access

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsSubResourceGetMappedArray](#)

4.24.3.8 `cudaError_t cudaD3D10ResourceSetMapFlags (ID3D10Resource * pResource, unsigned int flags)`

Deprecated

This function is deprecated as of Cuda 3.0.

Set usage flags for mapping the Direct3D resource *pResource*.

Changes to flags will take effect the next time *pResource* is mapped. The *flags* argument may be any of the following:

- [cudaD3D10MapFlagsNone](#): Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA kernels. This is the default value.
- [cudaD3D10MapFlagsReadOnly](#): Specifies that CUDA kernels which access this resource will not write to this resource.

- [cudaD3D10MapFlagsWriteDiscard](#): Specifies that CUDA kernels which access this resource will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

If `pResource` has not been registered for use with CUDA then `cudaErrorInvalidHandle` is returned. If `pResource` is presently mapped for access by CUDA then [cudaErrorUnknown](#) is returned.

Parameters:

pResource - Registered resource to set flags for
flags - Parameters for resource mapping

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsResourceSetMapFlags](#)

4.24.3.9 `cudaError_t cudaD3D10UnmapResources (int count, ID3D10Resource ** ppResources)`

Deprecated

This function is deprecated as of Cuda 3.0.

Unmaps the `count` Direct3D resource in `ppResources`.

This function provides the synchronization guarantee that any CUDA kernels issued before [cudaD3D10UnmapResources\(\)](#) will complete before any Direct3D calls issued after [cudaD3D10UnmapResources\(\)](#) begin.

If any of `ppResources` have not been registered for use with CUDA or if `ppResources` contains any duplicate entries, then [cudaErrorInvalidResourceHandle](#) is returned. If any of `ppResources` are not presently mapped for access by CUDA then [cudaErrorUnknown](#) is returned.

Parameters:

count - Number of resources to unmap for CUDA
ppResources - Resources to unmap for CUDA

Returns:

[cudaSuccess](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnmapResources](#)

4.24.3.10 `cudaError_t cudaD3D10UnregisterResource (ID3D10Resource * pResource)`**Deprecated**

This function is deprecated as of Cuda 3.0.

Unregisters the Direct3D resource `resource` so it is not accessible by CUDA unless registered again.

If `pResource` is not registered, then [cudaErrorInvalidResourceHandle](#) is returned.

Parameters:

pResource - Resource to unregister

Returns:

[cudaSuccess](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnregisterResource](#)

4.25 OpenGL Interoperability [DEPRECATED]

Enumerations

- enum `cudaGLMapFlags` {
`cudaGLMapFlagsNone` = 0,
`cudaGLMapFlagsReadOnly` = 1,
`cudaGLMapFlagsWriteDiscard` = 2 }

Functions

- `cudaError_t cudaGLMapBufferObject` (void **devPtr, GLuint bufObj)
Maps a buffer object for access by CUDA.
- `cudaError_t cudaGLMapBufferObjectAsync` (void **devPtr, GLuint bufObj, `cudaStream_t` stream)
Maps a buffer object for access by CUDA.
- `cudaError_t cudaGLRegisterBufferObject` (GLuint bufObj)
Registers a buffer object for access by CUDA.
- `cudaError_t cudaGLSetBufferObjectMapFlags` (GLuint bufObj, unsigned int flags)
Set usage flags for mapping an OpenGL buffer.
- `cudaError_t cudaGLUnmapBufferObject` (GLuint bufObj)
Unmaps a buffer object for access by CUDA.
- `cudaError_t cudaGLUnmapBufferObjectAsync` (GLuint bufObj, `cudaStream_t` stream)
Unmaps a buffer object for access by CUDA.
- `cudaError_t cudaGLUnregisterBufferObject` (GLuint bufObj)
Unregisters a buffer object for access by CUDA.

4.25.1 Detailed Description

This section describes deprecated OpenGL interoperability functionality.

4.25.2 Enumeration Type Documentation

4.25.2.1 enum `cudaGLMapFlags`

CUDA GL Map Flags

Enumerator:

- `cudaGLMapFlagsNone` Default; Assume resource can be read/written
- `cudaGLMapFlagsReadOnly` CUDA kernels will not write to this resource
- `cudaGLMapFlagsWriteDiscard` CUDA kernels will only write to and will not read from this resource

4.25.3 Function Documentation

4.25.3.1 `cudaError_t cudaGLMapBufferObject (void ** devPtr, GLuint bufObj)`

Deprecated

This function is deprecated as of Cuda 3.0.

Maps the buffer object of ID `bufObj` into the address space of CUDA and returns in `*devPtr` the base pointer of the resulting mapping. The buffer must have previously been registered by calling `cudaGLRegisterBufferObject()`. While a buffer is mapped by CUDA, any OpenGL operation which references the buffer will result in undefined behavior. The OpenGL context used to create the buffer, or another context from the same share group, must be bound to the current thread when this is called.

All streams in the current thread are synchronized with the current GL context.

Parameters:

devPtr - Returned device pointer to CUDA object

bufObj - Buffer object ID to map

Returns:

`cudaSuccess`, `cudaErrorMapBufferObjectFailed`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cudaGraphicsMapResources`

4.25.3.2 `cudaError_t cudaGLMapBufferObjectAsync (void ** devPtr, GLuint bufObj, cudaStream_t stream)`

Deprecated

This function is deprecated as of Cuda 3.0.

Maps the buffer object of ID `bufObj` into the address space of CUDA and returns in `*devPtr` the base pointer of the resulting mapping. The buffer must have previously been registered by calling `cudaGLRegisterBufferObject()`. While a buffer is mapped by CUDA, any OpenGL operation which references the buffer will result in undefined behavior. The OpenGL context used to create the buffer, or another context from the same share group, must be bound to the current thread when this is called.

Stream `/p stream` is synchronized with the current GL context.

Parameters:

devPtr - Returned device pointer to CUDA object

bufObj - Buffer object ID to map

stream - Stream to synchronize

Returns:

`cudaSuccess`, `cudaErrorMapBufferObjectFailed`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsMapResources](#)

4.25.3.3 `cudaError_t cudaGLRegisterBufferObject (GLuint bufObj)`**Deprecated**

This function is deprecated as of Cuda 3.0.

Registers the buffer object of ID `bufObj` for access by CUDA. This function must be called before CUDA can map the buffer object. The OpenGL context used to create the buffer, or another context from the same share group, must be bound to the current thread when this is called.

Parameters:

bufObj - Buffer object ID to register

Returns:

[cudaSuccess](#), [cudaErrorInitializationError](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsGLRegisterBuffer](#)

4.25.3.4 `cudaError_t cudaGLSetBufferObjectMapFlags (GLuint bufObj, unsigned int flags)`**Deprecated**

This function is deprecated as of Cuda 3.0.

Set flags for mapping the OpenGL buffer `bufObj`

Changes to flags will take effect the next time `bufObj` is mapped. The `flags` argument may be any of the following:

- [cudaGLMapFlagsNone](#): Specifies no hints about how this buffer will be used. It is therefore assumed that this buffer will be read from and written to by CUDA kernels. This is the default value.
- [cudaGLMapFlagsReadOnly](#): Specifies that CUDA kernels which access this buffer will not write to the buffer.
- [cudaGLMapFlagsWriteDiscard](#): Specifies that CUDA kernels which access this buffer will not read from the buffer and will write over the entire contents of the buffer, so none of the data previously stored in the buffer will be preserved.

If `bufObj` has not been registered for use with CUDA, then [cudaErrorInvalidResourceHandle](#) is returned. If `bufObj` is presently mapped for access by CUDA, then [cudaErrorUnknown](#) is returned.

Parameters:

bufObj - Registered buffer object to set flags for
flags - Parameters for buffer mapping

Returns:

[cudaSuccess](#), [cudaErrorInvalidValue](#), [cudaErrorInvalidResourceHandle](#), [cudaErrorUnknown](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsResourceSetMapFlags](#)

4.25.3.5 `cudaError_t cudaGLUnmapBufferObject (GLuint bufObj)`**Deprecated**

This function is deprecated as of Cuda 3.0.

Unmaps the buffer object of ID `bufObj` for access by CUDA. When a buffer is unmapped, the base address returned by [cudaGLMapBufferObject\(\)](#) is invalid and subsequent references to the address result in undefined behavior. The OpenGL context used to create the buffer, or another context from the same share group, must be bound to the current thread when this is called.

All streams in the current thread are synchronized with the current GL context.

Parameters:

bufObj - Buffer object to unmap

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorUnmapBufferObjectFailed](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnmapResources](#)

4.25.3.6 `cudaError_t cudaGLUnmapBufferObjectAsync (GLuint bufObj, cudaStream_t stream)`**Deprecated**

This function is deprecated as of Cuda 3.0.

Unmaps the buffer object of ID `bufObj` for access by CUDA. When a buffer is unmapped, the base address returned by [cudaGLMapBufferObject\(\)](#) is invalid and subsequent references to the address result in undefined behavior. The OpenGL context used to create the buffer, or another context from the same share group, must be bound to the current thread when this is called.

Stream `/p stream` is synchronized with the current GL context.

Parameters:

bufObj - Buffer object to unmap

stream - Stream to synchronize

Returns:

[cudaSuccess](#), [cudaErrorInvalidDevicePointer](#), [cudaErrorUnmapBufferObjectFailed](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnmapResources](#)

4.25.3.7 `cudaError_t cudaGLUnregisterBufferObject (GLuint bufObj)`

Deprecated

This function is deprecated as of Cuda 3.0.

Unregisters the buffer object of ID `bufObj` for access by CUDA and releases any CUDA resources associated with the buffer. Once a buffer is unregistered, it may no longer be mapped by CUDA. The GL context used to create the buffer, or another context from the same share group, must be bound to the current thread when this is called.

Parameters:

bufObj - Buffer object to unregister

Returns:

[cudaSuccess](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cudaGraphicsUnregisterResource](#)

4.26 Data types used by CUDA Runtime

Data Structures

- struct [cudaChannelFormatDesc](#)
- struct [cudaDeviceProp](#)
- struct [cudaExtent](#)
- struct [cudaFuncAttributes](#)
- struct [cudaMemcpy3DParms](#)
- struct [cudaMemcpy3DPeerParms](#)
- struct [cudaPitchedPtr](#)
- struct [cudaPointerAttributes](#)
- struct [cudaPos](#)
- struct [surfaceReference](#)
- struct [textureReference](#)

Enumerations

- enum [cudaSurfaceBoundaryMode](#) {
 [cudaBoundaryModeZero](#) = 0,
 [cudaBoundaryModeClamp](#) = 1,
 [cudaBoundaryModeTrap](#) = 2 }
- enum [cudaSurfaceFormatMode](#) {
 [cudaFormatModeForced](#) = 0,
 [cudaFormatModeAuto](#) = 1 }
- enum [cudaTextureAddressMode](#) {
 [cudaAddressModeWrap](#) = 0,
 [cudaAddressModeClamp](#) = 1,
 [cudaAddressModeMirror](#) = 2,
 [cudaAddressModeBorder](#) = 3 }
- enum [cudaTextureFilterMode](#) {
 [cudaFilterModePoint](#) = 0,
 [cudaFilterModeLinear](#) = 1 }
- enum [cudaTextureReadMode](#) {
 [cudaReadModeElementType](#) = 0,
 [cudaReadModeNormalizedFloat](#) = 1 }

Data types used by CUDA Runtime

Data types used by CUDA Runtime

Author:

NVIDIA Corporation

- enum `cudaChannelFormatKind` {
 `cudaChannelFormatKindSigned` = 0,
 `cudaChannelFormatKindUnsigned` = 1,
 `cudaChannelFormatKindFloat` = 2,
 `cudaChannelFormatKindNone` = 3 }
- enum `cudaComputeMode` {
 `cudaComputeModeDefault` = 0,
 `cudaComputeModeExclusive` = 1,
 `cudaComputeModeProhibited` = 2,
 `cudaComputeModeExclusiveProcess` = 3 }
- enum `cudaError` {
 `cudaSuccess` = 0,
 `cudaErrorMissingConfiguration` = 1,
 `cudaErrorMemoryAllocation` = 2,
 `cudaErrorInitializationError` = 3,
 `cudaErrorLaunchFailure` = 4,
 `cudaErrorPriorLaunchFailure` = 5,
 `cudaErrorLaunchTimeout` = 6,
 `cudaErrorLaunchOutOfResources` = 7,
 `cudaErrorInvalidDeviceFunction` = 8,
 `cudaErrorInvalidConfiguration` = 9,
 `cudaErrorInvalidDevice` = 10,
 `cudaErrorInvalidValue` = 11,
 `cudaErrorInvalidPitchValue` = 12,
 `cudaErrorInvalidSymbol` = 13,
 `cudaErrorMapBufferObjectFailed` = 14,
 `cudaErrorUnmapBufferObjectFailed` = 15,
 `cudaErrorInvalidHostPointer` = 16,
 `cudaErrorInvalidDevicePointer` = 17,
 `cudaErrorInvalidTexture` = 18,
 `cudaErrorInvalidTextureBinding` = 19,
 `cudaErrorInvalidChannelDescriptor` = 20,
 `cudaErrorInvalidMemcpyDirection` = 21,
 `cudaErrorAddressOfConstant` = 22,
 `cudaErrorTextureFetchFailed` = 23,
 `cudaErrorTextureNotBound` = 24,
 `cudaErrorSynchronizationError` = 25,
 `cudaErrorInvalidFilterSetting` = 26,
 `cudaErrorInvalidNormSetting` = 27,
 `cudaErrorMixedDeviceExecution` = 28,
 `cudaErrorCudartUnloading` = 29,

```
cudaErrorUnknown = 30,
cudaErrorNotYetImplemented = 31,
cudaErrorMemoryValueTooLarge = 32,
cudaErrorInvalidResourceHandle = 33,
cudaErrorNotReady = 34,
cudaErrorInsufficientDriver = 35,
cudaErrorSetOnActiveProcess = 36,
cudaErrorInvalidSurface = 37,
cudaErrorNoDevice = 38,
cudaErrorECCUncorrectable = 39,
cudaErrorSharedObjectSymbolNotFound = 40,
cudaErrorSharedObjectInitFailed = 41,
cudaErrorUnsupportedLimit = 42,
cudaErrorDuplicateVariableName = 43,
cudaErrorDuplicateTextureName = 44,
cudaErrorDuplicateSurfaceName = 45,
cudaErrorDevicesUnavailable = 46,
cudaErrorInvalidKernelImage = 47,
cudaErrorNoKernelImageForDevice = 48,
cudaErrorIncompatibleDriverContext = 49,
cudaErrorPeerAccessAlreadyEnabled = 50,
cudaErrorPeerAccessNotEnabled = 51,
cudaErrorDeviceAlreadyInUse = 54,
cudaErrorProfilerDisabled = 55,
cudaErrorProfilerNotInitialized = 56,
cudaErrorProfilerAlreadyStarted = 57,
cudaErrorProfilerAlreadyStopped = 58,
cudaErrorAssert = 59,
cudaErrorTooManyPeers = 60,
cudaErrorHostMemoryAlreadyRegistered = 61,
cudaErrorHostMemoryNotRegistered = 62,
cudaErrorStartupFailure = 0x7f,
cudaErrorApiFailureBase = 10000 }
• enum cudaFuncCache {
    cudaFuncCachePreferNone = 0,
    cudaFuncCachePreferShared = 1,
    cudaFuncCachePreferL1 = 2,
    cudaFuncCachePreferEqual = 3 }
```

- enum `cudaGraphicsCubeFace` {
`cudaGraphicsCubeFacePositiveX` = 0x00,
`cudaGraphicsCubeFaceNegativeX` = 0x01,
`cudaGraphicsCubeFacePositiveY` = 0x02,
`cudaGraphicsCubeFaceNegativeY` = 0x03,
`cudaGraphicsCubeFacePositiveZ` = 0x04,
`cudaGraphicsCubeFaceNegativeZ` = 0x05 }
- enum `cudaGraphicsMapFlags` {
`cudaGraphicsMapFlagsNone` = 0,
`cudaGraphicsMapFlagsReadOnly` = 1,
`cudaGraphicsMapFlagsWriteDiscard` = 2 }
- enum `cudaGraphicsRegisterFlags` {
`cudaGraphicsRegisterFlagsNone` = 0,
`cudaGraphicsRegisterFlagsReadOnly` = 1,
`cudaGraphicsRegisterFlagsWriteDiscard` = 2,
`cudaGraphicsRegisterFlagsSurfaceLoadStore` = 4,
`cudaGraphicsRegisterFlagsTextureGather` = 8 }
- enum `cudaLimit` {
`cudaLimitStackSize` = 0x00,
`cudaLimitPrintfFifoSize` = 0x01,
`cudaLimitMallocHeapSize` = 0x02 }
- enum `cudaMemcpyKind` {
`cudaMemcpyHostToHost` = 0,
`cudaMemcpyHostToDevice` = 1,
`cudaMemcpyDeviceToHost` = 2,
`cudaMemcpyDeviceToDevice` = 3,
`cudaMemcpyDefault` = 4 }
- enum `cudaMemoryType` {
`cudaMemoryTypeHost` = 1,
`cudaMemoryTypeDevice` = 2 }
- enum `cudaOutputMode` {
`cudaKeyValuePair` = 0x00,
`cudaCSV` = 0x01 }
- typedef enum `cudaError` `cudaError_t`
- typedef struct CUevent_st * `cudaEvent_t`
- typedef struct cudaGraphicsResource * `cudaGraphicsResource_t`
- typedef struct cudaIpcEventHandle_st `cudaIpcEventHandle_t`
- typedef struct cudaIpcMemHandle_st `cudaIpcMemHandle_t`
- typedef enum `cudaOutputMode` `cudaOutputMode_t`
- typedef struct CUstream_st * `cudaStream_t`
- typedef struct CUuuid_st `cudaUUID_t`
- #define `CUDA_IPC_HANDLE_SIZE` 64
- #define `cudaArrayCubemap` 0x04
- #define `cudaArrayDefault` 0x00

- `#define cudaArrayLayered 0x01`
- `#define cudaArraySurfaceLoadStore 0x02`
- `#define cudaArrayTextureGather 0x08`
- `#define cudaDeviceBlockingSync 0x04`
- `#define cudaDeviceLmemResizeToMax 0x10`
- `#define cudaDeviceMapHost 0x08`
- `#define cudaDeviceMask 0x1f`
- `#define cudaDevicePropDontCare`
- `#define cudaDeviceScheduleAuto 0x00`
- `#define cudaDeviceScheduleBlockingSync 0x04`
- `#define cudaDeviceScheduleMask 0x07`
- `#define cudaDeviceScheduleSpin 0x01`
- `#define cudaDeviceScheduleYield 0x02`
- `#define cudaEventBlockingSync 0x01`
- `#define cudaEventDefault 0x00`
- `#define cudaEventDisableTiming 0x02`
- `#define cudaEventInterprocess 0x04`
- `#define cudaHostAllocDefault 0x00`
- `#define cudaHostAllocMapped 0x02`
- `#define cudaHostAllocPortable 0x01`
- `#define cudaHostAllocWriteCombined 0x04`
- `#define cudaHostRegisterDefault 0x00`
- `#define cudaHostRegisterMapped 0x02`
- `#define cudaHostRegisterPortable 0x01`
- `#define cudaPeerAccessDefault 0x00`

4.26.1 Define Documentation

4.26.1.1 `#define CUDA_IPC_HANDLE_SIZE 64`

CUDA Interprocess types

4.26.1.2 `#define cudaArrayCubemap 0x04`

Must be set in `cudaMalloc3DArray` to create a cubemap CUDA array

4.26.1.3 `#define cudaArrayDefault 0x00`

Default CUDA array allocation flag

4.26.1.4 `#define cudaArrayLayered 0x01`

Must be set in `cudaMalloc3DArray` to create a layered CUDA array

4.26.1.5 `#define cudaArraySurfaceLoadStore 0x02`

Must be set in `cudaMallocArray` or `cudaMalloc3DArray` in order to bind surfaces to the CUDA array

4.26.1.6 **#define cudaArrayTextureGather 0x08**

Must be set in `cudaMallocArray` or `cudaMalloc3DArray` in order to perform texture gather operations on the CUDA array

4.26.1.7 **#define cudaDeviceBlockingSync 0x04**

Device flag - Use blocking synchronization

Deprecated

This flag was deprecated as of CUDA 4.0 and replaced with [cudaDeviceScheduleBlockingSync](#).

4.26.1.8 **#define cudaDeviceLmemResizeToMax 0x10**

Device flag - Keep local memory allocation after launch

4.26.1.9 **#define cudaDeviceMapHost 0x08**

Device flag - Support mapped pinned allocations

4.26.1.10 **#define cudaDeviceMask 0x1f**

Device flags mask

4.26.1.11 **#define cudaDevicePropDontCare**

Empty device properties

4.26.1.12 **#define cudaDeviceScheduleAuto 0x00**

Device flag - Automatic scheduling

4.26.1.13 **#define cudaDeviceScheduleBlockingSync 0x04**

Device flag - Use blocking synchronization

4.26.1.14 **#define cudaDeviceScheduleMask 0x07**

Device schedule flags mask

4.26.1.15 **#define cudaDeviceScheduleSpin 0x01**

Device flag - Spin default scheduling

4.26.1.16 #define cudaDeviceScheduleYield 0x02

Device flag - Yield default scheduling

4.26.1.17 #define cudaEventBlockingSync 0x01

Event uses blocking synchronization

4.26.1.18 #define cudaEventDefault 0x00

Default event flag

4.26.1.19 #define cudaEventDisableTiming 0x02

Event will not record timing data

4.26.1.20 #define cudaEventInterprocess 0x04

Event is suitable for interprocess use. cudaEventDisableTiming must be set

4.26.1.21 #define cudaHostAllocDefault 0x00

Default page-locked allocation flag

4.26.1.22 #define cudaHostAllocMapped 0x02

Map allocation into device space

4.26.1.23 #define cudaHostAllocPortable 0x01

Pinned memory accessible by all CUDA contexts

4.26.1.24 #define cudaHostAllocWriteCombined 0x04

Write-combined memory

4.26.1.25 #define cudaHostRegisterDefault 0x00

Default host memory registration flag

4.26.1.26 #define cudaHostRegisterMapped 0x02

Map registered memory into device space

4.26.1.27 #define cudaHostRegisterPortable 0x01

Pinned memory accessible by all CUDA contexts

4.26.1.28 `#define cudaPeerAccessDefault 0x00`

Default peer addressing enable flag

4.26.2 Typedef Documentation

4.26.2.1 `typedef enum cudaError cudaError_t`

CUDA Error types

4.26.2.2 `typedef struct CUevent_st* cudaEvent_t`

CUDA event types

4.26.2.3 `typedef struct cudaGraphicsResource* cudaGraphicsResource_t`

CUDA graphics resource types

4.26.2.4 `typedef struct cudaIpcEventHandle_st cudaIpcEventHandle_t`

Interprocess Handles

4.26.2.5 `typedef enum cudaOutputMode cudaOutputMode_t`

CUDA output file modes

4.26.2.6 `typedef struct CUstream_st* cudaStream_t`

CUDA stream

4.26.2.7 `typedef struct CUuuid_st cudaUUID_t`

CUDA UUID types

4.26.3 Enumeration Type Documentation

4.26.3.1 `enum cudaChannelFormatKind`

Channel format kind

Enumerator:

- cudaChannelFormatKindSigned* Signed channel format
- cudaChannelFormatKindUnsigned* Unsigned channel format
- cudaChannelFormatKindFloat* Float channel format
- cudaChannelFormatKindNone* No channel format

4.26.3.2 enum cudaComputeMode

CUDA device compute modes

Enumerator:

cudaComputeModeDefault Default compute mode (Multiple threads can use [cudaSetDevice\(\)](#) with this device)

cudaComputeModeExclusive Compute-exclusive-thread mode (Only one thread in one process will be able to use [cudaSetDevice\(\)](#) with this device)

cudaComputeModeProhibited Compute-prohibited mode (No threads can use [cudaSetDevice\(\)](#) with this device)

cudaComputeModeExclusiveProcess Compute-exclusive-process mode (Many threads in one process will be able to use [cudaSetDevice\(\)](#) with this device)

4.26.3.3 enum cudaError

CUDA error types

Enumerator:

cudaSuccess The API call returned with no errors. In the case of query calls, this can also mean that the operation being queried is complete (see [cudaEventQuery\(\)](#) and [cudaStreamQuery\(\)](#)).

cudaErrorMissingConfiguration The device function being invoked (usually via [cudaLaunch\(\)](#)) was not previously configured via the [cudaConfigureCall\(\)](#) function.

cudaErrorMemoryAllocation The API call failed because it was unable to allocate enough memory to perform the requested operation.

cudaErrorInitializationError The API call failed because the CUDA driver and runtime could not be initialized.

cudaErrorLaunchFailure An exception occurred on the device while executing a kernel. Common causes include dereferencing an invalid device pointer and accessing out of bounds shared memory. The device cannot be used until [cudaThreadExit\(\)](#) is called. All existing device memory allocations are invalid and must be reconstructed if the program is to continue using CUDA.

cudaErrorPriorLaunchFailure This indicated that a previous kernel launch failed. This was previously used for device emulation of kernel launches.

Deprecated

This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

cudaErrorLaunchTimeout This indicates that the device kernel took too long to execute. This can only occur if timeouts are enabled - see the device property [kernelExecTimeoutEnabled](#) for more information. The device cannot be used until [cudaThreadExit\(\)](#) is called. All existing device memory allocations are invalid and must be reconstructed if the program is to continue using CUDA.

cudaErrorLaunchOutOfResources This indicates that a launch did not occur because it did not have appropriate resources. Although this error is similar to [cudaErrorInvalidConfiguration](#), this error usually indicates that the user has attempted to pass too many arguments to the device kernel, or the kernel launch specifies too many threads for the kernel's register count.

cudaErrorInvalidDeviceFunction The requested device function does not exist or is not compiled for the proper device architecture.

cudaErrorInvalidConfiguration This indicates that a kernel launch is requesting resources that can never be satisfied by the current device. Requesting more shared memory per block than the device supports will trigger this error, as will requesting too many threads or blocks. See [cudaDeviceProp](#) for more device limitations.

cudaErrorInvalidDevice This indicates that the device ordinal supplied by the user does not correspond to a valid CUDA device.

cudaErrorInvalidValue This indicates that one or more of the parameters passed to the API call is not within an acceptable range of values.

cudaErrorInvalidPitchValue This indicates that one or more of the pitch-related parameters passed to the API call is not within the acceptable range for pitch.

cudaErrorInvalidSymbol This indicates that the symbol name/identifier passed to the API call is not a valid name or identifier.

cudaErrorMapBufferObjectFailed This indicates that the buffer object could not be mapped.

cudaErrorUnmapBufferObjectFailed This indicates that the buffer object could not be unmapped.

cudaErrorInvalidHostPointer This indicates that at least one host pointer passed to the API call is not a valid host pointer.

cudaErrorInvalidDevicePointer This indicates that at least one device pointer passed to the API call is not a valid device pointer.

cudaErrorInvalidTexture This indicates that the texture passed to the API call is not a valid texture.

cudaErrorInvalidTextureBinding This indicates that the texture binding is not valid. This occurs if you call [cudaGetTextureAlignmentOffset\(\)](#) with an unbound texture.

cudaErrorInvalidChannelDescriptor This indicates that the channel descriptor passed to the API call is not valid. This occurs if the format is not one of the formats specified by [cudaChannelFormatKind](#), or if one of the dimensions is invalid.

cudaErrorInvalidMemcpyDirection This indicates that the direction of the memcpy passed to the API call is not one of the types specified by [cudaMemcpyKind](#).

cudaErrorAddressOfConstant This indicated that the user has taken the address of a constant variable, which was forbidden up until the CUDA 3.1 release.

Deprecated

This error return is deprecated as of CUDA 3.1. Variables in constant memory may now have their address taken by the runtime via [cudaGetSymbolAddress\(\)](#).

cudaErrorTextureFetchFailed This indicated that a texture fetch was not able to be performed. This was previously used for device emulation of texture operations.

Deprecated

This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

cudaErrorTextureNotBound This indicated that a texture was not bound for access. This was previously used for device emulation of texture operations.

Deprecated

This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

cudaErrorSynchronizationError This indicated that a synchronization operation had failed. This was previously used for some device emulation functions.

Deprecated

This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

cudaErrorInvalidFilterSetting This indicates that a non-float texture was being accessed with linear filtering. This is not supported by CUDA.

cudaErrorInvalidNormSetting This indicates that an attempt was made to read a non-float texture as a normalized float. This is not supported by CUDA.

cudaErrorMixedDeviceExecution Mixing of device and device emulation code was not allowed.

Deprecated

This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

cudaErrorCudartUnloading This indicates that a CUDA Runtime API call cannot be executed because it is being called during process shut down, at a point in time after CUDA driver has been unloaded.

cudaErrorUnknown This indicates that an unknown internal error has occurred.

cudaErrorNotYetImplemented This indicates that the API call is not yet implemented. Production releases of CUDA will never return this error.

Deprecated

This error return is deprecated as of CUDA 4.1.

cudaErrorMemoryValueTooLarge This indicated that an emulated device pointer exceeded the 32-bit address range.

Deprecated

This error return is deprecated as of CUDA 3.1. Device emulation mode was removed with the CUDA 3.1 release.

cudaErrorInvalidResourceHandle This indicates that a resource handle passed to the API call was not valid. Resource handles are opaque types like [cudaStream_t](#) and [cudaEvent_t](#).

cudaErrorNotReady This indicates that asynchronous operations issued previously have not completed yet. This result is not actually an error, but must be indicated differently than [cudaSuccess](#) (which indicates completion). Calls that may return this value include [cudaEventQuery\(\)](#) and [cudaStreamQuery\(\)](#).

cudaErrorInsufficientDriver This indicates that the installed NVIDIA CUDA driver is older than the CUDA runtime library. This is not a supported configuration. Users should install an updated NVIDIA display driver to allow the application to run.

cudaErrorSetOnActiveProcess This indicates that the user has called [cudaSetValidDevices\(\)](#), [cudaSetDeviceFlags\(\)](#), [cudaD3D9SetDirect3DDevice\(\)](#), [cudaD3D10SetDirect3DDevice\(\)](#), [cudaD3D11SetDirect3DDevice\(\)](#), or [cudaVDPAUSetVDPAUDevice\(\)](#) after initializing the CUDA runtime by calling non-device management operations (allocating memory and launching kernels are examples of non-device management operations). This error can also be returned if using runtime/driver interoperability and there is an existing [CUcontext](#) active on the host thread.

cudaErrorInvalidSurface This indicates that the surface passed to the API call is not a valid surface.

cudaErrorNoDevice This indicates that no CUDA-capable devices were detected by the installed CUDA driver.

cudaErrorECCUncorrectable This indicates that an uncorrectable ECC error was detected during execution.

cudaErrorSharedObjectSymbolNotFound This indicates that a link to a shared object failed to resolve.

cudaErrorSharedObjectInitFailed This indicates that initialization of a shared object failed.

cudaErrorUnsupportedLimit This indicates that the [cudaLimit](#) passed to the API call is not supported by the active device.

cudaErrorDuplicateVariableName This indicates that multiple global or constant variables (across separate CUDA source files in the application) share the same string name.

cudaErrorDuplicateTextureName This indicates that multiple textures (across separate CUDA source files in the application) share the same string name.

- cudaErrorDuplicateSurfaceName*** This indicates that multiple surfaces (across separate CUDA source files in the application) share the same string name.
- cudaErrorDevicesUnavailable*** This indicates that all CUDA devices are busy or unavailable at the current time. Devices are often busy/unavailable due to use of [cudaComputeModeExclusive](#), [cudaComputeModeProhibited](#) or when long running CUDA kernels have filled up the GPU and are blocking new work from starting. They can also be unavailable due to memory constraints on a device that already has active CUDA work being performed.
- cudaErrorInvalidKernelImage*** This indicates that the device kernel image is invalid.
- cudaErrorNoKernelImageForDevice*** This indicates that there is no kernel image available that is suitable for the device. This can occur when a user specifies code generation options for a particular CUDA source file that do not include the corresponding device configuration.
- cudaErrorIncompatibleDriverContext*** This indicates that the current context is not compatible with this the CUDA Runtime. This can only occur if you are using CUDA Runtime/Driver interoperability and have created an existing Driver context using the driver API. The Driver context may be incompatible either because the Driver context was created using an older version of the API, because the Runtime API call expects a primary driver context and the Driver context is not primary, or because the Driver context has been destroyed. Please see [Interactions](#) with the CUDA Driver API" for more information.
- cudaErrorPeerAccessAlreadyEnabled*** This error indicates that a call to [cudaDeviceEnablePeerAccess\(\)](#) is trying to re-enable peer addressing on from a context which has already had peer addressing enabled.
- cudaErrorPeerAccessNotEnabled*** This error indicates that [cudaDeviceDisablePeerAccess\(\)](#) is trying to disable peer addressing which has not been enabled yet via [cudaDeviceEnablePeerAccess\(\)](#).
- cudaErrorDeviceAlreadyInUse*** This indicates that a call tried to access an exclusive-thread device that is already in use by a different thread.
- cudaErrorProfilerDisabled*** This indicates profiler has been disabled for this run and thus runtime APIs cannot be used to profile subsets of the program. This can happen when the application is running with external profiling tools like visual profiler.
- cudaErrorProfilerNotInitialized*** This indicates profiler has not been initialized yet. [cudaProfilerInitialize\(\)](#) must be called before calling [cudaProfilerStart](#) and [cudaProfilerStop](#) to initialize profiler.
- cudaErrorProfilerAlreadyStarted*** This indicates profiler is already started. This error can be returned if [cudaProfilerStart\(\)](#) is called multiple times without subsequent call to [cudaProfilerStop\(\)](#).
- cudaErrorProfilerAlreadyStopped*** This indicates profiler is already stopped. This error can be returned if [cudaProfilerStop\(\)](#) is called without starting profiler using [cudaProfilerStart\(\)](#).
- cudaErrorAssert*** An assert triggered in device code during kernel execution. The device cannot be used again until [cudaThreadExit\(\)](#) is called. All existing allocations are invalid and must be reconstructed if the program is to continue using CUDA.
- cudaErrorTooManyPeers*** This error indicates that the hardware resources required to enable peer access have been exhausted for one or more of the devices passed to [cudaEnablePeerAccess\(\)](#).
- cudaErrorHostMemoryAlreadyRegistered*** This error indicates that the memory range passed to [cudaHostRegister\(\)](#) has already been registered.
- cudaErrorHostMemoryNotRegistered*** This error indicates that the pointer passed to [cudaHostUnregister\(\)](#) does not correspond to any currently registered memory region.
- cudaErrorStartupFailure*** This indicates an internal startup failure in the CUDA runtime.
- cudaErrorApiFailureBase*** Any unhandled CUDA driver error is added to this value and returned via the runtime. Production releases of CUDA should not return such errors.
- Deprecated**

This error return is deprecated as of CUDA 4.1.

4.26.3.4 enum cudaFuncCache

CUDA function cache configurations

Enumerator:

cudaFuncCachePreferNone Default function cache configuration, no preference
cudaFuncCachePreferShared Prefer larger shared memory and smaller L1 cache
cudaFuncCachePreferL1 Prefer larger L1 cache and smaller shared memory
cudaFuncCachePreferEqual Prefer equal size L1 cache and shared memory

4.26.3.5 enum cudaGraphicsCubeFace

CUDA graphics interop array indices for cube maps

Enumerator:

cudaGraphicsCubeFacePositiveX Positive X face of cubemap
cudaGraphicsCubeFaceNegativeX Negative X face of cubemap
cudaGraphicsCubeFacePositiveY Positive Y face of cubemap
cudaGraphicsCubeFaceNegativeY Negative Y face of cubemap
cudaGraphicsCubeFacePositiveZ Positive Z face of cubemap
cudaGraphicsCubeFaceNegativeZ Negative Z face of cubemap

4.26.3.6 enum cudaGraphicsMapFlags

CUDA graphics interop map flags

Enumerator:

cudaGraphicsMapFlagsNone Default; Assume resource can be read/written
cudaGraphicsMapFlagsReadOnly CUDA will not write to this resource
cudaGraphicsMapFlagsWriteDiscard CUDA will only write to and will not read from this resource

4.26.3.7 enum cudaGraphicsRegisterFlags

CUDA graphics interop register flags

Enumerator:

cudaGraphicsRegisterFlagsNone Default
cudaGraphicsRegisterFlagsReadOnly CUDA will not write to this resource
cudaGraphicsRegisterFlagsWriteDiscard CUDA will only write to and will not read from this resource
cudaGraphicsRegisterFlagsSurfaceLoadStore CUDA will bind this resource to a surface reference
cudaGraphicsRegisterFlagsTextureGather CUDA will perform texture gather operations on this resource

4.26.3.8 enum cudaLimit

CUDA Limits

Enumerator:

cudaLimitStackSize GPU thread stack size
cudaLimitPrintfFifoSize GPU printf/fprintf FIFO size
cudaLimitMallocHeapSize GPU malloc heap size

4.26.3.9 enum cudaMemcpyKind

CUDA memory copy types

Enumerator:

cudaMemcpyHostToHost Host -> Host
cudaMemcpyHostToDevice Host -> Device
cudaMemcpyDeviceToHost Device -> Host
cudaMemcpyDeviceToDevice Device -> Device
cudaMemcpyDefault Default based unified virtual address space

4.26.3.10 enum cudaMemoryType

CUDA memory types

Enumerator:

cudaMemoryTypeHost Host memory
cudaMemoryTypeDevice Device memory

4.26.3.11 enum cudaOutputMode

CUDA Profiler Output modes

Enumerator:

cudaKeyValuePair Output mode Key-Value pair format.
cudaCSV Output mode Comma separated values format.

4.26.3.12 enum cudaSurfaceBoundaryMode

CUDA Surface boundary modes

Enumerator:

cudaBoundaryModeZero Zero boundary mode
cudaBoundaryModeClamp Clamp boundary mode
cudaBoundaryModeTrap Trap boundary mode

4.26.3.13 enum cudaSurfaceFormatMode

CUDA Surface format modes

Enumerator:

cudaFormatModeForced Forced format mode

cudaFormatModeAuto Auto format mode

4.26.3.14 enum cudaTextureAddressMode

CUDA texture address modes

Enumerator:

cudaAddressModeWrap Wrapping address mode

cudaAddressModeClamp Clamp to edge address mode

cudaAddressModeMirror Mirror address mode

cudaAddressModeBorder Border address mode

4.26.3.15 enum cudaTextureFilterMode

CUDA texture filter modes

Enumerator:

cudaFilterModePoint Point filter mode

cudaFilterModeLinear Linear filter mode

4.26.3.16 enum cudaTextureReadMode

CUDA texture read modes

Enumerator:

cudaReadModeElementType Read texture as specified element type

cudaReadModeNormalizedFloat Read texture as normalized float

4.27 CUDA Driver API

Modules

- [Data types used by CUDA driver](#)
- [Initialization](#)
- [Version Management](#)
- [Device Management](#)
- [Context Management](#)
- [Module Management](#)
- [Memory Management](#)
- [Unified Addressing](#)
- [Stream Management](#)
- [Event Management](#)
- [Execution Control](#)
- [Texture Reference Management](#)
- [Surface Reference Management](#)
- [Peer Context Memory Access](#)
- [Graphics Interoperability](#)
- [Profiler Control](#)
- [OpenGL Interoperability](#)
- [Direct3D 9 Interoperability](#)
- [Direct3D 10 Interoperability](#)
- [Direct3D 11 Interoperability](#)
- [VDPAU Interoperability](#)

4.27.1 Detailed Description

This section describes the low-level CUDA driver application programming interface.

4.28 Data types used by CUDA driver

Data Structures

- struct [CUDA_ARRAY3D_DESCRIPTOR_st](#)
- struct [CUDA_ARRAY_DESCRIPTOR_st](#)
- struct [CUDA_MEMCPY2D_st](#)
- struct [CUDA_MEMCPY3D_PEER_st](#)
- struct [CUDA_MEMCPY3D_st](#)
- struct [CUdevprop_st](#)

Defines

- `#define` [CU_IPC_HANDLE_SIZE](#) 64
- `#define` [CU_LAUNCH_PARAM_BUFFER_POINTER](#) ((void*)0x01)
- `#define` [CU_LAUNCH_PARAM_BUFFER_SIZE](#) ((void*)0x02)
- `#define` [CU_LAUNCH_PARAM_END](#) ((void*)0x00)
- `#define` [CU_MEMHOSTALLOC_DEVICEMAP](#) 0x02
- `#define` [CU_MEMHOSTALLOC_PORTABLE](#) 0x01
- `#define` [CU_MEMHOSTALLOC_WRITECOMBINED](#) 0x04
- `#define` [CU_MEMHOSTREGISTER_DEVICEMAP](#) 0x02
- `#define` [CU_MEMHOSTREGISTER_PORTABLE](#) 0x01
- `#define` [CU_PARAM_TR_DEFAULT](#) -1
- `#define` [CU_TRSA_OVERRIDE_FORMAT](#) 0x01
- `#define` [CU_TRSF_NORMALIZED_COORDINATES](#) 0x02
- `#define` [CU_TRSF_READ_AS_INTEGER](#) 0x01
- `#define` [CU_TRSF_SRGB](#) 0x10
- `#define` [CUDA_ARRAY3D_2DARRAY](#) 0x01
- `#define` [CUDA_ARRAY3D_CUBEMAP](#) 0x04
- `#define` [CUDA_ARRAY3D_LAYERED](#) 0x01
- `#define` [CUDA_ARRAY3D_SURFACE_LDST](#) 0x02
- `#define` [CUDA_ARRAY3D_TEXTURE_GATHER](#) 0x08
- `#define` [CUDA_VERSION](#) 4010

Typedefs

- typedef enum [CUaddress_mode_enum](#) [CUaddress_mode](#)
- typedef struct [CUarray_st](#) * [CUarray](#)
- typedef enum [CUarray_cubemap_face_enum](#) [CUarray_cubemap_face](#)
- typedef enum [CUarray_format_enum](#) [CUarray_format](#)
- typedef enum [CUcomputemode_enum](#) [CUcomputemode](#)
- typedef struct [CUctx_st](#) * [CUcontext](#)
- typedef enum [CUctx_flags_enum](#) [CUctx_flags](#)
- typedef struct [CUDA_ARRAY3D_DESCRIPTOR_st](#) [CUDA_ARRAY3D_DESCRIPTOR](#)
- typedef struct [CUDA_ARRAY_DESCRIPTOR_st](#) [CUDA_ARRAY_DESCRIPTOR](#)
- typedef struct [CUDA_MEMCPY2D_st](#) [CUDA_MEMCPY2D](#)
- typedef struct [CUDA_MEMCPY3D_st](#) [CUDA_MEMCPY3D](#)
- typedef struct [CUDA_MEMCPY3D_PEER_st](#) [CUDA_MEMCPY3D_PEER](#)
- typedef int [CUdevice](#)

- typedef enum [CUdevice_attribute_enum](#) [CUdevice_attribute](#)
- typedef unsigned int [CUdeviceptr](#)
- typedef struct [CUdevprop_st](#) [CUdevprop](#)
- typedef struct [CUevent_st](#) * [CUevent](#)
- typedef enum [CUevent_flags_enum](#) [CUevent_flags](#)
- typedef enum [CUfilter_mode_enum](#) [CUfilter_mode](#)
- typedef enum [CUfunc_cache_enum](#) [CUfunc_cache](#)
- typedef struct [CUfunc_st](#) * [CUfunction](#)
- typedef enum [CUfunction_attribute_enum](#) [CUfunction_attribute](#)
- typedef enum [CUgraphicsMapResourceFlags_enum](#) [CUgraphicsMapResourceFlags](#)
- typedef enum [CUgraphicsRegisterFlags_enum](#) [CUgraphicsRegisterFlags](#)
- typedef struct [CUgraphicsResource_st](#) * [CUgraphicsResource](#)
- typedef enum [CUjit_fallback_enum](#) [CUjit_fallback](#)
- typedef enum [CUjit_option_enum](#) [CUjit_option](#)
- typedef enum [CUjit_target_enum](#) [CUjit_target](#)
- typedef enum [CUlimit_enum](#) [CUlimit](#)
- typedef enum [CUmemorytype_enum](#) [CUmemorytype](#)
- typedef struct [CUmod_st](#) * [CUmodule](#)
- typedef enum [CUpointer_attribute_enum](#) [CUpointer_attribute](#)
- typedef enum [cudaError_enum](#) [CUresult](#)
- typedef struct [CUstream_st](#) * [CUstream](#)
- typedef struct [CUSurfref_st](#) * [CUSurfref](#)
- typedef struct [CUTexref_st](#) * [CUTexref](#)

Enumerations

- enum [CUaddress_mode_enum](#) {
[CU_TR_ADDRESS_MODE_WRAP](#) = 0,
[CU_TR_ADDRESS_MODE_CLAMP](#) = 1,
[CU_TR_ADDRESS_MODE_MIRROR](#) = 2,
[CU_TR_ADDRESS_MODE_BORDER](#) = 3 }
- enum [CUarray_cubemap_face_enum](#) {
[CU_CUBEMAP_FACE_POSITIVE_X](#) = 0x00,
[CU_CUBEMAP_FACE_NEGATIVE_X](#) = 0x01,
[CU_CUBEMAP_FACE_POSITIVE_Y](#) = 0x02,
[CU_CUBEMAP_FACE_NEGATIVE_Y](#) = 0x03,
[CU_CUBEMAP_FACE_POSITIVE_Z](#) = 0x04,
[CU_CUBEMAP_FACE_NEGATIVE_Z](#) = 0x05 }
- enum [CUarray_format_enum](#) {
[CU_AD_FORMAT_UNSIGNED_INT8](#) = 0x01,
[CU_AD_FORMAT_UNSIGNED_INT16](#) = 0x02,
[CU_AD_FORMAT_UNSIGNED_INT32](#) = 0x03,
[CU_AD_FORMAT_SIGNED_INT8](#) = 0x08,
[CU_AD_FORMAT_SIGNED_INT16](#) = 0x09,
[CU_AD_FORMAT_SIGNED_INT32](#) = 0x0a,
[CU_AD_FORMAT_HALF](#) = 0x10,
[CU_AD_FORMAT_FLOAT](#) = 0x20 }

- enum CUcomputemode_enum {
CU_COMPUTEMODE_DEFAULT = 0,
CU_COMPUTEMODE_EXCLUSIVE = 1,
CU_COMPUTEMODE_PROHIBITED = 2,
CU_COMPUTEMODE_EXCLUSIVE_PROCESS = 3 }
- enum CUctx_flags_enum {
CU_CTX_SCHED_AUTO = 0x00,
CU_CTX_SCHED_SPIN = 0x01,
CU_CTX_SCHED_YIELD = 0x02,
CU_CTX_SCHED_BLOCKING_SYNC = 0x04,
CU_CTX_BLOCKING_SYNC = 0x04 ,
CU_CTX_MAP_HOST = 0x08,
CU_CTX_LMEM_RESIZE_TO_MAX = 0x10 }
- enum cudaError_enum {
CUDA_SUCCESS = 0,
CUDA_ERROR_INVALID_VALUE = 1,
CUDA_ERROR_OUT_OF_MEMORY = 2,
CUDA_ERROR_NOT_INITIALIZED = 3,
CUDA_ERROR_DEINITIALIZED = 4,
CUDA_ERROR_PROFILER_DISABLED = 5,
CUDA_ERROR_PROFILER_NOT_INITIALIZED = 6,
CUDA_ERROR_PROFILER_ALREADY_STARTED = 7,
CUDA_ERROR_PROFILER_ALREADY_STOPPED = 8,
CUDA_ERROR_NO_DEVICE = 100,
CUDA_ERROR_INVALID_DEVICE = 101,
CUDA_ERROR_INVALID_IMAGE = 200,
CUDA_ERROR_INVALID_CONTEXT = 201,
CUDA_ERROR_CONTEXT_ALREADY_CURRENT = 202,
CUDA_ERROR_MAP_FAILED = 205,
CUDA_ERROR_UNMAP_FAILED = 206,
CUDA_ERROR_ARRAY_IS_MAPPED = 207,
CUDA_ERROR_ALREADY_MAPPED = 208,
CUDA_ERROR_NO_BINARY_FOR_GPU = 209,
CUDA_ERROR_ALREADY_ACQUIRED = 210,
CUDA_ERROR_NOT_MAPPED = 211,
CUDA_ERROR_NOT_MAPPED_AS_ARRAY = 212,
CUDA_ERROR_NOT_MAPPED_AS_POINTER = 213,
CUDA_ERROR_ECC_UNCORRECTABLE = 214,
CUDA_ERROR_UNSUPPORTED_LIMIT = 215,
CUDA_ERROR_CONTEXT_ALREADY_IN_USE = 216,
CUDA_ERROR_INVALID_SOURCE = 300,

```

CUDA_ERROR_FILE_NOT_FOUND = 301,
CUDA_ERROR_SHARED_OBJECT_SYMBOL_NOT_FOUND = 302,
CUDA_ERROR_SHARED_OBJECT_INIT_FAILED = 303,
CUDA_ERROR_OPERATING_SYSTEM = 304,
CUDA_ERROR_INVALID_HANDLE = 400,
CUDA_ERROR_NOT_FOUND = 500,
CUDA_ERROR_NOT_READY = 600,
CUDA_ERROR_LAUNCH_FAILED = 700,
CUDA_ERROR_LAUNCH_OUT_OF_RESOURCES = 701,
CUDA_ERROR_LAUNCH_TIMEOUT = 702,
CUDA_ERROR_LAUNCH_INCOMPATIBLE_TEXTURING = 703,
CUDA_ERROR_PEER_ACCESS_ALREADY_ENABLED = 704,
CUDA_ERROR_PEER_ACCESS_NOT_ENABLED = 705,
CUDA_ERROR_PRIMARY_CONTEXT_ACTIVE = 708,
CUDA_ERROR_CONTEXT_IS_DESTROYED = 709,
CUDA_ERROR_ASSERT = 710,
CUDA_ERROR_TOO_MANY_PEERS = 711,
CUDA_ERROR_HOST_MEMORY_ALREADY_REGISTERED = 712,
CUDA_ERROR_HOST_MEMORY_NOT_REGISTERED = 713,
CUDA_ERROR_UNKNOWN = 999 }
• enum CUdevice_attribute_enum {
    CU_DEVICE_ATTRIBUTE_MAX_THREADS_PER_BLOCK = 1,
    CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_X = 2,
    CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_Y = 3,
    CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_Z = 4,
    CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_X = 5,
    CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_Y = 6,
    CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_Z = 7,
    CU_DEVICE_ATTRIBUTE_MAX_SHARED_MEMORY_PER_BLOCK = 8,
    CU_DEVICE_ATTRIBUTE_SHARED_MEMORY_PER_BLOCK = 8,
    CU_DEVICE_ATTRIBUTE_TOTAL_CONSTANT_MEMORY = 9,
    CU_DEVICE_ATTRIBUTE_WARP_SIZE = 10,
    CU_DEVICE_ATTRIBUTE_MAX_PITCH = 11,
    CU_DEVICE_ATTRIBUTE_MAX_REGISTERS_PER_BLOCK = 12,
    CU_DEVICE_ATTRIBUTE_REGISTERS_PER_BLOCK = 12,
    CU_DEVICE_ATTRIBUTE_CLOCK_RATE = 13,
    CU_DEVICE_ATTRIBUTE_TEXTURE_ALIGNMENT = 14,
    CU_DEVICE_ATTRIBUTE_GPU_OVERLAP = 15,
    CU_DEVICE_ATTRIBUTE_MULTIPROCESSOR_COUNT = 16,
    CU_DEVICE_ATTRIBUTE_KERNEL_EXEC_TIMEOUT = 17,
    CU_DEVICE_ATTRIBUTE_INTEGRATED = 18,

```

```
CU_DEVICE_ATTRIBUTE_CAN_MAP_HOST_MEMORY = 19,  
CU_DEVICE_ATTRIBUTE_COMPUTE_MODE = 20,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_WIDTH = 21,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_WIDTH = 22,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_HEIGHT = 23,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_WIDTH = 24,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_HEIGHT = 25,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_DEPTH = 26,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_WIDTH = 27,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_HEIGHT = 28,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_LAYERS = 29,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_ARRAY_WIDTH = 27,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_ARRAY_HEIGHT = 28,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_ARRAY_NUMSLICES = 29,  
CU_DEVICE_ATTRIBUTE_SURFACE_ALIGNMENT = 30,  
CU_DEVICE_ATTRIBUTE_CONCURRENT_KERNELS = 31,  
CU_DEVICE_ATTRIBUTE_ECC_ENABLED = 32,  
CU_DEVICE_ATTRIBUTE_PCI_BUS_ID = 33,  
CU_DEVICE_ATTRIBUTE_PCI_DEVICE_ID = 34,  
CU_DEVICE_ATTRIBUTE_TCC_DRIVER = 35,  
CU_DEVICE_ATTRIBUTE_MEMORY_CLOCK_RATE = 36,  
CU_DEVICE_ATTRIBUTE_GLOBAL_MEMORY_BUS_WIDTH = 37,  
CU_DEVICE_ATTRIBUTE_L2_CACHE_SIZE = 38,  
CU_DEVICE_ATTRIBUTE_MAX_THREADS_PER_MULTIPROCESSOR = 39,  
CU_DEVICE_ATTRIBUTE_ASYNC_ENGINE_COUNT = 40,  
CU_DEVICE_ATTRIBUTE_UNIFIED_ADDRESSING = 41,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_LAYERED_WIDTH = 42,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_LAYERED_LAYERS = 43,  
CU_DEVICE_ATTRIBUTE_CAN_TEX2D_GATHER = 44,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_GATHER_WIDTH = 45,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_GATHER_HEIGHT = 46,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_WIDTH_ALTERNATE = 47,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_HEIGHT_ALTERNATE = 48,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_DEPTH_ALTERNATE = 49,  
CU_DEVICE_ATTRIBUTE_PCI_DOMAIN_ID = 50,  
CU_DEVICE_ATTRIBUTE_TEXTURE_PITCH_ALIGNMENT = 51,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURECUBEMAP_WIDTH = 52,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURECUBEMAP_LAYERED_WIDTH = 53,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURECUBEMAP_LAYERED_LAYERS = 54,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_WIDTH = 55,  
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_WIDTH = 56,
```

```

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_HEIGHT = 57,
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_WIDTH = 58,
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_HEIGHT = 59,
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_DEPTH = 60,
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_LAYERED_WIDTH = 61,
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_LAYERED_LAYERS = 62,
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_WIDTH = 63,
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_HEIGHT = 64,
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_LAYERS = 65,
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACECUBEMAP_WIDTH = 66,
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACECUBEMAP_LAYERED_WIDTH = 67,
CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACECUBEMAP_LAYERED_LAYERS = 68,
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_LINEAR_WIDTH = 69,
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_WIDTH = 70,
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_HEIGHT = 71,
CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_PITCH = 72 }
• enum CUevent_flags_enum {
    CU_EVENT_DEFAULT = 0x0,
    CU_EVENT_BLOCKING_SYNC = 0x1,
    CU_EVENT_DISABLE_TIMING = 0x2,
    CU_EVENT_INTERPROCESS = 0x4 }
• enum CUfilter_mode_enum {
    CU_TR_FILTER_MODE_POINT = 0,
    CU_TR_FILTER_MODE_LINEAR = 1 }
• enum CUfunc_cache_enum {
    CU_FUNC_CACHE_PREFER_NONE = 0x00,
    CU_FUNC_CACHE_PREFER_SHARED = 0x01,
    CU_FUNC_CACHE_PREFER_L1 = 0x02,
    CU_FUNC_CACHE_PREFER_EQUAL = 0x03 }
• enum CUfunction_attribute_enum {
    CU_FUNC_ATTRIBUTE_MAX_THREADS_PER_BLOCK = 0,
    CU_FUNC_ATTRIBUTE_SHARED_SIZE_BYTES = 1,
    CU_FUNC_ATTRIBUTE_CONST_SIZE_BYTES = 2,
    CU_FUNC_ATTRIBUTE_LOCAL_SIZE_BYTES = 3,
    CU_FUNC_ATTRIBUTE_NUM_REGS = 4,
    CU_FUNC_ATTRIBUTE_PTX_VERSION = 5,
    CU_FUNC_ATTRIBUTE_BINARY_VERSION = 6 }
• enum CUgraphicsMapResourceFlags_enum
• enum CUgraphicsRegisterFlags_enum
• enum CUjit_fallback_enum {
    CU_PREFER_PTX = 0,
    CU_PREFER_BINARY }

```

- `enum CUjit_option_enum {`
`CU_JIT_MAX_REGISTERS = 0,`
`CU_JIT_THREADS_PER_BLOCK,`
`CU_JIT_WALL_TIME,`
`CU_JIT_INFO_LOG_BUFFER,`
`CU_JIT_INFO_LOG_BUFFER_SIZE_BYTES,`
`CU_JIT_ERROR_LOG_BUFFER,`
`CU_JIT_ERROR_LOG_BUFFER_SIZE_BYTES,`
`CU_JIT_OPTIMIZATION_LEVEL,`
`CU_JIT_TARGET_FROM_CUCONTEXT,`
`CU_JIT_TARGET,`
`CU_JIT_FALLBACK_STRATEGY }`
- `enum CUjit_target_enum {`
`CU_TARGET_COMPUTE_10 = 0,`
`CU_TARGET_COMPUTE_11,`
`CU_TARGET_COMPUTE_12,`
`CU_TARGET_COMPUTE_13,`
`CU_TARGET_COMPUTE_20,`
`CU_TARGET_COMPUTE_21 }`
- `enum CUlimit_enum {`
`CU_LIMIT_STACK_SIZE = 0x00,`
`CU_LIMIT_PRINTF_FIFO_SIZE = 0x01,`
`CU_LIMIT_MALLOC_HEAP_SIZE = 0x02 }`
- `enum CUmemorytype_enum {`
`CU_MEMORYTYPE_HOST = 0x01,`
`CU_MEMORYTYPE_DEVICE = 0x02,`
`CU_MEMORYTYPE_ARRAY = 0x03,`
`CU_MEMORYTYPE_UNIFIED = 0x04 }`
- `enum CUpointer_attribute_enum {`
`CU_POINTER_ATTRIBUTE_CONTEXT = 1,`
`CU_POINTER_ATTRIBUTE_MEMORY_TYPE = 2,`
`CU_POINTER_ATTRIBUTE_DEVICE_POINTER = 3,`
`CU_POINTER_ATTRIBUTE_HOST_POINTER = 4 }`

4.28.1 Define Documentation

4.28.1.1 `#define CU_IPC_HANDLE_SIZE 64`

Interprocess Handles

4.28.1.2 `#define CU_LAUNCH_PARAM_BUFFER_POINTER ((void*)0x01)`

Indicator that the next value in the `extra` parameter to `cuLaunchKernel` will be a pointer to a buffer containing all kernel parameters used for launching kernel `f`. This buffer needs to honor all alignment/padding requirements of the individual parameters. If `CU_LAUNCH_PARAM_BUFFER_SIZE` is not also specified in the `extra` array, then `CU_LAUNCH_PARAM_BUFFER_POINTER` will have no effect.

4.28.1.3 `#define CU_LAUNCH_PARAM_BUFFER_SIZE ((void*)0x02)`

Indicator that the next value in the `extra` parameter to `cuLaunchKernel` will be a pointer to a `size_t` which contains the size of the buffer specified with `CU_LAUNCH_PARAM_BUFFER_POINTER`. It is required that `CU_LAUNCH_PARAM_BUFFER_POINTER` also be specified in the `extra` array if the value associated with `CU_LAUNCH_PARAM_BUFFER_SIZE` is not zero.

4.28.1.4 `#define CU_LAUNCH_PARAM_END ((void*)0x00)`

End of array terminator for the `extra` parameter to `cuLaunchKernel`

4.28.1.5 `#define CU_MEMHOSTALLOC_DEVICEMAP 0x02`

If set, host memory is mapped into CUDA address space and `cuMemHostGetDevicePointer()` may be called on the host pointer. Flag for `cuMemHostAlloc()`

4.28.1.6 `#define CU_MEMHOSTALLOC_PORTABLE 0x01`

If set, host memory is portable between CUDA contexts. Flag for `cuMemHostAlloc()`

4.28.1.7 `#define CU_MEMHOSTALLOC_WRITECOMBINED 0x04`

If set, host memory is allocated as write-combined - fast to write, faster to DMA, slow to read except via SSE4 streaming load instruction (MOVNTDQA). Flag for `cuMemHostAlloc()`

4.28.1.8 `#define CU_MEMHOSTREGISTER_DEVICEMAP 0x02`

If set, host memory is mapped into CUDA address space and `cuMemHostGetDevicePointer()` may be called on the host pointer. Flag for `cuMemHostRegister()`

4.28.1.9 `#define CU_MEMHOSTREGISTER_PORTABLE 0x01`

If set, host memory is portable between CUDA contexts. Flag for `cuMemHostRegister()`

4.28.1.10 `#define CU_PARAM_TR_DEFAULT -1`

For texture references loaded into the module, use default texunit from texture reference.

4.28.1.11 `#define CU_TRSA_OVERRIDE_FORMAT 0x01`

Override the texref format with a format inferred from the array. Flag for `cuTexRefSetArray()`

4.28.1.12 #define CU_TRSF_NORMALIZED_COORDINATES 0x02

Use normalized texture coordinates in the range [0,1) instead of [0,dim). Flag for [cuTexRefSetFlags\(\)](#)

4.28.1.13 #define CU_TRSF_READ_AS_INTEGER 0x01

Read the texture as integers rather than promoting the values to floats in the range [0,1]. Flag for [cuTexRefSetFlags\(\)](#)

4.28.1.14 #define CU_TRSF_SRGB 0x10

Perform sRGB->linear conversion during texture read. Flag for [cuTexRefSetFlags\(\)](#)

4.28.1.15 #define CUDA_ARRAY3D_2DARRAY 0x01

Deprecated, use `CUDA_ARRAY3D_LAYERED`

4.28.1.16 #define CUDA_ARRAY3D_CUBEMAP 0x04

If set, the CUDA array is a collection of six 2D arrays, representing faces of a cube. The width of such a CUDA array must be equal to its height, and Depth must be six. If [CUDA_ARRAY3D_LAYERED](#) flag is also set, then the CUDA array is a collection of cubemaps and Depth must be a multiple of six.

4.28.1.17 #define CUDA_ARRAY3D_LAYERED 0x01

If set, the CUDA array is a collection of layers, where each layer is either a 1D or a 2D array and the Depth member of `CUDA_ARRAY3D_DESCRIPTOR` specifies the number of layers, not the depth of a 3D array.

4.28.1.18 #define CUDA_ARRAY3D_SURFACE_LDST 0x02

This flag must be set in order to bind a surface reference to the CUDA array

4.28.1.19 #define CUDA_ARRAY3D_TEXTURE_GATHER 0x08

This flag must be set in order to perform texture gather operations on a CUDA array.

4.28.1.20 #define CUDA_VERSION 4010

CUDA API version number

4.28.2 Typedef Documentation**4.28.2.1 typedef enum CUaddress_mode_enum CUaddress_mode**

Texture reference addressing modes

4.28.2.2 typedef struct CUarray_st* CUarray

CUDA array

4.28.2.3 typedef enum CUarray_cubemap_face_enum CUarray_cubemap_face

Array indices for cube faces

4.28.2.4 typedef enum CUarray_format_enum CUarray_format

Array formats

4.28.2.5 typedef enum CUcomputemode_enum CUcomputemode

Compute Modes

4.28.2.6 typedef struct CUctx_st* CUcontext

CUDA context

4.28.2.7 typedef enum CUctx_flags_enum CUctx_flags

Context creation flags

4.28.2.8 typedef struct CUDA_ARRAY3D_DESCRIPTOR_st CUDA_ARRAY3D_DESCRIPTOR

3D array descriptor

4.28.2.9 typedef struct CUDA_ARRAY_DESCRIPTOR_st CUDA_ARRAY_DESCRIPTOR

Array descriptor

4.28.2.10 typedef struct CUDA_MEMCPY2D_st CUDA_MEMCPY2D

2D memory copy parameters

4.28.2.11 typedef struct CUDA_MEMCPY3D_st CUDA_MEMCPY3D

3D memory copy parameters

4.28.2.12 typedef struct CUDA_MEMCPY3D_PEER_st CUDA_MEMCPY3D_PEER

3D memory cross-context copy parameters

4.28.2.13 typedef int CUdevice

CUDA device

4.28.2.14 typedef enum CUdevice_attribute_enum CUdevice_attribute

Device properties

4.28.2.15 typedef unsigned int CUdeviceptr

CUDA device pointer

4.28.2.16 typedef struct CUdevprop_st CUdevprop

Legacy device properties

4.28.2.17 typedef struct CUevent_st* CUevent

CUDA event

4.28.2.18 typedef enum CUevent_flags_enum CUevent_flags

Event creation flags

4.28.2.19 typedef enum CUfilter_mode_enum CUfilter_mode

Texture reference filtering modes

4.28.2.20 typedef enum CUfunc_cache_enum CUfunc_cache

Function cache configurations

4.28.2.21 typedef struct CUfunc_st* CUfunction

CUDA function

4.28.2.22 typedef enum CUfunction_attribute_enum CUfunction_attribute

Function properties

4.28.2.23 typedef enum CUgraphicsMapResourceFlags_enum CUgraphicsMapResourceFlags

Flags for mapping and unmapping interop resources

4.28.2.24 typedef enum CUgraphicsRegisterFlags_enum CUgraphicsRegisterFlags

Flags to register a graphics resource

4.28.2.25 typedef struct CUgraphicsResource_st* CUgraphicsResource

CUDA graphics interop resource

4.28.2.26 `typedef enum CUjit_fallback_enum CUjit_fallback`

Cubin matching fallback strategies

4.28.2.27 `typedef enum CUjit_option_enum CUjit_option`

Online compiler options

4.28.2.28 `typedef enum CUjit_target_enum CUjit_target`

Online compilation targets

4.28.2.29 `typedef enum CUlimit_enum CUlimit`

Limits

4.28.2.30 `typedef enum CUmemorytype_enum CUmemorytype`

Memory types

4.28.2.31 `typedef struct CUmod_st* CUmodule`

CUDA module

4.28.2.32 `typedef enum CUpointer_attribute_enum CUpointer_attribute`

Pointer information

4.28.2.33 `typedef enum cudaError_enum CUresult`

Error codes

4.28.2.34 `typedef struct CUstream_st* CUstream`

CUDA stream

4.28.2.35 `typedef struct CUsurfref_st* CUsurfref`

CUDA surface reference

4.28.2.36 `typedef struct CUTexref_st* CUTexref`

CUDA texture reference

4.28.3 Enumeration Type Documentation

4.28.3.1 enum CUaddress_mode_enum

Texture reference addressing modes

Enumerator:

CU_TR_ADDRESS_MODE_WRAP Wrapping address mode
CU_TR_ADDRESS_MODE_CLAMP Clamp to edge address mode
CU_TR_ADDRESS_MODE_MIRROR Mirror address mode
CU_TR_ADDRESS_MODE_BORDER Border address mode

4.28.3.2 enum CUarray_cubemap_face_enum

Array indices for cube faces

Enumerator:

CU_CUBEMAP_FACE_POSITIVE_X Positive X face of cubemap
CU_CUBEMAP_FACE_NEGATIVE_X Negative X face of cubemap
CU_CUBEMAP_FACE_POSITIVE_Y Positive Y face of cubemap
CU_CUBEMAP_FACE_NEGATIVE_Y Negative Y face of cubemap
CU_CUBEMAP_FACE_POSITIVE_Z Positive Z face of cubemap
CU_CUBEMAP_FACE_NEGATIVE_Z Negative Z face of cubemap

4.28.3.3 enum CUarray_format_enum

Array formats

Enumerator:

CU_AD_FORMAT_UNSIGNED_INT8 Unsigned 8-bit integers
CU_AD_FORMAT_UNSIGNED_INT16 Unsigned 16-bit integers
CU_AD_FORMAT_UNSIGNED_INT32 Unsigned 32-bit integers
CU_AD_FORMAT_SIGNED_INT8 Signed 8-bit integers
CU_AD_FORMAT_SIGNED_INT16 Signed 16-bit integers
CU_AD_FORMAT_SIGNED_INT32 Signed 32-bit integers
CU_AD_FORMAT_HALF 16-bit floating point
CU_AD_FORMAT_FLOAT 32-bit floating point

4.28.3.4 enum CUcomputemode_enum

Compute Modes

Enumerator:

CU_COMPUTEMODE_DEFAULT Default compute mode (Multiple contexts allowed per device)

CU_COMPUTEMODE_EXCLUSIVE Compute-exclusive-thread mode (Only one context used by a single thread can be present on this device at a time)

CU_COMPUTEMODE_PROHIBITED Compute-prohibited mode (No contexts can be created on this device at this time)

CU_COMPUTEMODE_EXCLUSIVE_PROCESS Compute-exclusive-process mode (Only one context used by a single process can be present on this device at a time)

4.28.3.5 enum CUctx_flags_enum

Context creation flags

Enumerator:

CU_CTX_SCHED_AUTO Automatic scheduling

CU_CTX_SCHED_SPIN Set spin as default scheduling

CU_CTX_SCHED_YIELD Set yield as default scheduling

CU_CTX_SCHED_BLOCKING_SYNC Set blocking synchronization as default scheduling

CU_CTX_BLOCKING_SYNC Set blocking synchronization as default scheduling

Deprecated

This flag was deprecated as of CUDA 4.0 and was replaced with [CU_CTX_SCHED_BLOCKING_SYNC](#).

CU_CTX_MAP_HOST Support mapped pinned allocations

CU_CTX_LMEM_RESIZE_TO_MAX Keep local memory allocation after launch

4.28.3.6 enum cudaError_enum

Error codes

Enumerator:

CUDA_SUCCESS The API call returned with no errors. In the case of query calls, this can also mean that the operation being queried is complete (see [cuEventQuery\(\)](#) and [cuStreamQuery\(\)](#)).

CUDA_ERROR_INVALID_VALUE This indicates that one or more of the parameters passed to the API call is not within an acceptable range of values.

CUDA_ERROR_OUT_OF_MEMORY The API call failed because it was unable to allocate enough memory to perform the requested operation.

CUDA_ERROR_NOT_INITIALIZED This indicates that the CUDA driver has not been initialized with [cuInit\(\)](#) or that initialization has failed.

CUDA_ERROR_DEINITIALIZED This indicates that the CUDA driver is in the process of shutting down.

CUDA_ERROR_PROFILER_DISABLED This indicates profiling APIs are called while application is running in visual profiler mode.

CUDA_ERROR_PROFILER_NOT_INITIALIZED This indicates profiling has not been initialized for this context. Call [cuProfilerInitialize\(\)](#) to resolve this.

CUDA_ERROR_PROFILER_ALREADY_STARTED This indicates profiler has already been started and probably [cuProfilerStart\(\)](#) is incorrectly called.

CUDA_ERROR_PROFILER_ALREADY_STOPPED This indicates profiler has already been stopped and probably [cuProfilerStop\(\)](#) is incorrectly called.

CUDA_ERROR_NO_DEVICE This indicates that no CUDA-capable devices were detected by the installed CUDA driver.

CUDA_ERROR_INVALID_DEVICE This indicates that the device ordinal supplied by the user does not correspond to a valid CUDA device.

CUDA_ERROR_INVALID_IMAGE This indicates that the device kernel image is invalid. This can also indicate an invalid CUDA module.

CUDA_ERROR_INVALID_CONTEXT This most frequently indicates that there is no context bound to the current thread. This can also be returned if the context passed to an API call is not a valid handle (such as a context that has had [cuCtxDestroy\(\)](#) invoked on it). This can also be returned if a user mixes different API versions (i.e. 3010 context with 3020 API calls). See [cuCtxGetApiVersion\(\)](#) for more details.

CUDA_ERROR_CONTEXT_ALREADY_CURRENT This indicates that the context being supplied as a parameter to the API call was already the active context.

Deprecated

This error return is deprecated as of CUDA 3.2. It is no longer an error to attempt to push the active context via [cuCtxPushCurrent\(\)](#).

CUDA_ERROR_MAP_FAILED This indicates that a map or register operation has failed.

CUDA_ERROR_UNMAP_FAILED This indicates that an unmap or unregister operation has failed.

CUDA_ERROR_ARRAY_IS_MAPPED This indicates that the specified array is currently mapped and thus cannot be destroyed.

CUDA_ERROR_ALREADY_MAPPED This indicates that the resource is already mapped.

CUDA_ERROR_NO_BINARY_FOR_GPU This indicates that there is no kernel image available that is suitable for the device. This can occur when a user specifies code generation options for a particular CUDA source file that do not include the corresponding device configuration.

CUDA_ERROR_ALREADY_ACQUIRED This indicates that a resource has already been acquired.

CUDA_ERROR_NOT_MAPPED This indicates that a resource is not mapped.

CUDA_ERROR_NOT_MAPPED_AS_ARRAY This indicates that a mapped resource is not available for access as an array.

CUDA_ERROR_NOT_MAPPED_AS_POINTER This indicates that a mapped resource is not available for access as a pointer.

CUDA_ERROR_ECC_UNCORRECTABLE This indicates that an uncorrectable ECC error was detected during execution.

CUDA_ERROR_UNSUPPORTED_LIMIT This indicates that the [CUlimit](#) passed to the API call is not supported by the active device.

CUDA_ERROR_CONTEXT_ALREADY_IN_USE This indicates that the [CUcontext](#) passed to the API call can only be bound to a single CPU thread at a time but is already bound to a CPU thread.

CUDA_ERROR_INVALID_SOURCE This indicates that the device kernel source is invalid.

CUDA_ERROR_FILE_NOT_FOUND This indicates that the file specified was not found.

CUDA_ERROR_SHARED_OBJECT_SYMBOL_NOT_FOUND This indicates that a link to a shared object failed to resolve.

CUDA_ERROR_SHARED_OBJECT_INIT_FAILED This indicates that initialization of a shared object failed.

CUDA_ERROR_OPERATING_SYSTEM This indicates that an OS call failed.

CUDA_ERROR_INVALID_HANDLE This indicates that a resource handle passed to the API call was not valid. Resource handles are opaque types like [CUstream](#) and [CUevent](#).

CUDA_ERROR_NOT_FOUND This indicates that a named symbol was not found. Examples of symbols are global/constant variable names, texture names, and surface names.

CUDA_ERROR_NOT_READY This indicates that asynchronous operations issued previously have not completed yet. This result is not actually an error, but must be indicated differently than [CUDA_SUCCESS](#) (which indicates completion). Calls that may return this value include [cuEventQuery\(\)](#) and [cuStreamQuery\(\)](#).

CUDA_ERROR_LAUNCH_FAILED An exception occurred on the device while executing a kernel. Common causes include dereferencing an invalid device pointer and accessing out of bounds shared memory. The context cannot be used, so it must be destroyed (and a new one should be created). All existing device memory allocations from this context are invalid and must be reconstructed if the program is to continue using CUDA.

CUDA_ERROR_LAUNCH_OUT_OF_RESOURCES This indicates that a launch did not occur because it did not have appropriate resources. This error usually indicates that the user has attempted to pass too many arguments to the device kernel, or the kernel launch specifies too many threads for the kernel's register count. Passing arguments of the wrong size (i.e. a 64-bit pointer when a 32-bit int is expected) is equivalent to passing too many arguments and can also result in this error.

CUDA_ERROR_LAUNCH_TIMEOUT This indicates that the device kernel took too long to execute. This can only occur if timeouts are enabled - see the device attribute [CU_DEVICE_ATTRIBUTE_KERNEL_EXEC_TIMEOUT](#) for more information. The context cannot be used (and must be destroyed similar to [CUDA_ERROR_LAUNCH_FAILED](#)). All existing device memory allocations from this context are invalid and must be reconstructed if the program is to continue using CUDA.

CUDA_ERROR_LAUNCH_INCOMPATIBLE_TEXTURING This error indicates a kernel launch that uses an incompatible texturing mode.

CUDA_ERROR_PEER_ACCESS_ALREADY_ENABLED This error indicates that a call to [cuCtxEnablePeerAccess\(\)](#) is trying to re-enable peer access to a context which has already had peer access to it enabled.

CUDA_ERROR_PEER_ACCESS_NOT_ENABLED This error indicates that [cuCtxDisablePeerAccess\(\)](#) is trying to disable peer access which has not been enabled yet via [cuCtxEnablePeerAccess\(\)](#).

CUDA_ERROR_PRIMARY_CONTEXT_ACTIVE This error indicates that the primary context for the specified device has already been initialized.

CUDA_ERROR_CONTEXT_IS_DESTROYED This error indicates that the context current to the calling thread has been destroyed using [cuCtxDestroy](#), or is a primary context which has not yet been initialized.

CUDA_ERROR_ASSERT A device-side assert triggered during kernel execution. The context cannot be used anymore, and must be destroyed. All existing device memory allocations from this context are invalid and must be reconstructed if the program is to continue using CUDA.

CUDA_ERROR_TOO_MANY_PEERS This error indicates that the hardware resources required to enable peer access have been exhausted for one or more of the devices passed to [cuCtxEnablePeerAccess\(\)](#).

CUDA_ERROR_HOST_MEMORY_ALREADY_REGISTERED This error indicates that the memory range passed to [cuMemHostRegister\(\)](#) has already been registered.

CUDA_ERROR_HOST_MEMORY_NOT_REGISTERED This error indicates that the pointer passed to [cuMemHostUnregister\(\)](#) does not correspond to any currently registered memory region.

CUDA_ERROR_UNKNOWN This indicates that an unknown internal error has occurred.

4.28.3.7 enum CUdevice_attribute_enum

Device properties

Enumerator:

CU_DEVICE_ATTRIBUTE_MAX_THREADS_PER_BLOCK Maximum number of threads per block

CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_X Maximum block dimension X

CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_Y Maximum block dimension Y

CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_Z Maximum block dimension Z

CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_X Maximum grid dimension X

CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_Y Maximum grid dimension Y

CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_Z Maximum grid dimension Z

CU_DEVICE_ATTRIBUTE_MAX_SHARED_MEMORY_PER_BLOCK Maximum shared memory available per block in bytes

CU_DEVICE_ATTRIBUTE_SHARED_MEMORY_PER_BLOCK Deprecated, use ***CU_DEVICE_ATTRIBUTE_MAX_SHARED_MEMORY_PER_BLOCK***

CU_DEVICE_ATTRIBUTE_TOTAL_CONSTANT_MEMORY Memory available on device for __constant__ variables in a CUDA C kernel in bytes

CU_DEVICE_ATTRIBUTE_WARP_SIZE Warp size in threads

CU_DEVICE_ATTRIBUTE_MAX_PITCH Maximum pitch in bytes allowed by memory copies

CU_DEVICE_ATTRIBUTE_MAX_REGISTERS_PER_BLOCK Maximum number of 32-bit registers available per block

CU_DEVICE_ATTRIBUTE_REGISTERS_PER_BLOCK Deprecated, use ***CU_DEVICE_ATTRIBUTE_MAX_REGISTERS_PER_BLOCK***

CU_DEVICE_ATTRIBUTE_CLOCK_RATE Peak clock frequency in kilohertz

CU_DEVICE_ATTRIBUTE_TEXTURE_ALIGNMENT Alignment requirement for textures

CU_DEVICE_ATTRIBUTE_GPU_OVERLAP Device can possibly copy memory and execute a kernel concurrently. Deprecated. Use instead ***CU_DEVICE_ATTRIBUTE_ASYNC_ENGINE_COUNT***.

CU_DEVICE_ATTRIBUTE_MULTIPROCESSOR_COUNT Number of multiprocessors on device

CU_DEVICE_ATTRIBUTE_KERNEL_EXEC_TIMEOUT Specifies whether there is a run time limit on kernels

CU_DEVICE_ATTRIBUTE_INTEGRATED Device is integrated with host memory

CU_DEVICE_ATTRIBUTE_CAN_MAP_HOST_MEMORY Device can map host memory into CUDA address space

CU_DEVICE_ATTRIBUTE_COMPUTE_MODE Compute mode (See [CUcomputemode](#) for details)

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_WIDTH Maximum 1D texture width

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_WIDTH Maximum 2D texture width

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_HEIGHT Maximum 2D texture height

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_WIDTH Maximum 3D texture width

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_HEIGHT Maximum 3D texture height

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_DEPTH Maximum 3D texture depth

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_WIDTH Maximum 2D layered texture width

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_HEIGHT Maximum 2D layered texture height

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_LAYERS Maximum layers in a 2D layered texture

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_ARRAY_WIDTH Deprecated, use ***CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_WIDTH***

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_ARRAY_HEIGHT Deprecated, use ***CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_HEIGHT***

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_ARRAY_NUMSLICES Deprecated, use ***CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_LAYERS***

CU_DEVICE_ATTRIBUTE_SURFACE_ALIGNMENT Alignment requirement for surfaces

CU_DEVICE_ATTRIBUTE_CONCURRENT_KERNELS Device can possibly execute multiple kernels concurrently

CU_DEVICE_ATTRIBUTE_ECC_ENABLED Device has ECC support enabled

CU_DEVICE_ATTRIBUTE_PCI_BUS_ID PCI bus ID of the device

CU_DEVICE_ATTRIBUTE_PCI_DEVICE_ID PCI device ID of the device

CU_DEVICE_ATTRIBUTE_TCC_DRIVER Device is using TCC driver model

CU_DEVICE_ATTRIBUTE_MEMORY_CLOCK_RATE Peak memory clock frequency in kilohertz

CU_DEVICE_ATTRIBUTE_GLOBAL_MEMORY_BUS_WIDTH Global memory bus width in bits

CU_DEVICE_ATTRIBUTE_L2_CACHE_SIZE Size of L2 cache in bytes

CU_DEVICE_ATTRIBUTE_MAX_THREADS_PER_MULTIPROCESSOR Maximum resident threads per multiprocessor

CU_DEVICE_ATTRIBUTE_ASYNC_ENGINE_COUNT Number of asynchronous engines

CU_DEVICE_ATTRIBUTE_UNIFIED_ADDRESSING Device shares a unified address space with the host

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_LAYERED_WIDTH Maximum 1D layered texture width

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_LAYERED_LAYERS Maximum layers in a 1D layered texture

CU_DEVICE_ATTRIBUTE_CAN_TEX2D_GATHER Deprecated, do not use.

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_GATHER_WIDTH Maximum 2D texture width if ***CUDA_ARRAY3D_TEXTURE_GATHER*** is set

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_GATHER_HEIGHT Maximum 2D texture height if ***CUDA_ARRAY3D_TEXTURE_GATHER*** is set

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_WIDTH_ALTERNATE Alternate maximum 3D texture width

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_HEIGHT_ALTERNATE Alternate maximum 3D texture height

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_DEPTH_ALTERNATE Alternate maximum 3D texture depth

CU_DEVICE_ATTRIBUTE_PCI_DOMAIN_ID PCI domain ID of the device

CU_DEVICE_ATTRIBUTE_TEXTURE_PITCH_ALIGNMENT Pitch alignment requirement for textures

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURECUBEMAP_WIDTH Maximum cubemap texture width/height

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURECUBEMAP_LAYERED_WIDTH Maximum cubemap layered texture width/height

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURECUBEMAP_LAYERED_LAYERS Maximum layers in a cubemap layered texture

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_WIDTH Maximum 1D surface width

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_WIDTH Maximum 2D surface width

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_HEIGHT Maximum 2D surface height

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_WIDTH Maximum 3D surface width

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_HEIGHT Maximum 3D surface height

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_DEPTH Maximum 3D surface depth

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_LAYERED_WIDTH Maximum 1D layered surface width

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_LAYERED_LAYERS Maximum layers in a 1D layered surface

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_WIDTH Maximum 2D layered surface width

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_HEIGHT Maximum 2D layered surface height

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_LAYERS Maximum layers in a 2D layered surface

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACECUBEMAP_WIDTH Maximum cubemap surface width

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACECUBEMAP_LAYERED_WIDTH Maximum cubemap layered surface width

CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACECUBEMAP_LAYERED_LAYERS Maximum layers in a cubemap layered surface

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_LINEAR_WIDTH Maximum 1D linear texture width

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_WIDTH Maximum 2D linear texture width

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_HEIGHT Maximum 2D linear texture height

CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_PITCH Maximum 2D linear texture pitch in bytes

4.28.3.8 enum CUevent_flags_enum

Event creation flags

Enumerator:

CU_EVENT_DEFAULT Default event flag

CU_EVENT_BLOCKING_SYNC Event uses blocking synchronization

CU_EVENT_DISABLE_TIMING Event will not record timing data

CU_EVENT_INTERPROCESS Event is suitable for interprocess use. ***CU_EVENT_DISABLE_TIMING*** must be set

4.28.3.9 enum CUfilter_mode_enum

Texture reference filtering modes

Enumerator:

CU_TR_FILTER_MODE_POINT Point filter mode

CU_TR_FILTER_MODE_LINEAR Linear filter mode

4.28.3.10 enum CUfunc_cache_enum

Function cache configurations

Enumerator:

CU_FUNC_CACHE_PREFER_NONE no preference for shared memory or L1 (default)

CU_FUNC_CACHE_PREFER_SHARED prefer larger shared memory and smaller L1 cache

CU_FUNC_CACHE_PREFER_L1 prefer larger L1 cache and smaller shared memory

CU_FUNC_CACHE_PREFER_EQUAL prefer equal sized L1 cache and shared memory

4.28.3.11 enum CUfunction_attribute_enum

Function properties

Enumerator:

CU_FUNC_ATTRIBUTE_MAX_THREADS_PER_BLOCK The maximum number of threads per block, beyond which a launch of the function would fail. This number depends on both the function and the device on which the function is currently loaded.

CU_FUNC_ATTRIBUTE_SHARED_SIZE_BYTES The size in bytes of statically-allocated shared memory required by this function. This does not include dynamically-allocated shared memory requested by the user at runtime.

CU_FUNC_ATTRIBUTE_CONST_SIZE_BYTES The size in bytes of user-allocated constant memory required by this function.

CU_FUNC_ATTRIBUTE_LOCAL_SIZE_BYTES The size in bytes of local memory used by each thread of this function.

CU_FUNC_ATTRIBUTE_NUM_REGS The number of registers used by each thread of this function.

CU_FUNC_ATTRIBUTE_PTX_VERSION The PTX virtual architecture version for which the function was compiled. This value is the major PTX version * 10 + the minor PTX version, so a PTX version 1.3 function would return the value 13. Note that this may return the undefined value of 0 for cubins compiled prior to CUDA 3.0.

CU_FUNC_ATTRIBUTE_BINARY_VERSION The binary architecture version for which the function was compiled. This value is the major binary version * 10 + the minor binary version, so a binary version 1.3 function would return the value 13. Note that this will return a value of 10 for legacy cubins that do not have a properly-encoded binary architecture version.

4.28.3.12 enum CUgraphicsMapResourceFlags_enum

Flags for mapping and unmapping interop resources

4.28.3.13 enum CUgraphicsRegisterFlags_enum

Flags to register a graphics resource

4.28.3.14 enum CUjit_fallback_enum

Cubin matching fallback strategies

Enumerator:

CU_PREFER_PTX Prefer to compile ptx

CU_PREFER_BINARY Prefer to fall back to compatible binary code

4.28.3.15 enum CUjit_option_enum

Online compiler options

Enumerator:

CU_JIT_MAX_REGISTERS Max number of registers that a thread may use.

Option type: unsigned int

CU_JIT_THREADS_PER_BLOCK IN: Specifies minimum number of threads per block to target compilation for

OUT: Returns the number of threads the compiler actually targeted. This restricts the resource utilization for the compiler (e.g. max registers) such that a block with the given number of threads should be able to launch based on register limitations. Note, this option does not currently take into account any other resource limitations, such as shared memory utilization.

Option type: unsigned int

CU_JIT_WALL_TIME Returns a float value in the option of the wall clock time, in milliseconds, spent creating the cubin

Option type: float

CU_JIT_INFO_LOG_BUFFER Pointer to a buffer in which to print any log messages from PTXAS that are informational in nature (the buffer size is specified via option [CU_JIT_INFO_LOG_BUFFER_SIZE_BYTES](#))

Option type: char*

CU_JIT_INFO_LOG_BUFFER_SIZE_BYTES IN: Log buffer size in bytes. Log messages will be capped at this size (including null terminator)

OUT: Amount of log buffer filled with messages

Option type: unsigned int

CU_JIT_ERROR_LOG_BUFFER Pointer to a buffer in which to print any log messages from PTXAS that reflect errors (the buffer size is specified via option [CU_JIT_ERROR_LOG_BUFFER_SIZE_BYTES](#))

Option type: char*

CU_JIT_ERROR_LOG_BUFFER_SIZE_BYTES IN: Log buffer size in bytes. Log messages will be capped at this size (including null terminator)

OUT: Amount of log buffer filled with messages

Option type: unsigned int

CU_JIT_OPTIMIZATION_LEVEL Level of optimizations to apply to generated code (0 - 4), with 4 being the default and highest level of optimizations.

Option type: unsigned int

CU_JIT_TARGET_FROM_CUCONTEXT No option value required. Determines the target based on the current attached context (default)

Option type: No option value needed

CU_JIT_TARGET Target is chosen based on supplied [CUjit_target_enum](#).

Option type: unsigned int for enumerated type [CUjit_target_enum](#)

CU_JIT_FALLBACK_STRATEGY Specifies choice of fallback strategy if matching cubin is not found. Choice is based on supplied [CUjit_fallback_enum](#).

Option type: unsigned int for enumerated type [CUjit_fallback_enum](#)

4.28.3.16 enum CUjit_target_enum

Online compilation targets

Enumerator:

CU_TARGET_COMPUTE_10 Compute device class 1.0

CU_TARGET_COMPUTE_11 Compute device class 1.1

CU_TARGET_COMPUTE_12 Compute device class 1.2

CU_TARGET_COMPUTE_13 Compute device class 1.3

CU_TARGET_COMPUTE_20 Compute device class 2.0

CU_TARGET_COMPUTE_21 Compute device class 2.1

4.28.3.17 enum CUlimit_enum

Limits

Enumerator:

CU_LIMIT_STACK_SIZE GPU thread stack size

CU_LIMIT_PRINTF_FIFO_SIZE GPU printf FIFO size

CU_LIMIT_MALLOC_HEAP_SIZE GPU malloc heap size

4.28.3.18 enum CUmemorytype_enum

Memory types

Enumerator:

CU_MEMORYTYPE_HOST Host memory

CU_MEMORYTYPE_DEVICE Device memory

CU_MEMORYTYPE_ARRAY Array memory

CU_MEMORYTYPE_UNIFIED Unified device or host memory

4.28.3.19 enum CUpointer_attribute_enum

Pointer information

Enumerator:

CU_POINTER_ATTRIBUTE_CONTEXT The [CUcontext](#) on which a pointer was allocated or registered

- CU_POINTER_ATTRIBUTE_MEMORY_TYPE*** The [CUmemorytype](#) describing the physical location of a pointer
- CU_POINTER_ATTRIBUTE_DEVICE_POINTER*** The address at which a pointer's memory may be accessed on the device
- CU_POINTER_ATTRIBUTE_HOST_POINTER*** The address at which a pointer's memory may be accessed on the host

4.29 Initialization

Functions

- [CUresult cuInit](#) (unsigned int *Flags*)
Initialize the CUDA driver API.

4.29.1 Detailed Description

This section describes the initialization functions of the low-level CUDA driver application programming interface.

4.29.2 Function Documentation

4.29.2.1 CUresult cuInit (unsigned int *Flags*)

Initializes the driver API and must be called before any other function from the driver API. Currently, the `Flags` parameter must be 0. If [cuInit\(\)](#) has not been called, any function from the driver API will return [CUDA_ERROR_NOT_INITIALIZED](#).

Parameters:

Flags - Initialization flag for CUDA.

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_DEVICE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

4.30 Version Management

Functions

- [CUresult cuDriverGetVersion](#) (int *driverVersion)

Returns the CUDA driver version.

4.30.1 Detailed Description

This section describes the version management functions of the low-level CUDA driver application programming interface.

4.30.2 Function Documentation

4.30.2.1 CUresult cuDriverGetVersion (int * *driverVersion*)

Returns in *driverVersion the version number of the installed CUDA driver. This function automatically returns [CUDA_ERROR_INVALID_VALUE](#) if the driverVersion argument is NULL.

Parameters:

driverVersion - Returns the CUDA driver version

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

4.31 Device Management

Functions

- [CUresult cuDeviceComputeCapability](#) (int *major, int *minor, [CUdevice](#) dev)
Returns the compute capability of the device.
- [CUresult cuDeviceGet](#) ([CUdevice](#) *device, int ordinal)
Returns a handle to a compute device.
- [CUresult cuDeviceGetAttribute](#) (int *pi, [CUdevice_attribute](#) attrib, [CUdevice](#) dev)
Returns information about the device.
- [CUresult cuDeviceGetCount](#) (int *count)
Returns the number of compute-capable devices.
- [CUresult cuDeviceGetName](#) (char *name, int len, [CUdevice](#) dev)
Returns an identifier string for the device.
- [CUresult cuDeviceGetProperties](#) ([CUdevprop](#) *prop, [CUdevice](#) dev)
Returns properties for a selected device.
- [CUresult cuDeviceTotalMem](#) (size_t *bytes, [CUdevice](#) dev)
Returns the total amount of memory on the device.

4.31.1 Detailed Description

This section describes the device management functions of the low-level CUDA driver application programming interface.

4.31.2 Function Documentation

4.31.2.1 [CUresult cuDeviceComputeCapability](#) (int * *major*, int * *minor*, [CUdevice](#) *dev*)

Returns in *major and *minor the major and minor revision numbers that define the compute capability of the device dev.

Parameters:

major - Major revision number
minor - Minor revision number
dev - Device handle

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_DEVICE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuDeviceGetAttribute](#), [cuDeviceGetCount](#), [cuDeviceGetName](#), [cuDeviceGet](#), [cuDeviceGetProperties](#), [cuDeviceTotalMem](#)

4.31.2.2 CUresult cuDeviceGet (CUdevice * device, int ordinal)

Returns in *device a device handle given an ordinal in the range [0, [cuDeviceGetCount\(\)-1](#)].

Parameters:

device - Returned device handle

ordinal - Device number to get handle for

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_DEVICE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuDeviceComputeCapability](#), [cuDeviceGetAttribute](#), [cuDeviceGetCount](#), [cuDeviceGetName](#), [cuDeviceGetProperties](#), [cuDeviceTotalMem](#)

4.31.2.3 CUresult cuDeviceGetAttribute (int * pi, CUdevice_attribute attrib, CUdevice dev)

Returns in *pi the integer value of the attribute *attrib* on device *dev*. The supported attributes are:

- [CU_DEVICE_ATTRIBUTE_MAX_THREADS_PER_BLOCK](#): Maximum number of threads per block;
- [CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_X](#): Maximum x-dimension of a block;
- [CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_Y](#): Maximum y-dimension of a block;
- [CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_Z](#): Maximum z-dimension of a block;
- [CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_X](#): Maximum x-dimension of a grid;
- [CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_Y](#): Maximum y-dimension of a grid;
- [CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_Z](#): Maximum z-dimension of a grid;
- [CU_DEVICE_ATTRIBUTE_MAX_SHARED_MEMORY_PER_BLOCK](#): Maximum amount of shared memory available to a thread block in bytes; this amount is shared by all thread blocks simultaneously resident on a multiprocessor;
- [CU_DEVICE_ATTRIBUTE_TOTAL_CONSTANT_MEMORY](#): Memory available on device for `__constant__` variables in a CUDA C kernel in bytes;
- [CU_DEVICE_ATTRIBUTE_WARP_SIZE](#): Warp size in threads;
- [CU_DEVICE_ATTRIBUTE_MAX_PITCH](#): Maximum pitch in bytes allowed by the memory copy functions that involve memory regions allocated through [cuMemAllocPitch\(\)](#);

- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_WIDTH](#): Maximum 1D texture width;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_LINEAR_WIDTH](#): Maximum width for a 1D texture bound to linear memory;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_WIDTH](#): Maximum 2D texture width;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_HEIGHT](#): Maximum 2D texture height;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_WIDTH](#): Maximum width for a 2D texture bound to linear memory;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_HEIGHT](#): Maximum height for a 2D texture bound to linear memory;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_PITCH](#): Maximum pitch in bytes for a 2D texture bound to linear memory;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_WIDTH](#): Maximum 3D texture width;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_HEIGHT](#): Maximum 3D texture height;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_DEPTH](#): Maximum 3D texture depth;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_WIDTH_ALTERNATE](#): Alternate maximum 3D texture width, 0 if no alternate maximum 3D texture size is supported;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_HEIGHT_ALTERNATE](#): Alternate maximum 3D texture height, 0 if no alternate maximum 3D texture size is supported;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE3D_DEPTH_ALTERNATE](#): Alternate maximum 3D texture depth, 0 if no alternate maximum 3D texture size is supported;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURECUBEMAP_WIDTH](#): Maximum cubemap texture width or height;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_LAYERED_WIDTH](#): Maximum 1D layered texture width;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_LAYERED_LAYERS](#): Maximum layers in a 1D layered texture;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_WIDTH](#): Maximum 2D layered texture width;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_HEIGHT](#): Maximum 2D layered texture height;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LAYERED_LAYERS](#): Maximum layers in a 2D layered texture;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURECUBEMAP_LAYERED_WIDTH](#): Maximum cubemap layered texture width or height;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURECUBEMAP_LAYERED_LAYERS](#): Maximum layers in a cubemap layered texture;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_WIDTH](#): Maximum 1D surface width;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_WIDTH](#): Maximum 2D surface width;
- [CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_HEIGHT](#): Maximum 2D surface height;

- `CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_WIDTH`: Maximum 3D surface width;
- `CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_HEIGHT`: Maximum 3D surface height;
- `CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_DEPTH`: Maximum 3D surface depth;
- `CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_LAYERED_WIDTH`: Maximum 1D layered surface width;
- `CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_LAYERED_LAYERS`: Maximum layers in a 1D layered surface;
- `CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_WIDTH`: Maximum 2D layered surface width;
- `CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_HEIGHT`: Maximum 2D layered surface height;
- `CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_LAYERS`: Maximum layers in a 2D layered surface;
- `CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACECUBEMAP_WIDTH`: Maximum cubemap surface width;
- `CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACECUBEMAP_LAYERED_WIDTH`: Maximum cubemap layered surface width;
- `CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACECUBEMAP_LAYERED_LAYERS`: Maximum layers in a cubemap layered surface;
- `CU_DEVICE_ATTRIBUTE_MAX_REGISTERS_PER_BLOCK`: Maximum number of 32-bit registers available to a thread block; this number is shared by all thread blocks simultaneously resident on a multiprocessor;
- `CU_DEVICE_ATTRIBUTE_CLOCK_RATE`: Peak clock frequency in kilohertz;
- `CU_DEVICE_ATTRIBUTE_TEXTURE_ALIGNMENT`: Alignment requirement; texture base addresses aligned to textureAlign bytes do not need an offset applied to texture fetches;
- `CU_DEVICE_ATTRIBUTE_TEXTURE_PITCH_ALIGNMENT`: Pitch alignment requirement for 2D texture references bound to pitched memory;
- `CU_DEVICE_ATTRIBUTE_GPU_OVERLAP`: 1 if the device can concurrently copy memory between host and device while executing a kernel, or 0 if not;
- `CU_DEVICE_ATTRIBUTE_MULTIPROCESSOR_COUNT`: Number of multiprocessors on the device;
- `CU_DEVICE_ATTRIBUTE_KERNEL_EXEC_TIMEOUT`: 1 if there is a run time limit for kernels executed on the device, or 0 if not;
- `CU_DEVICE_ATTRIBUTE_INTEGRATED`: 1 if the device is integrated with the memory subsystem, or 0 if not;
- `CU_DEVICE_ATTRIBUTE_CAN_MAP_HOST_MEMORY`: 1 if the device can map host memory into the CUDA address space, or 0 if not;
- `CU_DEVICE_ATTRIBUTE_COMPUTE_MODE`: Compute mode that device is currently in. Available modes are as follows:
 - `CU_COMPUTEMODE_DEFAULT`: Default mode - Device is not restricted and can have multiple CUDA contexts present at a single time.

- [CU_COMPUTEMODE_EXCLUSIVE](#): Compute-exclusive mode - Device can have only one CUDA context present on it at a time.
- [CU_COMPUTEMODE_PROHIBITED](#): Compute-prohibited mode - Device is prohibited from creating new CUDA contexts.
- [CU_COMPUTEMODE_EXCLUSIVE_PROCESS](#): Compute-exclusive-process mode - Device can have only one context used by a single process at a time.
- [CU_DEVICE_ATTRIBUTE_CONCURRENT_KERNELS](#): 1 if the device supports executing multiple kernels within the same context simultaneously, or 0 if not. It is not guaranteed that multiple kernels will be resident on the device concurrently so this feature should not be relied upon for correctness;
- [CU_DEVICE_ATTRIBUTE_ECC_ENABLED](#): 1 if error correction is enabled on the device, 0 if error correction is disabled or not supported by the device;
- [CU_DEVICE_ATTRIBUTE_PCI_BUS_ID](#): PCI bus identifier of the device;
- [CU_DEVICE_ATTRIBUTE_PCI_DEVICE_ID](#): PCI device (also known as slot) identifier of the device;
- [CU_DEVICE_ATTRIBUTE_TCC_DRIVER](#): 1 if the device is using a TCC driver. TCC is only available on Tesla hardware running Windows Vista or later;
- [CU_DEVICE_ATTRIBUTE_MEMORY_CLOCK_RATE](#): Peak memory clock frequency in kilohertz;
- [CU_DEVICE_ATTRIBUTE_GLOBAL_MEMORY_BUS_WIDTH](#): Global memory bus width in bits;
- [CU_DEVICE_ATTRIBUTE_L2_CACHE_SIZE](#): Size of L2 cache in bytes. 0 if the device doesn't have L2 cache;
- [CU_DEVICE_ATTRIBUTE_MAX_THREADS_PER_MULTIPROCESSOR](#): Maximum resident threads per multiprocessor;
- [CU_DEVICE_ATTRIBUTE_UNIFIED_ADDRESSING](#): 1 if the device shares a unified address space with the host, or 0 if not;

Parameters:

pi - Returned device attribute value
attrib - Device attribute to query
dev - Device handle

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_DEVICE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuDeviceComputeCapability](#), [cuDeviceGetCount](#), [cuDeviceGetName](#), [cuDeviceGet](#), [cuDeviceGetProperties](#), [cuDeviceTotalMem](#)

4.31.2.4 CUresult cuDeviceGetCount (int * *count*)

Returns in **count* the number of devices with compute capability greater than or equal to 1.0 that are available for execution. If there is no such device, [cuDeviceGetCount\(\)](#) returns 0.

Parameters:

count - Returned number of compute-capable devices

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuDeviceComputeCapability](#), [cuDeviceGetAttribute](#), [cuDeviceGetName](#), [cuDeviceGet](#), [cuDeviceGetProperties](#), [cuDeviceTotalMem](#)

4.31.2.5 CUresult cuDeviceGetName (char * *name*, int *len*, CUdevice *dev*)

Returns an ASCII string identifying the device *dev* in the NULL-terminated string pointed to by *name*. *len* specifies the maximum length of the string that may be returned.

Parameters:

name - Returned identifier string for the device

len - Maximum length of string to store in *name*

dev - Device to get identifier string for

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_DEVICE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuDeviceComputeCapability](#), [cuDeviceGetAttribute](#), [cuDeviceGetCount](#), [cuDeviceGet](#), [cuDeviceGetProperties](#), [cuDeviceTotalMem](#)

4.31.2.6 CUresult cuDeviceGetProperties (CUdevprop * *prop*, CUdevice *dev*)

Returns in **prop* the properties of device *dev*. The [CUdevprop](#) structure is defined as:

```
typedef struct CUdevprop_st {
    int maxThreadsPerBlock;
    int maxThreadsDim[3];
    int maxGridSize[3];
    int sharedMemPerBlock;
    int totalConstantMemory;
    int SIMDWidth;
    int memPitch;
    int regsPerBlock;
    int clockRate;
    int textureAlign
} CUdevprop;
```

where:

- `maxThreadsPerBlock` is the maximum number of threads per block;
- `maxThreadsDim[3]` is the maximum sizes of each dimension of a block;
- `maxGridSize[3]` is the maximum sizes of each dimension of a grid;
- `sharedMemPerBlock` is the total amount of shared memory available per block in bytes;
- `totalConstantMemory` is the total amount of constant memory available on the device in bytes;
- `SIMDWidth` is the warp size;
- `memPitch` is the maximum pitch allowed by the memory copy functions that involve memory regions allocated through [cuMemAllocPitch\(\)](#);
- `regsPerBlock` is the total number of registers available per block;
- `clockRate` is the clock frequency in kilohertz;
- `textureAlign` is the alignment requirement; texture base addresses that are aligned to `textureAlign` bytes do not need an offset applied to texture fetches.

Parameters:

prop - Returned properties of device

dev - Device to get properties for

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_DEVICE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuDeviceComputeCapability](#), [cuDeviceGetAttribute](#), [cuDeviceGetCount](#), [cuDeviceGetName](#), [cuDeviceGet](#), [cuDeviceTotalMem](#)

4.31.2.7 CUresult cuDeviceTotalMem (size_t * *bytes*, CUdevice *dev*)

Returns in **bytes* the total amount of memory available on the device *dev* in bytes.

Parameters:

bytes - Returned memory available on device in bytes

dev - Device handle

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_INVALID_DEVICE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuDeviceComputeCapability, cuDeviceGetAttribute, cuDeviceGetCount, cuDeviceGetName, cuDeviceGet, cuDeviceGetProperties,

4.32 Context Management

Modules

- [Context Management \[DEPRECATED\]](#)

Functions

- [CUresult cuCtxCreate](#) ([CUcontext](#) *pctx, unsigned int flags, [CUdevice](#) dev)
Create a CUDA context.
- [CUresult cuCtxDestroy](#) ([CUcontext](#) ctx)
Destroy a CUDA context.
- [CUresult cuCtxGetApiVersion](#) ([CUcontext](#) ctx, unsigned int *version)
Gets the context's API version.
- [CUresult cuCtxGetCacheConfig](#) ([CUfunc_cache](#) *pconfig)
Returns the preferred cache configuration for the current context.
- [CUresult cuCtxGetCurrent](#) ([CUcontext](#) *pctx)
Returns the CUDA context bound to the calling CPU thread.
- [CUresult cuCtxGetDevice](#) ([CUdevice](#) *device)
Returns the device ID for the current context.
- [CUresult cuCtxGetLimit](#) (size_t *pvalue, [CUlimit](#) limit)
Returns resource limits.
- [CUresult cuCtxPopCurrent](#) ([CUcontext](#) *pctx)
Pops the current CUDA context from the current CPU thread.
- [CUresult cuCtxPushCurrent](#) ([CUcontext](#) ctx)
Pushes a context on the current CPU thread.
- [CUresult cuCtxSetCacheConfig](#) ([CUfunc_cache](#) config)
Sets the preferred cache configuration for the current context.
- [CUresult cuCtxSetCurrent](#) ([CUcontext](#) ctx)
Binds the specified CUDA context to the calling CPU thread.
- [CUresult cuCtxSetLimit](#) ([CUlimit](#) limit, size_t value)
Set resource limits.
- [CUresult cuCtxSynchronize](#) (void)
Block for a context's tasks to complete.

4.32.1 Detailed Description

This section describes the context management functions of the low-level CUDA driver application programming interface.

4.32.2 Function Documentation

4.32.2.1 CUresult cuCtxCreate (CUcontext *pctx, unsigned int flags, CUdevice dev)

Creates a new CUDA context and associates it with the calling thread. The `flags` parameter is described below. The context is created with a usage count of 1 and the caller of `cuCtxCreate()` must call `cuCtxDestroy()` or when done using the context. If a context is already current to the thread, it is supplanted by the newly created context and may be restored by a subsequent call to `cuCtxPopCurrent()`.

The three LSBs of the `flags` parameter can be used to control how the OS thread, which owns the CUDA context at the time of an API call, interacts with the OS scheduler when waiting for results from the GPU. Only one of the scheduling flags can be set when creating a context.

- **CU_CTX_SCHED_AUTO**: The default value if the `flags` parameter is zero, uses a heuristic based on the number of active CUDA contexts in the process C and the number of logical processors in the system P . If $C > P$, then CUDA will yield to other OS threads when waiting for the GPU, otherwise CUDA will not yield while waiting for results and actively spin on the processor.
- **CU_CTX_SCHED_SPIN**: Instruct CUDA to actively spin when waiting for results from the GPU. This can decrease latency when waiting for the GPU, but may lower the performance of CPU threads if they are performing work in parallel with the CUDA thread.
- **CU_CTX_SCHED_YIELD**: Instruct CUDA to yield its thread when waiting for results from the GPU. This can increase latency when waiting for the GPU, but can increase the performance of CPU threads performing work in parallel with the GPU.
- **CU_CTX_SCHED_BLOCKING_SYNC**: Instruct CUDA to block the CPU thread on a synchronization primitive when waiting for the GPU to finish work.
- **CU_CTX_BLOCKING_SYNC**: Instruct CUDA to block the CPU thread on a synchronization primitive when waiting for the GPU to finish work.
Deprecated: This flag was deprecated as of CUDA 4.0 and was replaced with **CU_CTX_SCHED_BLOCKING_SYNC**.
- **CU_CTX_MAP_HOST**: Instruct CUDA to support mapped pinned allocations. This flag must be set in order to allocate pinned host memory that is accessible to the GPU.
- **CU_CTX_LMEM_RESIZE_TO_MAX**: Instruct CUDA to not reduce local memory after resizing local memory for a kernel. This can prevent thrashing by local memory allocations when launching many kernels with high local memory usage at the cost of potentially increased memory usage.

Context creation will fail with **CUDA_ERROR_UNKNOWN** if the compute mode of the device is **CU_COMPUTEMODE_PROHIBITED**. Similarly, context creation will also fail with **CUDA_ERROR_UNKNOWN** if the compute mode for the device is set to **CU_COMPUTEMODE_EXCLUSIVE** and there is already an active context on the device. The function `cuDeviceGetAttribute()` can be used with **CU_DEVICE_ATTRIBUTE_COMPUTE_MODE** to determine the compute mode of the device. The `nvidia-smi` tool can be used to set the compute mode for devices. Documentation for `nvidia-smi` can be obtained by passing a `-h` option to it.

Parameters:

pctx - Returned context handle of the new context
flags - Context creation flags
dev - Device to create context on

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_DEVICE, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_OUT_OF_MEMORY, CUDA_ERROR_UNKNOWN

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxDestroy](#), [cuCtxGetApiVersion](#), [cuCtxGetCacheConfig](#), [cuCtxGetDevice](#), [cuCtxGetLimit](#), [cuCtxPopCurrent](#), [cuCtxPushCurrent](#), [cuCtxSetCacheConfig](#), [cuCtxSetLimit](#), [cuCtxSynchronize](#)

4.32.2.2 CUresult cuCtxDestroy (CUcontext ctx)

Destroys the CUDA context specified by *ctx*. The context *ctx* will be destroyed regardless of how many threads it is current to. It is the caller's responsibility to ensure that no API call is issued to *ctx* while [cuCtxDestroy\(\)](#) is executing.

If *ctx* is current to the calling thread then *ctx* will also be popped from the current thread's context stack (as though [cuCtxPopCurrent\(\)](#) were called). If *ctx* is current to other threads, then *ctx* will remain current to those threads, and attempting to access *ctx* from those threads will result in the error [CUDA_ERROR_CONTEXT_IS_DESTROYED](#).

Parameters:

ctx - Context to destroy

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxCreate](#), [cuCtxGetApiVersion](#), [cuCtxGetCacheConfig](#), [cuCtxGetDevice](#), [cuCtxGetLimit](#), [cuCtxPopCurrent](#), [cuCtxPushCurrent](#), [cuCtxSetCacheConfig](#), [cuCtxSetLimit](#), [cuCtxSynchronize](#)

4.32.2.3 CUresult cuCtxGetApiVersion (CUcontext ctx, unsigned int * version)

Returns the API version used to create *ctx* in *version*. If *ctx* is NULL, returns the API version used to create the currently bound context.

This will return the API version used to create a context (for example, 3010 or 3020), which library developers can use to direct callers to a specific API version. Note that this API version may not be the same as returned by [cuDriverGetVersion](#).

Parameters:

ctx - Context to check
version - Pointer to version

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_UNKNOWN

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuCtxCreate, cuCtxDestroy, cuCtxGetDevice, cuCtxGetLimit, cuCtxPopCurrent, cuCtxPushCurrent, cuCtxSetCacheConfig, cuCtxSetLimit, cuCtxSynchronize

4.32.2.4 CUresult cuCtxGetCacheConfig (CUfunc_cache * pconfig)

On devices where the L1 cache and shared memory use the same hardware resources, this returns through *pconfig* the preferred cache configuration for the current context. This is only a preference. The driver will use the requested configuration if possible, but it is free to choose a different configuration if required to execute functions.

This will return a *pconfig* of [CU_FUNC_CACHE_PREFER_NONE](#) on devices where the size of the L1 cache and shared memory are fixed.

The supported cache configurations are:

- [CU_FUNC_CACHE_PREFER_NONE](#): no preference for shared memory or L1 (default)
- [CU_FUNC_CACHE_PREFER_SHARED](#): prefer larger shared memory and smaller L1 cache
- [CU_FUNC_CACHE_PREFER_L1](#): prefer larger L1 cache and smaller shared memory
- [CU_FUNC_CACHE_PREFER_EQUAL](#): prefer equal sized L1 cache and shared memory

Parameters:

pconfig - Returned cache configuration

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuCtxCreate, cuCtxDestroy, cuCtxGetApiVersion, cuCtxGetDevice, cuCtxGetLimit, cuCtxPopCurrent, cuCtxPushCurrent, cuCtxSetCacheConfig, cuCtxSetLimit, cuCtxSynchronize, cuFuncSetCacheConfig

4.32.2.5 CUresult cuCtxGetCurrent (CUcontext * *pctx*)

Returns in **pctx* the CUDA context bound to the calling CPU thread. If no context is bound to the calling CPU thread then **pctx* is set to NULL and [CUDA_SUCCESS](#) is returned.

Parameters:

pctx - Returned context handle

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxSetCurrent](#), [cuCtxCreate](#), [cuCtxDestroy](#)

4.32.2.6 CUresult cuCtxGetDevice (CUdevice * *device*)

Returns in **device* the ordinal of the current context's device.

Parameters:

device - Returned device ID for the current context

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxCreate](#), [cuCtxDestroy](#), [cuCtxGetApiVersion](#), [cuCtxGetCacheConfig](#), [cuCtxGetLimit](#), [cuCtxPopCurrent](#), [cuCtxPushCurrent](#), [cuCtxSetCacheConfig](#), [cuCtxSetLimit](#), [cuCtxSynchronize](#)

4.32.2.7 CUresult cuCtxGetLimit (size_t * *pvalue*, CUlimit *limit*)

Returns in **pvalue* the current size of *limit*. The supported [CUlimit](#) values are:

- [CU_LIMIT_STACK_SIZE](#): stack size of each GPU thread;
- [CU_LIMIT_PRINTF_FIFO_SIZE](#): size of the FIFO used by the printf() device system call.
- [CU_LIMIT_MALLOC_HEAP_SIZE](#): size of the heap used by the malloc() and free() device system calls;

Parameters:

limit - Limit to query

pvalue - Returned size in bytes of limit

Returns:

CUDA_SUCCESS, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_UNSUPPORTED_LIMIT

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuCtxCreate, cuCtxDestroy, cuCtxGetApiVersion, cuCtxGetCacheConfig, cuCtxGetDevice, cuCtxPopCurrent, cuCtxPushCurrent, cuCtxSetCacheConfig, cuCtxSetLimit, cuCtxSynchronize

4.32.2.8 CUresult cuCtxPopCurrent (CUcontext * *pctx*)

Pops the current CUDA context from the CPU thread and passes back the old context handle in **pctx*. That context may then be made current to a different CPU thread by calling [cuCtxPushCurrent\(\)](#).

If a context was current to the CPU thread before [cuCtxCreate\(\)](#) or [cuCtxPushCurrent\(\)](#) was called, this function makes that context current to the CPU thread again.

Parameters:

pctx - Returned new context handle

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuCtxCreate, cuCtxDestroy, cuCtxGetApiVersion, cuCtxGetCacheConfig, cuCtxGetDevice, cuCtxGetLimit, cuCtxPushCurrent, cuCtxSetCacheConfig, cuCtxSetLimit, cuCtxSynchronize

4.32.2.9 CUresult cuCtxPushCurrent (CUcontext *ctx*)

Pushes the given context *ctx* onto the CPU thread's stack of current contexts. The specified context becomes the CPU thread's current context, so all CUDA functions that operate on the current context are affected.

The previous current context may be made current again by calling [cuCtxDestroy\(\)](#) or [cuCtxPopCurrent\(\)](#).

Parameters:

ctx - Context to push

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxCreate](#), [cuCtxDestroy](#), [cuCtxGetApiVersion](#), [cuCtxGetCacheConfig](#), [cuCtxGetDevice](#), [cuCtxGetLimit](#), [cuCtxPopCurrent](#), [cuCtxSetCacheConfig](#), [cuCtxSetLimit](#), [cuCtxSynchronize](#)

4.32.2.10 CUresult cuCtxSetCacheConfig (CUfunc_cache config)

On devices where the L1 cache and shared memory use the same hardware resources, this sets through `config` the preferred cache configuration for the current context. This is only a preference. The driver will use the requested configuration if possible, but it is free to choose a different configuration if required to execute the function. Any function preference set via [cuFuncSetCacheConfig\(\)](#) will be preferred over this context-wide setting. Setting the context-wide cache configuration to [CU_FUNC_CACHE_PREFER_NONE](#) will cause subsequent kernel launches to prefer to not change the cache configuration unless required to launch the kernel.

This setting does nothing on devices where the size of the L1 cache and shared memory are fixed.

Launching a kernel with a different preference than the most recent preference setting may insert a device-side synchronization point.

The supported cache configurations are:

- [CU_FUNC_CACHE_PREFER_NONE](#): no preference for shared memory or L1 (default)
- [CU_FUNC_CACHE_PREFER_SHARED](#): prefer larger shared memory and smaller L1 cache
- [CU_FUNC_CACHE_PREFER_L1](#): prefer larger L1 cache and smaller shared memory
- [CU_FUNC_CACHE_PREFER_EQUAL](#): prefer equal sized L1 cache and shared memory

Parameters:

config - Requested cache configuration

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxCreate](#), [cuCtxDestroy](#), [cuCtxGetApiVersion](#), [cuCtxGetCacheConfig](#), [cuCtxGetDevice](#), [cuCtxGetLimit](#), [cuCtxPopCurrent](#), [cuCtxPushCurrent](#), [cuCtxSetLimit](#), [cuCtxSynchronize](#), [cuFuncSetCacheConfig](#)

4.32.2.11 CUresult cuCtxSetCurrent (CUcontext ctx)

Binds the specified CUDA context to the calling CPU thread. If `ctx` is NULL then the CUDA context previously bound to the calling CPU thread is unbound and [CUDA_SUCCESS](#) is returned.

If there exists a CUDA context stack on the calling CPU thread, this will replace the top of that stack with `ctx`. If `ctx` is NULL then this will be equivalent to popping the top of the calling CPU thread's CUDA context stack (or a no-op if the calling CPU thread's CUDA context stack is empty).

Parameters:

ctx - Context to bind to the calling CPU thread

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuCtxGetCurrent, cuCtxCreate, cuCtxDestroy

4.32.2.12 CUresult cuCtxSetLimit (CUlimit *limit*, size_t *value*)

Setting *limit* to *value* is a request by the application to update the current limit maintained by the context. The driver is free to modify the requested value to meet h/w requirements (this could be clamping to minimum or maximum values, rounding up to nearest element size, etc). The application can use [cuCtxGetLimit\(\)](#) to find out exactly what the limit has been set to.

Setting each [CUlimit](#) has its own specific restrictions, so each is discussed here.

- [CU_LIMIT_STACK_SIZE](#) controls the stack size of each GPU thread. This limit is only applicable to devices of compute capability 2.0 and higher. Attempting to set this limit on devices of compute capability less than 2.0 will result in the error [CUDA_ERROR_UNSUPPORTED_LIMIT](#) being returned.
- [CU_LIMIT_PRINTF_FIFO_SIZE](#) controls the size of the FIFO used by the printf() device system call. Setting [CU_LIMIT_PRINTF_FIFO_SIZE](#) must be performed before launching any kernel that uses the printf() device system call, otherwise [CUDA_ERROR_INVALID_VALUE](#) will be returned. This limit is only applicable to devices of compute capability 2.0 and higher. Attempting to set this limit on devices of compute capability less than 2.0 will result in the error [CUDA_ERROR_UNSUPPORTED_LIMIT](#) being returned.
- [CU_LIMIT_MALLOC_HEAP_SIZE](#) controls the size of the heap used by the malloc() and free() device system calls. Setting [CU_LIMIT_MALLOC_HEAP_SIZE](#) must be performed before launching any kernel that uses the malloc() or free() device system calls, otherwise [CUDA_ERROR_INVALID_VALUE](#) will be returned. This limit is only applicable to devices of compute capability 2.0 and higher. Attempting to set this limit on devices of compute capability less than 2.0 will result in the error [CUDA_ERROR_UNSUPPORTED_LIMIT](#) being returned.

Parameters:

limit - Limit to set

value - Size in bytes of limit

Returns:

CUDA_SUCCESS, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_UNSUPPORTED_LIMIT

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxCreate](#), [cuCtxDestroy](#), [cuCtxGetApiVersion](#), [cuCtxGetCacheConfig](#), [cuCtxGetDevice](#), [cuCtxGetLimit](#), [cuCtxPopCurrent](#), [cuCtxPushCurrent](#), [cuCtxSetCacheConfig](#), [cuCtxSynchronize](#)

4.32.2.13 CUresult cuCtxSynchronize (void)

Blocks until the device has completed all preceding requested tasks. [cuCtxSynchronize\(\)](#) returns an error if one of the preceding tasks failed. If the context was created with the [CU_CTX_SCHED_BLOCKING_SYNC](#) flag, the CPU thread will block until the GPU context has finished its work.

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxCreate](#), [cuCtxDestroy](#), [cuCtxGetApiVersion](#), [cuCtxGetCacheConfig](#), [cuCtxGetDevice](#), [cuCtxGetLimit](#), [cuCtxPopCurrent](#), [cuCtxPushCurrent](#), [cuCtxSetCacheConfig](#), [cuCtxSetLimit](#)

4.33 Context Management [DEPRECATED]

Functions

- [CUresult cuCtxAttach](#) ([CUcontext](#) *pctx, unsigned int flags)

Increment a context's usage-count.

- [CUresult cuCtxDetach](#) ([CUcontext](#) ctx)

Decrement a context's usage-count.

4.33.1 Detailed Description

This section describes the deprecated context management functions of the low-level CUDA driver application programming interface.

4.33.2 Function Documentation

4.33.2.1 CUresult cuCtxAttach (CUcontext *pctx, unsigned int flags)

Deprecated

Note that this function is deprecated and should not be used.

Increments the usage count of the context and passes back a context handle in *pctx that must be passed to [cuCtxDetach\(\)](#) when the application is done with the context. [cuCtxAttach\(\)](#) fails if there is no context current to the thread.

Currently, the flags parameter must be 0.

Parameters:

pctx - Returned context handle of the current context

flags - Context attach flags (must be 0)

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxCreate](#), [cuCtxDestroy](#), [cuCtxDetach](#), [cuCtxGetApiVersion](#), [cuCtxGetCacheConfig](#), [cuCtxGetDevice](#), [cuCtxGetLimit](#), [cuCtxPopCurrent](#), [cuCtxPushCurrent](#), [cuCtxSetCacheConfig](#), [cuCtxSetLimit](#), [cuCtxSynchronize](#)

4.33.2.2 CUresult cuCtxDetach (CUcontext *ctx*)

Deprecated

Note that this function is deprecated and should not be used.

Decrements the usage count of the context `ctx`, and destroys the context if the usage count goes to 0. The context must be a handle that was passed back by [cuCtxCreate\(\)](#) or [cuCtxAttach\(\)](#), and must be current to the calling thread.

Parameters:

ctx - Context to destroy

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxCreate](#), [cuCtxDestroy](#), [cuCtxGetApiVersion](#), [cuCtxGetCacheConfig](#), [cuCtxGetDevice](#), [cuCtxGetLimit](#), [cuCtxPopCurrent](#), [cuCtxPushCurrent](#), [cuCtxSetCacheConfig](#), [cuCtxSetLimit](#), [cuCtxSynchronize](#)

4.34 Module Management

Functions

- **CUresult cuModuleGetFunction** (CUfunction *hfunc, CUmodule hmod, const char *name)
Returns a function handle.
- **CUresult cuModuleGetGlobal** (CUdeviceptr *dptr, size_t *bytes, CUmodule hmod, const char *name)
Returns a global pointer from a module.
- **CUresult cuModuleGetSurfRef** (CUSurfref *pSurfRef, CUmodule hmod, const char *name)
Returns a handle to a surface reference.
- **CUresult cuModuleGetTexRef** (CUTexref *pTexRef, CUmodule hmod, const char *name)
Returns a handle to a texture reference.
- **CUresult cuModuleLoad** (CUmodule *module, const char *fname)
Loads a compute module.
- **CUresult cuModuleLoadData** (CUmodule *module, const void *image)
Load a module's data.
- **CUresult cuModuleLoadDataEx** (CUmodule *module, const void *image, unsigned int numOptions, CUjit_option *options, void **optionValues)
Load a module's data with options.
- **CUresult cuModuleLoadFatBinary** (CUmodule *module, const void *fatCubin)
Load a module's data.
- **CUresult cuModuleUnload** (CUmodule hmod)
Unloads a module.

4.34.1 Detailed Description

This section describes the module management functions of the low-level CUDA driver application programming interface.

4.34.2 Function Documentation

4.34.2.1 CUresult cuModuleGetFunction (CUfunction * hfunc, CUmodule hmod, const char * name)

Returns in *hfunc the handle of the function of name name located in module hmod. If no function of that name exists, cuModuleGetFunction() returns CUDA_ERROR_NOT_FOUND.

Parameters:

- hfunc** - Returned function handle
- hmod** - Module to retrieve function from
- name** - Name of function to retrieve

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_NOT_FOUND](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuModuleGetGlobal](#), [cuModuleGetTexRef](#), [cuModuleLoad](#), [cuModuleLoadData](#), [cuModuleLoadDataEx](#), [cuModuleLoadFatBinary](#), [cuModuleUnload](#)

4.34.2.2 CUresult cuModuleGetGlobal (CUdeviceptr * *dptr*, size_t * *bytes*, CUmodule *hmod*, const char * *name*)

Returns in **dptr* and **bytes* the base pointer and size of the global of name *name* located in module *hmod*. If no variable of that name exists, [cuModuleGetGlobal\(\)](#) returns [CUDA_ERROR_NOT_FOUND](#). Both parameters *dptr* and *bytes* are optional. If one of them is NULL, it is ignored.

Parameters:

dptr - Returned global device pointer
bytes - Returned global size in bytes
hmod - Module to retrieve global from
name - Name of global to retrieve

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_NOT_FOUND](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuModuleGetFunction](#), [cuModuleGetTexRef](#), [cuModuleLoad](#), [cuModuleLoadData](#), [cuModuleLoadDataEx](#), [cuModuleLoadFatBinary](#), [cuModuleUnload](#)

4.34.2.3 CUresult cuModuleGetSurfRef (CUSurfref * *pSurfRef*, CUmodule *hmod*, const char * *name*)

Returns in **pSurfRef* the handle of the surface reference of name *name* in the module *hmod*. If no surface reference of that name exists, [cuModuleGetSurfRef\(\)](#) returns [CUDA_ERROR_NOT_FOUND](#).

Parameters:

pSurfRef - Returned surface reference
hmod - Module to retrieve surface reference from
name - Name of surface reference to retrieve

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_NOT_FOUND

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuModuleGetFunction, cuModuleGetGlobal, cuModuleGetTexRef, cuModuleLoad, cuModuleLoadData, cuModuleLoadDataEx, cuModuleLoadFatBinary, cuModuleUnload

4.34.2.4 CUresult cuModuleGetTexRef (CUtexref **pTexRef*, CUmodule *hmod*, const char **name*)

Returns in *pTexRef the handle of the texture reference of name *name* in the module *hmod*. If no texture reference of that name exists, cuModuleGetTexRef() returns CUDA_ERROR_NOT_FOUND. This texture reference handle should not be destroyed, since it will be destroyed when the module is unloaded.

Parameters:

pTexRef - Returned texture reference
hmod - Module to retrieve texture reference from
name - Name of texture reference to retrieve

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_NOT_FOUND

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuModuleGetFunction, cuModuleGetGlobal, cuModuleGetSurfRef, cuModuleLoad, cuModuleLoadData, cuModuleLoadDataEx, cuModuleLoadFatBinary, cuModuleUnload

4.34.2.5 CUresult cuModuleLoad (CUmodule **module*, const char **fname*)

Takes a filename *fname* and loads the corresponding module *module* into the current context. The CUDA driver API does not attempt to lazily allocate the resources needed by a module; if the memory for functions and data (constant and global) needed by the module cannot be allocated, cuModuleLoad() fails. The file should be a *cubin* file as output by **nvcc**, or a *PTX* file either as output by **nvcc** or handwritten, or a *fatbin* file as output by **nvcc** from toolchain 4.0 or later.

Parameters:

module - Returned module
fname - Filename of module to load

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_NOT_FOUND](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_FILE_NOT_FOUND](#), [CUDA_ERROR_SHARED_OBJECT_SYMBOL_NOT_FOUND](#), [CUDA_ERROR_SHARED_OBJECT_INIT_FAILED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuModuleGetFunction](#), [cuModuleGetGlobal](#), [cuModuleGetTexRef](#), [cuModuleLoadData](#), [cuModuleLoadDataEx](#), [cuModuleLoadFatBinary](#), [cuModuleUnload](#)

4.34.2.6 CUresult cuModuleLoadData (CUmodule * *module*, const void * *image*)

Takes a pointer *image* and loads the corresponding module *module* into the current context. The pointer may be obtained by mapping a *cubin* or *PTX* or *fatbin* file, passing a *cubin* or *PTX* or *fatbin* file as a NULL-terminated text string, or incorporating a *cubin* or *fatbin* object into the executable resources and using operating system calls such as Windows `FindResource()` to obtain the pointer.

Parameters:

module - Returned module
image - Module data to load

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_SHARED_OBJECT_SYMBOL_NOT_FOUND](#), [CUDA_ERROR_SHARED_OBJECT_INIT_FAILED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuModuleGetFunction](#), [cuModuleGetGlobal](#), [cuModuleGetTexRef](#), [cuModuleLoad](#), [cuModuleLoadDataEx](#), [cuModuleLoadFatBinary](#), [cuModuleUnload](#)

4.34.2.7 CUresult cuModuleLoadDataEx (CUmodule * *module*, const void * *image*, unsigned int *numOptions*, CUjit_option * *options*, void ** *optionValues*)

Takes a pointer *image* and loads the corresponding module *module* into the current context. The pointer may be obtained by mapping a *cubin* or *PTX* or *fatbin* file, passing a *cubin* or *PTX* or *fatbin* file as a NULL-terminated text string, or incorporating a *cubin* or *fatbin* object into the executable resources and using operating system calls such as Windows `FindResource()` to obtain the pointer. Options are passed as an array via *options* and any corresponding parameters are passed in *optionValues*. The number of total options is supplied via *numOptions*. Any outputs will be returned via *optionValues*. Supported options are (types for the option values are specified in parentheses after the option name):

- [CU_JIT_MAX_REGISTERS](#): (unsigned int) input specifies the maximum number of registers per thread;
- [CU_JIT_THREADS_PER_BLOCK](#): (unsigned int) input specifies number of threads per block to target compilation for; output returns the number of threads the compiler actually targeted;
- [CU_JIT_WALL_TIME](#): (float) output returns the float value of wall clock time, in milliseconds, spent compiling the *PTX* code;
- [CU_JIT_INFO_LOG_BUFFER](#): (char*) input is a pointer to a buffer in which to print any informational log messages from *PTX* assembly (the buffer size is specified via option [CU_JIT_INFO_LOG_BUFFER_SIZE_BYTES](#));
- [CU_JIT_INFO_LOG_BUFFER_SIZE_BYTES](#): (unsigned int) input is the size in bytes of the buffer; output is the number of bytes filled with messages;
- [CU_JIT_ERROR_LOG_BUFFER](#): (char*) input is a pointer to a buffer in which to print any error log messages from *PTX* assembly (the buffer size is specified via option [CU_JIT_ERROR_LOG_BUFFER_SIZE_BYTES](#));
- [CU_JIT_ERROR_LOG_BUFFER_SIZE_BYTES](#): (unsigned int) input is the size in bytes of the buffer; output is the number of bytes filled with messages;
- [CU_JIT_OPTIMIZATION_LEVEL](#): (unsigned int) input is the level of optimization to apply to generated code (0 - 4), with 4 being the default and highest level;
- [CU_JIT_TARGET_FROM_CUCONTEXT](#): (No option value) causes compilation target to be determined based on current attached context (default);
- [CU_JIT_TARGET](#): (unsigned int for enumerated type [CUjit_target_enum](#)) input is the compilation target based on supplied [CUjit_target_enum](#); possible values are:
 - [CU_TARGET_COMPUTE_10](#)
 - [CU_TARGET_COMPUTE_11](#)
 - [CU_TARGET_COMPUTE_12](#)
 - [CU_TARGET_COMPUTE_13](#)
 - [CU_TARGET_COMPUTE_20](#)
- [CU_JIT_FALLBACK_STRATEGY](#): (unsigned int for enumerated type [CUjit_fallback_enum](#)) chooses fallback strategy if matching cubin is not found; possible values are:
 - [CU_PREFER_PTX](#)
 - [CU_PREFER_BINARY](#)

Parameters:

module - Returned module

image - Module data to load

numOptions - Number of options

options - Options for JIT

optionValues - Option values for JIT

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_NO_BINARY_FOR_GPU](#), [CUDA_ERROR_SHARED_OBJECT_SYMBOL_NOT_FOUND](#), [CUDA_ERROR_SHARED_OBJECT_INIT_FAILED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuModuleGetFunction](#), [cuModuleGetGlobal](#), [cuModuleGetTexRef](#), [cuModuleLoad](#), [cuModuleLoadData](#), [cuModuleLoadFatBinary](#), [cuModuleUnload](#)

4.34.2.8 CUresult cuModuleLoadFatBinary (CUmodule * *module*, const void * *fatCubin*)

Takes a pointer *fatCubin* and loads the corresponding module *module* into the current context. The pointer represents a *fat binary* object, which is a collection of different *cubin* and/or *PTX* files, all representing the same device code, but compiled and optimized for different architectures.

Prior to CUDA 4.0, there was no documented API for constructing and using fat binary objects by programmers. Starting with CUDA 4.0, fat binary objects can be constructed by providing the *-fatbin option* to **nvcc**. More information can be found in the **nvcc** document.

Parameters:

module - Returned module
fatCubin - Fat binary to load

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_NOT_FOUND](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_NO_BINARY_FOR_GPU](#), [CUDA_ERROR_SHARED_OBJECT_SYMBOL_NOT_FOUND](#), [CUDA_ERROR_SHARED_OBJECT_INIT_FAILED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuModuleGetFunction](#), [cuModuleGetGlobal](#), [cuModuleGetTexRef](#), [cuModuleLoad](#), [cuModuleLoadData](#), [cuModuleLoadDataEx](#), [cuModuleUnload](#)

4.34.2.9 CUresult cuModuleUnload (CUmodule *hmod*)

Unloads a module *hmod* from the current context.

Parameters:

hmod - Module to unload

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuModuleGetFunction](#), [cuModuleGetGlobal](#), [cuModuleGetTexRef](#), [cuModuleLoad](#), [cuModuleLoadData](#), [cuModuleLoadDataEx](#), [cuModuleLoadFatBinary](#)

4.35 Memory Management

Functions

- **CUresult cuArray3DCreate** (CUarray *pHandle, const CUDA_ARRAY3D_DESCRIPTOR *pAllocateArray)
Creates a 3D CUDA array.
- **CUresult cuArray3DGetDescriptor** (CUDA_ARRAY3D_DESCRIPTOR *pArrayDescriptor, CUarray hArray)
Get a 3D CUDA array descriptor.
- **CUresult cuArrayCreate** (CUarray *pHandle, const CUDA_ARRAY_DESCRIPTOR *pAllocateArray)
Creates a 1D or 2D CUDA array.
- **CUresult cuArrayDestroy** (CUarray hArray)
Destroys a CUDA array.
- **CUresult cuArrayGetDescriptor** (CUDA_ARRAY_DESCRIPTOR *pArrayDescriptor, CUarray hArray)
Get a 1D or 2D CUDA array descriptor.
- **CUresult cuDeviceGetByPCIBusId** (CUdevice *dev, char *pciBusId)
Returns a handle to a compute device.
- **CUresult cuDeviceGetPCIBusId** (char *pciBusId, int len, CUdevice dev)
Returns a PCI Bus Id string for the device.
- **CUresult cuIpcCloseMemHandle** (CUdeviceptr dptr)
- **CUresult cuIpcGetEventHandle** (CUipcEventHandle *pHandle, CUevent event)
Gets an interprocess handle for a previously allocated event.
- **CUresult cuIpcGetMemHandle** (CUipcMemHandle *pHandle, CUdeviceptr dptr)
- **CUresult cuIpcOpenEventHandle** (CUevent *phEvent, CUipcEventHandle handle)
Opens an interprocess event handle for use in the current process.
- **CUresult cuIpcOpenMemHandle** (CUdeviceptr *pdptr, CUipcMemHandle handle)
- **CUresult cuMemAlloc** (CUdeviceptr *dptr, size_t bytesize)
Allocates device memory.
- **CUresult cuMemAllocHost** (void **pp, size_t bytesize)
Allocates page-locked host memory.
- **CUresult cuMemAllocPitch** (CUdeviceptr *dptr, size_t *pPitch, size_t WidthInBytes, size_t Height, unsigned int ElementSizeBytes)
Allocates pitched device memory.
- **CUresult cuMemcpy** (CUdeviceptr dst, CUdeviceptr src, size_t ByteCount)
Copies memory.
- **CUresult cuMemcpy2D** (const CUDA_MEMCPY2D *pCopy)
Copies memory for 2D arrays.

- **CUresult cuMemcpy2DAsync** (const **CUDA_MEMCPY2D** *pCopy, **CUstream** hStream)
Copies memory for 2D arrays.
- **CUresult cuMemcpy2DUnaligned** (const **CUDA_MEMCPY2D** *pCopy)
Copies memory for 2D arrays.
- **CUresult cuMemcpy3D** (const **CUDA_MEMCPY3D** *pCopy)
Copies memory for 3D arrays.
- **CUresult cuMemcpy3DAsync** (const **CUDA_MEMCPY3D** *pCopy, **CUstream** hStream)
Copies memory for 3D arrays.
- **CUresult cuMemcpy3DPeer** (const **CUDA_MEMCPY3D_PEER** *pCopy)
Copies memory between contexts.
- **CUresult cuMemcpy3DPeerAsync** (const **CUDA_MEMCPY3D_PEER** *pCopy, **CUstream** hStream)
Copies memory between contexts asynchronously.
- **CUresult cuMemcpyAsync** (**CUdeviceptr** dst, **CUdeviceptr** src, size_t ByteCount, **CUstream** hStream)
Copies memory asynchronously.
- **CUresult cuMemcpyAtoA** (**CUarray** dstArray, size_t dstOffset, **CUarray** srcArray, size_t srcOffset, size_t ByteCount)
Copies memory from Array to Array.
- **CUresult cuMemcpyAtoD** (**CUdeviceptr** dstDevice, **CUarray** srcArray, size_t srcOffset, size_t ByteCount)
Copies memory from Array to Device.
- **CUresult cuMemcpyAtoH** (void *dstHost, **CUarray** srcArray, size_t srcOffset, size_t ByteCount)
Copies memory from Array to Host.
- **CUresult cuMemcpyAtoHAsync** (void *dstHost, **CUarray** srcArray, size_t srcOffset, size_t ByteCount, **CUstream** hStream)
Copies memory from Array to Host.
- **CUresult cuMemcpyDtoA** (**CUarray** dstArray, size_t dstOffset, **CUdeviceptr** srcDevice, size_t ByteCount)
Copies memory from Device to Array.
- **CUresult cuMemcpyDtoD** (**CUdeviceptr** dstDevice, **CUdeviceptr** srcDevice, size_t ByteCount)
Copies memory from Device to Device.
- **CUresult cuMemcpyDtoDAsync** (**CUdeviceptr** dstDevice, **CUdeviceptr** srcDevice, size_t ByteCount, **CUstream** hStream)
Copies memory from Device to Device.
- **CUresult cuMemcpyDtoH** (void *dstHost, **CUdeviceptr** srcDevice, size_t ByteCount)
Copies memory from Device to Host.
- **CUresult cuMemcpyDtoHAsync** (void *dstHost, **CUdeviceptr** srcDevice, size_t ByteCount, **CUstream** hStream)

Copies memory from Device to Host.

- [CUresult cuMemcpyHtoA](#) ([CUarray](#) dstArray, size_t dstOffset, const void *srcHost, size_t ByteCount)
Copies memory from Host to Array.
- [CUresult cuMemcpyHtoAAsync](#) ([CUarray](#) dstArray, size_t dstOffset, const void *srcHost, size_t ByteCount, [CUstream](#) hStream)
Copies memory from Host to Array.
- [CUresult cuMemcpyHtoD](#) ([CUdeviceptr](#) dstDevice, const void *srcHost, size_t ByteCount)
Copies memory from Host to Device.
- [CUresult cuMemcpyHtoDAsync](#) ([CUdeviceptr](#) dstDevice, const void *srcHost, size_t ByteCount, [CUstream](#) hStream)
Copies memory from Host to Device.
- [CUresult cuMemcpyPeer](#) ([CUdeviceptr](#) dstDevice, [CUcontext](#) dstContext, [CUdeviceptr](#) srcDevice, [CUcontext](#) srcContext, size_t ByteCount)
Copies device memory between two contexts.
- [CUresult cuMemcpyPeerAsync](#) ([CUdeviceptr](#) dstDevice, [CUcontext](#) dstContext, [CUdeviceptr](#) srcDevice, [CUcontext](#) srcContext, size_t ByteCount, [CUstream](#) hStream)
Copies device memory between two contexts asynchronously.
- [CUresult cuMemFree](#) ([CUdeviceptr](#) dptr)
Frees device memory.
- [CUresult cuMemFreeHost](#) (void *p)
Frees page-locked host memory.
- [CUresult cuMemGetAddressRange](#) ([CUdeviceptr](#) *pbase, size_t *psize, [CUdeviceptr](#) dptr)
Get information on memory allocations.
- [CUresult cuMemGetInfo](#) (size_t *free, size_t *total)
Gets free and total memory.
- [CUresult cuMemHostAlloc](#) (void **pp, size_t bytesize, unsigned int Flags)
Allocates page-locked host memory.
- [CUresult cuMemHostGetDevicePointer](#) ([CUdeviceptr](#) *pdptr, void *p, unsigned int Flags)
Passes back device pointer of mapped pinned memory.
- [CUresult cuMemHostGetFlags](#) (unsigned int *pFlags, void *p)
Passes back flags that were used for a pinned allocation.
- [CUresult cuMemHostRegister](#) (void *p, size_t bytesize, unsigned int Flags)
Registers an existing host memory range for use by CUDA.
- [CUresult cuMemHostUnregister](#) (void *p)
Unregisters a memory range that was registered with [cuMemHostRegister\(\)](#).

- **CUresult cuMemsetD16** (CUdeviceptr dstDevice, unsigned short us, size_t N)
Initializes device memory.
- **CUresult cuMemsetD16Async** (CUdeviceptr dstDevice, unsigned short us, size_t N, CUstream hStream)
Sets device memory.
- **CUresult cuMemsetD2D16** (CUdeviceptr dstDevice, size_t dstPitch, unsigned short us, size_t Width, size_t Height)
Initializes device memory.
- **CUresult cuMemsetD2D16Async** (CUdeviceptr dstDevice, size_t dstPitch, unsigned short us, size_t Width, size_t Height, CUstream hStream)
Sets device memory.
- **CUresult cuMemsetD2D32** (CUdeviceptr dstDevice, size_t dstPitch, unsigned int ui, size_t Width, size_t Height)
Initializes device memory.
- **CUresult cuMemsetD2D32Async** (CUdeviceptr dstDevice, size_t dstPitch, unsigned int ui, size_t Width, size_t Height, CUstream hStream)
Sets device memory.
- **CUresult cuMemsetD2D8** (CUdeviceptr dstDevice, size_t dstPitch, unsigned char uc, size_t Width, size_t Height)
Initializes device memory.
- **CUresult cuMemsetD2D8Async** (CUdeviceptr dstDevice, size_t dstPitch, unsigned char uc, size_t Width, size_t Height, CUstream hStream)
Sets device memory.
- **CUresult cuMemsetD32** (CUdeviceptr dstDevice, unsigned int ui, size_t N)
Initializes device memory.
- **CUresult cuMemsetD32Async** (CUdeviceptr dstDevice, unsigned int ui, size_t N, CUstream hStream)
Sets device memory.
- **CUresult cuMemsetD8** (CUdeviceptr dstDevice, unsigned char uc, size_t N)
Initializes device memory.
- **CUresult cuMemsetD8Async** (CUdeviceptr dstDevice, unsigned char uc, size_t N, CUstream hStream)
Sets device memory.

4.35.1 Detailed Description

This section describes the memory management functions of the low-level CUDA driver application programming interface.

4.35.2 Function Documentation

4.35.2.1 CUresult cuArray3DCreate (CUarray * *pHandle*, const CUDA_ARRAY3D_DESCRIPTOR * *pAllocateArray*)

Creates a CUDA array according to the [CUDA_ARRAY3D_DESCRIPTOR](#) structure *pAllocateArray* and returns a handle to the new CUDA array in *pHandle*. The [CUDA_ARRAY3D_DESCRIPTOR](#) is defined as:

```
typedef struct {
    unsigned int Width;
    unsigned int Height;
    unsigned int Depth;
    CUarray_format Format;
    unsigned int NumChannels;
    unsigned int Flags;
} CUDA_ARRAY3D_DESCRIPTOR;
```

where:

- Width, Height, and Depth are the width, height, and depth of the CUDA array (in elements); the following types of CUDA arrays can be allocated:
 - A 1D array is allocated if Height and Depth extents are both zero.
 - A 2D array is allocated if only Depth extent is zero.
 - A 3D array is allocated if all three extents are non-zero.
 - A 1D layered CUDA array is allocated if only Height is zero and the [CUDA_ARRAY3D_LAYERED](#) flag is set. Each layer is a 1D array. The number of layers is determined by the depth extent.
 - A 2D layered CUDA array is allocated if all three extents are non-zero and the [CUDA_ARRAY3D_LAYERED](#) flag is set. Each layer is a 2D array. The number of layers is determined by the depth extent.
 - A cubemap CUDA array is allocated if all three extents are non-zero and the [CUDA_ARRAY3D_CUBEMAP](#) flag is set. Width must be equal to Height, and Depth must be six. A cubemap is a special type of 2D layered CUDA array, where the six layers represent the six faces of a cube. The order of the six layers in memory is the same as that listed in [CUarray_cubemap_face](#).
 - A cubemap layered CUDA array is allocated if all three extents are non-zero, and both, [CUDA_ARRAY3D_CUBEMAP](#) and [CUDA_ARRAY3D_LAYERED](#) flags are set. Width must be equal to Height, and Depth must be a multiple of six. A cubemap layered CUDA array is a special type of 2D layered CUDA array that consists of a collection of cubemaps. The first six layers represent the first cubemap, the next six layers form the second cubemap, and so on.
- Format specifies the format of the elements; [CUarray_format](#) is defined as:

```
typedef enum CUarray_format_enum {
    CU_AD_FORMAT_UNSIGNED_INT8 = 0x01,
    CU_AD_FORMAT_UNSIGNED_INT16 = 0x02,
    CU_AD_FORMAT_UNSIGNED_INT32 = 0x03,
    CU_AD_FORMAT_SIGNED_INT8 = 0x08,
    CU_AD_FORMAT_SIGNED_INT16 = 0x09,
    CU_AD_FORMAT_SIGNED_INT32 = 0x0a,
    CU_AD_FORMAT_HALF = 0x10,
    CU_AD_FORMAT_FLOAT = 0x20
} CUarray_format;
```

- NumChannels specifies the number of packed components per CUDA array element; it may be 1, 2, or 4;
- Flags may be set to

- [CUDA_ARRAY3D_LAYERED](#) to enable creation of layered CUDA arrays. If this flag is set, `Depth` specifies the number of layers, not the depth of a 3D array.
- [CUDA_ARRAY3D_SURFACE_LDST](#) to enable surface references to be bound to the CUDA array. If this flag is not set, `cuSurfRefSetArray` will fail when attempting to bind the CUDA array to a surface reference.
- [CUDA_ARRAY3D_CUBEMAP](#) to enable creation of cubemaps. If this flag is set, `Width` must be equal to `Height`, and `Depth` must be six. If the [CUDA_ARRAY3D_LAYERED](#) flag is also set, then `Depth` must be a multiple of six.
- [CUDA_ARRAY3D_TEXTURE_GATHER](#) to indicate that the CUDA array will be used for texture gather. Texture gather can only be performed on 2D CUDA arrays.

`Width`, `Height` and `Depth` must meet certain size requirements as listed in the following table. All values are specified in elements. Note that for brevity's sake, the full name of the device attribute is not specified. For ex., `TEXTURE1D_WIDTH` refers to the device attribute [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_WIDTH](#).

Note that 2D CUDA arrays have different size requirements if the [CUDA_ARRAY3D_TEXTURE_GATHER](#) flag is set. `Width` and `Height` must not be greater than [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_GATHER_WIDTH](#) and [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_GATHER_HEIGHT](#) respectively, in that case.

CUDA array type	Valid extents that must always be met {(width range in elements), (height range), (depth range)}	Valid extents with CUDA_ARRAY3D_SURFACE_LDST set {(width range in elements), (height range), (depth range)}
1D	{ (1,TEXTURE1D_WIDTH), 0, 0 }	{ (1,SURFACE1D_WIDTH), 0, 0 }
2D	{ (1,TEXTURE2D_WIDTH), (1,TEXTURE2D_HEIGHT), 0 }	{ (1,SURFACE2D_WIDTH), (1,SURFACE2D_HEIGHT), 0 }
3D	{ (1,TEXTURE3D_WIDTH), (1,TEXTURE3D_HEIGHT), (1,TEXTURE3D_DEPTH) } OR { (1,TEXTURE3D_WIDTH_ALTERNATE), (1,TEXTURE3D_HEIGHT_ALTERNATE), (1,TEXTURE3D_DEPTH_ALTERNATE) }	{ (1,SURFACE3D_WIDTH), (1,SURFACE3D_HEIGHT), (1,SURFACE3D_DEPTH) }
1D Layered	{ (1,TEXTURE1D_LAYERED_WIDTH), 0, (1,TEXTURE1D_LAYERED_LAYERS) }	{ (1,SURFACE1D_LAYERED_WIDTH), 0, (1,SURFACE1D_LAYERED_LAYERS) }
2D Layered	{ (1,TEXTURE2D_LAYERED_WIDTH), (1,TEXTURE2D_LAYERED_HEIGHT), (1,TEXTURE2D_LAYERED_LAYERS) }	{ (1,SURFACE2D_LAYERED_WIDTH), (1,SURFACE2D_LAYERED_HEIGHT), (1,SURFACE2D_LAYERED_LAYERS) }
Cubemap	{ (1,TEXTURECUBEMAP_WIDTH), (1,TEXTURECUBEMAP_WIDTH), 6 }	{ (1,SURFACECUBEMAP_WIDTH), (1,SURFACECUBEMAP_WIDTH), 6 }
Cubemap Layered	{ (1,TEXTURECUBEMAP_LAYERED_WIDTH), (1,TEXTURECUBEMAP_LAYERED_WIDTH), (1,TEXTURECUBEMAP_LAYERED_LAYERS) }	{ (1,SURFACECUBEMAP_LAYERED_WIDTH), (1,SURFACECUBEMAP_LAYERED_WIDTH), (1,SURFACECUBEMAP_LAYERED_LAYERS) }

Here are examples of CUDA array descriptions:

Description for a CUDA array of 2048 floats:

```
CUDA_ARRAY3D_DESCRIPTOR desc;
```

```
desc.Format = CU_AD_FORMAT_FLOAT;
desc.NumChannels = 1;
desc.Width = 2048;
desc.Height = 0;
desc.Depth = 0;
```

Description for a 64 x 64 CUDA array of floats:

```
CUDA_ARRAY3D_DESCRIPTOR desc;
desc.Format = CU_AD_FORMAT_FLOAT;
desc.NumChannels = 1;
desc.Width = 64;
desc.Height = 64;
desc.Depth = 0;
```

Description for a width x height x depth CUDA array of 64-bit, 4x16-bit float16's:

```
CUDA_ARRAY3D_DESCRIPTOR desc;
desc.FormatFlags = CU_AD_FORMAT_HALF;
desc.NumChannels = 4;
desc.Width = width;
desc.Height = height;
desc.Depth = depth;
```

Parameters:

pHandle - Returned array
pAllocateArray - 3D array descriptor

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_OUT_OF_MEMORY, CUDA_ERROR_UNKNOWN

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.2 CUresult cuArray3DGetDescriptor (CUDA_ARRAY3D_DESCRIPTOR * pArrayDescriptor, CUarray hArray)

Returns in *pArrayDescriptor a descriptor containing information on the format and dimensions of the CUDA array hArray. It is useful for subroutines that have been passed a CUDA array, but need to know the CUDA array parameters for validation or other purposes.

This function may be called on 1D and 2D arrays, in which case the Height and/or Depth members of the descriptor struct will be set to 0.

Parameters:

pArrayDescriptor - Returned 3D array descriptor

hArray - 3D array to get descriptor of

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_INVALID_HANDLE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D16, cuMemsetD2D32, cuMemsetD8, cuMemsetD16, cuMemsetD32

4.35.2.3 CUresult cuArrayCreate (CUarray * *pHandle*, const CUDA_ARRAY_DESCRIPTOR * *pAllocateArray*)

Creates a CUDA array according to the [CUDA_ARRAY_DESCRIPTOR](#) structure *pAllocateArray* and returns a handle to the new CUDA array in *pHandle*. The [CUDA_ARRAY_DESCRIPTOR](#) is defined as:

```
typedef struct {
    unsigned int Width;
    unsigned int Height;
    CUarray_format Format;
    unsigned int NumChannels;
} CUDA_ARRAY_DESCRIPTOR;
```

where:

- Width, and Height are the width, and height of the CUDA array (in elements); the CUDA array is one-dimensional if height is 0, two-dimensional otherwise;
- Format specifies the format of the elements; [CUarray_format](#) is defined as:

```
typedef enum CUarray_format_enum {
    CU_AD_FORMAT_UNSIGNED_INT8 = 0x01,
    CU_AD_FORMAT_UNSIGNED_INT16 = 0x02,
    CU_AD_FORMAT_UNSIGNED_INT32 = 0x03,
    CU_AD_FORMAT_SIGNED_INT8 = 0x08,
    CU_AD_FORMAT_SIGNED_INT16 = 0x09,
    CU_AD_FORMAT_SIGNED_INT32 = 0x0a,
    CU_AD_FORMAT_HALF = 0x10,
    CU_AD_FORMAT_FLOAT = 0x20
} CUarray_format;
```

- NumChannels specifies the number of packed components per CUDA array element; it may be 1, 2, or 4;

Here are examples of CUDA array descriptions:

Description for a CUDA array of 2048 floats:

```
CUDA_ARRAY_DESCRIPTOR desc;
desc.Format = CU_AD_FORMAT_FLOAT;
desc.NumChannels = 1;
desc.Width = 2048;
desc.Height = 1;
```

Description for a 64 x 64 CUDA array of floats:

```
CUDA_ARRAY_DESCRIPTOR desc;
desc.Format = CU_AD_FORMAT_FLOAT;
desc.NumChannels = 1;
desc.Width = 64;
desc.Height = 64;
```

Description for a width x height CUDA array of 64-bit, 4x16-bit float16's:

```
CUDA_ARRAY_DESCRIPTOR desc;
desc.FormatFlags = CU_AD_FORMAT_HALF;
desc.NumChannels = 4;
desc.Width = width;
desc.Height = height;
```

Description for a width x height CUDA array of 16-bit elements, each of which is two 8-bit unsigned chars:

```
CUDA_ARRAY_DESCRIPTOR arrayDesc;
desc.FormatFlags = CU_AD_FORMAT_UNSIGNED_INT8;
desc.NumChannels = 2;
desc.Width = width;
desc.Height = height;
```

Parameters:

pHandle - Returned array
pAllocateArray - Array descriptor

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.4 CUresult cuArrayDestroy (CUarray *hArray*)

Destroys the CUDA array *hArray*.

Parameters:

hArray - Array to destroy

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_HANDLE, CUDA_ERROR_ARRAY_IS_MAPPED

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D16, cuMemsetD2D32, cuMemsetD8, cuMemsetD16, cuMemsetD32

4.35.2.5 CUresult cuArrayGetDescriptor (CUDA_ARRAY_DESCRIPTOR **pArrayDescriptor*, CUarray *hArray*)

Returns in *pArrayDescriptor* a descriptor containing information on the format and dimensions of the CUDA array *hArray*. It is useful for subroutines that have been passed a CUDA array, but need to know the CUDA array parameters for validation or other purposes.

Parameters:

pArrayDescriptor - Returned array descriptor

hArray - Array to get descriptor of

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_INVALID_HANDLE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D16, cuMemsetD2D32, cuMemsetD8, cuMemsetD16, cuMemsetD32

4.35.2.6 CUresult cuDeviceGetByPCIBusId (CUdevice *dev, char *pciBusId)

Returns in *device a device handle given a PCI bus ID string.

Parameters:

dev - Returned device handle

pciBusId - String in one of the following forms: [domain]:[bus]:[device].[function] [domain]:[bus]:[device] [bus]:[device].[function] where domain, bus, device, and function are all hexadecimal values

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_INVALID_DEVICE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuDeviceGet](#), [cuDeviceGetAttribute](#), [cuDeviceGetPCIBusId](#)

4.35.2.7 CUresult cuDeviceGetPCIBusId (char *pciBusId, int len, CUdevice dev)

Returns an ASCII string identifying the device dev in the NULL-terminated string pointed to by pciBusId. len specifies the maximum length of the string that may be returned.

Parameters:

pciBusId - Returned identifier string for the device in the following format [domain]:[bus]:[device].[function] where domain, bus, device, and function are all hexadecimal values. pciBusId should be large enough to store 13 characters including the NULL-terminator.

len - Maximum length of string to store in name

dev - Device to get identifier string for

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_INVALID_DEVICE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuDeviceGet](#), [cuDeviceGetAttribute](#), [cuDeviceGetByPCIBusId](#)

4.35.2.8 CUresult cuIpcCloseMemHandle (CUdeviceptr dptr)

/brief Close memory mapped with [cuIpcOpenMemHandle](#)

Unmaps memory returned by [cuIpcOpenMemHandle](#). The original allocation in the exporting process as well as imported mappings in other processes will be unaffected.

Any resources used to enable peer access will be freed if this is the last mapping using them.

Parameters:

dptr - Device pointer returned by [cuIpcOpenMemHandle](#)

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_MAP_FAILED](#), [CUDA_ERROR_INVALID_HANDLE](#),

See also:

[cuMemAlloc](#), [cuMemFree](#), [cuIpcGetEventHandle](#), [cuIpcOpenEventHandle](#), [cuIpcGetMemHandle](#), [cuIpcOpenMemHandle](#),

4.35.2.9 CUresult cuIpcGetEventHandle (CUipcEventHandle * *pHandle*, CUevent *event*)

Takes as input a previously allocated event. This event must have been created with the [CU_EVENT_INTERPROCESS](#) and [CU_EVENT_DISABLE_TIMING](#) flags set. This opaque handle may be copied into other processes and opened with [cuIpcOpenEventHandle](#) to allow efficient hardware synchronization between GPU work in different processes.

After the event has been opened in the importing process, [cuEventRecord](#), [cuEventSynchronize](#), [cuStreamWaitEvent](#) and [cuEventQuery](#) may be used in either process. Performing operations on the imported event after the exported event has been freed with [cuEventDestroy](#) will result in undefined behavior.

Parameters:

pHandle - Pointer to a user allocated CUipcEventHandle in which to return the opaque event handle

event - Event allocated with [CU_EVENT_INTERPROCESS](#) and [CU_EVENT_DISABLE_TIMING](#) flags.

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_MAP_FAILED](#)

See also:

[cuEventCreate](#), [cuEventDestroy](#), [cuEventSynchronize](#), [cuEventQuery](#), [cuStreamWaitEvent](#), [cuIpcOpenEventHandle](#), [cuIpcGetMemHandle](#), [cuIpcOpenMemHandle](#), [cuIpcCloseMemHandle](#)

4.35.2.10 CUresult cuIpcGetMemHandle (CUipcMemHandle * *pHandle*, CUdeviceptr *dptr*)

/brief Gets an interprocess memory handle for an existing device memory allocation

Takes a pointer to the base of an existing device memory allocation created with [cuMemAlloc](#) and exports it for use in another process. This is a lightweight operation and may be called multiple times on an allocation without adverse effects.

If a region of memory is freed with [cuMemFree](#) and a subsequent call to [cuMemAlloc](#) returns memory with the same device address, [cuIpcGetMemHandle](#) will return a unique handle for the new memory.

Parameters:

pHandle - Pointer to user allocated CUipcMemHandle to return the handle in.

dptr - Base pointer to previously allocated device memory

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_MAP_FAILED](#),

See also:

[cuMemAlloc](#), [cuMemFree](#), [cuIpcGetEventHandle](#), [cuIpcOpenEventHandle](#), [cuIpcOpenMemHandle](#), [cuIpcCloseMemHandle](#)

4.35.2.11 CUresult cuIpcOpenEventHandle (CUevent * *phEvent*, CUipcEventHandle *handle*)

Opens an interprocess event handle exported from another process with [cuIpcGetEventHandle](#). This function returns a [CUevent](#) that behaves like a locally created event with the [CU_EVENT_DISABLE_TIMING](#) flag specified. This event must be freed with [cuEventDestroy](#).

Performing operations on the imported event after the exported event has been freed with [cuEventDestroy](#) will result in undefined behavior.

Parameters:

phEvent - Returns the imported event

handle - Interprocess handle to open

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_MAP_FAILED](#), [CUDA_ERROR_INVALID_HANDLE](#)

See also:

[cuEventCreate](#), [cuEventDestroy](#), [cuEventSynchronize](#), [cuEventQuery](#), [cuStreamWaitEvent](#), [cuIpcGetEventHandle](#), [cuIpcGetMemHandle](#), [cuIpcOpenMemHandle](#), [cuIpcCloseMemHandle](#)

4.35.2.12 CUresult cuIpcOpenMemHandle (CUdeviceptr * *pdptr*, CUipcMemHandle *handle*)

/brief Opens an interprocess memory handle exported from another process and returns a device pointer usable in the local process.

Maps memory exported from another process with [cuIpcGetMemHandle](#) into the current device address space. For contexts on different devices [cuIpcOpenMemHandle](#) will attempt to enable peer access between the devices as if the user called [cuCtxEnablePeerAccess](#). Calling [cuDeviceCanAccessPeer](#) can determine if this mapping is possible.

Calling [cuMemFree](#) on an exported memory region before calling [cuIpcCloseMemHandle](#) in the importing context will result in undefined behavior.

Memory returned from [cuIpcOpenMemHandle](#) must be freed with [cuIpcCloseMemHandle](#).

Parameters:

pdptr - Returned device pointer

handle - CUipcMemHandle to open

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_MAP_FAILED](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_TOO_MANY_PEERS](#)

See also:

[cuMemAlloc](#), [cuMemFree](#), [cuIpcGetEventHandle](#), [cuIpcOpenEventHandle](#), [cuIpcGetMemHandle](#), [cuIpcCloseMemHandle](#), [cuCtxEnablePeerAccess](#), [cuDeviceCanAccessPeer](#),

4.35.2.13 CUresult cuMemAlloc (CUdeviceptr * *dptr*, size_t *bytesize*)

Allocates *bytesize* bytes of linear memory on the device and returns in **dptr* a pointer to the allocated memory. The allocated memory is suitably aligned for any kind of variable. The memory is not cleared. If *bytesize* is 0, [cuMemAlloc\(\)](#) returns [CUDA_ERROR_INVALID_VALUE](#).

Parameters:

dptr - Returned device pointer

bytesize - Requested allocation size in bytes

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.14 CUresult cuMemAllocHost (void ** *pp*, size_t *bytesize*)

Allocates *bytesize* bytes of host memory that is page-locked and accessible to the device. The driver tracks the virtual memory ranges allocated with this function and automatically accelerates calls to functions such as [cuMemcpy\(\)](#). Since the memory can be accessed directly by the device, it can be read or written with much higher bandwidth than pageable memory obtained with functions such as `malloc()`. Allocating excessive amounts of memory with [cuMemAllocHost\(\)](#) may degrade system performance, since it reduces the amount of memory available to the system for paging. As a result, this function is best used sparingly to allocate staging areas for data exchange between host and device.

Note all host memory allocated using [cuMemHostAlloc\(\)](#) will automatically be immediately accessible to all contexts on all devices which support unified addressing (as may be queried using [CU_DEVICE_ATTRIBUTE_UNIFIED_ADDRESSING](#)). The device pointer that may be used to access this host memory from those contexts is always equal to the returned host pointer **pp*. See [Unified Addressing](#) for additional details.

Parameters:

pp - Returned host pointer to page-locked memory

bytesize - Requested allocation size in bytes

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_OUT_OF_MEMORY

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.15 CUresult cuMemAllocPitch (CUdeviceptr * *dptr*, size_t * *pPitch*, size_t *WidthInBytes*, size_t *Height*, unsigned int *ElementSizeBytes*)

Allocates at least *WidthInBytes* * *Height* bytes of linear memory on the device and returns in **dptr* a pointer to the allocated memory. The function may pad the allocation to ensure that corresponding pointers in any given row will continue to meet the alignment requirements for coalescing as the address is updated from row to row. *ElementSizeBytes* specifies the size of the largest reads and writes that will be performed on the memory range. *ElementSizeBytes* may be 4, 8 or 16 (since coalesced memory transactions are not possible on other data sizes). If *ElementSizeBytes* is smaller than the actual read/write size of a kernel, the kernel will run correctly, but possibly at reduced speed. The pitch returned in **pPitch* by [cuMemAllocPitch\(\)](#) is the width in bytes of the allocation. The intended usage of pitch is as a separate parameter of the allocation, used to compute addresses within the 2D array. Given the row and column of an array element of type **T**, the address is computed as:

```
T* pElement = (T*)((char*)BaseAddress + Row * Pitch) + Column;
```

The pitch returned by [cuMemAllocPitch\(\)](#) is guaranteed to work with [cuMemcpy2D\(\)](#) under all circumstances. For allocations of 2D arrays, it is recommended that programmers consider performing pitch allocations using [cuMemAllocPitch\(\)](#). Due to alignment restrictions in the hardware, this is especially true if the application will be performing 2D memory copies between different regions of device memory (whether linear memory or CUDA arrays).

The byte alignment of the pitch returned by [cuMemAllocPitch\(\)](#) is guaranteed to match or exceed the alignment requirement for texture binding with [cuTexRefSetAddress2D\(\)](#).

Parameters:

dptr - Returned device pointer
pPitch - Returned pitch of allocation in bytes
WidthInBytes - Requested allocation width in bytes
Height - Requested allocation height in rows
ElementSizeBytes - Size of largest reads/writes for range

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_OUT_OF_MEMORY

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.16 CUresult cuMemcpy (CUdeviceptr *dst*, CUdeviceptr *src*, size_t *ByteCount*)

Copies data between two pointers. *dst* and *src* are base pointers of the destination and source, respectively. *ByteCount* specifies the number of bytes to copy. Note that this function infers the type of the transfer (host to host, host to device, device to device, or device to host) from the pointer values. This function is only allowed in contexts which support unified addressing. Note that this function is synchronous.

Parameters:

dst - Destination unified virtual address space pointer

src - Source unified virtual address space pointer

ByteCount - Size of memory copy in bytes

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.17 CUresult cuMemcpy2D (const CUDA_MEMCPY2D **pCopy*)

Perform a 2D memory copy according to the parameters specified in *pCopy*. The [CUDA_MEMCPY2D](#) structure is defined as:

```
typedef struct CUDA_MEMCPY2D_st {
    unsigned int srcXInBytes, srcY;
    CUMemorytype srcMemoryType;
```

```

    const void *srcHost;
    CUdeviceptr srcDevice;
    CUarray srcArray;
    unsigned int srcPitch;

    unsigned int dstXInBytes, dstY;
    CUMemorytype dstMemoryType;
    void *dstHost;
    CUdeviceptr dstDevice;
    CUarray dstArray;
    unsigned int dstPitch;

    unsigned int WidthInBytes;
    unsigned int Height;
} CUDA_MEMCPY2D;

```

where:

- srcMemoryType and dstMemoryType specify the type of memory of the source and destination, respectively; [CUMemorytype_enum](#) is defined as:

```

typedef enum CUMemorytype_enum {
    CU_MEMORYTYPE_HOST = 0x01,
    CU_MEMORYTYPE_DEVICE = 0x02,
    CU_MEMORYTYPE_ARRAY = 0x03,
    CU_MEMORYTYPE_UNIFIED = 0x04
} CUMemorytype;

```

If srcMemoryType is [CU_MEMORYTYPE_UNIFIED](#), srcDevice and srcPitch specify the (unified virtual address space) base address of the source data and the bytes per row to apply. srcArray is ignored. This value may be used only if unified addressing is supported in the calling context.

If srcMemoryType is [CU_MEMORYTYPE_HOST](#), srcHost and srcPitch specify the (host) base address of the source data and the bytes per row to apply. srcArray is ignored.

If srcMemoryType is [CU_MEMORYTYPE_DEVICE](#), srcDevice and srcPitch specify the (device) base address of the source data and the bytes per row to apply. srcArray is ignored.

If srcMemoryType is [CU_MEMORYTYPE_ARRAY](#), srcArray specifies the handle of the source data. srcHost, srcDevice and srcPitch are ignored.

If dstMemoryType is [CU_MEMORYTYPE_HOST](#), dstHost and dstPitch specify the (host) base address of the destination data and the bytes per row to apply. dstArray is ignored.

If dstMemoryType is [CU_MEMORYTYPE_UNIFIED](#), dstDevice and dstPitch specify the (unified virtual address space) base address of the source data and the bytes per row to apply. dstArray is ignored. This value may be used only if unified addressing is supported in the calling context.

If dstMemoryType is [CU_MEMORYTYPE_DEVICE](#), dstDevice and dstPitch specify the (device) base address of the destination data and the bytes per row to apply. dstArray is ignored.

If `dstMemoryType` is [CU_MEMORYTYPE_ARRAY](#), `dstArray` specifies the handle of the destination data. `dstHost`, `dstDevice` and `dstPitch` are ignored.

- `srcXInBytes` and `srcY` specify the base address of the source data for the copy.

For host pointers, the starting address is

```
void* Start = (void*)((char*)srcHost+srcY*srcPitch + srcXInBytes);
```

For device pointers, the starting address is

```
CUdeviceptr Start = srcDevice+srcY*srcPitch+srcXInBytes;
```

For CUDA arrays, `srcXInBytes` must be evenly divisible by the array element size.

- `dstXInBytes` and `dstY` specify the base address of the destination data for the copy.

For host pointers, the base address is

```
void* dstStart = (void*)((char*)dstHost+dstY*dstPitch + dstXInBytes);
```

For device pointers, the starting address is

```
CUdeviceptr dstStart = dstDevice+dstY*dstPitch+dstXInBytes;
```

For CUDA arrays, `dstXInBytes` must be evenly divisible by the array element size.

- `WidthInBytes` and `Height` specify the width (in bytes) and height of the 2D copy being performed.
- If specified, `srcPitch` must be greater than or equal to `WidthInBytes + srcXInBytes`, and `dstPitch` must be greater than or equal to `WidthInBytes + dstXInBytes`.

[cuMemcpy2D\(\)](#) returns an error if any pitch is greater than the maximum allowed ([CU_DEVICE_ATTRIBUTE_MAX_PITCH](#)). [cuMemAllocPitch\(\)](#) passes back pitches that always work with [cuMemcpy2D\(\)](#). On intra-device memory copies (device to device, CUDA array to device, CUDA array to CUDA array), [cuMemcpy2D\(\)](#) may fail for pitches not computed by [cuMemAllocPitch\(\)](#). [cuMemcpy2DUnaligned\(\)](#) does not have this restriction, but may run significantly slower in the cases where [cuMemcpy2D\(\)](#) would have returned an error code.

Parameters:

pCopy - Parameters for the memory copy

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.18 CUresult cuMemcpy2DAsync (const CUDA_MEMCPY2D *pCopy, CUstream hStream)

Perform a 2D memory copy according to the parameters specified in `pCopy`. The [CUDA_MEMCPY2D](#) structure is defined as:

```
typedef struct CUDA_MEMCPY2D_st {
    unsigned int srcXInBytes, srcY;
    CUMemorytype srcMemoryType;
    const void *srcHost;
    CUdeviceptr srcDevice;
    CUarray srcArray;
    unsigned int srcPitch;
    unsigned int dstXInBytes, dstY;
    CUMemorytype dstMemoryType;
    void *dstHost;
    CUdeviceptr dstDevice;
    CUarray dstArray;
    unsigned int dstPitch;
    unsigned int WidthInBytes;
    unsigned int Height;
} CUDA_MEMCPY2D;
```

where:

- `srcMemoryType` and `dstMemoryType` specify the type of memory of the source and destination, respectively; [CUMemorytype_enum](#) is defined as:

```
typedef enum CUMemorytype_enum {
    CU_MEMORYTYPE_HOST = 0x01,
    CU_MEMORYTYPE_DEVICE = 0x02,
    CU_MEMORYTYPE_ARRAY = 0x03,
    CU_MEMORYTYPE_UNIFIED = 0x04
} CUMemorytype;
```

If `srcMemoryType` is [CU_MEMORYTYPE_HOST](#), `srcHost` and `srcPitch` specify the (host) base address of the source data and the bytes per row to apply. `srcArray` is ignored.

If `srcMemoryType` is [CU_MEMORYTYPE_UNIFIED](#), `srcDevice` and `srcPitch` specify the (unified virtual address space) base address of the source data and the bytes per row to apply. `srcArray` is ignored. This value may be used only if unified addressing is supported in the calling context.

If `srcMemoryType` is [CU_MEMORYTYPE_DEVICE](#), `srcDevice` and `srcPitch` specify the (device) base address of the source data and the bytes per row to apply. `srcArray` is ignored.

If `srcMemoryType` is `CU_MEMORYTYPE_ARRAY`, `srcArray` specifies the handle of the source data. `srcHost`, `srcDevice` and `srcPitch` are ignored.

If `dstMemoryType` is `CU_MEMORYTYPE_UNIFIED`, `dstDevice` and `dstPitch` specify the (unified virtual address space) base address of the source data and the bytes per row to apply. `dstArray` is ignored. This value may be used only if unified addressing is supported in the calling context.

If `dstMemoryType` is `CU_MEMORYTYPE_HOST`, `dstHost` and `dstPitch` specify the (host) base address of the destination data and the bytes per row to apply. `dstArray` is ignored.

If `dstMemoryType` is `CU_MEMORYTYPE_DEVICE`, `dstDevice` and `dstPitch` specify the (device) base address of the destination data and the bytes per row to apply. `dstArray` is ignored.

If `dstMemoryType` is `CU_MEMORYTYPE_ARRAY`, `dstArray` specifies the handle of the destination data. `dstHost`, `dstDevice` and `dstPitch` are ignored.

- `srcXInBytes` and `srcY` specify the base address of the source data for the copy.

For host pointers, the starting address is

```
void* Start = (void*)((char*)srcHost+srcY*srcPitch + srcXInBytes);
```

For device pointers, the starting address is

```
CUdeviceptr Start = srcDevice+srcY*srcPitch+srcXInBytes;
```

For CUDA arrays, `srcXInBytes` must be evenly divisible by the array element size.

- `dstXInBytes` and `dstY` specify the base address of the destination data for the copy.

For host pointers, the base address is

```
void* dstStart = (void*)((char*)dstHost+dstY*dstPitch + dstXInBytes);
```

For device pointers, the starting address is

```
CUdeviceptr dstStart = dstDevice+dstY*dstPitch+dstXInBytes;
```

For CUDA arrays, `dstXInBytes` must be evenly divisible by the array element size.

- `WidthInBytes` and `Height` specify the width (in bytes) and height of the 2D copy being performed.
- If specified, `srcPitch` must be greater than or equal to `WidthInBytes + srcXInBytes`, and `dstPitch` must be greater than or equal to `WidthInBytes + dstXInBytes`.

- If specified, `srcPitch` must be greater than or equal to `WidthInBytes + srcXInBytes`, and `dstPitch` must be greater than or equal to `WidthInBytes + dstXInBytes`.
- If specified, `srcHeight` must be greater than or equal to `Height + srcY`, and `dstHeight` must be greater than or equal to `Height + dstY`.

`cuMemcpy2D()` returns an error if any pitch is greater than the maximum allowed (`CU_DEVICE_ATTRIBUTE_MAX_PITCH`). `cuMemAllocPitch()` passes back pitches that always work with `cuMemcpy2D()`. On intra-device memory copies (device to device, CUDA array to device, CUDA array to CUDA array), `cuMemcpy2D()` may fail for pitches not computed by `cuMemAllocPitch()`. `cuMemcpy2DUnaligned()` does not have this restriction, but may run significantly slower in the cases where `cuMemcpy2D()` would have returned an error code.

`cuMemcpy2DAsync()` is asynchronous and can optionally be associated to a stream by passing a non-zero `hStream` argument. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input.

Parameters:

pCopy - Parameters for the memory copy

hStream - Stream identifier

Returns:

`CUDA_SUCCESS`, `CUDA_ERROR_DEINITIALIZED`, `CUDA_ERROR_NOT_INITIALIZED`, `CUDA_ERROR_INVALID_CONTEXT`, `CUDA_ERROR_INVALID_VALUE`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cuArray3DCreate`, `cuArray3DGetDescriptor`, `cuArrayCreate`, `cuArrayDestroy`, `cuArrayGetDescriptor`, `cuMemAlloc`, `cuMemAllocHost`, `cuMemAllocPitch`, `cuMemcpy2D`, `cuMemcpy2DUnaligned`, `cuMemcpy3D`, `cuMemcpy3DAsync`, `cuMemcpyAtoA`, `cuMemcpyAtoD`, `cuMemcpyAtoH`, `cuMemcpyAtoHAsync`, `cuMemcpyDtoA`, `cuMemcpyDtoD`, `cuMemcpyDtoDAsync`, `cuMemcpyDtoH`, `cuMemcpyDtoHAsync`, `cuMemcpyHtoA`, `cuMemcpyHtoAAsync`, `cuMemcpyHtoD`, `cuMemcpyHtoDAsync`, `cuMemFree`, `cuMemFreeHost`, `cuMemGetAddressRange`, `cuMemGetInfo`, `cuMemHostAlloc`, `cuMemHostGetDevicePointer`, `cuMemsetD2D8`, `cuMemsetD2D8Async`, `cuMemsetD2D16`, `cuMemsetD2D16Async`, `cuMemsetD2D32`, `cuMemsetD2D32Async`, `cuMemsetD8`, `cuMemsetD8Async`, `cuMemsetD16`, `cuMemsetD16Async`, `cuMemsetD32`, `cuMemsetD32Async`

4.35.2.19 CUresult cuMemcpy2DUnaligned (const CUDA_MEMCPY2D * pCopy)

Perform a 2D memory copy according to the parameters specified in `pCopy`. The `CUDA_MEMCPY2D` structure is defined as:

```
typedef struct CUDA_MEMCPY2D_st {
    unsigned int srcXInBytes, srcY;
    CUMemorytype srcMemoryType;
    const void *srcHost;
    CUdeviceptr srcDevice;
    CUarray srcArray;
    unsigned int srcPitch;
    unsigned int dstXInBytes, dstY;
    CUMemorytype dstMemoryType;
```

```

void *dstHost;
CUdeviceptr dstDevice;
CUarray dstArray;
unsigned int dstPitch;
unsigned int WidthInBytes;
unsigned int Height;
} CUDA_MEMCPY2D;

```

where:

- srcMemoryType and dstMemoryType specify the type of memory of the source and destination, respectively; [CUmemorytype_enum](#) is defined as:

```

typedef enum CUmemorytype_enum {
    CU_MEMORYTYPE_HOST = 0x01,
    CU_MEMORYTYPE_DEVICE = 0x02,
    CU_MEMORYTYPE_ARRAY = 0x03,
    CU_MEMORYTYPE_UNIFIED = 0x04
} CUmemorytype;

```

If srcMemoryType is [CU_MEMORYTYPE_UNIFIED](#), srcDevice and srcPitch specify the (unified virtual address space) base address of the source data and the bytes per row to apply. srcArray is ignored. This value may be used only if unified addressing is supported in the calling context.

If srcMemoryType is [CU_MEMORYTYPE_HOST](#), srcHost and srcPitch specify the (host) base address of the source data and the bytes per row to apply. srcArray is ignored.

If srcMemoryType is [CU_MEMORYTYPE_DEVICE](#), srcDevice and srcPitch specify the (device) base address of the source data and the bytes per row to apply. srcArray is ignored.

If srcMemoryType is [CU_MEMORYTYPE_ARRAY](#), srcArray specifies the handle of the source data. srcHost, srcDevice and srcPitch are ignored.

If dstMemoryType is [CU_MEMORYTYPE_UNIFIED](#), dstDevice and dstPitch specify the (unified virtual address space) base address of the source data and the bytes per row to apply. dstArray is ignored. This value may be used only if unified addressing is supported in the calling context.

If dstMemoryType is [CU_MEMORYTYPE_HOST](#), dstHost and dstPitch specify the (host) base address of the destination data and the bytes per row to apply. dstArray is ignored.

If dstMemoryType is [CU_MEMORYTYPE_DEVICE](#), dstDevice and dstPitch specify the (device) base address of the destination data and the bytes per row to apply. dstArray is ignored.

If dstMemoryType is [CU_MEMORYTYPE_ARRAY](#), dstArray specifies the handle of the destination data. dstHost, dstDevice and dstPitch are ignored.

- srcXInBytes and srcY specify the base address of the source data for the copy.

For host pointers, the starting address is

```
void* Start = (void*)((char*)srcHost+srcY*srcPitch + srcXInBytes);
```

For device pointers, the starting address is

```
CUdeviceptr Start = srcDevice+srcY*srcPitch+srcXInBytes;
```

For CUDA arrays, `srcXInBytes` must be evenly divisible by the array element size.

- `dstXInBytes` and `dstY` specify the base address of the destination data for the copy.

For host pointers, the base address is

```
void* dstStart = (void*)((char*)dstHost+dstY*dstPitch + dstXInBytes);
```

For device pointers, the starting address is

```
CUdeviceptr dstStart = dstDevice+dstY*dstPitch+dstXInBytes;
```

For CUDA arrays, `dstXInBytes` must be evenly divisible by the array element size.

- `WidthInBytes` and `Height` specify the width (in bytes) and height of the 2D copy being performed.
- If specified, `srcPitch` must be greater than or equal to `WidthInBytes + srcXInBytes`, and `dstPitch` must be greater than or equal to `WidthInBytes + dstXInBytes`.

[cuMemcpy2D\(\)](#) returns an error if any pitch is greater than the maximum allowed ([CU_DEVICE_ATTRIBUTE_MAX_PITCH](#)). [cuMemAllocPitch\(\)](#) passes back pitches that always work with [cuMemcpy2D\(\)](#). On intra-device memory copies (device to device, CUDA array to device, CUDA array to CUDA array), [cuMemcpy2D\(\)](#) may fail for pitches not computed by [cuMemAllocPitch\(\)](#). [cuMemcpy2DUnaligned\(\)](#) does not have this restriction, but may run significantly slower in the cases where [cuMemcpy2D\(\)](#) would have returned an error code.

Parameters:

pCopy - Parameters for the memory copy

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.20 CUresult cuMemcpy3D (const CUDA_MEMCPY3D *pCopy)

Perform a 3D memory copy according to the parameters specified in pCopy. The [CUDA_MEMCPY3D](#) structure is defined as:

```
typedef struct CUDA_MEMCPY3D_st {
    unsigned int srcXInBytes, srcY, srcZ;
    unsigned int srcLOD;
    CUMemorytype srcMemoryType;
    const void *srcHost;
    CUdeviceptr srcDevice;
    CUarray srcArray;
    unsigned int srcPitch; // ignored when src is array
    unsigned int srcHeight; // ignored when src is array; may be 0 if Depth==1

    unsigned int dstXInBytes, dstY, dstZ;
    unsigned int dstLOD;
    CUMemorytype dstMemoryType;
    void *dstHost;
    CUdeviceptr dstDevice;
    CUarray dstArray;
    unsigned int dstPitch; // ignored when dst is array
    unsigned int dstHeight; // ignored when dst is array; may be 0 if Depth==1

    unsigned int WidthInBytes;
    unsigned int Height;
    unsigned int Depth;
} CUDA_MEMCPY3D;
```

where:

- srcMemoryType and dstMemoryType specify the type of memory of the source and destination, respectively; [CUMemorytype_enum](#) is defined as:

```
typedef enum CUMemorytype_enum {
    CU_MEMORYTYPE_HOST = 0x01,
    CU_MEMORYTYPE_DEVICE = 0x02,
    CU_MEMORYTYPE_ARRAY = 0x03,
    CU_MEMORYTYPE_UNIFIED = 0x04
} CUMemorytype;
```

If srcMemoryType is [CU_MEMORYTYPE_UNIFIED](#), srcDevice and srcPitch specify the (unified virtual address space) base address of the source data and the bytes per row to apply. srcArray is ignored. This value may be used only if unified addressing is supported in the calling context.

If srcMemoryType is [CU_MEMORYTYPE_HOST](#), srcHost, srcPitch and srcHeight specify the (host) base address of the source data, the bytes per row, and the height of each 2D slice of the 3D array. srcArray is ignored.

If srcMemoryType is [CU_MEMORYTYPE_DEVICE](#), srcDevice, srcPitch and srcHeight specify the (device) base address of the source data, the bytes per row, and the height of each 2D slice of the 3D array. srcArray is ignored.

If srcMemoryType is [CU_MEMORYTYPE_ARRAY](#), srcArray specifies the handle of the source data. srcHost, srcDevice, srcPitch and srcHeight are ignored.

If `dstMemoryType` is `CU_MEMORYTYPE_UNIFIED`, `dstDevice` and `dstPitch` specify the (unified virtual address space) base address of the source data and the bytes per row to apply. `dstArray` is ignored. This value may be used only if unified addressing is supported in the calling context.

If `dstMemoryType` is `CU_MEMORYTYPE_HOST`, `dstHost` and `dstPitch` specify the (host) base address of the destination data, the bytes per row, and the height of each 2D slice of the 3D array. `dstArray` is ignored.

If `dstMemoryType` is `CU_MEMORYTYPE_DEVICE`, `dstDevice` and `dstPitch` specify the (device) base address of the destination data, the bytes per row, and the height of each 2D slice of the 3D array. `dstArray` is ignored.

If `dstMemoryType` is `CU_MEMORYTYPE_ARRAY`, `dstArray` specifies the handle of the destination data. `dstHost`, `dstDevice`, `dstPitch` and `dstHeight` are ignored.

- `srcXInBytes`, `srcY` and `srcZ` specify the base address of the source data for the copy.

For host pointers, the starting address is

```
void* Start = (void*)((char*)srcHost+(srcZ*srcHeight+srcY)*srcPitch + srcXInBytes);
```

For device pointers, the starting address is

```
CUdeviceptr Start = srcDevice+(srcZ*srcHeight+srcY)*srcPitch+srcXInBytes;
```

For CUDA arrays, `srcXInBytes` must be evenly divisible by the array element size.

- `dstXInBytes`, `dstY` and `dstZ` specify the base address of the destination data for the copy.

For host pointers, the base address is

```
void* dstStart = (void*)((char*)dstHost+(dstZ*dstHeight+dstY)*dstPitch + dstXInBytes);
```

For device pointers, the starting address is

```
CUdeviceptr dstStart = dstDevice+(dstZ*dstHeight+dstY)*dstPitch+dstXInBytes;
```

For CUDA arrays, `dstXInBytes` must be evenly divisible by the array element size.

- `WidthInBytes`, `Height` and `Depth` specify the width (in bytes), height and depth of the 3D copy being performed.
- If specified, `srcPitch` must be greater than or equal to `WidthInBytes + srcXInBytes`, and `dstPitch` must be greater than or equal to `WidthInBytes + dstXInBytes`.
- If specified, `srcHeight` must be greater than or equal to `Height + srcY`, and `dstHeight` must be greater than or equal to `Height + dstY`.

`cuMemcpy3D()` returns an error if any pitch is greater than the maximum allowed (`CUDA_DEVICE_ATTRIBUTE_MAX_PITCH`).

The `srcLOD` and `dstLOD` members of the `CUDA_MEMCPY3D` structure must be set to 0.

Parameters:

pCopy - Parameters for the memory copy

Returns:

`CUDA_SUCCESS`, `CUDA_ERROR_DEINITIALIZED`, `CUDA_ERROR_NOT_INITIALIZED`, `CUDA_ERROR_INVALID_CONTEXT`, `CUDA_ERROR_INVALID_VALUE`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cuArray3DCreate`, `cuArray3DGetDescriptor`, `cuArrayCreate`, `cuArrayDestroy`, `cuArrayGetDescriptor`, `cuMemAlloc`, `cuMemAllocHost`, `cuMemAllocPitch`, `cuMemcpy2D`, `cuMemcpy2DAsync`, `cuMemcpy2DUnaligned`, `cuMemcpy3DAsync`, `cuMemcpyAtoA`, `cuMemcpyAtoD`, `cuMemcpyAtoH`, `cuMemcpyAtoHAsync`, `cuMemcpyDtoA`, `cuMemcpyDtoD`, `cuMemcpyDtoDAsync`, `cuMemcpyDtoH`, `cuMemcpyDtoHAsync`, `cuMemcpyHtoA`, `cuMemcpyHtoAAsync`, `cuMemcpyHtoD`, `cuMemcpyHtoDAsync`, `cuMemFree`, `cuMemFreeHost`, `cuMemGetAddressRange`, `cuMemGetInfo`, `cuMemHostAlloc`, `cuMemHostGetDevicePointer`, `cuMemsetD2D8`, `cuMemsetD2D16`, `cuMemsetD2D32`, `cuMemsetD8`, `cuMemsetD16`, `cuMemsetD32`

4.35.2.21 CUresult cuMemcpy3DAsync (const CUDA_MEMCPY3D *pCopy, CUstream hStream)

Perform a 3D memory copy according to the parameters specified in `pCopy`. The `CUDA_MEMCPY3D` structure is defined as:

```
typedef struct CUDA_MEMCPY3D_st {
    unsigned int srcXInBytes, srcY, srcZ;
    unsigned int srcLOD;
    CUMemorytype srcMemoryType;
    const void *srcHost;
    CUdeviceptr srcDevice;
    CUarray srcArray;
    unsigned int srcPitch; // ignored when src is array
    unsigned int srcHeight; // ignored when src is array; may be 0 if Depth==1

    unsigned int dstXInBytes, dstY, dstZ;
    unsigned int dstLOD;
    CUMemorytype dstMemoryType;
    void *dstHost;
    CUdeviceptr dstDevice;
    CUarray dstArray;
    unsigned int dstPitch; // ignored when dst is array
    unsigned int dstHeight; // ignored when dst is array; may be 0 if Depth==1

    unsigned int WidthInBytes;
    unsigned int Height;
    unsigned int Depth;
} CUDA_MEMCPY3D;
```

where:

- `srcMemoryType` and `dstMemoryType` specify the type of memory of the source and destination, respectively; `CUmemorytype_enum` is defined as:

```
typedef enum CUmemorytype_enum {
    CU_MEMORYTYPE_HOST = 0x01,
    CU_MEMORYTYPE_DEVICE = 0x02,
    CU_MEMORYTYPE_ARRAY = 0x03,
    CU_MEMORYTYPE_UNIFIED = 0x04
} CUmemorytype;
```

If `srcMemoryType` is `CU_MEMORYTYPE_UNIFIED`, `srcDevice` and `srcPitch` specify the (unified virtual address space) base address of the source data and the bytes per row to apply. `srcArray` is ignored. This value may be used only if unified addressing is supported in the calling context.

If `srcMemoryType` is `CU_MEMORYTYPE_HOST`, `srcHost`, `srcPitch` and `srcHeight` specify the (host) base address of the source data, the bytes per row, and the height of each 2D slice of the 3D array. `srcArray` is ignored.

If `srcMemoryType` is `CU_MEMORYTYPE_DEVICE`, `srcDevice`, `srcPitch` and `srcHeight` specify the (device) base address of the source data, the bytes per row, and the height of each 2D slice of the 3D array. `srcArray` is ignored.

If `srcMemoryType` is `CU_MEMORYTYPE_ARRAY`, `srcArray` specifies the handle of the source data. `srcHost`, `srcDevice`, `srcPitch` and `srcHeight` are ignored.

If `dstMemoryType` is `CU_MEMORYTYPE_UNIFIED`, `dstDevice` and `dstPitch` specify the (unified virtual address space) base address of the source data and the bytes per row to apply. `dstArray` is ignored. This value may be used only if unified addressing is supported in the calling context.

If `dstMemoryType` is `CU_MEMORYTYPE_HOST`, `dstHost` and `dstPitch` specify the (host) base address of the destination data, the bytes per row, and the height of each 2D slice of the 3D array. `dstArray` is ignored.

If `dstMemoryType` is `CU_MEMORYTYPE_DEVICE`, `dstDevice` and `dstPitch` specify the (device) base address of the destination data, the bytes per row, and the height of each 2D slice of the 3D array. `dstArray` is ignored.

If `dstMemoryType` is `CU_MEMORYTYPE_ARRAY`, `dstArray` specifies the handle of the destination data. `dstHost`, `dstDevice`, `dstPitch` and `dstHeight` are ignored.

- `srcXInBytes`, `srcY` and `srcZ` specify the base address of the source data for the copy.

For host pointers, the starting address is

```
void* Start = (void*)((char*)srcHost+(srcZ*srcHeight+srcY)*srcPitch + srcXInBytes);
```

For device pointers, the starting address is

```
CUdeviceptr Start = srcDevice+(srcZ*srcHeight+srcY)*srcPitch+srcXInBytes;
```

For CUDA arrays, `srcXInBytes` must be evenly divisible by the array element size.

- `dstXInBytes`, `dstY` and `dstZ` specify the base address of the destination data for the copy.

For host pointers, the base address is

```
void* dstStart = (void*)((char*)dstHost+(dstZ*dstHeight+dstY)*dstPitch + dstXInBytes);
```

For device pointers, the starting address is

```
CUdeviceptr dstStart = dstDevice+(dstZ*dstHeight+dstY)*dstPitch+dstXInBytes;
```

For CUDA arrays, `dstXInBytes` must be evenly divisible by the array element size.

- `WidthInBytes`, `Height` and `Depth` specify the width (in bytes), height and depth of the 3D copy being performed.
- If specified, `srcPitch` must be greater than or equal to `WidthInBytes + srcXInBytes`, and `dstPitch` must be greater than or equal to `WidthInBytes + dstXInBytes`.
- If specified, `srcHeight` must be greater than or equal to `Height + srcY`, and `dstHeight` must be greater than or equal to `Height + dstY`.

[`cuMemcpy3D\(\)`](#) returns an error if any pitch is greater than the maximum allowed (`CU_DEVICE_ATTRIBUTE_MAX_PITCH`).

[`cuMemcpy3DAsync\(\)`](#) is asynchronous and can optionally be associated to a stream by passing a non-zero `hStream` argument. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input.

The `srcLOD` and `dstLOD` members of the [`CUDA_MEMCPY3D`](#) structure must be set to 0.

Parameters:

pCopy - Parameters for the memory copy

hStream - Stream identifier

Returns:

[`CUDA_SUCCESS`](#), [`CUDA_ERROR_DEINITIALIZED`](#), [`CUDA_ERROR_NOT_INITIALIZED`](#), [`CUDA_ERROR_INVALID_CONTEXT`](#), [`CUDA_ERROR_INVALID_VALUE`](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.22 CUresult cuMemcpy3DPeer (const CUDA_MEMCPY3D_PEER * *pCopy*)

Perform a 3D memory copy according to the parameters specified in *pCopy*. See the definition of the [CUDA_MEMCPY3D_PEER](#) structure for documentation of its parameters.

Note that this function is synchronous with respect to the host only if the source or destination memory is of type [CU_MEMORYTYPE_HOST](#). Note also that this copy is serialized with respect all pending and future asynchronous work in to the current context, the copy's source context, and the copy's destination context (use [cuMemcpy3DPeerAsync](#) to avoid this synchronization).

Parameters:

pCopy - Parameters for the memory copy

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuMemcpyDtoD](#), [cuMemcpyPeer](#), [cuMemcpyDtoDAsync](#), [cuMemcpyPeerAsync](#), [cuMemcpy3DPeerAsync](#)

4.35.2.23 CUresult cuMemcpy3DPeerAsync (const CUDA_MEMCPY3D_PEER * *pCopy*, CUstream *hStream*)

Perform a 3D memory copy according to the parameters specified in *pCopy*. See the definition of the [CUDA_MEMCPY3D_PEER](#) structure for documentation of its parameters.

Parameters:

pCopy - Parameters for the memory copy

hStream - Stream identifier

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuMemcpyDtoD](#), [cuMemcpyPeer](#), [cuMemcpyDtoDAsync](#), [cuMemcpyPeerAsync](#), [cuMemcpy3DPeerAsync](#)

4.35.2.24 CUresult cuMemcpyAsync (CUdeviceptr *dst*, CUdeviceptr *src*, size_t *ByteCount*, CUstream *hStream*)

Copies data between two pointers. *dst* and *src* are base pointers of the destination and source, respectively. *ByteCount* specifies the number of bytes to copy. Note that this function infers the type of the transfer (host to

host, host to device, device to device, or device to host) from the pointer values. This function is only allowed in contexts which support unified addressing. Note that this function is asynchronous and can optionally be associated to a stream by passing a non-zero `hStream` argument

Parameters:

dst - Destination unified virtual address space pointer

src - Source unified virtual address space pointer

ByteCount - Size of memory copy in bytes

hStream - Stream identifier

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.25 CUresult cuMemcpyAtoA (CUarray dstArray, size_t dstOffset, CUarray srcArray, size_t srcOffset, size_t ByteCount)

Copies from one 1D CUDA array to another. `dstArray` and `srcArray` specify the handles of the destination and source CUDA arrays for the copy, respectively. `dstOffset` and `srcOffset` specify the destination and source offsets in bytes into the CUDA arrays. `ByteCount` is the number of bytes to be copied. The size of the elements in the CUDA arrays need not be the same format, but the elements must be the same size; and count must be evenly divisible by that size.

Parameters:

dstArray - Destination array

dstOffset - Offset in bytes of destination array

srcArray - Source array

srcOffset - Offset in bytes of source array

ByteCount - Size of memory copy in bytes

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.26 CUresult cuMemcpyAtoD (CUdeviceptr *dstDevice*, CUarray *srcArray*, size_t *srcOffset*, size_t *ByteCount*)

Copies from one 1D CUDA array to device memory. *dstDevice* specifies the base pointer of the destination and must be naturally aligned with the CUDA array elements. *srcArray* and *srcOffset* specify the CUDA array handle and the offset in bytes into the array where the copy is to begin. *ByteCount* specifies the number of bytes to copy and must be evenly divisible by the array element size.

Parameters:

dstDevice - Destination device pointer
srcArray - Source array
srcOffset - Offset in bytes of source array
ByteCount - Size of memory copy in bytes

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.27 CUresult cuMemcpyAtoH (void * *dstHost*, CUarray *srcArray*, size_t *srcOffset*, size_t *ByteCount*)

Copies from one 1D CUDA array to host memory. *dstHost* specifies the base pointer of the destination. *srcArray* and *srcOffset* specify the CUDA array handle and starting offset in bytes of the source data. *ByteCount* specifies the number of bytes to copy.

Parameters:

dstHost - Destination device pointer
srcArray - Source array
srcOffset - Offset in bytes of source array
ByteCount - Size of memory copy in bytes

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D16, cuMemsetD2D32, cuMemsetD8, cuMemsetD16, cuMemsetD32

4.35.2.28 CUresult cuMemcpyAtoHAsync (void * *dstHost*, CUarray *srcArray*, size_t *srcOffset*, size_t *ByteCount*, CUstream *hStream*)

Copies from one 1D CUDA array to host memory. *dstHost* specifies the base pointer of the destination. *srcArray* and *srcOffset* specify the CUDA array handle and starting offset in bytes of the source data. *ByteCount* specifies the number of bytes to copy.

[cuMemcpyAtoHAsync\(\)](#) is asynchronous and can optionally be associated to a stream by passing a non-zero *stream* argument. It only works on page-locked host memory and returns an error if a pointer to pageable memory is passed as input.

Parameters:

dstHost - Destination pointer
srcArray - Source array
srcOffset - Offset in bytes of source array
ByteCount - Size of memory copy in bytes
hStream - Stream identifier

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.29 CUresult cuMemcpyDtoA (CUarray *dstArray*, size_t *dstOffset*, CUdeviceptr *srcDevice*, size_t *ByteCount*)

Copies from device memory to a 1D CUDA array. *dstArray* and *dstOffset* specify the CUDA array handle and starting index of the destination data. *srcDevice* specifies the base pointer of the source. *ByteCount* specifies the number of bytes to copy.

Parameters:

dstArray - Destination array
dstOffset - Offset in bytes of destination array
srcDevice - Source device pointer
ByteCount - Size of memory copy in bytes

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.30 CUresult cuMemcpyDtoD (CUdeviceptr *dstDevice*, CUdeviceptr *srcDevice*, size_t *ByteCount*)

Copies from device memory to device memory. *dstDevice* and *srcDevice* are the base pointers of the destination and source, respectively. *ByteCount* specifies the number of bytes to copy. Note that this function is asynchronous.

Parameters:

dstDevice - Destination device pointer
srcDevice - Source device pointer

ByteCount - Size of memory copy in bytes

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D16, cuMemsetD2D32, cuMemsetD8, cuMemsetD16, cuMemsetD32

4.35.2.31 CUresult cuMemcpyDtoDAsync (CUdeviceptr *dstDevice*, CUdeviceptr *srcDevice*, size_t *ByteCount*, CUstream *hStream*)

Copies from device memory to device memory. *dstDevice* and *srcDevice* are the base pointers of the destination and source, respectively. *ByteCount* specifies the number of bytes to copy. Note that this function is asynchronous and can optionally be associated to a stream by passing a non-zero *hStream* argument

Parameters:

dstDevice - Destination device pointer
srcDevice - Source device pointer
ByteCount - Size of memory copy in bytes
hStream - Stream identifier

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D8Async, cuMemsetD2D16, cuMemsetD2D16Async, cuMemsetD2D32, cuMemsetD2D32Async, cuMemsetD8, cuMemsetD8Async, cuMemsetD16, cuMemsetD16Async, cuMemsetD32, cuMemsetD32Async

4.35.2.32 CUresult cuMemcpyDtoH (void * *dstHost*, CUdeviceptr *srcDevice*, size_t *ByteCount*)

Copies from device to host memory. *dstHost* and *srcDevice* specify the base pointers of the destination and source, respectively. *ByteCount* specifies the number of bytes to copy. Note that this function is synchronous.

Parameters:

dstHost - Destination host pointer
srcDevice - Source device pointer
ByteCount - Size of memory copy in bytes

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D16, cuMemsetD2D32, cuMemsetD8, cuMemsetD16, cuMemsetD32

4.35.2.33 CUresult cuMemcpyDtoHAsync (void * *dstHost*, CUdeviceptr *srcDevice*, size_t *ByteCount*, CUstream *hStream*)

Copies from device to host memory. *dstHost* and *srcDevice* specify the base pointers of the destination and source, respectively. *ByteCount* specifies the number of bytes to copy.

[cuMemcpyDtoHAsync\(\)](#) is asynchronous and can optionally be associated to a stream by passing a non-zero *hStream* argument. It only works on page-locked memory and returns an error if a pointer to pageable memory is passed as input.

Parameters:

dstHost - Destination host pointer
srcDevice - Source device pointer
ByteCount - Size of memory copy in bytes
hStream - Stream identifier

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.34 CUresult cuMemcpyHtoA (CUarray *dstArray*, size_t *dstOffset*, const void * *srcHost*, size_t *ByteCount*)

Copies from host memory to a 1D CUDA array. *dstArray* and *dstOffset* specify the CUDA array handle and starting offset in bytes of the destination data. *srcHost* specifies the base address of the source. *ByteCount* specifies the number of bytes to copy.

Parameters:

dstArray - Destination array
dstOffset - Offset in bytes of destination array
srcHost - Source host pointer
ByteCount - Size of memory copy in bytes

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.35 CUresult cuMemcpyHtoAAsync (CUarray *dstArray*, size_t *dstOffset*, const void * *srcHost*, size_t *ByteCount*, CUstream *hStream*)

Copies from host memory to a 1D CUDA array. *dstArray* and *dstOffset* specify the CUDA array handle and starting offset in bytes of the destination data. *srcHost* specifies the base address of the source. *ByteCount* specifies the number of bytes to copy.

[cuMemcpyHtoAAsync\(\)](#) is asynchronous and can optionally be associated to a stream by passing a non-zero *hStream* argument. It only works on page-locked memory and returns an error if a pointer to pageable memory is passed as input.

Parameters:

dstArray - Destination array
dstOffset - Offset in bytes of destination array
srcHost - Source host pointer
ByteCount - Size of memory copy in bytes
hStream - Stream identifier

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.36 CUresult cuMemcpyHtoD (CUdeviceptr dstDevice, const void * srcHost, size_t ByteCount)

Copies from host memory to device memory. *dstDevice* and *srcHost* are the base addresses of the destination and source, respectively. *ByteCount* specifies the number of bytes to copy. Note that this function is synchronous.

Parameters:

dstDevice - Destination device pointer
srcHost - Source host pointer
ByteCount - Size of memory copy in bytes

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.37 CUresult cuMemcpyHtoDAsync (CUdeviceptr *dstDevice*, const void * *srcHost*, size_t *ByteCount*, CUstream *hStream*)

Copies from host memory to device memory. *dstDevice* and *srcHost* are the base addresses of the destination and source, respectively. *ByteCount* specifies the number of bytes to copy.

[cuMemcpyHtoDAsync\(\)](#) is asynchronous and can optionally be associated to a stream by passing a non-zero *hStream* argument. It only works on page-locked memory and returns an error if a pointer to pageable memory is passed as input.

Parameters:

dstDevice - Destination device pointer
srcHost - Source host pointer
ByteCount - Size of memory copy in bytes
hStream - Stream identifier

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.38 CUresult cuMemcpyPeer (CUdeviceptr *dstDevice*, CUcontext *dstContext*, CUdeviceptr *srcDevice*, CUcontext *srcContext*, size_t *ByteCount*)

Copies from device memory in one context to device memory in another context. *dstDevice* is the base device pointer of the destination memory and *dstContext* is the destination context. *srcDevice* is the base device pointer of the source memory and *srcContext* is the source pointer. *ByteCount* specifies the number of bytes to copy.

Note that this function is asynchronous with respect to the host, but serialized with respect all pending and future asynchronous work in to the current context, *srcContext*, and *dstContext* (use [cuMemcpyPeerAsync](#) to avoid this synchronization).

Parameters:

dstDevice - Destination device pointer
dstContext - Destination context
srcDevice - Source device pointer

srcContext - Source context

ByteCount - Size of memory copy in bytes

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuMemcpyDtoD](#), [cuMemcpy3DPeer](#), [cuMemcpyDtoDAsync](#), [cuMemcpyPeerAsync](#), [cuMemcpy3DPeerAsync](#)

4.35.2.39 CUresult cuMemcpyPeerAsync (CUdeviceptr *dstDevice*, CUcontext *dstContext*, CUdeviceptr *srcDevice*, CUcontext *srcContext*, size_t *ByteCount*, CUstream *hStream*)

Copies from device memory in one context to device memory in another context. *dstDevice* is the base device pointer of the destination memory and *dstContext* is the destination context. *srcDevice* is the base device pointer of the source memory and *srcContext* is the source pointer. *ByteCount* specifies the number of bytes to copy. Note that this function is asynchronous with respect to the host and all work in other streams in other devices.

Parameters:

dstDevice - Destination device pointer

dstContext - Destination context

srcDevice - Source device pointer

srcContext - Source context

ByteCount - Size of memory copy in bytes

hStream - Stream identifier

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuMemcpyDtoD](#), [cuMemcpyPeer](#), [cuMemcpy3DPeer](#), [cuMemcpyDtoDAsync](#), [cuMemcpy3DPeerAsync](#)

4.35.2.40 CUresult cuMemFree (CUdeviceptr *dptr*)

Frees the memory space pointed to by *dptr*, which must have been returned by a previous call to [cuMemAlloc\(\)](#) or [cuMemAllocPitch\(\)](#).

Parameters:

dptr - Pointer to memory to free

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFreeHost, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D16, cuMemsetD2D32, cuMemsetD8, cuMemsetD16, cuMemsetD32

4.35.2.41 CUresult cuMemFreeHost (void * *p*)

Frees the memory space pointed to by *p*, which must have been returned by a previous call to [cuMemAllocHost\(\)](#).

Parameters:

p - Pointer to memory to free

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D16, cuMemsetD2D32, cuMemsetD8, cuMemsetD16, cuMemsetD32

4.35.2.42 CUresult cuMemGetAddressRange (CUdeviceptr * *pbase*, size_t * *psize*, CUdeviceptr *dptr*)

Returns the base address in *pbase* and size in *psize* of the allocation by [cuMemAlloc\(\)](#) or [cuMemAllocPitch\(\)](#) that contains the input pointer *dptr*. Both parameters *pbase* and *psize* are optional. If one of them is NULL, it is ignored.

Parameters:

pbase - Returned base address

psize - Returned size of device memory allocation

dptr - Device pointer to query

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D16, cuMemsetD2D32, cuMemsetD8, cuMemsetD16, cuMemsetD32

4.35.2.43 CUresult cuMemGetInfo (size_t *free, size_t *total)

Returns in *free and *total respectively, the free and total amount of memory available for allocation by the CUDA context, in bytes.

Parameters:

free - Returned free memory in bytes

total - Returned total memory in bytes

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetAddressRange, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D16, cuMemsetD2D32, cuMemsetD8, cuMemsetD16, cuMemsetD32

4.35.2.44 CUresult cuMemHostAlloc (void **pp, size_t bytesize, unsigned int Flags)

Allocates `bytesize` bytes of host memory that is page-locked and accessible to the device. The driver tracks the virtual memory ranges allocated with this function and automatically accelerates calls to functions such as `cuMemcpyHtoD()`. Since the memory can be accessed directly by the device, it can be read or written with much higher bandwidth than pageable memory obtained with functions such as `malloc()`. Allocating excessive amounts of pinned memory may degrade system performance, since it reduces the amount of memory available to the system for paging. As a result, this function is best used sparingly to allocate staging areas for data exchange between host and device.

The `Flags` parameter enables different options to be specified that affect the allocation, as follows.

- **CU_MEMHOSTALLOC_PORTABLE**: The memory returned by this call will be considered as pinned memory by all CUDA contexts, not just the one that performed the allocation.
- **CU_MEMHOSTALLOC_DEVICEMAP**: Maps the allocation into the CUDA address space. The device pointer to the memory may be obtained by calling `cuMemHostGetDevicePointer()`. This feature is available only on GPUs with compute capability greater than or equal to 1.1.
- **CU_MEMHOSTALLOC_WRITECOMBINED**: Allocates the memory as write-combined (WC). WC memory can be transferred across the PCI Express bus more quickly on some system configurations, but cannot be read efficiently by most CPUs. WC memory is a good option for buffers that will be written by the CPU and read by the GPU via mapped pinned memory or host->device transfers.

All of these flags are orthogonal to one another: a developer may allocate memory that is portable, mapped and/or write-combined with no restrictions.

The CUDA context must have been created with the **CU_CTX_MAP_HOST** flag in order for the **CU_MEMHOSTALLOC_MAPPED** flag to have any effect.

The **CU_MEMHOSTALLOC_MAPPED** flag may be specified on CUDA contexts for devices that do not support mapped pinned memory. The failure is deferred to `cuMemHostGetDevicePointer()` because the memory may be mapped into other CUDA contexts via the **CU_MEMHOSTALLOC_PORTABLE** flag.

The memory allocated by this function must be freed with `cuMemFreeHost()`.

Note all host memory allocated using `cuMemHostAlloc()` will automatically be immediately accessible to all contexts on all devices which support unified addressing (as may be queried using **CU_DEVICE_ATTRIBUTE_UNIFIED_ADDRESSING**). Unless the flag **CU_MEMHOSTALLOC_WRITECOMBINED** is specified, the device pointer that may be used to access this host memory from those contexts is always equal to the returned host pointer `*pp`. If the flag **CU_MEMHOSTALLOC_WRITECOMBINED** is specified, then the function `cuMemHostGetDevicePointer()` must be used to query the device pointer, even if the context supports unified addressing. See [Unified Addressing](#) for additional details.

Parameters:

pp - Returned host pointer to page-locked memory

bytesize - Requested allocation size in bytes

Flags - Flags for allocation request

Returns:

CUDA_SUCCESS, **CUDA_ERROR_DEINITIALIZED**, **CUDA_ERROR_NOT_INITIALIZED**, **CUDA_ERROR_INVALID_CONTEXT**, **CUDA_ERROR_INVALID_VALUE**, **CUDA_ERROR_OUT_OF_MEMORY**

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.45 CUresult cuMemHostGetDevicePointer (CUdeviceptr * *pdptr*, void * *p*, unsigned int *Flags*)

Passes back the device pointer `pdptr` corresponding to the mapped, pinned host buffer `p` allocated by [cuMemHostAlloc](#).

[cuMemHostGetDevicePointer\(\)](#) will fail if the `CU_MEMALLOCHOST_DEVICEMAP` flag was not specified at the time the memory was allocated, or if the function is called on a GPU that does not support mapped pinned memory.

`Flags` provides for future releases. For now, it must be set to 0.

Parameters:

pdptr - Returned device pointer

p - Host pointer

Flags - Options (must be 0)

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD16](#), [cuMemsetD32](#)

4.35.2.46 CUresult cuMemHostGetFlags (unsigned int * *pFlags*, void * *p*)

Passes back the flags `pFlags` that were specified when allocating the pinned host buffer `p` allocated by [cuMemHostAlloc](#).

[cuMemHostGetFlags\(\)](#) will fail if the pointer does not reside in an allocation performed by [cuMemAllocHost\(\)](#) or [cuMemHostAlloc\(\)](#).

Parameters:

pFlags - Returned flags word

p - Host pointer

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuMemAllocHost](#), [cuMemHostAlloc](#)

4.35.2.47 CUresult cuMemHostRegister (void **p*, size_t *bytesize*, unsigned int *Flags*)

Page-locks the memory range specified by *p* and *bytesize* and maps it for the device(s) as specified by *Flags*. This memory range also is added to the same tracking mechanism as [cuMemHostAlloc](#) to automatically accelerate calls to functions such as [cuMemcpyHtoD\(\)](#). Since the memory can be accessed directly by the device, it can be read or written with much higher bandwidth than pageable memory that has not been registered. Page-locking excessive amounts of memory may degrade system performance, since it reduces the amount of memory available to the system for paging. As a result, this function is best used sparingly to register staging areas for data exchange between host and device.

This function has limited support on Mac OS X. OS 10.7 or higher is required.

The *Flags* parameter enables different options to be specified that affect the allocation, as follows.

- [CU_MEMHOSTREGISTER_PORTABLE](#): The memory returned by this call will be considered as pinned memory by all CUDA contexts, not just the one that performed the allocation.
- [CU_MEMHOSTREGISTER_DEVICEMAP](#): Maps the allocation into the CUDA address space. The device pointer to the memory may be obtained by calling [cuMemHostGetDevicePointer\(\)](#). This feature is available only on GPUs with compute capability greater than or equal to 1.1.

All of these flags are orthogonal to one another: a developer may page-lock memory that is portable or mapped with no restrictions.

The CUDA context must have been created with the [CU_CTX_MAP_HOST](#) flag in order for the [CU_MEMHOSTREGISTER_DEVICEMAP](#) flag to have any effect.

The [CU_MEMHOSTREGISTER_DEVICEMAP](#) flag may be specified on CUDA contexts for devices that do not support mapped pinned memory. The failure is deferred to [cuMemHostGetDevicePointer\(\)](#) because the memory may be mapped into other CUDA contexts via the [CU_MEMHOSTREGISTER_PORTABLE](#) flag.

The memory page-locked by this function must be unregistered with [cuMemHostUnregister\(\)](#).

Parameters:

p - Host pointer to memory to page-lock

bytesize - Size in bytes of the address range to page-lock

Flags - Flags for allocation request

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuMemHostUnregister](#), [cuMemHostGetFlags](#), [cuMemHostGetDevicePointer](#)

4.35.2.48 CUresult cuMemHostUnregister (void * *p*)

Unmaps the memory range whose base address is specified by *p*, and makes it pageable again.

The base address must be the same one specified to [cuMemHostRegister\(\)](#).

Parameters:

p - Host pointer to memory to unregister

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuMemHostRegister](#)

4.35.2.49 CUresult cuMemsetD16 (CUdeviceptr *dstDevice*, unsigned short *us*, size_t *N*)

Sets the memory range of *N* 16-bit values to the specified value *us*. The *dstDevice* pointer must be two byte aligned.

Parameters:

dstDevice - Destination device pointer

us - Value to set

N - Number of elements

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#),

[cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.50 CUresult cuMemsetD16Async (CUdeviceptr *dstDevice*, unsigned short *us*, size_t *N*, CUSTream *hStream*)

Sets the memory range of *N* 16-bit values to the specified value *us*. The *dstDevice* pointer must be two byte aligned.

[cuMemsetD16Async\(\)](#) is asynchronous and can optionally be associated to a stream by passing a non-zero *stream* argument.

Parameters:

dstDevice - Destination device pointer
us - Value to set
N - Number of elements
hStream - Stream identifier

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.51 CUresult cuMemsetD2D16 (CUdeviceptr *dstDevice*, size_t *dstPitch*, unsigned short *us*, size_t *Width*, size_t *Height*)

Sets the 2D memory range of *Width* 16-bit values to the specified value *us*. *Height* specifies the number of rows to set, and *dstPitch* specifies the number of bytes between each row. The *dstDevice* pointer and *dstPitch* offset must be two byte aligned. This function performs fastest when the pitch is one that has been passed back by [cuMemAllocPitch\(\)](#).

Parameters:

dstDevice - Destination device pointer

dstPitch - Pitch of destination device pointer

us - Value to set

Width - Width of row

Height - Number of rows

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D8Async, cuMemsetD2D16Async, cuMemsetD2D32, cuMemsetD2D32Async, cuMemsetD8, cuMemsetD8Async, cuMemsetD16, cuMemsetD16Async, cuMemsetD32, cuMemsetD32Async

4.35.2.52 CUresult cuMemsetD2D16Async (CUdeviceptr *dstDevice*, size_t *dstPitch*, unsigned short *us*, size_t *Width*, size_t *Height*, CUstream *hStream*)

Sets the 2D memory range of *Width* 16-bit values to the specified value *us*. *Height* specifies the number of rows to set, and *dstPitch* specifies the number of bytes between each row. The *dstDevice* pointer and *dstPitch* offset must be two byte aligned. This function performs fastest when the pitch is one that has been passed back by [cuMemAllocPitch\(\)](#).

[cuMemsetD2D16Async\(\)](#) is asynchronous and can optionally be associated to a stream by passing a non-zero *stream* argument.

Parameters:

dstDevice - Destination device pointer

dstPitch - Pitch of destination device pointer

us - Value to set

Width - Width of row

Height - Number of rows

hStream - Stream identifier

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.53 CUresult cuMemsetD2D32 (CUdeviceptr *dstDevice*, size_t *dstPitch*, unsigned int *ui*, size_t *Width*, size_t *Height*)

Sets the 2D memory range of *Width* 32-bit values to the specified value *ui*. *Height* specifies the number of rows to set, and *dstPitch* specifies the number of bytes between each row. The *dstDevice* pointer and *dstPitch* offset must be four byte aligned. This function performs fastest when the pitch is one that has been passed back by [cuMemAllocPitch\(\)](#).

Parameters:

dstDevice - Destination device pointer
dstPitch - Pitch of destination device pointer
ui - Value to set
Width - Width of row
Height - Number of rows

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.54 CUresult cuMemsetD2D32Async (CUdeviceptr *dstDevice*, size_t *dstPitch*, unsigned int *ui*, size_t *Width*, size_t *Height*, CUstream *hStream*)

Sets the 2D memory range of *Width* 32-bit values to the specified value *ui*. *Height* specifies the number of rows to set, and *dstPitch* specifies the number of bytes between each row. The *dstDevice* pointer and *dstPitch*

offset must be four byte aligned. This function performs fastest when the pitch is one that has been passed back by [cuMemAllocPitch\(\)](#).

[cuMemsetD2D32Async\(\)](#) is asynchronous and can optionally be associated to a stream by passing a non-zero `stream` argument.

Parameters:

dstDevice - Destination device pointer
dstPitch - Pitch of destination device pointer
ui - Value to set
Width - Width of row
Height - Number of rows
hStream - Stream identifier

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.55 CUresult cuMemsetD2D8 (CUdeviceptr *dstDevice*, size_t *dstPitch*, unsigned char *uc*, size_t *Width*, size_t *Height*)

Sets the 2D memory range of *Width* 8-bit values to the specified value *uc*. *Height* specifies the number of rows to set, and *dstPitch* specifies the number of bytes between each row. This function performs fastest when the pitch is one that has been passed back by [cuMemAllocPitch\(\)](#).

Parameters:

dstDevice - Destination device pointer
dstPitch - Pitch of destination device pointer
uc - Value to set
Width - Width of row
Height - Number of rows

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.56 CUresult cuMemsetD2D8Async (CUdeviceptr *dstDevice*, size_t *dstPitch*, unsigned char *uc*, size_t *Width*, size_t *Height*, CUstream *hStream*)

Sets the 2D memory range of *Width* 8-bit values to the specified value *uc*. *Height* specifies the number of rows to set, and *dstPitch* specifies the number of bytes between each row. This function performs fastest when the pitch is one that has been passed back by [cuMemAllocPitch\(\)](#).

[cuMemsetD2D8Async\(\)](#) is asynchronous and can optionally be associated to a stream by passing a non-zero *stream* argument.

Parameters:

dstDevice - Destination device pointer
dstPitch - Pitch of destination device pointer
uc - Value to set
Width - Width of row
Height - Number of rows
hStream - Stream identifier

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.57 CUresult cuMemsetD32 (CUdeviceptr *dstDevice*, unsigned int *ui*, size_t *N*)

Sets the memory range of *N* 32-bit values to the specified value *ui*. The *dstDevice* pointer must be four byte aligned.

Parameters:

dstDevice - Destination device pointer

ui - Value to set

N - Number of elements

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D8Async, cuMemsetD2D16, cuMemsetD2D16Async, cuMemsetD2D32, cuMemsetD2D32Async, cuMemsetD8, cuMemsetD8Async, cuMemsetD16, cuMemsetD16Async, cuMemsetD32Async

4.35.2.58 CUresult cuMemsetD32Async (CUdeviceptr *dstDevice*, unsigned int *ui*, size_t *N*, CUSTream *hStream*)

Sets the memory range of *N* 32-bit values to the specified value *ui*. The *dstDevice* pointer must be four byte aligned.

[cuMemsetD32Async\(\)](#) is asynchronous and can optionally be associated to a stream by passing a non-zero *stream* argument.

Parameters:

dstDevice - Destination device pointer

ui - Value to set

N - Number of elements

hStream - Stream identifier

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#)

4.35.2.59 CUresult cuMemsetD8 (CUdeviceptr *dstDevice*, unsigned char *uc*, size_t *N*)

Sets the memory range of *N* 8-bit values to the specified value *uc*.

Parameters:

dstDevice - Destination device pointer

uc - Value to set

N - Number of elements

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuArray3DCreate](#), [cuArray3DGetDescriptor](#), [cuArrayCreate](#), [cuArrayDestroy](#), [cuArrayGetDescriptor](#), [cuMemAlloc](#), [cuMemAllocHost](#), [cuMemAllocPitch](#), [cuMemcpy2D](#), [cuMemcpy2DAsync](#), [cuMemcpy2DUnaligned](#), [cuMemcpy3D](#), [cuMemcpy3DAsync](#), [cuMemcpyAtoA](#), [cuMemcpyAtoD](#), [cuMemcpyAtoH](#), [cuMemcpyAtoHAsync](#), [cuMemcpyDtoA](#), [cuMemcpyDtoD](#), [cuMemcpyDtoDAsync](#), [cuMemcpyDtoH](#), [cuMemcpyDtoHAsync](#), [cuMemcpyHtoA](#), [cuMemcpyHtoAAsync](#), [cuMemcpyHtoD](#), [cuMemcpyHtoDAsync](#), [cuMemFree](#), [cuMemFreeHost](#), [cuMemGetAddressRange](#), [cuMemGetInfo](#), [cuMemHostAlloc](#), [cuMemHostGetDevicePointer](#), [cuMemsetD2D8](#), [cuMemsetD2D8Async](#), [cuMemsetD2D16](#), [cuMemsetD2D16Async](#), [cuMemsetD2D32](#), [cuMemsetD2D32Async](#), [cuMemsetD8Async](#), [cuMemsetD16](#), [cuMemsetD16Async](#), [cuMemsetD32](#), [cuMemsetD32Async](#)

4.35.2.60 CUresult cuMemsetD8Async (CUdeviceptr *dstDevice*, unsigned char *uc*, size_t *N*, CUstream *hStream*)

Sets the memory range of *N* 8-bit values to the specified value *uc*.

[cuMemsetD8Async\(\)](#) is asynchronous and can optionally be associated to a stream by passing a non-zero *stream* argument.

Parameters:

dstDevice - Destination device pointer

uc - Value to set

N - Number of elements

hStream - Stream identifier

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuArray3DCreate, cuArray3DGetDescriptor, cuArrayCreate, cuArrayDestroy, cuArrayGetDescriptor, cuMemAlloc, cuMemAllocHost, cuMemAllocPitch, cuMemcpy2D, cuMemcpy2DAsync, cuMemcpy2DUnaligned, cuMemcpy3D, cuMemcpy3DAsync, cuMemcpyAtoA, cuMemcpyAtoD, cuMemcpyAtoH, cuMemcpyAtoHAsync, cuMemcpyDtoA, cuMemcpyDtoD, cuMemcpyDtoDAsync, cuMemcpyDtoH, cuMemcpyDtoHAsync, cuMemcpyHtoA, cuMemcpyHtoAAsync, cuMemcpyHtoD, cuMemcpyHtoDAsync, cuMemFree, cuMemFreeHost, cuMemGetAddressRange, cuMemGetInfo, cuMemHostAlloc, cuMemHostGetDevicePointer, cuMemsetD2D8, cuMemsetD2D8Async, cuMemsetD2D16, cuMemsetD2D16Async, cuMemsetD2D32, cuMemsetD2D32Async, cuMemsetD8, cuMemsetD16, cuMemsetD16Async, cuMemsetD32, cuMemsetD32Async

4.36 Unified Addressing

Functions

- [CUresult cuPointerGetAttribute](#) (void *data, [CUpointer_attribute](#) attribute, [CUdeviceptr](#) ptr)

Returns information about a pointer.

4.36.1 Detailed Description

This section describes the unified addressing functions of the low-level CUDA driver application programming interface.

4.36.2 Overview

CUDA devices can share a unified address space with the host. For these devices there is no distinction between a device pointer and a host pointer – the same pointer value may be used to access memory from the host program and from a kernel running on the device (with exceptions enumerated below).

4.36.3 Supported Platforms

Whether or not a device supports unified addressing may be queried by calling [cuDeviceGetAttribute\(\)](#) with the device attribute [CU_DEVICE_ATTRIBUTE_UNIFIED_ADDRESSING](#).

Unified addressing is automatically enabled in 64-bit processes on devices with compute capability greater than or equal to 2.0.

Unified addressing is not yet supported on Windows Vista or Windows 7 for devices that do not use the TCC driver model.

4.36.4 Looking Up Information from Pointer Values

It is possible to look up information about the memory which backs a pointer value. For instance, one may want to know if a pointer points to host or device memory. As another example, in the case of device memory, one may want to know on which CUDA device the memory resides. These properties may be queried using the function [cuPointerGetAttribute\(\)](#)

Because pointers are unique, it is not necessary to specify information about the pointers specified to the various copy functions in the CUDA API. The function [cuMemcpy\(\)](#) may be used to perform a copy between two pointers, ignoring whether they point to host or device memory (making [cuMemcpyHtoD\(\)](#), [cuMemcpyDtoD\(\)](#), and [cuMemcpyDtoH\(\)](#) unnecessary for devices supporting unified addressing). For multidimensional copies, the memory type [CU_MEMORYTYPE_UNIFIED](#) may be used to specify that the CUDA driver should infer the location of the pointer from its value.

4.36.5 Automatic Mapping of Host Allocated Host Memory

All host memory allocated in all contexts using [cuMemAllocHost\(\)](#) and [cuMemHostAlloc\(\)](#) is always directly accessible from all contexts on all devices that support unified addressing. This is the case regardless of whether or not the flags [CU_MEMHOSTALLOC_PORTABLE](#) and [CU_MEMHOSTALLOC_DEVICEMAP](#) are specified.

The pointer value through which allocated host memory may be accessed in kernels on all devices that support unified addressing is the same as the pointer value through which that memory is accessed on the host, so it is not necessary to call `cuMemHostGetDevicePointer()` to get the device pointer for these allocations.

Note that this is not the case for memory allocated using the flag `CU_MEMHOSTALLOC_WRITECOMBINED`, as discussed below.

4.36.6 Automatic Registration of Peer Memory

Upon enabling direct access from a context that supports unified addressing to another peer context that supports unified addressing using `cuCtxEnablePeerAccess()` all memory allocated in the peer context using `cuMemAlloc()` and `cuMemAllocPitch()` will immediately be accessible by the current context. The device pointer value through which any peer memory may be accessed in the current context is the same pointer value through which that memory may be accessed in the peer context.

4.36.7 Exceptions, Disjoint Addressing

Not all memory may be accessed on devices through the same pointer value through which they are accessed on the host. These exceptions are host memory registered using `cuMemHostRegister()` and host memory allocated using the flag `CU_MEMHOSTALLOC_WRITECOMBINED`. For these exceptions, there exists a distinct host and device address for the memory. The device address is guaranteed to not overlap any valid host pointer range and is guaranteed to have the same value across all contexts that support unified addressing.

This device address may be queried using `cuMemHostGetDevicePointer()` when a context using unified addressing is current. Either the host or the unified device pointer value may be used to refer to this memory through `cuMemcpy()` and similar functions using the `CU_MEMORYTYPE_UNIFIED` memory type.

4.36.8 Function Documentation

4.36.8.1 `CUresult cuPointerGetAttribute (void * data, CUpointer_attribute attribute, CUdeviceptr ptr)`

The supported attributes are:

- `CU_POINTER_ATTRIBUTE_CONTEXT`:

Returns in `*data` the `CUcontext` in which `ptr` was allocated or registered. The type of `data` must be `CUcontext *`.

If `ptr` was not allocated by, mapped by, or registered with a `CUcontext` which uses unified virtual addressing then `CUDA_ERROR_INVALID_VALUE` is returned.

- `CU_POINTER_ATTRIBUTE_MEMORY_TYPE`:

Returns in `*data` the physical memory type of the memory that `ptr` addresses as a `CUmemorytype` enumerated value. The type of `data` must be unsigned int.

If `ptr` addresses device memory then `*data` is set to `CU_MEMORYTYPE_DEVICE`. The particular `CUdevice` on which the memory resides is the `CUdevice` of the `CUcontext` returned by the `CU_POINTER_ATTRIBUTE_CONTEXT` attribute of `ptr`.

If `ptr` addresses host memory then `*data` is set to `CU_MEMORYTYPE_HOST`.

If `ptr` was not allocated by, mapped by, or registered with a `CUcontext` which uses unified virtual addressing then `CUDA_ERROR_INVALID_VALUE` is returned.

If the current `CUcontext` does not support unified virtual addressing then `CUDA_ERROR_INVALID_CONTEXT` is returned.

- `CU_POINTER_ATTRIBUTE_DEVICE_POINTER`:

Returns in `*data` the device pointer value through which `ptr` may be accessed by kernels running in the current `CUcontext`. The type of `data` must be `CUdeviceptr *`.

If there exists no device pointer value through which kernels running in the current `CUcontext` may access `ptr` then `CUDA_ERROR_INVALID_VALUE` is returned.

If there is no current `CUcontext` then `CUDA_ERROR_INVALID_CONTEXT` is returned.

Except in the exceptional disjoint addressing cases discussed below, the value returned in `*data` will equal the input value `ptr`.

- `CU_POINTER_ATTRIBUTE_HOST_POINTER`:

Returns in `*data` the host pointer value through which `ptr` may be accessed by the host program. The type of `data` must be `void **`. If there exists no host pointer value through which the host program may directly access `ptr` then `CUDA_ERROR_INVALID_VALUE` is returned.

Except in the exceptional disjoint addressing cases discussed below, the value returned in `*data` will equal the input value `ptr`.

Note that for most allocations in the unified virtual address space the host and device pointer for accessing the allocation will be the same. The exceptions to this are

- user memory registered using `cuMemHostRegister`
- host memory allocated using `cuMemHostAlloc` with the `CU_MEMHOSTALLOC_WRITECOMBINED` flag
For these types of allocation there will exist separate, disjoint host and device addresses for accessing the allocation. In particular
- The host address will correspond to an invalid unmapped device address (which will result in an exception if accessed from the device)
- The device address will correspond to an invalid unmapped host address (which will result in an exception if accessed from the host). For these types of allocations, querying `CU_POINTER_ATTRIBUTE_HOST_POINTER` and `CU_POINTER_ATTRIBUTE_DEVICE_POINTER` may be used to retrieve the host and device addresses from either address.

Parameters:

data - Returned pointer attribute value

attribute - Pointer attribute to query

ptr - Pointer

Returns:

`CUDA_SUCCESS`, `CUDA_ERROR_DEINITIALIZED`, `CUDA_ERROR_NOT_INITIALIZED`, `CUDA_ERROR_INVALID_CONTEXT`, `CUDA_ERROR_INVALID_VALUE`, `CUDA_ERROR_INVALID_DEVICE`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuMemAlloc](#), [cuMemFree](#), [cuMemAllocHost](#), [cuMemFreeHost](#), [cuMemHostAlloc](#), [cuMemHostRegister](#),
[cuMemHostUnregister](#)

4.37 Stream Management

Functions

- [CUresult cuStreamCreate](#) ([CUstream](#) *phStream, unsigned int Flags)
Create a stream.
- [CUresult cuStreamDestroy](#) ([CUstream](#) hStream)
Destroys a stream.
- [CUresult cuStreamQuery](#) ([CUstream](#) hStream)
Determine status of a compute stream.
- [CUresult cuStreamSynchronize](#) ([CUstream](#) hStream)
Wait until a stream's tasks are completed.
- [CUresult cuStreamWaitEvent](#) ([CUstream](#) hStream, [CUEvent](#) hEvent, unsigned int Flags)
Make a compute stream wait on an event.

4.37.1 Detailed Description

This section describes the stream management functions of the low-level CUDA driver application programming interface.

4.37.2 Function Documentation

4.37.2.1 [CUresult cuStreamCreate](#) ([CUstream](#) *phStream, unsigned int Flags)

Creates a stream and returns a handle in phStream. Flags is required to be 0.

Parameters:

- phStream* - Returned newly created stream
Flags - Parameters for stream creation (must be 0)

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuStreamDestroy](#), [cuStreamWaitEvent](#), [cuStreamQuery](#), [cuStreamSynchronize](#)

4.37.2.2 CUresult cuStreamDestroy (CUstream *hStream*)

Destroys the stream specified by `hStream`.

In the case that the device is still doing work in the stream `hStream` when `cuStreamDestroy()` is called, the function will return immediately and the resources associated with `hStream` will be released automatically once the device has completed all work in `hStream`.

Parameters:

hStream - Stream to destroy

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuStreamCreate](#), [cuStreamWaitEvent](#), [cuStreamQuery](#), [cuStreamSynchronize](#)

4.37.2.3 CUresult cuStreamQuery (CUstream *hStream*)

Returns [CUDA_SUCCESS](#) if all operations in the stream specified by `hStream` have completed, or [CUDA_ERROR_NOT_READY](#) if not.

Parameters:

hStream - Stream to query status of

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_READY](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuStreamCreate](#), [cuStreamWaitEvent](#), [cuStreamDestroy](#), [cuStreamSynchronize](#)

4.37.2.4 CUresult cuStreamSynchronize (CUstream *hStream*)

Waits until the device has completed all operations in the stream specified by `hStream`. If the context was created with the [CU_CTX_SCHED_BLOCKING_SYNC](#) flag, the CPU thread will block until the stream is finished with all of its tasks.

Parameters:

hStream - Stream to wait for

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuStreamCreate](#), [cuStreamDestroy](#), [cuStreamWaitEvent](#), [cuStreamQuery](#)

4.37.2.5 CUresult cuStreamWaitEvent (CUstream hStream, CUEvent hEvent, unsigned int Flags)

Makes all future work submitted to `hStream` wait until `hEvent` reports completion before beginning execution. This synchronization will be performed efficiently on the device. The event `hEvent` may be from a different context than `hStream`, in which case this function will perform cross-device synchronization.

The stream `hStream` will wait only for the completion of the most recent host call to [cuEventRecord\(\)](#) on `hEvent`. Once this call has returned, any functions (including [cuEventRecord\(\)](#) and [cuEventDestroy\(\)](#)) may be called on `hEvent` again, and the subsequent calls will not have any effect on `hStream`.

If `hStream` is 0 (the NULL stream) any future work submitted in any stream will wait for `hEvent` to complete before beginning execution. This effectively creates a barrier for all future work submitted to the context.

If [cuEventRecord\(\)](#) has not been called on `hEvent`, this call acts as if the record has already completed, and so is a functional no-op.

Parameters:

hStream - Stream to wait

hEvent - Event to wait on (may not be NULL)

Flags - Parameters for the operation (must be 0)

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuStreamCreate](#), [cuEventRecord](#), [cuStreamQuery](#), [cuStreamSynchronize](#), [cuStreamDestroy](#)

4.38 Event Management

Functions

- [CUresult cuEventCreate](#) ([CUevent](#) *phEvent, unsigned int Flags)
Creates an event.
- [CUresult cuEventDestroy](#) ([CUevent](#) hEvent)
Destroys an event.
- [CUresult cuEventElapsedTime](#) (float *pMilliseconds, [CUevent](#) hStart, [CUevent](#) hEnd)
Computes the elapsed time between two events.
- [CUresult cuEventQuery](#) ([CUevent](#) hEvent)
Queries an event's status.
- [CUresult cuEventRecord](#) ([CUevent](#) hEvent, [CUstream](#) hStream)
Records an event.
- [CUresult cuEventSynchronize](#) ([CUevent](#) hEvent)
Waits for an event to complete.

4.38.1 Detailed Description

This section describes the event management functions of the low-level CUDA driver application programming interface.

4.38.2 Function Documentation

4.38.2.1 [CUresult cuEventCreate](#) ([CUevent](#) *phEvent, unsigned int Flags)

Creates an event *phEvent with the flags specified via `Flags`. Valid flags include:

- [CU_EVENT_DEFAULT](#): Default event creation flag.
- [CU_EVENT_BLOCKING_SYNC](#): Specifies that the created event should use blocking synchronization. A CPU thread that uses [cuEventSynchronize\(\)](#) to wait on an event created with this flag will block until the event has actually been recorded.
- [CU_EVENT_DISABLE_TIMING](#): Specifies that the created event does not need to record timing data. Events created with this flag specified and the [CU_EVENT_BLOCKING_SYNC](#) flag not specified will provide the best performance when used with [cuStreamWaitEvent\(\)](#) and [cuEventQuery\(\)](#).

Parameters:

phEvent - Returns newly created event
Flags - Event creation flags

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuEventRecord](#), [cuEventQuery](#), [cuEventSynchronize](#), [cuEventDestroy](#), [cuEventElapsedTime](#)

4.38.2.2 CUresult cuEventDestroy (CUevent *hEvent*)

Destroys the event specified by *hEvent*.

In the case that *hEvent* has been recorded but has not yet been completed when [cuEventDestroy\(\)](#) is called, the function will return immediately and the resources associated with *hEvent* will be released automatically once the device has completed *hEvent*.

Parameters:

hEvent - Event to destroy

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuEventCreate](#), [cuEventRecord](#), [cuEventQuery](#), [cuEventSynchronize](#), [cuEventElapsedTime](#)

4.38.2.3 CUresult cuEventElapsedTime (float * *pMilliseconds*, CUevent *hStart*, CUevent *hEnd*)

Computes the elapsed time between two events (in milliseconds with a resolution of around 0.5 microseconds).

If either event was last recorded in a non-NULL stream, the resulting time may be greater than expected (even if both used the same stream handle). This happens because the [cuEventRecord\(\)](#) operation takes place asynchronously and there is no guarantee that the measured latency is actually just between the two events. Any number of other different stream operations could execute in between the two measured events, thus altering the timing in a significant way.

If [cuEventRecord\(\)](#) has not been called on either event then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If [cuEventRecord\(\)](#) has been called on both events but one or both of them has not yet been completed (that is, [cuEventQuery\(\)](#) would return [CUDA_ERROR_NOT_READY](#) on at least one of the events), [CUDA_ERROR_NOT_READY](#) is returned. If either event was created with the [CU_EVENT_DISABLE_TIMING](#) flag, then this function will return [CUDA_ERROR_INVALID_HANDLE](#).

Parameters:

pMilliseconds - Time between *hStart* and *hEnd* in ms

hStart - Starting event

hEnd - Ending event

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_READY](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuEventCreate](#), [cuEventRecord](#), [cuEventQuery](#), [cuEventSynchronize](#), [cuEventDestroy](#)

4.38.2.4 CUresult cuEventQuery (CUevent *hEvent*)

Query the status of all device work preceding the most recent call to [cuEventRecord\(\)](#) (in the appropriate compute streams, as specified by the arguments to [cuEventRecord\(\)](#)).

If this work has successfully been completed by the device, or if [cuEventRecord\(\)](#) has not been called on `hEvent`, then [CUDA_SUCCESS](#) is returned. If this work has not yet been completed by the device then [CUDA_ERROR_NOT_READY](#) is returned.

Parameters:

hEvent - Event to query

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_NOT_READY](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuEventCreate](#), [cuEventRecord](#), [cuEventSynchronize](#), [cuEventDestroy](#), [cuEventElapsedTime](#)

4.38.2.5 CUresult cuEventRecord (CUevent *hEvent*, CUstream *hStream*)

Records an event. If `hStream` is non-zero, the event is recorded after all preceding operations in `hStream` have been completed; otherwise, it is recorded after all preceding operations in the CUDA context have been completed. Since operation is asynchronous, [cuEventQuery](#) and/or [cuEventSynchronize\(\)](#) must be used to determine when the event has actually been recorded.

If [cuEventRecord\(\)](#) has previously been called on `hEvent`, then this call will overwrite any existing state in `hEvent`. Any subsequent calls which examine the status of `hEvent` will only examine the completion of this most recent call to [cuEventRecord\(\)](#).

It is necessary that `hEvent` and `hStream` be created on the same context.

Parameters:

hEvent - Event to record

hStream - Stream to record event for

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuEventCreate](#), [cuEventQuery](#), [cuEventSynchronize](#), [cuStreamWaitEvent](#), [cuEventDestroy](#), [cuEventElapsedTime](#)

4.38.2.6 CUresult cuEventSynchronize (CUevent *hEvent*)

Wait until the completion of all device work preceding the most recent call to [cuEventRecord\(\)](#) (in the appropriate compute streams, as specified by the arguments to [cuEventRecord\(\)](#)).

If [cuEventRecord\(\)](#) has not been called on *hEvent*, [CUDA_SUCCESS](#) is returned immediately.

Waiting for an event that was created with the [CU_EVENT_BLOCKING_SYNC](#) flag will cause the calling CPU thread to block until the event has been completed by the device. If the [CU_EVENT_BLOCKING_SYNC](#) flag has not been set, then the CPU thread will busy-wait until the event has been completed by the device.

Parameters:

hEvent - Event to wait for

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuEventCreate](#), [cuEventRecord](#), [cuEventQuery](#), [cuEventDestroy](#), [cuEventElapsedTime](#)

4.39 Execution Control

Modules

- [Execution Control \[DEPRECATED\]](#)

Functions

- [CUresult cuFuncGetAttribute](#) (int *pi, [CUfunction_attribute](#) attrib, [CUfunction](#) hfunc)
Returns information about a function.
- [CUresult cuFuncSetCacheConfig](#) ([CUfunction](#) hfunc, [CUfunc_cache](#) config)
Sets the preferred cache configuration for a device function.
- [CUresult cuLaunchKernel](#) ([CUfunction](#) f, unsigned int gridDimX, unsigned int gridDimY, unsigned int gridDimZ, unsigned int blockDimX, unsigned int blockDimY, unsigned int blockDimZ, unsigned int sharedMemBytes, [CUSTream](#) hStream, void **kernelParams, void **extra)
Launches a CUDA function.

4.39.1 Detailed Description

This section describes the execution control functions of the low-level CUDA driver application programming interface.

4.39.2 Function Documentation

4.39.2.1 [CUresult cuFuncGetAttribute](#) (int *pi, [CUfunction_attribute](#) attrib, [CUfunction](#) hfunc)

Returns in *pi the integer value of the attribute `attrib` on the kernel given by `hfunc`. The supported attributes are:

- [CU_FUNC_ATTRIBUTE_MAX_THREADS_PER_BLOCK](#): The maximum number of threads per block, beyond which a launch of the function would fail. This number depends on both the function and the device on which the function is currently loaded.
- [CU_FUNC_ATTRIBUTE_SHARED_SIZE_BYTES](#): The size in bytes of statically-allocated shared memory per block required by this function. This does not include dynamically-allocated shared memory requested by the user at runtime.
- [CU_FUNC_ATTRIBUTE_CONST_SIZE_BYTES](#): The size in bytes of user-allocated constant memory required by this function.
- [CU_FUNC_ATTRIBUTE_LOCAL_SIZE_BYTES](#): The size in bytes of local memory used by each thread of this function.
- [CU_FUNC_ATTRIBUTE_NUM_REGS](#): The number of registers used by each thread of this function.
- [CU_FUNC_ATTRIBUTE_PTX_VERSION](#): The PTX virtual architecture version for which the function was compiled. This value is the major PTX version * 10 + the minor PTX version, so a PTX version 1.3 function would return the value 13. Note that this may return the undefined value of 0 for cubins compiled prior to CUDA 3.0.

- [CU_FUNC_ATTRIBUTE_BINARY_VERSION](#): The binary architecture version for which the function was compiled. This value is the major binary version * 10 + the minor binary version, so a binary version 1.3 function would return the value 13. Note that this will return a value of 10 for legacy cubins that do not have a properly-encoded binary architecture version.

Parameters:

pi - Returned attribute value
attrib - Attribute requested
hfunc - Function to query attribute of

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxGetCacheConfig](#), [cuCtxSetCacheConfig](#), [cuFuncSetCacheConfig](#), [cuLaunchKernel](#)

4.39.2.2 CUresult cuFuncSetCacheConfig (CUfunction *hfunc*, CUfunc_cache *config*)

On devices where the L1 cache and shared memory use the same hardware resources, this sets through `config` the preferred cache configuration for the device function `hfunc`. This is only a preference. The driver will use the requested configuration if possible, but it is free to choose a different configuration if required to execute `hfunc`. Any context-wide preference set via [cuCtxSetCacheConfig\(\)](#) will be overridden by this per-function setting unless the per-function setting is [CU_FUNC_CACHE_PREFER_NONE](#). In that case, the current context-wide setting will be used.

This setting does nothing on devices where the size of the L1 cache and shared memory are fixed.

Launching a kernel with a different preference than the most recent preference setting may insert a device-side synchronization point.

The supported cache configurations are:

- [CU_FUNC_CACHE_PREFER_NONE](#): no preference for shared memory or L1 (default)
- [CU_FUNC_CACHE_PREFER_SHARED](#): prefer larger shared memory and smaller L1 cache
- [CU_FUNC_CACHE_PREFER_L1](#): prefer larger L1 cache and smaller shared memory
- [CU_FUNC_CACHE_PREFER_EQUAL](#): prefer equal sized L1 cache and shared memory

Parameters:

hfunc - Kernel to configure cache for
config - Requested cache configuration

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxGetCacheConfig](#), [cuCtxSetCacheConfig](#), [cuFuncGetAttribute](#), [cuLaunchKernel](#)

4.39.2.3 CUresult cuLaunchKernel (CUfunction *f*, unsigned int *gridDimX*, unsigned int *gridDimY*, unsigned int *gridDimZ*, unsigned int *blockDimX*, unsigned int *blockDimY*, unsigned int *blockDimZ*, unsigned int *sharedMemBytes*, CUSTream *hStream*, void ** *kernelParams*, void ** *extra*)

Invokes the kernel *f* on a *gridDimX* x *gridDimY* x *gridDimZ* grid of blocks. Each block contains *blockDimX* x *blockDimY* x *blockDimZ* threads.

sharedMemBytes sets the amount of dynamic shared memory that will be available to each thread block.

[cuLaunchKernel\(\)](#) can optionally be associated to a stream by passing a non-zero *hStream* argument.

Kernel parameters to *f* can be specified in one of two ways:

1) Kernel parameters can be specified via *kernelParams*. If *f* has *N* parameters, then *kernelParams* needs to be an array of *N* pointers. Each of *kernelParams*[0] through *kernelParams*[*N*-1] must point to a region of memory from which the actual kernel parameter will be copied. The number of kernel parameters and their offsets and sizes do not need to be specified as that information is retrieved directly from the kernel's image.

2) Kernel parameters can also be packaged by the application into a single buffer that is passed in via the *extra* parameter. This places the burden on the application of knowing each kernel parameter's size and alignment/padding within the buffer. Here is an example of using the *extra* parameter in this manner:

```
size_t argBufferSize;
char argBuffer[256];

// populate argBuffer and argBufferSize

void *config[] = {
    CU_LAUNCH_PARAM_BUFFER_POINTER, argBuffer,
    CU_LAUNCH_PARAM_BUFFER_SIZE,    &argBufferSize,
    CU_LAUNCH_PARAM_END
};
status = cuLaunchKernel(f, gx, gy, gz, bx, by, bz, sh, s, NULL, config);
```

The *extra* parameter exists to allow [cuLaunchKernel](#) to take additional less commonly used arguments. *extra* specifies a list of names of extra settings and their corresponding values. Each extra setting name is immediately followed by the corresponding value. The list must be terminated with either NULL or [CU_LAUNCH_PARAM_END](#).

- [CU_LAUNCH_PARAM_END](#), which indicates the end of the *extra* array;
- [CU_LAUNCH_PARAM_BUFFER_POINTER](#), which specifies that the next value in *extra* will be a pointer to a buffer containing all the kernel parameters for launching kernel *f*;
- [CU_LAUNCH_PARAM_BUFFER_SIZE](#), which specifies that the next value in *extra* will be a pointer to a `size_t` containing the size of the buffer specified with [CU_LAUNCH_PARAM_BUFFER_POINTER](#);

The error [CUDA_ERROR_INVALID_VALUE](#) will be returned if kernel parameters are specified with both *kernelParams* and *extra* (i.e. both *kernelParams* and *extra* are non-NULL).

Calling [cuLaunchKernel\(\)](#) sets persistent function state that is the same as function state set through the following deprecated APIs:

[cuFuncSetBlockShape\(\)](#) [cuFuncSetSharedSize\(\)](#) [cuParamSetSize\(\)](#) [cuParamSeti\(\)](#) [cuParamSetf\(\)](#) [cuParamSetv\(\)](#)

When the kernel `f` is launched via [cuLaunchKernel\(\)](#), the previous block shape, shared size and parameter info associated with `f` is overwritten.

Note that to use [cuLaunchKernel\(\)](#), the kernel `f` must either have been compiled with toolchain version 3.2 or later so that it will contain kernel parameter information, or have no kernel parameters. If either of these conditions is not met, then [cuLaunchKernel\(\)](#) will return [CUDA_ERROR_INVALID_IMAGE](#).

Parameters:

f - Kernel to launch
gridDimX - Width of grid in blocks
gridDimY - Height of grid in blocks
gridDimZ - Depth of grid in blocks
blockDimX - X dimension of each thread block
blockDimY - Y dimension of each thread block
blockDimZ - Z dimension of each thread block
sharedMemBytes - Dynamic shared-memory size per thread block in bytes
hStream - Stream identifier
kernelParams - Array of pointers to kernel parameters
extra - Extra options

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_INVALID_IMAGE](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_LAUNCH_FAILED](#), [CUDA_ERROR_LAUNCH_OUT_OF_RESOURCES](#), [CUDA_ERROR_LAUNCH_TIMEOUT](#), [CUDA_ERROR_LAUNCH_INCOMPATIBLE_TEXTURING](#), [CUDA_ERROR_SHARED_OBJECT_INIT_FAILED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxGetCacheConfig](#), [cuCtxSetCacheConfig](#), [cuFuncSetCacheConfig](#), [cuFuncGetAttribute](#),

4.40 Execution Control [DEPRECATED]

Functions

- **CUresult cuFuncSetBlockShape** (**CUfunction** hfunc, int x, int y, int z)
Sets the block-dimensions for the function.
- **CUresult cuFuncSetSharedSize** (**CUfunction** hfunc, unsigned int bytes)
Sets the dynamic shared-memory size for the function.
- **CUresult cuLaunch** (**CUfunction** f)
Launches a CUDA function.
- **CUresult cuLaunchGrid** (**CUfunction** f, int grid_width, int grid_height)
Launches a CUDA function.
- **CUresult cuLaunchGridAsync** (**CUfunction** f, int grid_width, int grid_height, **CUstream** hStream)
Launches a CUDA function.
- **CUresult cuParamSetf** (**CUfunction** hfunc, int offset, float value)
Adds a floating-point parameter to the function's argument list.
- **CUresult cuParamSeti** (**CUfunction** hfunc, int offset, unsigned int value)
Adds an integer parameter to the function's argument list.
- **CUresult cuParamSetSize** (**CUfunction** hfunc, unsigned int numbytes)
Sets the parameter size for the function.
- **CUresult cuParamSetTexRef** (**CUfunction** hfunc, int texunit, **CUTexref** hTexRef)
Adds a texture-reference to the function's argument list.
- **CUresult cuParamSetv** (**CUfunction** hfunc, int offset, void *ptr, unsigned int numbytes)
Adds arbitrary data to the function's argument list.

4.40.1 Detailed Description

This section describes the deprecated execution control functions of the low-level CUDA driver application programming interface.

4.40.2 Function Documentation

4.40.2.1 CUresult cuFuncSetBlockShape (**CUfunction** hfunc, int x, int y, int z)

Deprecated

Specifies the x, y, and z dimensions of the thread blocks that are created when the kernel given by hfunc is launched.

Parameters:

hfunc - Kernel to specify dimensions of

x - X dimension

y - Y dimension

z - Z dimension

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_HANDLE, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuFuncSetSharedSize, cuFuncSetCacheConfig, cuFuncGetAttribute, cuParamSetSize, cuParamSeti, cuParamSetf, cuParamSetv, cuLaunch, cuLaunchGrid, cuLaunchGridAsync, cuLaunchKernel

4.40.2.2 CUresult cuFuncSetSharedSize (CUfunction *hfunc*, unsigned int *bytes*)**Deprecated**

Sets through *bytes* the amount of dynamic shared memory that will be available to each thread block when the kernel given by *hfunc* is launched.

Parameters:

hfunc - Kernel to specify dynamic shared-memory size for

bytes - Dynamic shared-memory size per thread in bytes

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_HANDLE, CUDA_ERROR_INVALID_VALUE

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuFuncSetBlockShape, cuFuncSetCacheConfig, cuFuncGetAttribute, cuParamSetSize, cuParamSeti, cuParamSetf, cuParamSetv, cuLaunch, cuLaunchGrid, cuLaunchGridAsync, cuLaunchKernel

4.40.2.3 CUresult cuLaunch (CUfunction *f*)**Deprecated**

Invokes the kernel `f` on a 1 x 1 x 1 grid of blocks. The block contains the number of threads specified by a previous call to [cuFuncSetBlockShape\(\)](#).

Parameters:

f - Kernel to launch

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_LAUNCH_FAILED](#), [CUDA_ERROR_LAUNCH_OUT_OF_RESOURCES](#), [CUDA_ERROR_LAUNCH_TIMEOUT](#), [CUDA_ERROR_LAUNCH_INCOMPATIBLE_TEXTURING](#), [CUDA_ERROR_SHARED_OBJECT_INIT_FAILED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuFuncSetBlockShape](#), [cuFuncSetSharedSize](#), [cuFuncGetAttribute](#), [cuParamSetSize](#), [cuParamSetf](#), [cuParamSeti](#), [cuParamSetv](#), [cuLaunchGrid](#), [cuLaunchGridAsync](#), [cuLaunchKernel](#)

4.40.2.4 CUresult cuLaunchGrid (CUfunction *f*, int *grid_width*, int *grid_height*)

Deprecated

Invokes the kernel `f` on a `grid_width` x `grid_height` grid of blocks. Each block contains the number of threads specified by a previous call to [cuFuncSetBlockShape\(\)](#).

Parameters:

f - Kernel to launch

grid_width - Width of grid in blocks

grid_height - Height of grid in blocks

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_LAUNCH_FAILED](#), [CUDA_ERROR_LAUNCH_OUT_OF_RESOURCES](#), [CUDA_ERROR_LAUNCH_TIMEOUT](#), [CUDA_ERROR_LAUNCH_INCOMPATIBLE_TEXTURING](#), [CUDA_ERROR_SHARED_OBJECT_INIT_FAILED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuFuncSetBlockShape](#), [cuFuncSetSharedSize](#), [cuFuncGetAttribute](#), [cuParamSetSize](#), [cuParamSetf](#), [cuParamSeti](#), [cuParamSetv](#), [cuLaunch](#), [cuLaunchGridAsync](#), [cuLaunchKernel](#)

4.40.2.5 CUresult cuLaunchGridAsync (CUfunction *f*, int *grid_width*, int *grid_height*, CUSTream *hStream*)**Deprecated**

Invokes the kernel *f* on a *grid_width* x *grid_height* grid of blocks. Each block contains the number of threads specified by a previous call to [cuFuncSetBlockShape\(\)](#).

[cuLaunchGridAsync\(\)](#) can optionally be associated to a stream by passing a non-zero *hStream* argument.

Parameters:

f - Kernel to launch

grid_width - Width of grid in blocks

grid_height - Height of grid in blocks

hStream - Stream identifier

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_LAUNCH_FAILED](#), [CUDA_ERROR_LAUNCH_OUT_OF_RESOURCES](#), [CUDA_ERROR_LAUNCH_TIMEOUT](#), [CUDA_ERROR_LAUNCH_INCOMPATIBLE_TEXTURING](#), [CUDA_ERROR_SHARED_OBJECT_INIT_FAILED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuFuncSetBlockShape](#), [cuFuncSetSharedSize](#), [cuFuncGetAttribute](#), [cuParamSetSize](#), [cuParamSetf](#), [cuParamSeti](#), [cuParamSetv](#), [cuLaunch](#), [cuLaunchGrid](#), [cuLaunchKernel](#)

4.40.2.6 CUresult cuParamSetf (CUfunction *hfunc*, int *offset*, float *value*)**Deprecated**

Sets a floating-point parameter that will be specified the next time the kernel corresponding to *hfunc* will be invoked. *offset* is a byte offset.

Parameters:

hfunc - Kernel to add parameter to

offset - Offset to add parameter to argument list

value - Value of parameter

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuFuncSetBlockShape](#), [cuFuncSetSharedSize](#), [cuFuncGetAttribute](#), [cuParamSetSize](#), [cuParamSeti](#), [cuParamSetv](#), [cuLaunch](#), [cuLaunchGrid](#), [cuLaunchGridAsync](#), [cuLaunchKernel](#)

4.40.2.7 CUresult cuParamSeti (CUfunction *hfunc*, int *offset*, unsigned int *value*)**Deprecated**

Sets an integer parameter that will be specified the next time the kernel corresponding to *hfunc* will be invoked. *offset* is a byte offset.

Parameters:

hfunc - Kernel to add parameter to
offset - Offset to add parameter to argument list
value - Value of parameter

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuFuncSetBlockShape](#), [cuFuncSetSharedSize](#), [cuFuncGetAttribute](#), [cuParamSetSize](#), [cuParamSetf](#), [cuParamSetv](#), [cuLaunch](#), [cuLaunchGrid](#), [cuLaunchGridAsync](#), [cuLaunchKernel](#)

4.40.2.8 CUresult cuParamSetSize (CUfunction *hfunc*, unsigned int *numbytes*)**Deprecated**

Sets through *numbytes* the total size in bytes needed by the function parameters of the kernel corresponding to *hfunc*.

Parameters:

hfunc - Kernel to set parameter size for
numbytes - Size of parameter list in bytes

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuFuncSetBlockShape](#), [cuFuncSetSharedSize](#), [cuFuncGetAttribute](#), [cuParamSetf](#), [cuParamSeti](#), [cuParamSetv](#), [cuLaunch](#), [cuLaunchGrid](#), [cuLaunchGridAsync](#), [cuLaunchKernel](#)

4.40.2.9 CUresult cuParamSetTexRef (CUfunction *hfunc*, int *texunit*, CUtexref *hTexRef*)**Deprecated**

Makes the CUDA array or linear memory bound to the texture reference `hTexRef` available to a device program as a texture. In this version of CUDA, the texture-reference must be obtained via [cuModuleGetTexRef\(\)](#) and the `texunit` parameter must be set to [CU_PARAM_TR_DEFAULT](#).

Parameters:

hfunc - Kernel to add texture-reference to
texunit - Texture unit (must be [CU_PARAM_TR_DEFAULT](#))
hTexRef - Texture-reference to add to argument list

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

4.40.2.10 CUresult cuParamSetv (CUfunction *hfunc*, int *offset*, void * *ptr*, unsigned int *numbytes*)**Deprecated**

Copies an arbitrary amount of data (specified in `numbytes`) from `ptr` into the parameter space of the kernel corresponding to `hfunc`. `offset` is a byte offset.

Parameters:

hfunc - Kernel to add data to
offset - Offset to add data to argument list
ptr - Pointer to arbitrary data
numbytes - Size of data to copy in bytes

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuFuncSetBlockShape](#), [cuFuncSetSharedSize](#), [cuFuncGetAttribute](#), [cuParamSetSize](#), [cuParamSetf](#), [cuParamSeti](#), [cuLaunch](#), [cuLaunchGrid](#), [cuLaunchGridAsync](#), [cuLaunchKernel](#)

4.41 Texture Reference Management

Modules

- [Texture Reference Management \[DEPRECATED\]](#)

Functions

- [CUresult cuTexRefGetAddress](#) (CUdeviceptr *pdptr, CUtexref hTexRef)
Gets the address associated with a texture reference.
- [CUresult cuTexRefGetAddressMode](#) (CUaddress_mode *pam, CUtexref hTexRef, int dim)
Gets the addressing mode used by a texture reference.
- [CUresult cuTexRefGetArray](#) (CUarray *phArray, CUtexref hTexRef)
Gets the array bound to a texture reference.
- [CUresult cuTexRefGetFilterMode](#) (CUfilter_mode *pfm, CUtexref hTexRef)
Gets the filter-mode used by a texture reference.
- [CUresult cuTexRefGetFlags](#) (unsigned int *pFlags, CUtexref hTexRef)
Gets the flags used by a texture reference.
- [CUresult cuTexRefGetFormat](#) (CUarray_format *pFormat, int *pNumChannels, CUtexref hTexRef)
Gets the format used by a texture reference.
- [CUresult cuTexRefSetAddress](#) (size_t *ByteOffset, CUtexref hTexRef, CUdeviceptr dptr, size_t bytes)
Binds an address as a texture reference.
- [CUresult cuTexRefSetAddress2D](#) (CUtexref hTexRef, const CUDA_ARRAY_DESCRIPTOR *desc, CUdeviceptr dptr, size_t Pitch)
Binds an address as a 2D texture reference.
- [CUresult cuTexRefSetAddressMode](#) (CUtexref hTexRef, int dim, CUaddress_mode am)
Sets the addressing mode for a texture reference.
- [CUresult cuTexRefSetArray](#) (CUtexref hTexRef, CUarray hArray, unsigned int Flags)
Binds an array as a texture reference.
- [CUresult cuTexRefSetFilterMode](#) (CUtexref hTexRef, CUfilter_mode fm)
Sets the filtering mode for a texture reference.
- [CUresult cuTexRefSetFlags](#) (CUtexref hTexRef, unsigned int Flags)
Sets the flags for a texture reference.
- [CUresult cuTexRefSetFormat](#) (CUtexref hTexRef, CUarray_format fmt, int NumPackedComponents)
Sets the format for a texture reference.

4.41.1 Detailed Description

This section describes the texture reference management functions of the low-level CUDA driver application programming interface.

4.41.2 Function Documentation

4.41.2.1 CUresult cuTexRefGetAddress (CUdeviceptr **pdptr*, CUtexref *hTexRef*)

Returns in **pdptr* the base address bound to the texture reference *hTexRef*, or returns [CUDA_ERROR_INVALID_VALUE](#) if the texture reference is not bound to any device memory range.

Parameters:

pdptr - Returned device address

hTexRef - Texture reference

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefSetAddress](#), [cuTexRefSetAddress2D](#), [cuTexRefSetAddressMode](#), [cuTexRefSetArray](#), [cuTexRefSetFilterMode](#), [cuTexRefSetFlags](#), [cuTexRefSetFormat](#), [cuTexRefGetAddressMode](#), [cuTexRefGetArray](#), [cuTexRefGetFilterMode](#), [cuTexRefGetFlags](#), [cuTexRefGetFormat](#)

4.41.2.2 CUresult cuTexRefGetAddressMode (CUaddress_mode **pam*, CUtexref *hTexRef*, int *dim*)

Returns in **pam* the addressing mode corresponding to the dimension *dim* of the texture reference *hTexRef*. Currently, the only valid value for *dim* are 0 and 1.

Parameters:

pam - Returned addressing mode

hTexRef - Texture reference

dim - Dimension

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefSetAddress](#), [cuTexRefSetAddress2D](#), [cuTexRefSetAddressMode](#), [cuTexRefSetArray](#), [cuTexRefSetFilterMode](#), [cuTexRefSetFlags](#), [cuTexRefSetFormat](#), [cuTexRefGetAddress](#), [cuTexRefGetArray](#), [cuTexRefGetFilterMode](#), [cuTexRefGetFlags](#), [cuTexRefGetFormat](#)

4.41.2.3 CUresult cuTexRefGetArray (CUarray * *phArray*, CUtexref *hTexRef*)

Returns in **phArray* the CUDA array bound to the texture reference *hTexRef*, or returns [CUDA_ERROR_INVALID_VALUE](#) if the texture reference is not bound to any CUDA array.

Parameters:

phArray - Returned array
hTexRef - Texture reference

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefSetAddress](#), [cuTexRefSetAddress2D](#), [cuTexRefSetAddressMode](#), [cuTexRefSetArray](#), [cuTexRefSetFilterMode](#), [cuTexRefSetFlags](#), [cuTexRefSetFormat](#), [cuTexRefGetAddress](#), [cuTexRefGetAddressMode](#), [cuTexRefGetFilterMode](#), [cuTexRefGetFlags](#), [cuTexRefGetFormat](#)

4.41.2.4 CUresult cuTexRefGetFilterMode (CUfilter_mode * *pfm*, CUtexref *hTexRef*)

Returns in **pfm* the filtering mode of the texture reference *hTexRef*.

Parameters:

pfm - Returned filtering mode
hTexRef - Texture reference

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefSetAddress](#), [cuTexRefSetAddress2D](#), [cuTexRefSetAddressMode](#), [cuTexRefSetArray](#), [cuTexRefSetFilterMode](#), [cuTexRefSetFlags](#), [cuTexRefSetFormat](#), [cuTexRefGetAddress](#), [cuTexRefGetAddressMode](#), [cuTexRefGetArray](#), [cuTexRefGetFlags](#), [cuTexRefGetFormat](#)

4.41.2.5 CUresult cuTexRefGetFlags (unsigned int * *pFlags*, CUtexref *hTexRef*)

Returns in **pFlags* the flags of the texture reference *hTexRef*.

Parameters:

pFlags - Returned flags
hTexRef - Texture reference

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefSetAddress](#), [cuTexRefSetAddress2D](#), [cuTexRefSetAddressMode](#), [cuTexRefSetArray](#), [cuTexRefSetFilterMode](#), [cuTexRefSetFlags](#), [cuTexRefSetFormat](#), [cuTexRefGetAddress](#), [cuTexRefGetAddressMode](#), [cuTexRefGetArray](#), [cuTexRefGetFilterMode](#), [cuTexRefGetFormat](#)

4.41.2.6 CUresult cuTexRefGetFormat (CUarray_format * *pFormat*, int * *pNumChannels*, CUtexref *hTexRef*)

Returns in **pFormat* and **pNumChannels* the format and number of components of the CUDA array bound to the texture reference *hTexRef*. If *pFormat* or *pNumChannels* is NULL, it will be ignored.

Parameters:

pFormat - Returned format
pNumChannels - Returned number of components
hTexRef - Texture reference

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefSetAddress](#), [cuTexRefSetAddress2D](#), [cuTexRefSetAddressMode](#), [cuTexRefSetArray](#), [cuTexRefSetFilterMode](#), [cuTexRefSetFlags](#), [cuTexRefSetFormat](#), [cuTexRefGetAddress](#), [cuTexRefGetAddressMode](#), [cuTexRefGetArray](#), [cuTexRefGetFilterMode](#), [cuTexRefGetFlags](#)

4.41.2.7 CUresult cuTexRefSetAddress (size_t * *ByteOffset*, CUtexref *hTexRef*, CUdeviceptr *dptr*, size_t *bytes*)

Binds a linear address range to the texture reference *hTexRef*. Any previous address or CUDA array state associated with the texture reference is superseded by this function. Any memory previously bound to *hTexRef* is unbound.

Since the hardware enforces an alignment requirement on texture base addresses, [cuTexRefSetAddress\(\)](#) passes back a byte offset in **ByteOffset* that must be applied to texture fetches in order to read from the desired memory. This offset must be divided by the texel size and passed to kernels that read from the texture so they can be applied to the [tex1Dfetch\(\)](#) function.

If the device memory pointer was returned from [cuMemAlloc\(\)](#), the offset is guaranteed to be 0 and NULL may be passed as the *ByteOffset* parameter.

The total number of elements (or texels) in the linear address range cannot exceed [CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE1D_LINEAR_WIDTH](#). The number of elements is computed as (*bytes* / *bytesPerElement*), where *bytesPerElement* is determined from the data format and number of components set using [cuTexRefSetFormat\(\)](#).

Parameters:

ByteOffset - Returned byte offset
hTexRef - Texture reference to bind
dptr - Device pointer to bind
bytes - Size of memory to bind in bytes

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

See also:

cuTexRefSetAddress2D, cuTexRefSetAddressMode, cuTexRefSetArray, cuTexRefSetFilterMode, cuTexRefSetFlags, cuTexRefSetFormat, cuTexRefGetAddress, cuTexRefGetAddressMode, cuTexRefGetArray, cuTexRefGetFilterMode, cuTexRefGetFlags, cuTexRefGetFormat

4.41.2.8 CUresult cuTexRefSetAddress2D (CUtexref *hTexRef*, const CUDA_ARRAY_DESCRIPTOR * *desc*, CUdeviceptr *dptr*, size_t *Pitch*)

Binds a linear address range to the texture reference *hTexRef*. Any previous address or CUDA array state associated with the texture reference is superseded by this function. Any memory previously bound to *hTexRef* is unbound.

Using a `tex2D()` function inside a kernel requires a call to either `cuTexRefSetArray()` to bind the corresponding texture reference to an array, or `cuTexRefSetAddress2D()` to bind the texture reference to linear memory.

Function calls to `cuTexRefSetFormat()` cannot follow calls to `cuTexRefSetAddress2D()` for the same texture reference.

It is required that *dptr* be aligned to the appropriate hardware-specific texture alignment. You can query this value using the device attribute `CU_DEVICE_ATTRIBUTE_TEXTURE_ALIGNMENT`. If an unaligned *dptr* is supplied, `CUDA_ERROR_INVALID_VALUE` is returned.

Pitch has to be aligned to the hardware-specific texture pitch alignment. This value can be queried using the device attribute `CU_DEVICE_ATTRIBUTE_TEXTURE_PITCH_ALIGNMENT`. If an unaligned *Pitch* is supplied, `CUDA_ERROR_INVALID_VALUE` is returned.

Width and Height, which are specified in elements (or texels), cannot exceed `CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_WIDTH` and `CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_HEIGHT` respectively. *Pitch*, which is specified in bytes, cannot exceed `CU_DEVICE_ATTRIBUTE_MAXIMUM_TEXTURE2D_LINEAR_PITCH`.

Parameters:

hTexRef - Texture reference to bind

desc - Descriptor of CUDA array

dptr - Device pointer to bind

Pitch - Line pitch in bytes

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE

See also:

cuTexRefSetAddress, cuTexRefSetAddressMode, cuTexRefSetArray, cuTexRefSetFilterMode, cuTexRefSetFlags, cuTexRefSetFormat, cuTexRefGetAddress, cuTexRefGetAddressMode, cuTexRefGetArray, cuTexRefGetFilterMode, cuTexRefGetFlags, cuTexRefGetFormat

4.41.2.9 CUresult cuTexRefSetAddressMode (CUtexref *hTexRef*, int *dim*, CUaddress_mode *am*)

Specifies the addressing mode *am* for the given dimension *dim* of the texture reference *hTexRef*. If *dim* is zero, the addressing mode is applied to the first parameter of the functions used to fetch from the texture; if *dim* is 1, the second, and so on. `CUaddress_mode` is defined as:

```
typedef enum CUaddress_mode_enum {
    CU_TR_ADDRESS_MODE_WRAP = 0,
    CU_TR_ADDRESS_MODE_CLAMP = 1,
    CU_TR_ADDRESS_MODE_MIRROR = 2,
    CU_TR_ADDRESS_MODE_BORDER = 3
} CUaddress_mode;
```

Note that this call has no effect if `hTexRef` is bound to linear memory. Also, if the flag, [CU_TRSF_NORMALIZED_COORDINATES](#), is not set, the only supported address mode is [CU_TR_ADDRESS_MODE_CLAMP](#).

Parameters:

hTexRef - Texture reference

dim - Dimension

am - Addressing mode to set

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefSetAddress](#), [cuTexRefSetAddress2D](#), [cuTexRefSetArray](#), [cuTexRefSetFilterMode](#), [cuTexRefSetFlags](#), [cuTexRefSetFormat](#), [cuTexRefGetAddress](#), [cuTexRefGetAddressMode](#), [cuTexRefGetArray](#), [cuTexRefGetFilterMode](#), [cuTexRefGetFlags](#), [cuTexRefGetFormat](#)

4.41.2.10 CUresult cuTexRefSetArray (CUtexref hTexRef, CUarray hArray, unsigned int Flags)

Binds the CUDA array `hArray` to the texture reference `hTexRef`. Any previous address or CUDA array state associated with the texture reference is superseded by this function. `Flags` must be set to [CU_TRSA_OVERRIDE_FORMAT](#). Any CUDA array previously bound to `hTexRef` is unbound.

Parameters:

hTexRef - Texture reference to bind

hArray - Array to bind

Flags - Options (must be [CU_TRSA_OVERRIDE_FORMAT](#))

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefSetAddress](#), [cuTexRefSetAddress2D](#), [cuTexRefSetAddressMode](#), [cuTexRefSetFilterMode](#), [cuTexRefSetFlags](#), [cuTexRefSetFormat](#), [cuTexRefGetAddress](#), [cuTexRefGetAddressMode](#), [cuTexRefGetArray](#), [cuTexRefGetFilterMode](#), [cuTexRefGetFlags](#), [cuTexRefGetFormat](#)

4.41.2.11 CUresult cuTexRefSetFilterMode (CUtexref *hTexRef*, CUfilter_mode *fm*)

Specifies the filtering mode *fm* to be used when reading memory through the texture reference *hTexRef*. [CUfilter_mode_enum](#) is defined as:

```
typedef enum CUfilter_mode_enum {
    CU_TR_FILTER_MODE_POINT = 0,
    CU_TR_FILTER_MODE_LINEAR = 1
} CUfilter_mode;
```

Note that this call has no effect if *hTexRef* is bound to linear memory.

Parameters:

hTexRef - Texture reference
fm - Filtering mode to set

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefSetAddress](#), [cuTexRefSetAddress2D](#), [cuTexRefSetAddressMode](#), [cuTexRefSetArray](#), [cuTexRefSetFlags](#), [cuTexRefSetFormat](#), [cuTexRefGetAddress](#), [cuTexRefGetAddressMode](#), [cuTexRefGetArray](#), [cuTexRefGetFilterMode](#), [cuTexRefGetFlags](#), [cuTexRefGetFormat](#)

4.41.2.12 CUresult cuTexRefSetFlags (CUtexref *hTexRef*, unsigned int *Flags*)

Specifies optional flags via *Flags* to specify the behavior of data returned through the texture reference *hTexRef*. The valid flags are:

- [CU_TRSF_READ_AS_INTEGER](#), which suppresses the default behavior of having the texture promote integer data to floating point data in the range [0, 1]. Note that texture with 32-bit integer format would not be promoted, regardless of whether or not this flag is specified;
- [CU_TRSF_NORMALIZED_COORDINATES](#), which suppresses the default behavior of having the texture coordinates range from [0, Dim) where Dim is the width or height of the CUDA array. Instead, the texture coordinates [0, 1.0) reference the entire breadth of the array dimension;

Parameters:

hTexRef - Texture reference
Flags - Optional flags to set

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefSetAddress](#), [cuTexRefSetAddress2D](#), [cuTexRefSetAddressMode](#), [cuTexRefSetArray](#), [cuTexRefSetFilterMode](#), [cuTexRefSetFormat](#), [cuTexRefGetAddress](#), [cuTexRefGetAddressMode](#), [cuTexRefGetArray](#), [cuTexRefGetFilterMode](#), [cuTexRefGetFlags](#), [cuTexRefGetFormat](#)

4.41.2.13 CUresult cuTexRefSetFormat (CUtexref *hTexRef*, CUarray_format *fmt*, int *NumPackedComponents*)

Specifies the format of the data to be read by the texture reference *hTexRef*. *fmt* and *NumPackedComponents* are exactly analogous to the *Format* and *NumChannels* members of the [CUDA_ARRAY_DESCRIPTOR](#) structure: They specify the format of each component and the number of components per array element.

Parameters:

hTexRef - Texture reference

fmt - Format to set

NumPackedComponents - Number of components per array element

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefSetAddress](#), [cuTexRefSetAddress2D](#), [cuTexRefSetAddressMode](#), [cuTexRefSetArray](#), [cuTexRefSetFilterMode](#), [cuTexRefSetFlags](#), [cuTexRefGetAddress](#), [cuTexRefGetAddressMode](#), [cuTexRefGetArray](#), [cuTexRefGetFilterMode](#), [cuTexRefGetFlags](#), [cuTexRefGetFormat](#)

4.42 Texture Reference Management [DEPRECATED]

Functions

- [CUresult cuTexRefCreate](#) (CUtexref *pTexRef)
Creates a texture reference.
- [CUresult cuTexRefDestroy](#) (CUtexref hTexRef)
Destroys a texture reference.

4.42.1 Detailed Description

This section describes the deprecated texture reference management functions of the low-level CUDA driver application programming interface.

4.42.2 Function Documentation

4.42.2.1 CUresult cuTexRefCreate (CUtexref *pTexRef)

Deprecated

Creates a texture reference and returns its handle in *pTexRef. Once created, the application must call [cuTexRefSetArray\(\)](#) or [cuTexRefSetAddress\(\)](#) to associate the reference with allocated memory. Other texture reference functions are used to specify the format and interpretation (addressing, filtering, etc.) to be used when the memory is read through this texture reference.

Parameters:

pTexRef - Returned texture reference

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefDestroy](#)

4.42.2.2 CUresult cuTexRefDestroy (CUtexref hTexRef)

Deprecated

Destroys the texture reference specified by hTexRef.

Parameters:

hTexRef - Texture reference to destroy

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuTexRefCreate](#)

4.43 Surface Reference Management

Functions

- [CUresult cuSurfRefGetArray](#) ([CUarray](#) *phArray, [CUSurfref](#) hSurfRef)
Passes back the CUDA array bound to a surface reference.
- [CUresult cuSurfRefSetArray](#) ([CUSurfref](#) hSurfRef, [CUarray](#) hArray, unsigned int Flags)
Sets the CUDA array for a surface reference.

4.43.1 Detailed Description

This section describes the surface reference management functions of the low-level CUDA driver application programming interface.

4.43.2 Function Documentation

4.43.2.1 [CUresult cuSurfRefGetArray](#) ([CUarray](#) *phArray, [CUSurfref](#) hSurfRef)

Returns in *phArray the CUDA array bound to the surface reference hSurfRef, or returns [CUDA_ERROR_INVALID_VALUE](#) if the surface reference is not bound to any CUDA array.

Parameters:

phArray - Surface reference handle

hSurfRef - Surface reference handle

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuModuleGetSurfRef](#), [cuSurfRefSetArray](#)

4.43.2.2 [CUresult cuSurfRefSetArray](#) ([CUSurfref](#) hSurfRef, [CUarray](#) hArray, unsigned int Flags)

Sets the CUDA array hArray to be read and written by the surface reference hSurfRef. Any previous CUDA array state associated with the surface reference is superseded by this function. Flags must be set to 0. The [CUDA_ARRAY3D_SURFACE_LDST](#) flag must have been set for the CUDA array. Any CUDA array previously bound to hSurfRef is unbound.

Parameters:

hSurfRef - Surface reference handle

hArray - CUDA array handle

Flags - set to 0

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

See also:

[cuModuleGetSurfRef](#), [cuSurfRefGetArray](#)

4.44 Peer Context Memory Access

Functions

- [CUresult cuCtxDisablePeerAccess](#) ([CUcontext](#) peerContext)
Disables direct access to memory allocations in a peer context and unregisters any registered allocations.
- [CUresult cuCtxEnablePeerAccess](#) ([CUcontext](#) peerContext, unsigned int Flags)
Enables direct access to memory allocations in a peer context.
- [CUresult cuDeviceCanAccessPeer](#) (int *canAccessPeer, [CUdevice](#) dev, [CUdevice](#) peerDev)
Queries if a device may directly access a peer device's memory.

4.44.1 Detailed Description

This section describes the direct peer context memory access functions of the low-level CUDA driver application programming interface.

4.44.2 Function Documentation

4.44.2.1 CUresult cuCtxDisablePeerAccess (CUcontext peerContext)

Returns [CUDA_ERROR_PEER_ACCESS_NOT_ENABLED](#) if direct peer access has not yet been enabled from `peerContext` to the current context.

Returns [CUDA_ERROR_INVALID_CONTEXT](#) if there is no current context, or if `peerContext` is not a valid context.

Parameters:

peerContext - Peer context to disable direct access to

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_PEER_ACCESS_NOT_ENABLED](#), [CUDA_ERROR_INVALID_CONTEXT](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuDeviceCanAccessPeer](#), [cuCtxEnablePeerAccess](#)

4.44.2.2 CUresult cuCtxEnablePeerAccess (CUcontext peerContext, unsigned int Flags)

If both the current context and `peerContext` are on devices which support unified addressing (as may be queried using [CU_DEVICE_ATTRIBUTE_UNIFIED_ADDRESSING](#)), then on success all allocations from `peerContext` will immediately be accessible by the current context. See [Unified Addressing](#) for additional details.

Note that access granted by this call is unidirectional and that in order to access memory from the current context in `peerContext`, a separate symmetric call to `cuCtxEnablePeerAccess()` is required.

Returns `CUDA_ERROR_INVALID_DEVICE` if `cuDeviceCanAccessPeer()` indicates that the `CUdevice` of the current context cannot directly access memory from the `CUdevice` of `peerContext`.

Returns `CUDA_ERROR_PEER_ACCESS_ALREADY_ENABLED` if direct access of `peerContext` from the current context has already been enabled.

Returns `CUDA_ERROR_TOO_MANY_PEERS` if direct peer access is not possible because hardware resources required for peer access have been exhausted.

Returns `CUDA_ERROR_INVALID_CONTEXT` if there is no current context, `peerContext` is not a valid context, or if the current context is `peerContext`.

Returns `CUDA_ERROR_INVALID_VALUE` if `Flags` is not 0.

Parameters:

peerContext - Peer context to enable direct access to from the current context

Flags - Reserved for future use and must be set to 0

Returns:

`CUDA_SUCCESS`, `CUDA_ERROR_DEINITIALIZED`, `CUDA_ERROR_NOT_INITIALIZED`, `CUDA_ERROR_INVALID_DEVICE`, `CUDA_ERROR_PEER_ACCESS_ALREADY_ENABLED`, `CUDA_ERROR_TOO_MANY_PEERS`, `CUDA_ERROR_INVALID_CONTEXT`, `CUDA_ERROR_INVALID_VALUE`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cuDeviceCanAccessPeer`, `cuCtxDisablePeerAccess`

4.44.2.3 CUresult cuDeviceCanAccessPeer (int * canAccessPeer, CUdevice dev, CUdevice peerDev)

Returns in `*canAccessPeer` a value of 1 if contexts on `dev` are capable of directly accessing memory from contexts on `peerDev` and 0 otherwise. If direct access of `peerDev` from `dev` is possible, then access may be enabled on two specific contexts by calling `cuCtxEnablePeerAccess()`.

Parameters:

canAccessPeer - Returned access capability

dev - Device from which allocations on `peerDev` are to be directly accessed.

peerDev - Device on which the allocations to be directly accessed by `dev` reside.

Returns:

`CUDA_SUCCESS`, `CUDA_ERROR_DEINITIALIZED`, `CUDA_ERROR_NOT_INITIALIZED`, `CUDA_ERROR_INVALID_DEVICE`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

`cuCtxEnablePeerAccess`, `cuCtxDisablePeerAccess`

4.45 Graphics Interoperability

Functions

- **CUresult cuGraphicsMapResources** (unsigned int count, CUgraphicsResource *resources, CUstream hStream)
Map graphics resources for access by CUDA.
- **CUresult cuGraphicsResourceGetMappedPointer** (CUdeviceptr *pDevPtr, size_t *pSize, CUgraphicsResource resource)
Get a device pointer through which to access a mapped graphics resource.
- **CUresult cuGraphicsResourceSetMapFlags** (CUgraphicsResource resource, unsigned int flags)
Set usage flags for mapping a graphics resource.
- **CUresult cuGraphicsSubResourceGetMappedArray** (CUarray *pArray, CUgraphicsResource resource, unsigned int arrayIndex, unsigned int mipLevel)
Get an array through which to access a subresource of a mapped graphics resource.
- **CUresult cuGraphicsUnmapResources** (unsigned int count, CUgraphicsResource *resources, CUstream hStream)
Unmap graphics resources.
- **CUresult cuGraphicsUnregisterResource** (CUgraphicsResource resource)
Unregisters a graphics resource for access by CUDA.

4.45.1 Detailed Description

This section describes the graphics interoperability functions of the low-level CUDA driver application programming interface.

4.45.2 Function Documentation

4.45.2.1 CUresult cuGraphicsMapResources (unsigned int count, CUgraphicsResource *resources, CUstream hStream)

Maps the count graphics resources in resources for access by CUDA.

The resources in resources may be accessed by CUDA until they are unmapped. The graphics API from which resources were registered should not access any resources while they are mapped by CUDA. If an application does so, the results are undefined.

This function provides the synchronization guarantee that any graphics calls issued before cuGraphicsMapResources() will complete before any subsequent CUDA work issued in stream begins.

If resources includes any duplicate entries then CUDA_ERROR_INVALID_HANDLE is returned. If any of resources are presently mapped for access by CUDA then CUDA_ERROR_ALREADY_MAPPED is returned.

Parameters:

count - Number of resources to map

resources - Resources to map for CUDA usage

hStream - Stream with which to synchronize

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_HANDLE, CUDA_ERROR_ALREADY_MAPPED, CUDA_ERROR_UNKNOWN

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsResourceGetMappedPointer](#) [cuGraphicsSubResourceGetMappedArray](#) [cuGraphicsUnmapResources](#)

4.45.2.2 CUresult cuGraphicsResourceGetMappedPointer (CUdeviceptr * *pDevPtr*, size_t * *pSize*, CUgraphicsResource *resource*)

Returns in *pDevPtr* a pointer through which the mapped graphics resource *resource* may be accessed. Returns in *pSize* the size of the memory in bytes which may be accessed from that pointer. The value set in *pPointer* may change every time that *resource* is mapped.

If *resource* is not a buffer then it cannot be accessed via a pointer and CUDA_ERROR_NOT_MAPPED_AS_POINTER is returned. If *resource* is not mapped then CUDA_ERROR_NOT_MAPPED is returned. *

Parameters:

pDevPtr - Returned pointer through which *resource* may be accessed

pSize - Returned size of the buffer accessible starting at *pPointer*

resource - Mapped resource to access

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_INVALID_HANDLE, CUDA_ERROR_NOT_MAPPED, CUDA_ERROR_NOT_MAPPED_AS_POINTER

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsMapResources](#), [cuGraphicsSubResourceGetMappedArray](#)

4.45.2.3 CUresult cuGraphicsResourceSetMapFlags (CUgraphicsResource *resource*, unsigned int *flags*)

Set *flags* for mapping the graphics resource *resource*.

Changes to *flags* will take effect the next time *resource* is mapped. The *flags* argument may be any of the following:

- `CU_GRAPHICS_MAP_RESOURCE_FLAGS_NONE`: Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA kernels. This is the default value.
- `CU_GRAPHICS_MAP_RESOURCE_FLAGS_READONLY`: Specifies that CUDA kernels which access this resource will not write to this resource.
- `CU_GRAPHICS_MAP_RESOURCE_FLAGS_WRITEDISCARD`: Specifies that CUDA kernels which access this resource will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

If `resource` is presently mapped for access by CUDA then `CUDA_ERROR_ALREADY_MAPPED` is returned. If `flags` is not one of the above values then `CUDA_ERROR_INVALID_VALUE` is returned.

Parameters:

resource - Registered resource to set flags for

flags - Parameters for resource mapping

Returns:

`CUDA_SUCCESS`, `CUDA_ERROR_DEINITIALIZED`, `CUDA_ERROR_NOT_INITIALIZED`, `CUDA_ERROR_INVALID_CONTEXT`, `CUDA_ERROR_INVALID_VALUE`, `CUDA_ERROR_INVALID_HANDLE`, `CUDA_ERROR_ALREADY_MAPPED`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsMapResources](#)

4.45.2.4 `CUresult cuGraphicsSubResourceGetMappedArray (CUarray * pArray, CUgraphicsResource resource, unsigned int arrayIndex, unsigned int mipLevel)`

Returns in `*pArray` an array through which the subresource of the mapped graphics resource `resource` which corresponds to array index `arrayIndex` and mipmap level `mipLevel` may be accessed. The value set in `*pArray` may change every time that `resource` is mapped.

If `resource` is not a texture then it cannot be accessed via an array and `CUDA_ERROR_NOT_MAPPED_AS_ARRAY` is returned. If `arrayIndex` is not a valid array index for `resource` then `CUDA_ERROR_INVALID_VALUE` is returned. If `mipLevel` is not a valid mipmap level for `resource` then `CUDA_ERROR_INVALID_VALUE` is returned. If `resource` is not mapped then `CUDA_ERROR_NOT_MAPPED` is returned.

Parameters:

pArray - Returned array through which a subresource of `resource` may be accessed

resource - Mapped resource to access

arrayIndex - Array index for array textures or cubemap face index as defined by `CUarray_cubemap_face` for cubemap textures for the subresource to access

mipLevel - Mipmap level for the subresource to access

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_MAPPED](#) [CUDA_ERROR_NOT_MAPPED_AS_ARRAY](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsResourceGetMappedPointer](#)

4.45.2.5 CUresult cuGraphicsUnmapResources (unsigned int *count*, CUgraphicsResource * *resources*, CUSTream *hStream*)

Unmaps the *count* graphics resources in *resources*.

Once unmapped, the resources in *resources* may not be accessed by CUDA until they are mapped again.

This function provides the synchronization guarantee that any CUDA work issued in *stream* before [cuGraphicsUnmapResources\(\)](#) will complete before any subsequently issued graphics work begins.

If *resources* includes any duplicate entries then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If any of *resources* are not presently mapped for access by CUDA then [CUDA_ERROR_NOT_MAPPED](#) is returned.

Parameters:

count - Number of resources to unmap
resources - Resources to unmap
hStream - Stream with which to synchronize

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_MAPPED](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsMapResources](#)

4.45.2.6 CUresult cuGraphicsUnregisterResource (CUgraphicsResource *resource*)

Unregisters the graphics resource *resource* so it is not accessible by CUDA unless registered again.

If *resource* is invalid then [CUDA_ERROR_INVALID_HANDLE](#) is returned.

Parameters:

resource - Resource to unregister

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsD3D9RegisterResource](#), [cuGraphicsD3D10RegisterResource](#), [cuGraphicsD3D11RegisterResource](#), [cuGraphicsGLRegisterBuffer](#), [cuGraphicsGLRegisterImage](#)

4.46 Profiler Control

Functions

- [CUresult cuProfilerInitialize](#) (const char *configFile, const char *outputFile, CUoutput_mode outputMode)
Initialize the profiling.
- [CUresult cuProfilerStart](#) (void)
Start the profiling.
- [CUresult cuProfilerStop](#) (void)
Stop the profiling.

4.46.1 Detailed Description

This section describes the profiler control functions of the low-level CUDA driver application programming interface.

4.46.2 Function Documentation

4.46.2.1 CUresult cuProfilerInitialize (const char * configFile, const char * outputFile, CUoutput_mode outputMode)

Using this API user can specify the configuration file, output file and output file format. This API is generally used to profile different set of counters/options by looping the kernel launch. `configFile` parameter can be used to select profiling options including profiler counters/options. Refer the "Command Line Profiler" section in the "Compute Visual Profiler User Guide" for supported profiler options and counters.

Configurations defined initially by environment variable settings are overwritten by [cuProfilerInitialize\(\)](#).

Limitation: Profiling APIs do not work when the application is running with any profiler tool such as Compute Visual Profiler. User must handle error [CUDA_ERROR_PROFILER_DISABLED](#) returned by profiler APIs if application is likely to be used with any profiler tool.

Typical usage of the profiling APIs is as follows:

for each set of counters/options

```
{
cuProfilerInitialize\(\); //Initialize profiling, set the counters or options in the config file
...
cuProfilerStart\(\);
// code to be profiled
cuProfilerStop\(\);
...
cuProfilerStart\(\);
// code to be profiled
cuProfilerStop\(\);
...
}
```

```
}
```

Parameters:

configFile - Name of the config file that lists the counters/options for profiling.

outputFile - Name of the output file where the profiling results will be stored.

outputMode - outputMode, can be CU_OUT_KEY_VALUE_PAIR or CU_OUT_CSV.

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_PROFILER_DISABLED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuProfilerStart](#), [cuProfilerStop](#)

4.46.2.2 CUresult cuProfilerStart (void)

This API starts the profiling for a context if it is not started already. Profiling must be initialized using [cuProfilerInitialize\(\)](#) before calling this API.

[cuProfilerStart](#) and [cuProfilerStop](#) APIs are used to programmatically control the profiling granularity by allowing profiling to be done only on selective pieces of code.

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_PROFILER_DISABLED](#),
[CUDA_ERROR_PROFILER_ALREADY_STARTED](#), [CUDA_ERROR_PROFILER_NOT_INITIALIZED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuProfilerInitialize](#), [cuProfilerStop](#)

4.46.2.3 CUresult cuProfilerStop (void)

This API stops the profiling if it is not stopped already.

[cuProfilerStart](#) and [cuProfilerStop](#) APIs are used to programmatically control the profiling granularity by allowing profiling to be done only on selective pieces of code.

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_PROFILER_DISABLED](#),
[CUDA_ERROR_PROFILER_ALREADY_STOPPED](#), [CUDA_ERROR_PROFILER_NOT_INITIALIZED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuProfilerInitialize](#), [cuProfilerStart](#)

4.47 OpenGL Interoperability

Modules

- [OpenGL Interoperability \[DEPRECATED\]](#)

Typedefs

- typedef enum [CUGLDeviceList_enum](#) [CUGLDeviceList](#)

Enumerations

- enum [CUGLDeviceList_enum](#) {
[CU_GL_DEVICE_LIST_ALL](#) = 0x01,
[CU_GL_DEVICE_LIST_CURRENT_FRAME](#) = 0x02,
[CU_GL_DEVICE_LIST_NEXT_FRAME](#) = 0x03 }

Functions

- [CUresult cuGLCtxCreate](#) ([CUcontext](#) *pCtx, unsigned int Flags, [CUdevice](#) device)
Create a CUDA context for interoperability with OpenGL.
- [CUresult cuGLGetDevices](#) (unsigned int *pCudaDeviceCount, [CUdevice](#) *pCudaDevices, unsigned int cudaDeviceCount, [CUGLDeviceList](#) deviceList)
Gets the CUDA devices associated with the current OpenGL context.
- [CUresult cuGraphicsGLRegisterBuffer](#) ([CUgraphicsResource](#) *pCudaResource, GLuint buffer, unsigned int Flags)
Registers an OpenGL buffer object.
- [CUresult cuGraphicsGLRegisterImage](#) ([CUgraphicsResource](#) *pCudaResource, GLuint image, GLenum target, unsigned int Flags)
Register an OpenGL texture or renderbuffer object.
- [CUresult cuWGLGetDevice](#) ([CUdevice](#) *pDevice, HGPUNV hGpu)
Gets the CUDA device associated with hGpu.

4.47.1 Detailed Description

This section describes the OpenGL interoperability functions of the low-level CUDA driver application programming interface. Note that mapping of OpenGL resources is performed with the graphics API agnostic, resource mapping interface described in [Graphics Interopability](#).

4.47.2 Typedef Documentation

4.47.2.1 typedef enum CUGLDeviceList_enum CUGLDeviceList

CUDA devices corresponding to an OpenGL device

4.47.3 Enumeration Type Documentation

4.47.3.1 enum CUGLDeviceList_enum

CUDA devices corresponding to an OpenGL device

Enumerator:

CU_GL_DEVICE_LIST_ALL The CUDA devices for all GPUs used by the current OpenGL context

CU_GL_DEVICE_LIST_CURRENT_FRAME The CUDA devices for the GPUs used by the current OpenGL context in its currently rendering frame

CU_GL_DEVICE_LIST_NEXT_FRAME The CUDA devices for the GPUs to be used by the current OpenGL context in the next frame

4.47.4 Function Documentation

4.47.4.1 CUresult cuGLCtxCreate (CUcontext *pCtx, unsigned int Flags, CUdevice device)

Creates a new CUDA context, initializes OpenGL interoperability, and associates the CUDA context with the calling thread. It must be called before performing any other OpenGL interoperability operations. It may fail if the needed OpenGL driver facilities are not available. For usage of the `Flags` parameter, see [cuCtxCreate\(\)](#).

Parameters:

pCtx - Returned CUDA context

Flags - Options for CUDA context creation

device - Device on which to create the context

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxCreate](#), [cuGLInit](#), [cuGLMapBufferObject](#), [cuGLRegisterBufferObject](#), [cuGLUnmapBufferObject](#), [cuGLUnregisterBufferObject](#), [cuGLMapBufferObjectAsync](#), [cuGLUnmapBufferObjectAsync](#), [cuGLSetBufferObjectMapFlags](#), [cuWGLGetDevice](#)

4.47.4.2 CUresult cuGLGetDevices (unsigned int *pCudaDeviceCount, CUdevice *pCudaDevices, unsigned int cudaDeviceCount, CUGLDeviceList deviceList)

Returns in **pCudaDeviceCount* the number of CUDA-compatible devices corresponding to the current OpenGL context. Also returns in **pCudaDevices* at most *cudaDeviceCount* of the CUDA-compatible devices corresponding to the current OpenGL context. If any of the GPUs being used by the current OpenGL context are not CUDA capable then the call will return `CUDA_ERROR_NO_DEVICE`.

The *deviceList* argument may be any of the following:

- [CU_GL_DEVICE_LIST_ALL](#): Query all devices used by the current OpenGL context.

- [CU_GL_DEVICE_LIST_CURRENT_FRAME](#): Query the devices used by the current OpenGL context to render the current frame (in SLI).
- [CU_GL_DEVICE_LIST_NEXT_FRAME](#): Query the devices used by the current OpenGL context to render the next frame (in SLI). Note that this is a prediction, it can't be guaranteed that this is correct in all cases.

Parameters:

pCudaDeviceCount - Returned number of CUDA devices.
pCudaDevices - Returned CUDA devices.
cudaDeviceCount - The size of the output device array pCudaDevices.
deviceList - The set of devices to return.

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_NO_DEVICE](#), [CUDA_ERROR_INVALID_VALUE](#) [CUDA_ERROR_INVALID_CONTEXT](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGLCtxCreate](#), [cuGLInit](#), [cuWGLGetDevice](#)

4.47.4.3 CUresult cuGraphicsGLRegisterBuffer (CUgraphicsResource * pCudaResource, GLuint buffer, unsigned int Flags)

Registers the buffer object specified by `buffer` for access by CUDA. A handle to the registered object is returned as `pCudaResource`. The register flags `Flags` specify the intended usage, as follows:

- [CU_GRAPHICS_REGISTER_FLAGS_NONE](#): Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA. This is the default value.
- [CU_GRAPHICS_REGISTER_FLAGS_READ_ONLY](#): Specifies that CUDA will not write to this resource.
- [CU_GRAPHICS_REGISTER_FLAGS_WRITE_DISCARD](#): Specifies that CUDA will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

Parameters:

pCudaResource - Pointer to the returned object handle
buffer - name of buffer object to be registered
Flags - Register flags

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_ALREADY_MAPPED](#), [CUDA_ERROR_INVALID_CONTEXT](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGLCtxCreate](#), [cuGraphicsUnregisterResource](#), [cuGraphicsMapResources](#), [cuGraphicsResourceGetMapped-Pointer](#)

4.47.4.4 CUresult cuGraphicsGLRegisterImage (CUgraphicsResource * pCudaResource, GLuint image, GLenum target, unsigned int Flags)

Registers the texture or renderbuffer object specified by `image` for access by CUDA. A handle to the registered object is returned as `pCudaResource`.

`target` must match the type of the object, and must be one of `GL_TEXTURE_2D`, `GL_TEXTURE_RECTANGLE`, `GL_TEXTURE_CUBE_MAP`, `GL_TEXTURE_3D`, `GL_TEXTURE_2D_ARRAY`, or `GL_RENDERBUFFER`.

The register flags `Flags` specify the intended usage, as follows:

- `CU_GRAPHICS_REGISTER_FLAGS_NONE`: Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA. This is the default value.
- `CU_GRAPHICS_REGISTER_FLAGS_READ_ONLY`: Specifies that CUDA will not write to this resource.
- `CU_GRAPHICS_REGISTER_FLAGS_WRITE_DISCARD`: Specifies that CUDA will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.
- `CU_GRAPHICS_REGISTER_FLAGS_SURFACE_LDST`: Specifies that CUDA will bind this resource to a surface reference.
- `CU_GRAPHICS_REGISTER_FLAGS_TEXTURE_GATHER`: Specifies that CUDA will perform texture gather operations on this resource.

The following image formats are supported. For brevity's sake, the list is abbreviated. For ex., `{GL_R, GL_RG} X {8, 16}` would expand to the following 4 formats `{GL_R8, GL_R16, GL_RG8, GL_RG16}` :

- `GL_RED`, `GL_RG`, `GL_RGBA`, `GL_LUMINANCE`, `GL_ALPHA`, `GL_LUMINANCE_ALPHA`, `GL_INTENSITY`
- `{GL_R, GL_RG, GL_RGBA} X {8, 16, 16F, 32F, 8UI, 16UI, 32UI, 8I, 16I, 32I}`
- `{GL_LUMINANCE, GL_ALPHA, GL_LUMINANCE_ALPHA, GL_INTENSITY} X {8, 16, 16F_ARB, 32F_ARB, 8UI_EXT, 16UI_EXT, 32UI_EXT, 8I_EXT, 16I_EXT, 32I_EXT}`

The following image classes are currently disallowed:

- Textures with borders
- Multisampled renderbuffers

Parameters:

pCudaResource - Pointer to the returned object handle
image - name of texture or renderbuffer object to be registered
target - Identifies the type of object specified by `image`
Flags - Register flags

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_ALREADY_MAPPED](#), [CUDA_ERROR_INVALID_CONTEXT](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGLCtxCreate](#), [cuGraphicsUnregisterResource](#), [cuGraphicsMapResources](#), [cuGraphicsSubResourceGetMappedArray](#)

4.47.4.5 CUresult cuWGLGetDevice (CUdevice **pDevice*, HGPUNV *hGpu*)

Returns in **pDevice* the CUDA device associated with a *hGpu*, if applicable.

Parameters:

pDevice - Device associated with *hGpu*

hGpu - Handle to a GPU, as queried via `WGL_NV_gpu_affinity()`

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGLCtxCreate](#), [cuGLInit](#), [cuGLMapBufferObject](#), [cuGLRegisterBufferObject](#), [cuGLUnmapBufferObject](#), [cuGLUnregisterBufferObject](#), [cuGLUnmapBufferObjectAsync](#), [cuGLSetBufferObjectMapFlags](#)

4.48 OpenGL Interoperability [DEPRECATED]

Typedefs

- typedef enum [CUGLmap_flags_enum](#) [CUGLmap_flags](#)

Enumerations

- enum [CUGLmap_flags_enum](#)

Functions

- [CUresult cuGLInit](#) (void)
Initializes OpenGL interoperability.
- [CUresult cuGLMapBufferObject](#) ([CUdeviceptr](#) *dptr, size_t *size, GLuint buffer)
Maps an OpenGL buffer object.
- [CUresult cuGLMapBufferObjectAsync](#) ([CUdeviceptr](#) *dptr, size_t *size, GLuint buffer, [CUstream](#) hStream)
Maps an OpenGL buffer object.
- [CUresult cuGLRegisterBufferObject](#) (GLuint buffer)
Registers an OpenGL buffer object.
- [CUresult cuGLSetBufferObjectMapFlags](#) (GLuint buffer, unsigned int Flags)
Set the map flags for an OpenGL buffer object.
- [CUresult cuGLUnmapBufferObject](#) (GLuint buffer)
Unmaps an OpenGL buffer object.
- [CUresult cuGLUnmapBufferObjectAsync](#) (GLuint buffer, [CUstream](#) hStream)
Unmaps an OpenGL buffer object.
- [CUresult cuGLUnregisterBufferObject](#) (GLuint buffer)
Unregister an OpenGL buffer object.

4.48.1 Detailed Description

This section describes deprecated OpenGL interoperability functionality.

4.48.2 Typedef Documentation

4.48.2.1 typedef enum [CUGLmap_flags_enum](#) [CUGLmap_flags](#)

Flags to map or unmap a resource

4.48.3 Enumeration Type Documentation

4.48.3.1 enum CUGLmap_flags_enum

Flags to map or unmap a resource

4.48.4 Function Documentation

4.48.4.1 CUresult cuGLInit (void)

Deprecated

This function is deprecated as of Cuda 3.0.

Initializes OpenGL interoperability. This function is deprecated and calling it is no longer required. It may fail if the needed OpenGL driver facilities are not available.

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGLCtxCreate](#), [cuGLMapBufferObject](#), [cuGLRegisterBufferObject](#), [cuGLUnmapBufferObject](#), [cuGLUnregisterBufferObject](#), [cuGLMapBufferObjectAsync](#), [cuGLUnmapBufferObjectAsync](#), [cuGLSetBufferObjectMapFlags](#), [cuWGLGetDevice](#)

4.48.4.2 CUresult cuGLMapBufferObject (CUdeviceptr * *dptr*, size_t * *size*, GLuint *buffer*)

Deprecated

This function is deprecated as of Cuda 3.0.

Maps the buffer object specified by *buffer* into the address space of the current CUDA context and returns in **dptr* and **size* the base pointer and size of the resulting mapping.

There must be a valid OpenGL context bound to the current thread when this function is called. This must be the same context, or a member of the same shareGroup, as the context that was bound when the buffer was registered.

All streams in the current CUDA context are synchronized with the current GL context.

Parameters:

dptr - Returned mapped base pointer
size - Returned size of mapping
buffer - The name of the buffer object to map

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_MAP_FAILED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsMapResources](#)

4.48.4.3 CUresult cuGLMapBufferObjectAsync (CUdeviceptr * *dptr*, size_t * *size*, GLuint *buffer*, CUstream *hStream*)**Deprecated**

This function is deprecated as of Cuda 3.0.

Maps the buffer object specified by *buffer* into the address space of the current CUDA context and returns in **dptr* and **size* the base pointer and size of the resulting mapping.

There must be a valid OpenGL context bound to the current thread when this function is called. This must be the same context, or a member of the same shareGroup, as the context that was bound when the buffer was registered.

Stream *hStream* in the current CUDA context is synchronized with the current GL context.

Parameters:

dptr - Returned mapped base pointer

size - Returned size of mapping

buffer - The name of the buffer object to map

hStream - Stream to synchronize

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_MAP_FAILED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsMapResources](#)

4.48.4.4 CUresult cuGLRegisterBufferObject (GLuint *buffer*)**Deprecated**

This function is deprecated as of Cuda 3.0.

Registers the buffer object specified by *buffer* for access by CUDA. This function must be called before CUDA can map the buffer object. There must be a valid OpenGL context bound to the current thread when this function is called, and the buffer name is resolved by that context.

Parameters:

buffer - The name of the buffer object to register.

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_ALREADY_MAPPED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsGLRegisterBuffer](#)

4.48.4.5 CUresult cuGLSetBufferObjectMapFlags (GLuint *buffer*, unsigned int *Flags*)**Deprecated**

This function is deprecated as of Cuda 3.0.

Sets the map flags for the buffer object specified by *buffer*.

Changes to *Flags* will take effect the next time *buffer* is mapped. The *Flags* argument may be any of the following:

- [CU_GL_MAP_RESOURCE_FLAGS_NONE](#): Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA kernels. This is the default value.
- [CU_GL_MAP_RESOURCE_FLAGS_READ_ONLY](#): Specifies that CUDA kernels which access this resource will not write to this resource.
- [CU_GL_MAP_RESOURCE_FLAGS_WRITE_DISCARD](#): Specifies that CUDA kernels which access this resource will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

If *buffer* has not been registered for use with CUDA, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *buffer* is presently mapped for access by CUDA, then [CUDA_ERROR_ALREADY_MAPPED](#) is returned.

There must be a valid OpenGL context bound to the current thread when this function is called. This must be the same context, or a member of the same shareGroup, as the context that was bound when the buffer was registered.

Parameters:

buffer - Buffer object to unmap

Flags - Map flags

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_ALREADY_MAPPED](#), [CUDA_ERROR_INVALID_CONTEXT](#),

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsResourceSetMapFlags](#)

4.48.4.6 CUresult cuGLUnmapBufferObject (GLuint *buffer*)

Deprecated

This function is deprecated as of Cuda 3.0.

Unmaps the buffer object specified by *buffer* for access by CUDA.

There must be a valid OpenGL context bound to the current thread when this function is called. This must be the same context, or a member of the same shareGroup, as the context that was bound when the buffer was registered.

All streams in the current CUDA context are synchronized with the current GL context.

Parameters:

buffer - Buffer object to unmap

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsUnmapResources](#)

4.48.4.7 CUresult cuGLUnmapBufferObjectAsync (GLuint *buffer*, CUstream *hStream*)

Deprecated

This function is deprecated as of Cuda 3.0.

Unmaps the buffer object specified by *buffer* for access by CUDA.

There must be a valid OpenGL context bound to the current thread when this function is called. This must be the same context, or a member of the same shareGroup, as the context that was bound when the buffer was registered.

Stream *hStream* in the current CUDA context is synchronized with the current GL context.

Parameters:

buffer - Name of the buffer object to unmap

hStream - Stream to synchronize

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsUnmapResources](#)

4.48.4.8 CUresult cuGLUnregisterBufferObject (GLuint *buffer*)

Deprecated

This function is deprecated as of Cuda 3.0.

Unregisters the buffer object specified by `buffer`. This releases any resources associated with the registered buffer. After this call, the buffer may no longer be mapped for access by CUDA.

There must be a valid OpenGL context bound to the current thread when this function is called. This must be the same context, or a member of the same `shareGroup`, as the context that was bound when the buffer was registered.

Parameters:

buffer - Name of the buffer object to unregister

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsUnregisterResource](#)

4.49 Direct3D 9 Interoperability

Modules

- [Direct3D 9 Interoperability \[DEPRECATED\]](#)

Typedefs

- typedef enum [CUd3d9DeviceList_enum](#) [CUd3d9DeviceList](#)

Enumerations

- enum [CUd3d9DeviceList_enum](#) {
[CU_D3D9_DEVICE_LIST_ALL](#) = 0x01,
[CU_D3D9_DEVICE_LIST_CURRENT_FRAME](#) = 0x02,
[CU_D3D9_DEVICE_LIST_NEXT_FRAME](#) = 0x03 }

Functions

- [CUresult cuD3D9CtxCreate](#) ([CUcontext](#) *pCtx, [CUdevice](#) *pCudaDevice, unsigned int Flags, [IDirect3DDevice9](#) *pD3DDevice)
Create a CUDA context for interoperability with Direct3D 9.
- [CUresult cuD3D9CtxCreateOnDevice](#) ([CUcontext](#) *pCtx, unsigned int flags, [IDirect3DDevice9](#) *pD3DDevice, [CUdevice](#) cudaDevice)
Create a CUDA context for interoperability with Direct3D 9.
- [CUresult cuD3D9GetDevice](#) ([CUdevice](#) *pCudaDevice, const char *pszAdapterName)
Gets the CUDA device corresponding to a display adapter.
- [CUresult cuD3D9GetDevices](#) (unsigned int *pCudaDeviceCount, [CUdevice](#) *pCudaDevices, unsigned int cudaDeviceCount, [IDirect3DDevice9](#) *pD3D9Device, [CUd3d9DeviceList](#) deviceList)
Gets the CUDA devices corresponding to a Direct3D 9 device.
- [CUresult cuD3D9GetDirect3DDevice](#) ([IDirect3DDevice9](#) **ppD3DDevice)
Get the Direct3D 9 device against which the current CUDA context was created.
- [CUresult cuGraphicsD3D9RegisterResource](#) ([CUgraphicsResource](#) *pCudaResource, [IDirect3DResource9](#) *pD3DResource, unsigned int Flags)
Register a Direct3D 9 resource for access by CUDA.

4.49.1 Detailed Description

This section describes the Direct3D 9 interoperability functions of the low-level CUDA driver application programming interface. Note that mapping of Direct3D 9 resources is performed with the graphics API agnostic, resource mapping interface described in [Graphics Interopability](#).

4.49.2 Typedef Documentation

4.49.2.1 typedef enum CUd3d9DeviceList_enum CUd3d9DeviceList

CUDA devices corresponding to a D3D9 device

4.49.3 Enumeration Type Documentation

4.49.3.1 enum CUd3d9DeviceList_enum

CUDA devices corresponding to a D3D9 device

Enumerator:

CU_D3D9_DEVICE_LIST_ALL The CUDA devices for all GPUs used by a D3D9 device

CU_D3D9_DEVICE_LIST_CURRENT_FRAME The CUDA devices for the GPUs used by a D3D9 device in its currently rendering frame

CU_D3D9_DEVICE_LIST_NEXT_FRAME The CUDA devices for the GPUs to be used by a D3D9 device in the next frame

4.49.4 Function Documentation

4.49.4.1 CUresult cuD3D9CtxCreate (CUcontext * *pCtx*, CUdevice * *pCudaDevice*, unsigned int *Flags*, IDirect3DDevice9 * *pD3DDevice*)

Creates a new CUDA context, enables interoperability for that context with the Direct3D device *pD3DDevice*, and associates the created CUDA context with the calling thread. The created [CUcontext](#) will be returned in **pCtx*. Direct3D resources from this device may be registered and mapped through the lifetime of this CUDA context. If *pCudaDevice* is non-NULL then the [CUdevice](#) on which this CUDA context was created will be returned in **pCudaDevice*.

On success, this call will increase the internal reference count on *pD3DDevice*. This reference count will be decremented upon destruction of this context through [cuCtxDestroy\(\)](#). This context will cease to function if *pD3DDevice* is destroyed or encounters an error.

Parameters:

pCtx - Returned newly created CUDA context

pCudaDevice - Returned pointer to the device on which the context was created

Flags - Context creation flags (see [cuCtxCreate\(\)](#) for details)

pD3DDevice - Direct3D device to create interoperability context with

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D9GetDevice](#), [cuGraphicsD3D9RegisterResource](#)

4.49.4.2 CUresult cuD3D9CtxCreateOnDevice (CUcontext *pCtx, unsigned int flags, IDirect3DDevice9 *pD3DDevice, CUdevice cudaDevice)

Creates a new CUDA context, enables interoperability for that context with the Direct3D device pD3DDevice, and associates the created CUDA context with the calling thread. The created [CUcontext](#) will be returned in *pCtx. Direct3D resources from this device may be registered and mapped through the lifetime of this CUDA context.

On success, this call will increase the internal reference count on pD3DDevice. This reference count will be decremented upon destruction of this context through [cuCtxDestroy\(\)](#). This context will cease to function if pD3DDevice is destroyed or encounters an error.

Parameters:

pCtx - Returned newly created CUDA context

flags - Context creation flags (see [cuCtxCreate\(\)](#) for details)

pD3DDevice - Direct3D device to create interoperability context with

cudaDevice - The CUDA device on which to create the context. This device must be among the devices returned when querying CU_D3D9_DEVICES_ALL from [cuD3D9GetDevices](#).

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D9GetDevices](#), [cuGraphicsD3D9RegisterResource](#)

4.49.4.3 CUresult cuD3D9GetDevice (CUdevice *pCudaDevice, const char *pszAdapterName)

Returns in *pCudaDevice the CUDA-compatible device corresponding to the adapter name pszAdapterName obtained from EnumDisplayDevices() or IDirect3D9::GetAdapterIdentifier().

If no device on the adapter with name pszAdapterName is CUDA-compatible, then the call will fail.

Parameters:

pCudaDevice - Returned CUDA device corresponding to pszAdapterName

pszAdapterName - Adapter name to query for device

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_NOT_FOUND](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D9CtxCreate](#)

4.49.4.4 CUresult cuD3D9GetDevices (unsigned int * *pCudaDeviceCount*, CUdevice * *pCudaDevices*, unsigned int *cudaDeviceCount*, IDirect3DDevice9 * *pD3D9Device*, CUD3D9DeviceList *deviceList*)

Returns in **pCudaDeviceCount* the number of CUDA-compatible device corresponding to the Direct3D 9 device *pD3D9Device*. Also returns in **pCudaDevices* at most *cudaDeviceCount* of the the CUDA-compatible devices corresponding to the Direct3D 9 device *pD3D9Device*.

If any of the GPUs being used to render *pDevice* are not CUDA capable then the call will return [CUDA_ERROR_NO_DEVICE](#).

Parameters:

pCudaDeviceCount - Returned number of CUDA devices corresponding to *pD3D9Device*

pCudaDevices - Returned CUDA devices corresponding to *pD3D9Device*

cudaDeviceCount - The size of the output device array *pCudaDevices*

pD3D9Device - Direct3D 9 device to query for CUDA devices

deviceList - The set of devices to return. This set may be [CU_D3D9_DEVICE_LIST_ALL](#) for all devices, [CU_D3D9_DEVICE_LIST_CURRENT_FRAME](#) for the devices used to render the current frame (in SLI), or [CU_D3D9_DEVICE_LIST_NEXT_FRAME](#) for the devices used to render the next frame (in SLI).

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_NO_DEVICE](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_NOT_FOUND](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D9CtxCreate](#)

4.49.4.5 CUresult cuD3D9GetDirect3DDevice (IDirect3DDevice9 ** *ppD3DDevice*)

Returns in **ppD3DDevice* the Direct3D device against which this CUDA context was created in [cuD3D9CtxCreate\(\)](#).

Parameters:

ppD3DDevice - Returned Direct3D device corresponding to CUDA context

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D9GetDevice](#)

4.49.4.6 CUresult cuGraphicsD3D9RegisterResource (CUgraphicsResource * pCudaResource, IDirect3DResource9 * pD3DResource, unsigned int Flags)

Registers the Direct3D 9 resource `pD3DResource` for access by CUDA and returns a CUDA handle to `pD3DResource` in `pCudaResource`. The handle returned in `pCudaResource` may be used to map and unmap this resource until it is unregistered. On success this call will increase the internal reference count on `pD3DResource`. This reference count will be decremented when this resource is unregistered through `cuGraphicsUnregisterResource()`.

This call is potentially high-overhead and should not be called every frame in interactive applications.

The type of `pD3DResource` must be one of the following.

- `IDirect3DVertexBuffer9`: may be accessed through a device pointer
- `IDirect3DIndexBuffer9`: may be accessed through a device pointer
- `IDirect3DSurface9`: may be accessed through an array. Only stand-alone objects of type `IDirect3DSurface9` may be explicitly shared. In particular, individual mipmap levels and faces of cube maps may not be registered directly. To access individual surfaces associated with a texture, one must register the base texture object.
- `IDirect3DBaseTexture9`: individual surfaces on this texture may be accessed through an array.

The `Flags` argument may be used to specify additional parameters at register time. The valid values for this parameter are

- `CU_GRAPHICS_REGISTER_FLAGS_NONE`: Specifies no hints about how this resource will be used.
- `CU_GRAPHICS_REGISTER_FLAGS_SURFACE_LDST`: Specifies that CUDA will bind this resource to a surface reference.
- `CU_GRAPHICS_REGISTER_FLAGS_TEXTURE_GATHER`: Specifies that CUDA will perform texture gather operations on this resource.

Not all Direct3D resources of the above types may be used for interoperability with CUDA. The following are some limitations.

- The primary rendertarget may not be registered with CUDA.
- Resources allocated as shared may not be registered with CUDA.
- Textures which are not of a format which is 1, 2, or 4 channels of 8, 16, or 32-bit integer or floating-point data cannot be shared.
- Surfaces of depth or stencil formats cannot be shared.

If Direct3D interoperability is not initialized for this context using `cuD3D9CtxCreate` then `CUDA_ERROR_INVALID_CONTEXT` is returned. If `pD3DResource` is of incorrect type or is already registered then `CUDA_ERROR_INVALID_HANDLE` is returned. If `pD3DResource` cannot be registered then `CUDA_ERROR_UNKNOWN` is returned. If `Flags` is not one of the above specified value then `CUDA_ERROR_INVALID_VALUE` is returned.

Parameters:

- pCudaResource* - Returned graphics resource handle
- pD3DResource* - Direct3D resource to register
- Flags* - Parameters for resource registration

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D9CtxCreate](#), [cuGraphicsUnregisterResource](#), [cuGraphicsMapResources](#), [cuGraphicsSubResourceGetMappedArray](#), [cuGraphicsResourceGetMappedPointer](#)

4.50 Direct3D 9 Interoperability [DEPRECATED]

Typedefs

- typedef enum [CUd3d9map_flags_enum](#) [CUd3d9map_flags](#)
- typedef enum [CUd3d9register_flags_enum](#) [CUd3d9register_flags](#)

Enumerations

- enum [CUd3d9map_flags_enum](#)
- enum [CUd3d9register_flags_enum](#)

Functions

- [CUresult cuD3D9MapResources](#) (unsigned int count, IDirect3DResource9 **ppResource)
Map Direct3D resources for access by CUDA.
- [CUresult cuD3D9RegisterResource](#) (IDirect3DResource9 *pResource, unsigned int Flags)
Register a Direct3D resource for access by CUDA.
- [CUresult cuD3D9ResourceGetMappedArray](#) (CUarray *pArray, IDirect3DResource9 *pResource, unsigned int Face, unsigned int Level)
Get an array through which to access a subresource of a Direct3D resource which has been mapped for access by CUDA.
- [CUresult cuD3D9ResourceGetMappedPitch](#) (size_t *pPitch, size_t *pPitchSlice, IDirect3DResource9 *pResource, unsigned int Face, unsigned int Level)
Get the pitch of a subresource of a Direct3D resource which has been mapped for access by CUDA.
- [CUresult cuD3D9ResourceGetMappedPointer](#) (CUdeviceptr *pDevPtr, IDirect3DResource9 *pResource, unsigned int Face, unsigned int Level)
Get the pointer through which to access a subresource of a Direct3D resource which has been mapped for access by CUDA.
- [CUresult cuD3D9ResourceGetMappedSize](#) (size_t *pSize, IDirect3DResource9 *pResource, unsigned int Face, unsigned int Level)
Get the size of a subresource of a Direct3D resource which has been mapped for access by CUDA.
- [CUresult cuD3D9ResourceGetSurfaceDimensions](#) (size_t *pWidth, size_t *pHeight, size_t *pDepth, IDirect3DResource9 *pResource, unsigned int Face, unsigned int Level)
Get the dimensions of a registered surface.
- [CUresult cuD3D9ResourceSetMapFlags](#) (IDirect3DResource9 *pResource, unsigned int Flags)
Set usage flags for mapping a Direct3D resource.
- [CUresult cuD3D9UnmapResources](#) (unsigned int count, IDirect3DResource9 **ppResource)
Unmaps Direct3D resources.
- [CUresult cuD3D9UnregisterResource](#) (IDirect3DResource9 *pResource)
Unregister a Direct3D resource.

4.50.1 Detailed Description

This section describes deprecated Direct3D 9 interoperability functionality.

4.50.2 Typedef Documentation

4.50.2.1 typedef enum CUd3d9map_flags_enum CUd3d9map_flags

Flags to map or unmap a resource

4.50.2.2 typedef enum CUd3d9register_flags_enum CUd3d9register_flags

Flags to register a resource

4.50.3 Enumeration Type Documentation

4.50.3.1 enum CUd3d9map_flags_enum

Flags to map or unmap a resource

4.50.3.2 enum CUd3d9register_flags_enum

Flags to register a resource

4.50.4 Function Documentation

4.50.4.1 CUresult cuD3D9MapResources (unsigned int *count*, IDirect3DResource9 ** *ppResource*)

Deprecated

This function is deprecated as of Cuda 3.0.

Maps the *count* Direct3D resources in *ppResource* for access by CUDA.

The resources in *ppResource* may be accessed in CUDA kernels until they are unmapped. Direct3D should not access any resources while they are mapped by CUDA. If an application does so the results are undefined.

This function provides the synchronization guarantee that any Direct3D calls issued before [cuD3D9MapResources\(\)](#) will complete before any CUDA kernels issued after [cuD3D9MapResources\(\)](#) begin.

If any of *ppResource* have not been registered for use with CUDA or if *ppResource* contains any duplicate entries, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If any of *ppResource* are presently mapped for access by CUDA, then [CUDA_ERROR_ALREADY_MAPPED](#) is returned.

Parameters:

count - Number of resources in *ppResource*

ppResource - Resources to map for CUDA usage

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_HANDLE, CUDA_ERROR_ALREADY_MAPPED, CUDA_ERROR_UNKNOWN

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsMapResources](#)

4.50.4.2 CUresult cuD3D9RegisterResource (IDirect3DResource9 *pResource, unsigned int Flags)

Deprecated

This function is deprecated as of Cuda 3.0.

Registers the Direct3D resource pResource for access by CUDA.

If this call is successful, then the application will be able to map and unmap this resource until it is unregistered through [cuD3D9UnregisterResource\(\)](#). Also on success, this call will increase the internal reference count on pResource. This reference count will be decremented when this resource is unregistered through [cuD3D9UnregisterResource\(\)](#).

This call is potentially high-overhead and should not be called every frame in interactive applications.

The type of pResource must be one of the following.

- IDirect3DVertexBuffer9: Cannot be used with Flags set to CU_D3D9_REGISTER_FLAGS_ARRAY.
- IDirect3DIndexBuffer9: Cannot be used with Flags set to CU_D3D9_REGISTER_FLAGS_ARRAY.
- IDirect3DSurface9: Only stand-alone objects of type IDirect3DSurface9 may be explicitly shared. In particular, individual mipmap levels and faces of cube maps may not be registered directly. To access individual surfaces associated with a texture, one must register the base texture object. For restrictions on the Flags parameter, see type IDirect3DBaseTexture9.
- IDirect3DBaseTexture9: When a texture is registered, all surfaces associated with the all mipmap levels of all faces of the texture will be accessible to CUDA.

The Flags argument specifies the mechanism through which CUDA will access the Direct3D resource. The following values are allowed.

- CU_D3D9_REGISTER_FLAGS_NONE: Specifies that CUDA will access this resource through a [Cudeviceptr](#). The pointer, size, and (for textures), pitch for each subresource of this allocation may be queried through [cuD3D9ResourceGetMappedPointer\(\)](#), [cuD3D9ResourceGetMappedSize\(\)](#), and [cuD3D9ResourceGetMappedPitch\(\)](#) respectively. This option is valid for all resource types.
- CU_D3D9_REGISTER_FLAGS_ARRAY: Specifies that CUDA will access this resource through a [CUarray](#) queried on a sub-resource basis through [cuD3D9ResourceGetMappedArray\(\)](#). This option is only valid for resources of type IDirect3DSurface9 and subtypes of IDirect3DBaseTexture9.

Not all Direct3D resources of the above types may be used for interoperability with CUDA. The following are some limitations.

- The primary rendertarget may not be registered with CUDA.
- Resources allocated as shared may not be registered with CUDA.
- Any resources allocated in D3DPOOL_SYSTEMMEM or D3DPOOL_MANAGED may not be registered with CUDA.
- Textures which are not of a format which is 1, 2, or 4 channels of 8, 16, or 32-bit integer or floating-point data cannot be shared.
- Surfaces of depth or stencil formats cannot be shared.

If Direct3D interoperability is not initialized on this context, then [CUDA_ERROR_INVALID_CONTEXT](#) is returned. If `pResource` is of incorrect type (e.g. is a non-stand-alone IDirect3DSurface9) or is already registered, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If `pResource` cannot be registered then [CUDA_ERROR_UNKNOWN](#) is returned.

Parameters:

pResource - Resource to register for CUDA access

Flags - Flags for resource registration

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsD3D9RegisterResource](#)

4.50.4.3 CUresult cuD3D9ResourceGetMappedArray (CUarray *pArray, IDirect3DResource9 *pResource, unsigned int Face, unsigned int Level)

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in `*pArray` an array through which the subresource of the mapped Direct3D resource `pResource` which corresponds to `Face` and `Level` may be accessed. The value set in `pArray` may change every time that `pResource` is mapped.

If `pResource` is not registered then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If `pResource` was not registered with usage flags `CU_D3D9_REGISTER_FLAGS_ARRAY` then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If `pResource` is not mapped then [CUDA_ERROR_NOT_MAPPED](#) is returned.

For usage requirements of `Face` and `Level` parameters, see [cuD3D9ResourceGetMappedPointer\(\)](#).

Parameters:

pArray - Returned array corresponding to subresource

pResource - Mapped resource to access

Face - Face of resource to access

Level - Level of resource to access

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_INVALID_HANDLE, CUDA_ERROR_NOT_MAPPED

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsSubResourceGetMappedArray](#)

4.50.4.4 CUresult cuD3D9ResourceGetMappedPitch (size_t * pPitch, size_t * pPitchSlice, IDirect3DResource9 * pResource, unsigned int Face, unsigned int Level)

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in *pPitch and *pPitchSlice the pitch and Z-slice pitch of the subresource of the mapped Direct3D resource pResource, which corresponds to Face and Level. The values set in pPitch and pPitchSlice may change every time that pResource is mapped.

The pitch and Z-slice pitch values may be used to compute the location of a sample on a surface as follows.

For a 2D surface, the byte offset of the sample at position **x**, **y** from the base pointer of the surface is:

y * pitch + (bytes per pixel) * x

For a 3D surface, the byte offset of the sample at position **x**, **y**, **z** from the base pointer of the surface is:

z* slicePitch + y * pitch + (bytes per pixel) * x

Both parameters pPitch and pPitchSlice are optional and may be set to NULL.

If pResource is not of type IDirect3DBaseTexture9 or one of its sub-types or if pResource has not been registered for use with CUDA, then [cudaErrorInvalidResourceHandle](#) is returned. If pResource was not registered with usage flags CU_D3D9_REGISTER_FLAGS_NONE, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If pResource is not mapped for access by CUDA then [CUDA_ERROR_NOT_MAPPED](#) is returned.

For usage requirements of Face and Level parameters, see [cuD3D9ResourceGetMappedPointer\(\)](#).

Parameters:

pPitch - Returned pitch of subresource

pPitchSlice - Returned Z-slice pitch of subresource

pResource - Mapped resource to access

Face - Face of resource to access

Level - Level of resource to access

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_INVALID_HANDLE, CUDA_ERROR_NOT_MAPPED

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsSubResourceGetMappedArray](#)

4.50.4.5 CUresult cuD3D9ResourceGetMappedPointer (CUdeviceptr * *pDevPtr*, IDirect3DResource9 * *pResource*, unsigned int *Face*, unsigned int *Level*)

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in **pDevPtr* the base pointer of the subresource of the mapped Direct3D resource *pResource*, which corresponds to *Face* and *Level*. The value set in *pDevPtr* may change every time that *pResource* is mapped.

If *pResource* is not registered, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *pResource* was not registered with usage flags CU_D3D9_REGISTER_FLAGS_NONE, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *pResource* is not mapped, then [CUDA_ERROR_NOT_MAPPED](#) is returned.

If *pResource* is of type IDirect3DCubeTexture9, then *Face* must one of the values enumerated by type D3DCUBEMAP_FACES. For all other types *Face* must be 0. If *Face* is invalid, then [CUDA_ERROR_INVALID_VALUE](#) is returned.

If *pResource* is of type IDirect3DBaseTexture9, then *Level* must correspond to a valid mipmap level. At present only mipmap level 0 is supported. For all other types *Level* must be 0. If *Level* is invalid, then [CUDA_ERROR_INVALID_VALUE](#) is returned.

Parameters:

pDevPtr - Returned pointer corresponding to subresource

pResource - Mapped resource to access

Face - Face of resource to access

Level - Level of resource to access

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_MAPPED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsResourceGetMappedPointer](#)

4.50.4.6 CUresult cuD3D9ResourceGetMappedSize (size_t * *pSize*, IDirect3DResource9 * *pResource*, unsigned int *Face*, unsigned int *Level*)

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in *pSize* the size of the subresource of the mapped Direct3D resource *pResource*, which corresponds to *Face* and *Level*. The value set in *pSize* may change every time that *pResource* is mapped.

If *pResource* has not been registered for use with CUDA, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *pResource* was not registered with usage flags `CU_D3D9_REGISTER_FLAGS_NONE`, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *pResource* is not mapped for access by CUDA, then [CUDA_ERROR_NOT_MAPPED](#) is returned.

For usage requirements of *Face* and *Level* parameters, see [cuD3D9ResourceGetMappedPointer](#).

Parameters:

- pSize* - Returned size of subresource
- pResource* - Mapped resource to access
- Face* - Face of resource to access
- Level* - Level of resource to access

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_MAPPED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsResourceGetMappedPointer](#)

4.50.4.7 CUresult cuD3D9ResourceGetSurfaceDimensions (size_t * pWidth, size_t * pHeight, size_t * pDepth, IDirect3DResource9 * pResource, unsigned int Face, unsigned int Level)

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in *pWidth*, *pHeight*, and *pDepth* the dimensions of the subresource of the mapped Direct3D resource *pResource*, which corresponds to *Face* and *Level*.

Because anti-aliased surfaces may have multiple samples per pixel, it is possible that the dimensions of a resource will be an integer factor larger than the dimensions reported by the Direct3D runtime.

The parameters *pWidth*, *pHeight*, and *pDepth* are optional. For 2D surfaces, the value returned in *pDepth* will be 0.

If *pResource* is not of type `IDirect3DBaseTexture9` or `IDirect3DSurface9` or if *pResource* has not been registered for use with CUDA, then [CUDA_ERROR_INVALID_HANDLE](#) is returned.

For usage requirements of *Face* and *Level* parameters, see [cuD3D9ResourceGetMappedPointer\(\)](#).

Parameters:

- pWidth* - Returned width of surface
- pHeight* - Returned height of surface
- pDepth* - Returned depth of surface

pResource - Registered resource to access

Face - Face of resource to access

Level - Level of resource to access

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsSubResourceGetMappedArray](#)

4.50.4.8 CUresult cuD3D9ResourceSetMapFlags (IDirect3DResource9 * *pResource*, unsigned int *Flags*)

Deprecated

This function is deprecated as of Cuda 3.0.

Set *Flags* for mapping the Direct3D resource *pResource*.

Changes to *Flags* will take effect the next time *pResource* is mapped. The *Flags* argument may be any of the following:

- [CU_D3D9_MAPRESOURCE_FLAGS_NONE](#): Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA kernels. This is the default value.
- [CU_D3D9_MAPRESOURCE_FLAGS_READONLY](#): Specifies that CUDA kernels which access this resource will not write to this resource.
- [CU_D3D9_MAPRESOURCE_FLAGS_WRITEDISCARD](#): Specifies that CUDA kernels which access this resource will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

If *pResource* has not been registered for use with CUDA, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *pResource* is presently mapped for access by CUDA, then [CUDA_ERROR_ALREADY_MAPPED](#) is returned.

Parameters:

pResource - Registered resource to set flags for

Flags - Parameters for resource mapping

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_ALREADY_MAPPED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsResourceSetMapFlags](#)

4.50.4.9 CUresult cuD3D9UnmapResources (unsigned int *count*, IDirect3DResource9 ** *ppResource*)**Deprecated**

This function is deprecated as of Cuda 3.0.

Unmaps the *count* Direct3D resources in *ppResource*.

This function provides the synchronization guarantee that any CUDA kernels issued before [cuD3D9UnmapResources\(\)](#) will complete before any Direct3D calls issued after [cuD3D9UnmapResources\(\)](#) begin.

If any of *ppResource* have not been registered for use with CUDA or if *ppResource* contains any duplicate entries, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If any of *ppResource* are not presently mapped for access by CUDA, then [CUDA_ERROR_NOT_MAPPED](#) is returned.

Parameters:

count - Number of resources to unmap for CUDA

ppResource - Resources to unmap for CUDA

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_MAPPED](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsUnmapResources](#)

4.50.4.10 CUresult cuD3D9UnregisterResource (IDirect3DResource9 * *pResource*)**Deprecated**

This function is deprecated as of Cuda 3.0.

Unregisters the Direct3D resource *pResource* so it is not accessible by CUDA unless registered again.

If *pResource* is not registered, then [CUDA_ERROR_INVALID_HANDLE](#) is returned.

Parameters:

pResource - Resource to unregister

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsUnregisterResource](#)

4.51 Direct3D 10 Interoperability

Modules

- [Direct3D 10 Interoperability \[DEPRECATED\]](#)

Typedefs

- typedef enum [CUd3d10DeviceList_enum](#) [CUd3d10DeviceList](#)

Enumerations

- enum [CUd3d10DeviceList_enum](#) {
[CU_D3D10_DEVICE_LIST_ALL](#) = 0x01,
[CU_D3D10_DEVICE_LIST_CURRENT_FRAME](#) = 0x02,
[CU_D3D10_DEVICE_LIST_NEXT_FRAME](#) = 0x03 }

Functions

- [CUresult cuD3D10CtxCreate](#) ([CUcontext](#) *pCtx, [CUdevice](#) *pCudaDevice, unsigned int Flags, [ID3D10Device](#) *pD3DDevice)
Create a CUDA context for interoperability with Direct3D 10.
- [CUresult cuD3D10CtxCreateOnDevice](#) ([CUcontext](#) *pCtx, unsigned int flags, [ID3D10Device](#) *pD3DDevice, [CUdevice](#) cudaDevice)
Create a CUDA context for interoperability with Direct3D 10.
- [CUresult cuD3D10GetDevice](#) ([CUdevice](#) *pCudaDevice, [IDXGIAdapter](#) *pAdapter)
Gets the CUDA device corresponding to a display adapter.
- [CUresult cuD3D10GetDevices](#) (unsigned int *pCudaDeviceCount, [CUdevice](#) *pCudaDevices, unsigned int cudaDeviceCount, [ID3D10Device](#) *pD3D10Device, [CUd3d10DeviceList](#) deviceList)
Gets the CUDA devices corresponding to a Direct3D 10 device.
- [CUresult cuD3D10GetDirect3DDevice](#) ([ID3D10Device](#) **ppD3DDevice)
Get the Direct3D 10 device against which the current CUDA context was created.
- [CUresult cuGraphicsD3D10RegisterResource](#) ([CUgraphicsResource](#) *pCudaResource, [ID3D10Resource](#) *pD3DResource, unsigned int Flags)
Register a Direct3D 10 resource for access by CUDA.

4.51.1 Detailed Description

This section describes the Direct3D 10 interoperability functions of the low-level CUDA driver application programming interface. Note that mapping of Direct3D 10 resources is performed with the graphics API agnostic, resource mapping interface described in [Graphics Interopability](#).

4.51.2 Typedef Documentation

4.51.2.1 typedef enum CUd3d10DeviceList_enum CUd3d10DeviceList

CUDA devices corresponding to a D3D10 device

4.51.3 Enumeration Type Documentation

4.51.3.1 enum CUd3d10DeviceList_enum

CUDA devices corresponding to a D3D10 device

Enumerator:

CU_D3D10_DEVICE_LIST_ALL The CUDA devices for all GPUs used by a D3D10 device

CU_D3D10_DEVICE_LIST_CURRENT_FRAME The CUDA devices for the GPUs used by a D3D10 device in its currently rendering frame

CU_D3D10_DEVICE_LIST_NEXT_FRAME The CUDA devices for the GPUs to be used by a D3D10 device in the next frame

4.51.4 Function Documentation

4.51.4.1 CUresult cuD3D10CtxCreate (CUcontext * *pCtx*, CUdevice * *pCudaDevice*, unsigned int *Flags*, ID3D10Device * *pD3DDevice*)

Creates a new CUDA context, enables interoperability for that context with the Direct3D device *pD3DDevice*, and associates the created CUDA context with the calling thread. The created [CUcontext](#) will be returned in **pCtx*. Direct3D resources from this device may be registered and mapped through the lifetime of this CUDA context. If *pCudaDevice* is non-NULL then the [CUdevice](#) on which this CUDA context was created will be returned in **pCudaDevice*.

On success, this call will increase the internal reference count on *pD3DDevice*. This reference count will be decremented upon destruction of this context through [cuCtxDestroy\(\)](#). This context will cease to function if *pD3DDevice* is destroyed or encounters an error.

Parameters:

pCtx - Returned newly created CUDA context

pCudaDevice - Returned pointer to the device on which the context was created

Flags - Context creation flags (see [cuCtxCreate\(\)](#) for details)

pD3DDevice - Direct3D device to create interoperability context with

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D10GetDevice](#), [cuGraphicsD3D10RegisterResource](#)

4.51.4.2 CUresult cuD3D10CtxCreateOnDevice (CUcontext * *pCtx*, unsigned int *flags*, IDXGIAdapter * *pD3DDevice*, CUdevice *cudaDevice*)

Creates a new CUDA context, enables interoperability for that context with the Direct3D device *pD3DDevice*, and associates the created CUDA context with the calling thread. The created [CUcontext](#) will be returned in **pCtx*. Direct3D resources from this device may be registered and mapped through the lifetime of this CUDA context.

On success, this call will increase the internal reference count on *pD3DDevice*. This reference count will be decremented upon destruction of this context through [cuCtxDestroy\(\)](#). This context will cease to function if *pD3DDevice* is destroyed or encounters an error.

Parameters:

pCtx - Returned newly created CUDA context

flags - Context creation flags (see [cuCtxCreate\(\)](#) for details)

pD3DDevice - Direct3D device to create interoperability context with

cudaDevice - The CUDA device on which to create the context. This device must be among the devices returned when querying CU_D3D10_DEVICES_ALL from [cuD3D10GetDevices](#).

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D10GetDevices](#), [cuGraphicsD3D10RegisterResource](#)

4.51.4.3 CUresult cuD3D10GetDevice (CUdevice * *pCudaDevice*, IDXGIAdapter * *pAdapter*)

Returns in **pCudaDevice* the CUDA-compatible device corresponding to the adapter *pAdapter* obtained from `IDXGIFactory::EnumAdapters`.

If no device on *pAdapter* is CUDA-compatible then the call will fail.

Parameters:

pCudaDevice - Returned CUDA device corresponding to *pAdapter*

pAdapter - Adapter to query for CUDA device

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_NOT_FOUND](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D10CtxCreate](#)

4.51.4.4 CUresult cuD3D10GetDevices (unsigned int * *pCudaDeviceCount*, CUdevice * *pCudaDevices*, unsigned int *cudaDeviceCount*, ID3D10Device * *pD3D10Device*, CUd3d10DeviceList *deviceList*)

Returns in **pCudaDeviceCount* the number of CUDA-compatible device corresponding to the Direct3D 10 device *pD3D10Device*. Also returns in **pCudaDevices* at most *cudaDeviceCount* of the the CUDA-compatible devices corresponding to the Direct3D 10 device *pD3D10Device*.

If any of the GPUs being used to render *pDevice* are not CUDA capable then the call will return [CUDA_ERROR_NO_DEVICE](#).

Parameters:

pCudaDeviceCount - Returned number of CUDA devices corresponding to *pD3D10Device*

pCudaDevices - Returned CUDA devices corresponding to *pD3D10Device*

cudaDeviceCount - The size of the output device array *pCudaDevices*

pD3D10Device - Direct3D 10 device to query for CUDA devices

deviceList - The set of devices to return. This set may be [CU_D3D10_DEVICE_LIST_ALL](#) for all devices, [CU_D3D10_DEVICE_LIST_CURRENT_FRAME](#) for the devices used to render the current frame (in SLI), or [CU_D3D10_DEVICE_LIST_NEXT_FRAME](#) for the devices used to render the next frame (in SLI).

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_NO_DEVICE](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_NOT_FOUND](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D10CtxCreate](#)

4.51.4.5 CUresult cuD3D10GetDirect3DDevice (ID3D10Device ** *ppD3DDevice*)

Returns in **ppD3DDevice* the Direct3D device against which this CUDA context was created in [cuD3D10CtxCreate\(\)](#).

Parameters:

ppD3DDevice - Returned Direct3D device corresponding to CUDA context

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D10GetDevice](#)

4.51.4.6 CUresult cuGraphicsD3D10RegisterResource (CUgraphicsResource * pCudaResource, ID3D10Resource * pD3DResource, unsigned int Flags)

Registers the Direct3D 10 resource `pD3DResource` for access by CUDA and returns a CUDA handle to `pD3DResource` in `pCudaResource`. The handle returned in `pCudaResource` may be used to map and unmap this resource until it is unregistered. On success this call will increase the internal reference count on `pD3DResource`. This reference count will be decremented when this resource is unregistered through [cuGraphicsUnregisterResource\(\)](#).

This call is potentially high-overhead and should not be called every frame in interactive applications.

The type of `pD3DResource` must be one of the following.

- `ID3D10Buffer`: may be accessed through a device pointer.
- `ID3D10Texture1D`: individual subresources of the texture may be accessed via arrays
- `ID3D10Texture2D`: individual subresources of the texture may be accessed via arrays
- `ID3D10Texture3D`: individual subresources of the texture may be accessed via arrays

The `Flags` argument may be used to specify additional parameters at register time. The valid values for this parameter are

- `CU_GRAPHICS_REGISTER_FLAGS_NONE`: Specifies no hints about how this resource will be used.
- `CU_GRAPHICS_REGISTER_FLAGS_SURFACE_LDST`: Specifies that CUDA will bind this resource to a surface reference.
- `CU_GRAPHICS_REGISTER_FLAGS_TEXTURE_GATHER`: Specifies that CUDA will perform texture gather operations on this resource.

Not all Direct3D resources of the above types may be used for interoperability with CUDA. The following are some limitations.

- The primary rendertarget may not be registered with CUDA.
- Resources allocated as shared may not be registered with CUDA.
- Textures which are not of a format which is 1, 2, or 4 channels of 8, 16, or 32-bit integer or floating-point data cannot be shared.
- Surfaces of depth or stencil formats cannot be shared.

If Direct3D interoperability is not initialized for this context using [cuD3D10CtxCreate](#) then `CUDA_ERROR_INVALID_CONTEXT` is returned. If `pD3DResource` is of incorrect type or is already registered then `CUDA_ERROR_INVALID_HANDLE` is returned. If `pD3DResource` cannot be registered then `CUDA_ERROR_UNKNOWN` is returned. If `Flags` is not one of the above specified value then `CUDA_ERROR_INVALID_VALUE` is returned.

Parameters:

pCudaResource - Returned graphics resource handle

pD3DResource - Direct3D resource to register

Flags - Parameters for resource registration

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_INVALID_HANDLE, CUDA_ERROR_OUT_OF_MEMORY, CUDA_ERROR_UNKNOWN

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuD3D10CtxCreate, cuGraphicsUnregisterResource, cuGraphicsMapResources, cuGraphicsSubResourceGetMappedArray, cuGraphicsResourceGetMappedPointer

4.52 Direct3D 10 Interoperability [DEPRECATED]

Typedefs

- typedef enum [CUD3D10map_flags_enum](#) [CUD3D10map_flags](#)
- typedef enum [CUD3D10register_flags_enum](#) [CUD3D10register_flags](#)

Enumerations

- enum [CUD3D10map_flags_enum](#)
- enum [CUD3D10register_flags_enum](#)

Functions

- [CUresult cuD3D10MapResources](#) (unsigned int count, ID3D10Resource **ppResources)
Map Direct3D resources for access by CUDA.
- [CUresult cuD3D10RegisterResource](#) (ID3D10Resource *pResource, unsigned int Flags)
Register a Direct3D resource for access by CUDA.
- [CUresult cuD3D10ResourceGetMappedArray](#) (CUarray *pArray, ID3D10Resource *pResource, unsigned int SubResource)
Get an array through which to access a subresource of a Direct3D resource which has been mapped for access by CUDA.
- [CUresult cuD3D10ResourceGetMappedPitch](#) (size_t *pPitch, size_t *pPitchSlice, ID3D10Resource *pResource, unsigned int SubResource)
Get the pitch of a subresource of a Direct3D resource which has been mapped for access by CUDA.
- [CUresult cuD3D10ResourceGetMappedPointer](#) (CUdeviceptr *pDevPtr, ID3D10Resource *pResource, unsigned int SubResource)
Get a pointer through which to access a subresource of a Direct3D resource which has been mapped for access by CUDA.
- [CUresult cuD3D10ResourceGetMappedSize](#) (size_t *pSize, ID3D10Resource *pResource, unsigned int SubResource)
Get the size of a subresource of a Direct3D resource which has been mapped for access by CUDA.
- [CUresult cuD3D10ResourceGetSurfaceDimensions](#) (size_t *pWidth, size_t *pHeight, size_t *pDepth, ID3D10Resource *pResource, unsigned int SubResource)
Get the dimensions of a registered surface.
- [CUresult cuD3D10ResourceSetMapFlags](#) (ID3D10Resource *pResource, unsigned int Flags)
Set usage flags for mapping a Direct3D resource.
- [CUresult cuD3D10UnmapResources](#) (unsigned int count, ID3D10Resource **ppResources)
Unmap Direct3D resources.
- [CUresult cuD3D10UnregisterResource](#) (ID3D10Resource *pResource)
Unregister a Direct3D resource.

4.52.1 Detailed Description

This section describes deprecated Direct3D 10 interoperability functionality.

4.52.2 Typedef Documentation

4.52.2.1 typedef enum CUD3D10map_flags_enum CUD3D10map_flags

Flags to map or unmap a resource

4.52.2.2 typedef enum CUD3D10register_flags_enum CUD3D10register_flags

Flags to register a resource

4.52.3 Enumeration Type Documentation

4.52.3.1 enum CUD3D10map_flags_enum

Flags to map or unmap a resource

4.52.3.2 enum CUD3D10register_flags_enum

Flags to register a resource

4.52.4 Function Documentation

4.52.4.1 CUresult cuD3D10MapResources (unsigned int *count*, ID3D10Resource ** *ppResources*)

Deprecated

This function is deprecated as of Cuda 3.0.

Maps the *count* Direct3D resources in *ppResources* for access by CUDA.

The resources in *ppResources* may be accessed in CUDA kernels until they are unmapped. Direct3D should not access any resources while they are mapped by CUDA. If an application does so, the results are undefined.

This function provides the synchronization guarantee that any Direct3D calls issued before [cuD3D10MapResources\(\)](#) will complete before any CUDA kernels issued after [cuD3D10MapResources\(\)](#) begin.

If any of *ppResources* have not been registered for use with CUDA or if *ppResources* contains any duplicate entries, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If any of *ppResources* are presently mapped for access by CUDA, then [CUDA_ERROR_ALREADY_MAPPED](#) is returned.

Parameters:

count - Number of resources to map for CUDA

ppResources - Resources to map for CUDA

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_ALREADY_MAPPED](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsMapResources](#)

4.52.4.2 CUresult cuD3D10RegisterResource (ID3D10Resource * *pResource*, unsigned int *Flags*)

Deprecated

This function is deprecated as of Cuda 3.0.

Registers the Direct3D resource *pResource* for access by CUDA.

If this call is successful, then the application will be able to map and unmap this resource until it is unregistered through [cuD3D10UnregisterResource\(\)](#). Also on success, this call will increase the internal reference count on *pResource*. This reference count will be decremented when this resource is unregistered through [cuD3D10UnregisterResource\(\)](#).

This call is potentially high-overhead and should not be called every frame in interactive applications.

The type of *pResource* must be one of the following.

- ID3D10Buffer: Cannot be used with *Flags* set to `CU_D3D10_REGISTER_FLAGS_ARRAY`.
- ID3D10Texture1D: No restrictions.
- ID3D10Texture2D: No restrictions.
- ID3D10Texture3D: No restrictions.

The *Flags* argument specifies the mechanism through which CUDA will access the Direct3D resource. The following values are allowed.

- `CU_D3D10_REGISTER_FLAGS_NONE`: Specifies that CUDA will access this resource through a [CUdeviceptr](#). The pointer, size, and (for textures), pitch for each subresource of this allocation may be queried through [cuD3D10ResourceGetMappedPointer\(\)](#), [cuD3D10ResourceGetMappedSize\(\)](#), and [cuD3D10ResourceGetMappedPitch\(\)](#) respectively. This option is valid for all resource types.
- `CU_D3D10_REGISTER_FLAGS_ARRAY`: Specifies that CUDA will access this resource through a [CUarray](#) queried on a sub-resource basis through [cuD3D10ResourceGetMappedArray\(\)](#). This option is only valid for resources of type ID3D10Texture1D, ID3D10Texture2D, and ID3D10Texture3D.

Not all Direct3D resources of the above types may be used for interoperability with CUDA. The following are some limitations.

- The primary rendertarget may not be registered with CUDA.
- Resources allocated as shared may not be registered with CUDA.

- Textures which are not of a format which is 1, 2, or 4 channels of 8, 16, or 32-bit integer or floating-point data cannot be shared.
- Surfaces of depth or stencil formats cannot be shared.

If Direct3D interoperability is not initialized on this context then [CUDA_ERROR_INVALID_CONTEXT](#) is returned. If `pResource` is of incorrect type or is already registered, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If `pResource` cannot be registered, then [CUDA_ERROR_UNKNOWN](#) is returned.

Parameters:

pResource - Resource to register
Flags - Parameters for resource registration

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsD3D10RegisterResource](#)

4.52.4.3 CUresult cuD3D10ResourceGetMappedArray (CUarray * pArray, ID3D10Resource * pResource, unsigned int SubResource)

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in `*pArray` an array through which the subresource of the mapped Direct3D resource `pResource`, which corresponds to `SubResource` may be accessed. The value set in `pArray` may change every time that `pResource` is mapped.

If `pResource` is not registered, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If `pResource` was not registered with usage flags `CU_D3D10_REGISTER_FLAGS_ARRAY`, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If `pResource` is not mapped, then [CUDA_ERROR_NOT_MAPPED](#) is returned.

For usage requirements of the `SubResource` parameter, see [cuD3D10ResourceGetMappedPointer\(\)](#).

Parameters:

pArray - Returned array corresponding to subresource
pResource - Mapped resource to access
SubResource - Subresource of `pResource` to access

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_MAPPED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsSubResourceGetMappedArray](#)

4.52.4.4 CUresult cuD3D10ResourceGetMappedPitch (size_t * *pPitch*, size_t * *pPitchSlice*, ID3D10Resource * *pResource*, unsigned int *SubResource*)

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in *pPitch* and *pPitchSlice* the pitch and Z-slice pitch of the subresource of the mapped Direct3D resource *pResource*, which corresponds to *SubResource*. The values set in *pPitch* and *pPitchSlice* may change every time that *pResource* is mapped.

The pitch and Z-slice pitch values may be used to compute the location of a sample on a surface as follows.

For a 2D surface, the byte offset of the sample at position *x*, *y* from the base pointer of the surface is:

$$y * \text{pitch} + (\text{bytes per pixel}) * x$$

For a 3D surface, the byte offset of the sample at position *x*, *y*, *z* from the base pointer of the surface is:

$$z * \text{slicePitch} + y * \text{pitch} + (\text{bytes per pixel}) * x$$

Both parameters *pPitch* and *pPitchSlice* are optional and may be set to NULL.

If *pResource* is not of type IDirect3DBaseTexture10 or one of its sub-types or if *pResource* has not been registered for use with CUDA, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *pResource* was not registered with usage flags CU_D3D10_REGISTER_FLAGS_NONE, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *pResource* is not mapped for access by CUDA, then [CUDA_ERROR_NOT_MAPPED](#) is returned.

For usage requirements of the *SubResource* parameter, see [cuD3D10ResourceGetMappedPointer\(\)](#).

Parameters:

pPitch - Returned pitch of subresource

pPitchSlice - Returned Z-slice pitch of subresource

pResource - Mapped resource to access

SubResource - Subresource of *pResource* to access

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_MAPPED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsSubResourceGetMappedArray](#)

4.52.4.5 CUresult cuD3D10ResourceGetMappedPointer (CUdeviceptr * *pDevPtr*, ID3D10Resource * *pResource*, unsigned int *SubResource*)

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in **pDevPtr* the base pointer of the subresource of the mapped Direct3D resource *pResource*, which corresponds to *SubResource*. The value set in *pDevPtr* may change every time that *pResource* is mapped.

If *pResource* is not registered, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *pResource* was not registered with usage flags `CU_D3D10_REGISTER_FLAGS_NONE`, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *pResource* is not mapped, then [CUDA_ERROR_NOT_MAPPED](#) is returned.

If *pResource* is of type `ID3D10Buffer`, then *SubResource* must be 0. If *pResource* is of any other type, then the value of *SubResource* must come from the subresource calculation in `D3D10CalcSubResource()`.

Parameters:

pDevPtr - Returned pointer corresponding to subresource

pResource - Mapped resource to access

SubResource - Subresource of *pResource* to access

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_MAPPED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsResourceGetMappedPointer](#)

4.52.4.6 CUresult cuD3D10ResourceGetMappedSize (size_t * *pSize*, ID3D10Resource * *pResource*, unsigned int *SubResource*)

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in **pSize* the size of the subresource of the mapped Direct3D resource *pResource*, which corresponds to *SubResource*. The value set in *pSize* may change every time that *pResource* is mapped.

If *pResource* has not been registered for use with CUDA, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *pResource* was not registered with usage flags `CU_D3D10_REGISTER_FLAGS_NONE`, then [CUDA_ERROR_INVALID_HANDLE](#) is returned. If *pResource* is not mapped for access by CUDA, then [CUDA_ERROR_NOT_MAPPED](#) is returned.

For usage requirements of the *SubResource* parameter, see [cuD3D10ResourceGetMappedPointer\(\)](#).

Parameters:

pSize - Returned size of subresource

pResource - Mapped resource to access

SubResource - Subresource of pResource to access

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_MAPPED](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsResourceGetMappedPointer](#)

4.52.4.7 `CUresult cuD3D10ResourceGetSurfaceDimensions (size_t * pWidth, size_t * pHeight, size_t * pDepth, ID3D10Resource * pResource, unsigned int SubResource)`

Deprecated

This function is deprecated as of Cuda 3.0.

Returns in *pWidth, *pHeight, and *pDepth the dimensions of the subresource of the mapped Direct3D resource pResource, which corresponds to SubResource.

Because anti-aliased surfaces may have multiple samples per pixel, it is possible that the dimensions of a resource will be an integer factor larger than the dimensions reported by the Direct3D runtime.

The parameters pWidth, pHeight, and pDepth are optional. For 2D surfaces, the value returned in *pDepth will be 0.

If pResource is not of type IDirect3DBaseTexture10 or IDirect3DSurface10 or if pResource has not been registered for use with CUDA, then [CUDA_ERROR_INVALID_HANDLE](#) is returned.

For usage requirements of the SubResource parameter, see [cuD3D10ResourceGetMappedPointer\(\)](#).

Parameters:

pWidth - Returned width of surface

pHeight - Returned height of surface

pDepth - Returned depth of surface

pResource - Registered resource to access

SubResource - Subresource of pResource to access

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsSubResourceGetMappedArray](#)

4.52.4.8 CUresult cuD3D10ResourceSetMapFlags (ID3D10Resource * *pResource*, unsigned int *Flags*)**Deprecated**

This function is deprecated as of Cuda 3.0.

Set flags for mapping the Direct3D resource *pResource*.

Changes to flags will take effect the next time *pResource* is mapped. The *Flags* argument may be any of the following.

- `CU_D3D10_MAPRESOURCE_FLAGS_NONE`: Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA kernels. This is the default value.
- `CU_D3D10_MAPRESOURCE_FLAGS_READONLY`: Specifies that CUDA kernels which access this resource will not write to this resource.
- `CU_D3D10_MAPRESOURCE_FLAGS_WRITEDISCARD`: Specifies that CUDA kernels which access this resource will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

If *pResource* has not been registered for use with CUDA, then `CUDA_ERROR_INVALID_HANDLE` is returned. If *pResource* is presently mapped for access by CUDA then `CUDA_ERROR_ALREADY_MAPPED` is returned.

Parameters:

pResource - Registered resource to set flags for

Flags - Parameters for resource mapping

Returns:

`CUDA_SUCCESS`, `CUDA_ERROR_DEINITIALIZED`, `CUDA_ERROR_NOT_INITIALIZED`, `CUDA_ERROR_INVALID_CONTEXT`, `CUDA_ERROR_INVALID_VALUE`, `CUDA_ERROR_INVALID_HANDLE`, `CUDA_ERROR_ALREADY_MAPPED`

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsResourceSetMapFlags](#)

4.52.4.9 CUresult cuD3D10UnmapResources (unsigned int *count*, ID3D10Resource ** *ppResources*)**Deprecated**

This function is deprecated as of Cuda 3.0.

Unmaps the *count* Direct3D resources in *ppResources*.

This function provides the synchronization guarantee that any CUDA kernels issued before `cuD3D10UnmapResources()` will complete before any Direct3D calls issued after `cuD3D10UnmapResources()` begin.

If any of *ppResources* have not been registered for use with CUDA or if *ppResources* contains any duplicate entries, then `CUDA_ERROR_INVALID_HANDLE` is returned. If any of *ppResources* are not presently mapped for access by CUDA, then `CUDA_ERROR_NOT_MAPPED` is returned.

Parameters:

count - Number of resources to unmap for CUDA

ppResources - Resources to unmap for CUDA

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_NOT_MAPPED](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsUnmapResources](#)

4.52.4.10 CUresult cuD3D10UnregisterResource (ID3D10Resource * *pResource*)**Deprecated**

This function is deprecated as of Cuda 3.0.

Unregisters the Direct3D resource *pResource* so it is not accessible by CUDA unless registered again.

If *pResource* is not registered, then [CUDA_ERROR_INVALID_HANDLE](#) is returned.

Parameters:

pResource - Resources to unregister

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuGraphicsUnregisterResource](#)

4.53 Direct3D 11 Interoperability

Typedefs

- typedef enum [CUd3d11DeviceList_enum](#) [CUd3d11DeviceList](#)

Enumerations

- enum [CUd3d11DeviceList_enum](#) {
[CU_D3D11_DEVICE_LIST_ALL](#) = 0x01,
[CU_D3D11_DEVICE_LIST_CURRENT_FRAME](#) = 0x02,
[CU_D3D11_DEVICE_LIST_NEXT_FRAME](#) = 0x03 }

Functions

- [CUresult cuD3D11CtxCreate](#) ([CUcontext](#) *pCtx, [CUdevice](#) *pCudaDevice, unsigned int Flags, [ID3D11Device](#) *pD3DDevice)
Create a CUDA context for interoperability with Direct3D 11.
- [CUresult cuD3D11CtxCreateOnDevice](#) ([CUcontext](#) *pCtx, unsigned int flags, [ID3D11Device](#) *pD3DDevice, [CUdevice](#) cudaDevice)
Create a CUDA context for interoperability with Direct3D 11.
- [CUresult cuD3D11GetDevice](#) ([CUdevice](#) *pCudaDevice, [IDXGIAdapter](#) *pAdapter)
Gets the CUDA device corresponding to a display adapter.
- [CUresult cuD3D11GetDevices](#) (unsigned int *pCudaDeviceCount, [CUdevice](#) *pCudaDevices, unsigned int cudaDeviceCount, [ID3D11Device](#) *pD3D11Device, [CUd3d11DeviceList](#) deviceList)
Gets the CUDA devices corresponding to a Direct3D 11 device.
- [CUresult cuD3D11GetDirect3DDevice](#) ([ID3D11Device](#) **ppD3DDevice)
Get the Direct3D 11 device against which the current CUDA context was created.
- [CUresult cuGraphicsD3D11RegisterResource](#) ([CUgraphicsResource](#) *pCudaResource, [ID3D11Resource](#) *pD3DResource, unsigned int Flags)
Register a Direct3D 11 resource for access by CUDA.

4.53.1 Detailed Description

This section describes the Direct3D 11 interoperability functions of the low-level CUDA driver application programming interface. Note that mapping of Direct3D 11 resources is performed with the graphics API agnostic, resource mapping interface described in [Graphics Interoperability](#).

4.53.2 Typedef Documentation

4.53.2.1 typedef enum [CUd3d11DeviceList_enum](#) [CUd3d11DeviceList](#)

CUDA devices corresponding to a D3D11 device

4.53.3 Enumeration Type Documentation

4.53.3.1 enum CUd3d11DeviceList_enum

CUDA devices corresponding to a D3D11 device

Enumerator:

CU_D3D11_DEVICE_LIST_ALL The CUDA devices for all GPUs used by a D3D11 device

CU_D3D11_DEVICE_LIST_CURRENT_FRAME The CUDA devices for the GPUs used by a D3D11 device in its currently rendering frame

CU_D3D11_DEVICE_LIST_NEXT_FRAME The CUDA devices for the GPUs to be used by a D3D11 device in the next frame

4.53.4 Function Documentation

4.53.4.1 CUresult cuD3D11CtxCreate (CUcontext *pCtx, CUdevice *pCudaDevice, unsigned int Flags, ID3D11Device *pD3DDevice)

Creates a new CUDA context, enables interoperability for that context with the Direct3D device pD3DDevice, and associates the created CUDA context with the calling thread. The created [CUcontext](#) will be returned in *pCtx. Direct3D resources from this device may be registered and mapped through the lifetime of this CUDA context. If pCudaDevice is non-NULL then the [CUdevice](#) on which this CUDA context was created will be returned in *pCudaDevice.

On success, this call will increase the internal reference count on pD3DDevice. This reference count will be decremented upon destruction of this context through [cuCtxDestroy\(\)](#). This context will cease to function if pD3DDevice is destroyed or encounters an error.

Parameters:

pCtx - Returned newly created CUDA context

pCudaDevice - Returned pointer to the device on which the context was created

Flags - Context creation flags (see [cuCtxCreate\(\)](#) for details)

pD3DDevice - Direct3D device to create interoperability context with

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D11GetDevice](#), [cuGraphicsD3D11RegisterResource](#)

4.53.4.2 CUresult cuD3D11CtxCreateOnDevice (CUcontext *pCtx, unsigned int flags, ID3D11Device *pD3DDevice, CUdevice cudaDevice)

Creates a new CUDA context, enables interoperability for that context with the Direct3D device pD3DDevice, and associates the created CUDA context with the calling thread. The created [CUcontext](#) will be returned in *pCtx. Direct3D resources from this device may be registered and mapped through the lifetime of this CUDA context.

On success, this call will increase the internal reference count on `pD3DDevice`. This reference count will be decremented upon destruction of this context through [cuCtxDestroy\(\)](#). This context will cease to function if `pD3DDevice` is destroyed or encounters an error.

Parameters:

pCtx - Returned newly created CUDA context

flags - Context creation flags (see [cuCtxCreate\(\)](#) for details)

pD3DDevice - Direct3D device to create interoperability context with

cudaDevice - The CUDA device on which to create the context. This device must be among the devices returned when querying `CU_D3D11_DEVICES_ALL` from [cuD3D11GetDevices](#).

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D11GetDevices](#), [cuGraphicsD3D11RegisterResource](#)

4.53.4.3 CUresult cuD3D11GetDevice (CUdevice *pCudaDevice, IDXGIAdapter *pAdapter)

Returns in *pCudaDevice* the CUDA-compatible device corresponding to the adapter *pAdapter* obtained from `IDXGIFactory::EnumAdapters`.

If no device on *pAdapter* is CUDA-compatible the call will return [CUDA_ERROR_NO_DEVICE](#).

Parameters:

pCudaDevice - Returned CUDA device corresponding to *pAdapter*

pAdapter - Adapter to query for CUDA device

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_NO_DEVICE](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_NOT_FOUND](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D11CtxCreate](#)

4.53.4.4 CUresult cuD3D11GetDevices (unsigned int * *pCudaDeviceCount*, CUdevice * *pCudaDevices*, unsigned int *cudaDeviceCount*, ID3D11Device * *pD3D11Device*, CUd3d11DeviceList *deviceList*)

Returns in **pCudaDeviceCount* the number of CUDA-compatible device corresponding to the Direct3D 11 device *pD3D11Device*. Also returns in **pCudaDevices* at most *cudaDeviceCount* of the the CUDA-compatible devices corresponding to the Direct3D 11 device *pD3D11Device*.

If any of the GPUs being used to render *pDevice* are not CUDA capable then the call will return [CUDA_ERROR_NO_DEVICE](#).

Parameters:

pCudaDeviceCount - Returned number of CUDA devices corresponding to *pD3D11Device*

pCudaDevices - Returned CUDA devices corresponding to *pD3D11Device*

cudaDeviceCount - The size of the output device array *pCudaDevices*

pD3D11Device - Direct3D 11 device to query for CUDA devices

deviceList - The set of devices to return. This set may be [CU_D3D11_DEVICE_LIST_ALL](#) for all devices, [CU_D3D11_DEVICE_LIST_CURRENT_FRAME](#) for the devices used to render the current frame (in SLI), or [CU_D3D11_DEVICE_LIST_NEXT_FRAME](#) for the devices used to render the next frame (in SLI).

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_NO_DEVICE](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_NOT_FOUND](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D11CtxCreate](#)

4.53.4.5 CUresult cuD3D11GetDirect3DDevice (ID3D11Device ** *ppD3DDevice*)

Returns in **ppD3DDevice* the Direct3D device against which this CUDA context was created in [cuD3D11CtxCreate\(\)](#).

Parameters:

ppD3DDevice - Returned Direct3D device corresponding to CUDA context

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D11GetDevice](#)

4.53.4.6 CUresult cuGraphicsD3D11RegisterResource (CUgraphicsResource * pCudaResource, ID3D11Resource * pD3DResource, unsigned int Flags)

Registers the Direct3D 11 resource `pD3DResource` for access by CUDA and returns a CUDA handle to `pD3DResource` in `pCudaResource`. The handle returned in `pCudaResource` may be used to map and unmap this resource until it is unregistered. On success this call will increase the internal reference count on `pD3DResource`. This reference count will be decremented when this resource is unregistered through `cuGraphicsUnregisterResource()`.

This call is potentially high-overhead and should not be called every frame in interactive applications.

The type of `pD3DResource` must be one of the following.

- `ID3D11Buffer`: may be accessed through a device pointer.
- `ID3D11Texture1D`: individual subresources of the texture may be accessed via arrays
- `ID3D11Texture2D`: individual subresources of the texture may be accessed via arrays
- `ID3D11Texture3D`: individual subresources of the texture may be accessed via arrays

The `Flags` argument may be used to specify additional parameters at register time. The valid values for this parameter are

- `CU_GRAPHICS_REGISTER_FLAGS_NONE`: Specifies no hints about how this resource will be used.
- `CU_GRAPHICS_REGISTER_FLAGS_SURFACE_LDST`: Specifies that CUDA will bind this resource to a surface reference.
- `CU_GRAPHICS_REGISTER_FLAGS_TEXTURE_GATHER`: Specifies that CUDA will perform texture gather operations on this resource.

Not all Direct3D resources of the above types may be used for interoperability with CUDA. The following are some limitations.

- The primary rendertarget may not be registered with CUDA.
- Resources allocated as shared may not be registered with CUDA.
- Textures which are not of a format which is 1, 2, or 4 channels of 8, 16, or 32-bit integer or floating-point data cannot be shared.
- Surfaces of depth or stencil formats cannot be shared.

If Direct3D interoperability is not initialized for this context using `cuD3D11CtxCreate` then `CUDA_ERROR_INVALID_CONTEXT` is returned. If `pD3DResource` is of incorrect type or is already registered then `CUDA_ERROR_INVALID_HANDLE` is returned. If `pD3DResource` cannot be registered then `CUDA_ERROR_UNKNOWN` is returned. If `Flags` is not one of the above specified value then `CUDA_ERROR_INVALID_VALUE` is returned.

Parameters:

pCudaResource - Returned graphics resource handle

pD3DResource - Direct3D resource to register

Flags - Parameters for resource registration

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#), [CUDA_ERROR_INVALID_HANDLE](#), [CUDA_ERROR_OUT_OF_MEMORY](#), [CUDA_ERROR_UNKNOWN](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuD3D11CtxCreate](#), [cuGraphicsUnregisterResource](#), [cuGraphicsMapResources](#), [cuGraphicsSubResourceGetMappedArray](#), [cuGraphicsResourceGetMappedPointer](#)

4.54 VDPAU Interoperability

Functions

- **CUresult cuGraphicsVDPAURegisterOutputSurface** (**CUgraphicsResource** *pCudaResource, VdpOutputSurface vdpSurface, unsigned int flags)
Registers a VDPAU VdpOutputSurface object.
- **CUresult cuGraphicsVDPAURegisterVideoSurface** (**CUgraphicsResource** *pCudaResource, VdpVideoSurface vdpSurface, unsigned int flags)
Registers a VDPAU VdpVideoSurface object.
- **CUresult cuVDPAUCtxCreate** (**CUcontext** *pCtx, unsigned int flags, **CUdevice** device, VdpDevice vdpDevice, VdpGetProcAddress *vdpGetProcAddress)
Create a CUDA context for interoperability with VDPAU.
- **CUresult cuVDPAUGetDevice** (**CUdevice** *pDevice, VdpDevice vdpDevice, VdpGetProcAddress *vdpGetProcAddress)
Gets the CUDA device associated with a VDPAU device.

4.54.1 Detailed Description

This section describes the VDPAU interoperability functions of the low-level CUDA driver application programming interface.

4.54.2 Function Documentation

4.54.2.1 CUresult cuGraphicsVDPAURegisterOutputSurface (CUgraphicsResource *pCudaResource, VdpOutputSurface vdpSurface, unsigned int flags)

Registers the VdpOutputSurface specified by vdpSurface for access by CUDA. A handle to the registered object is returned as pCudaResource. The surface's intended usage is specified using flags, as follows:

- **CU_GRAPHICS_MAP_RESOURCE_FLAGS_NONE**: Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA. This is the default value.
- **CU_GRAPHICS_MAP_RESOURCE_FLAGS_READ_ONLY**: Specifies that CUDA will not write to this resource.
- **CU_GRAPHICS_MAP_RESOURCE_FLAGS_WRITE_DISCARD**: Specifies that CUDA will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

The VdpOutputSurface is presented as an array of subresources that may be accessed using pointers returned by **cuGraphicsSubResourceGetMappedArray**. The exact number of valid arrayIndex values depends on the VDPAU surface format. The mapping is shown in the table below. mipLevel must be 0.

VdpRGBAFormat	arrayIndex	Size	Format	Content
VDP_RGBA_FORMAT_B8G8R8A8	0	w x h	ARGB8	Entire surface
VDP_RGBA_FORMAT_R10G10B10A2	0	w x h	A2BGR10	Entire surface

Parameters:

pCudaResource - Pointer to the returned object handle

vdpSurface - The VdpOutputSurface to be registered

flags - Map flags

Returns:

CUDA_SUCCESS, CUDA_ERROR_INVALID_HANDLE, CUDA_ERROR_ALREADY_MAPPED, CUDA_ERROR_INVALID_CONTEXT,

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxCreate](#), [cuVDPACtxCreate](#), [cuGraphicsVDPAResourceRegisterVideoSurface](#), [cuGraphicsUnregisterResource](#), [cuGraphicsResourceSetMapFlags](#), [cuGraphicsMapResources](#), [cuGraphicsUnmapResources](#), [cuGraphicsSubResourceGetMappedArray](#), [cuVDPAGetDevice](#)

4.54.2.2 CUresult cuGraphicsVDPAResourceRegisterVideoSurface (CUgraphicsResource * pCudaResource, VdpVideoSurface vdpSurface, unsigned int flags)

Registers the VdpVideoSurface specified by vdpSurface for access by CUDA. A handle to the registered object is returned as pCudaResource. The surface's intended usage is specified using flags, as follows:

- CU_GRAPHICS_MAP_RESOURCE_FLAGS_NONE: Specifies no hints about how this resource will be used. It is therefore assumed that this resource will be read from and written to by CUDA. This is the default value.
- CU_GRAPHICS_MAP_RESOURCE_FLAGS_READ_ONLY: Specifies that CUDA will not write to this resource.
- CU_GRAPHICS_MAP_RESOURCE_FLAGS_WRITE_DISCARD: Specifies that CUDA will not read from this resource and will write over the entire contents of the resource, so none of the data previously stored in the resource will be preserved.

The VdpVideoSurface is presented as an array of subresources that may be accessed using pointers returned by [cuGraphicsSubResourceGetMappedArray](#). The exact number of valid arrayIndex values depends on the VDP surface format. The mapping is shown in the table below. mipLevel must be 0.

VdpChromaType	arrayIndex	Size	Format	Content
VDP_CHROMA_TYPE_420	0	w x h/2	R8	Top-field luma
	1	w x h/2	R8	Bottom-field luma
	2	w/2 x h/4	R8G8	Top-field chroma
	3	w/2 x h/4	R8G8	Bottom-field chroma
VDP_CHROMA_TYPE_422	0	w x h/2	R8	Top-field luma
	1	w x h/2	R8	Bottom-field luma
	2	w/2 x h/2	R8G8	Top-field chroma
	3	w/2 x h/2	R8G8	Bottom-field chroma

Parameters:

pCudaResource - Pointer to the returned object handle

vdpSurface - The VdpVideoSurface to be registered

flags - Map flags

Returns:

CUDA_SUCCESS, CUDA_ERROR_INVALID_HANDLE, CUDA_ERROR_ALREADY_MAPPED, CUDA_ERROR_INVALID_CONTEXT,

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuCtxCreate, cuVDPAUCtxCreate, cuGraphicsVDPAURegisterOutputSurface, cuGraphicsUnregisterResource, cuGraphicsResourceSetMapFlags, cuGraphicsMapResources, cuGraphicsUnmapResources, cuGraphicsSubResourceGetMappedArray, cuVDPAUGetDevice

4.54.2.3 CUresult cuVDPAUCtxCreate (CUcontext * *pCtx*, unsigned int *flags*, CUdevice *device*, VdpDevice *vdpDevice*, VdpGetProcAddress * *vdpGetProcAddress*)

Creates a new CUDA context, initializes VDPAU interoperability, and associates the CUDA context with the calling thread. It must be called before performing any other VDPAU interoperability operations. It may fail if the needed VDPAU driver facilities are not available. For usage of the *flags* parameter, see [cuCtxCreate\(\)](#).

Parameters:

pCtx - Returned CUDA context

flags - Options for CUDA context creation

device - Device on which to create the context

vdpDevice - The VdpDevice to interop with

vdpGetProcAddress - VDPAU's VdpGetProcAddress function pointer

Returns:

CUDA_SUCCESS, CUDA_ERROR_DEINITIALIZED, CUDA_ERROR_NOT_INITIALIZED, CUDA_ERROR_INVALID_CONTEXT, CUDA_ERROR_INVALID_VALUE, CUDA_ERROR_OUT_OF_MEMORY

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

cuCtxCreate, cuGraphicsVDPAURegisterVideoSurface, cuGraphicsVDPAURegisterOutputSurface, cuGraphicsUnregisterResource, cuGraphicsResourceSetMapFlags, cuGraphicsMapResources, cuGraphicsUnmapResources, cuGraphicsSubResourceGetMappedArray, cuVDPAUGetDevice

4.54.2.4 CUresult cuVDPAUGetDevice (CUdevice * *pDevice*, VdpDevice *vdpDevice*, VdpGetProcAddress * *vdpGetProcAddress*)

Returns in **pDevice* the CUDA device associated with a *vdpDevice*, if applicable.

Parameters:

pDevice - Device associated with vdpDevice

vdpDevice - A VdpDevice handle

vdpGetProcAddress - VDPAU's VdpGetProcAddress function pointer

Returns:

[CUDA_SUCCESS](#), [CUDA_ERROR_DEINITIALIZED](#), [CUDA_ERROR_NOT_INITIALIZED](#), [CUDA_ERROR_INVALID_CONTEXT](#), [CUDA_ERROR_INVALID_VALUE](#)

Note:

Note that this function may also return error codes from previous, asynchronous launches.

See also:

[cuCtxCreate](#), [cuVDPAUCtxCreate](#), [cuGraphicsVDPAURegisterVideoSurface](#), [cuGraphicsVDPAURegisterOutputSurface](#), [cuGraphicsUnregisterResource](#), [cuGraphicsResourceSetMapFlags](#), [cuGraphicsMapResources](#), [cuGraphicsUnmapResources](#), [cuGraphicsSubResourceGetMappedArray](#)

4.55 Mathematical Functions

Modules

- [Single Precision Mathematical Functions](#)
- [Double Precision Mathematical Functions](#)
- [Single Precision Intrinsic](#)
- [Double Precision Intrinsic](#)
- [Integer Intrinsic](#)
- [Type Casting Intrinsic](#)

4.55.1 Detailed Description

CUDA mathematical functions are always available in device code. Some functions are also available in host code as indicated.

Note that floating-point functions are overloaded for different argument types. For example, the [log\(\)](#) function has the following prototypes:

```
double log(double x);  
float log(float x);  
float logf(float x);
```

4.56 Single Precision Mathematical Functions

Functions

- `__device__ float acosf (float x)`
Calculate the arc cosine of the input argument.
- `__device__ float acoshf (float x)`
Calculate the nonnegative arc hyperbolic cosine of the input argument.
- `__device__ float asinf (float x)`
Calculate the arc sine of the input argument.
- `__device__ float asinhf (float x)`
Calculate the arc hyperbolic sine of the input argument.
- `__device__ float atan2f (float x, float y)`
Calculate the arc tangent of the ratio of first and second input arguments.
- `__device__ float atanf (float x)`
Calculate the arc tangent of the input argument.
- `__device__ float atanhf (float x)`
Calculate the arc hyperbolic tangent of the input argument.
- `__device__ float cbrtf (float x)`
Calculate the cube root of the input argument.
- `__device__ float ceilf (float x)`
Calculate ceiling of the input argument.
- `__device__ float copysignf (float x, float y)`
Create value with given magnitude, copying sign of second value.
- `__device__ float cosf (float x)`
Calculate the cosine of the input argument.
- `__device__ float coshf (float x)`
Calculate the hyperbolic cosine of the input argument.
- `__device__ float cospif (float x)`
Calculate the cosine of the input argument $\times \pi$.
- `__device__ float erfcf (float x)`
Calculate the complementary error function of the input argument.
- `__device__ float erfcinvf (float y)`
Calculate the inverse complementary error function of the input argument.
- `__device__ float erfcxf (float x)`

Calculate the scaled complementary error function of the input argument.

- `__device__ float erff (float x)`

Calculate the error function of the input argument.

- `__device__ float erfinvf (float y)`

Calculate the inverse error function of the input argument.

- `__device__ float exp10f (float x)`

Calculate the base 10 exponential of the input argument.

- `__device__ float exp2f (float x)`

Calculate the base 2 exponential of the input argument.

- `__device__ float expf (float x)`

Calculate the base e exponential of the input argument.

- `__device__ float expm1f (float x)`

Calculate the base e exponential of the input argument, minus 1.

- `__device__ float fabsf (float x)`

Calculate the absolute value of its argument.

- `__device__ float fdimf (float x, float y)`

Compute the positive difference between x and y .

- `__device__ float fdividef (float x, float y)`

Divide two floating point values.

- `__device__ float floorf (float x)`

Calculate the largest integer less than or equal to x .

- `__device__ float fmaf (float x, float y, float z)`

Compute $x \times y + z$ as a single operation.

- `__device__ float fmaxf (float x, float y)`

Determine the maximum numeric value of the arguments.

- `__device__ float fminf (float x, float y)`

Determine the minimum numeric value of the arguments.

- `__device__ float fmodf (float x, float y)`

Calculate the floating-point remainder of x / y .

- `__device__ float frexpf (float x, int *nptr)`

Extract mantissa and exponent of a floating-point value.

- `__device__ float hypotf (float x, float y)`

Calculate the square root of the sum of squares of two arguments.

- `__device__ int ilogbf (float x)`
Compute the unbiased integer exponent of the argument.
- `__device__ int isfinite (float a)`
Determine whether argument is finite.
- `__device__ int isinf (float a)`
Determine whether argument is infinite.
- `__device__ int isnan (float a)`
Determine whether argument is a NaN.
- `__device__ float j0f (float x)`
Calculate the value of the Bessel function of the first kind of order 0 for the input argument.
- `__device__ float j1f (float x)`
Calculate the value of the Bessel function of the first kind of order 1 for the input argument.
- `__device__ float jnf (int n, float x)`
Calculate the value of the Bessel function of the first kind of order n for the input argument.
- `__device__ float ldexpf (float x, int exp)`
Calculate the value of $x \cdot 2^{\text{exp}}$.
- `__device__ float lgammaf (float x)`
Calculate the natural logarithm of the gamma function of the input argument.
- `__device__ long long int llrintf (float x)`
Round input to nearest integer value.
- `__device__ long long int llroundf (float x)`
Round to nearest integer value.
- `__device__ float log10f (float x)`
Calculate the base 10 logarithm of the input argument.
- `__device__ float log1pf (float x)`
Calculate the value of $\log_e(1 + x)$.
- `__device__ float log2f (float x)`
Calculate the base 2 logarithm of the input argument.
- `__device__ float logbf (float x)`
Calculate the floating point representation of the exponent of the input argument.
- `__device__ float logf (float x)`
Calculate the natural logarithm of the input argument.
- `__device__ long int lrintf (float x)`
Round input to nearest integer value.

- `__device__ long int lroundf (float x)`
Round to nearest integer value.
- `__device__ float modff (float x, float *iptr)`
Break down the input argument into fractional and integral parts.
- `__device__ float nanf (const char *tagp)`
Returns "Not a Number" value.
- `__device__ float nearbyintf (float x)`
Round the input argument to the nearest integer.
- `__device__ float nextafterf (float x, float y)`
Return next representable single-precision floating-point value after argument.
- `__device__ float powf (float x, float y)`
Calculate the value of first argument to the power of second argument.
- `__device__ float rcbtrf (float x)`
Calculate reciprocal cube root function.
- `__device__ float remainderf (float x, float y)`
Compute single-precision floating-point remainder.
- `__device__ float remquof (float x, float y, int *quo)`
Compute single-precision floating-point remainder and part of quotient.
- `__device__ float rintf (float x)`
Round input to nearest integer value in floating-point.
- `__device__ float roundf (float x)`
Round to nearest integer value in floating-point.
- `__device__ float rsqrtf (float x)`
Calculate the reciprocal of the square root of the input argument.
- `__device__ float scalblnf (float x, long int n)`
Scale floating-point input by integer power of two.
- `__device__ float scalbnf (float x, int n)`
Scale floating-point input by integer power of two.
- `__device__ int signbit (float a)`
Return the sign bit of the input.
- `__device__ void sincosf (float x, float *sptr, float *cptr)`
Calculate the sine and cosine of the first input argument.
- `__device__ float sinf (float x)`

Calculate the sine of the input argument.

- `__device__ float sinh (float x)`
Calculate the hyperbolic sine of the input argument.
- `__device__ float sinpif (float x)`
Calculate the sine of the input argument $\times \pi$.
- `__device__ float sqrtf (float x)`
Calculate the square root of the input argument.
- `__device__ float tanf (float x)`
Calculate the tangent of the input argument.
- `__device__ float tanhf (float x)`
Calculate the hyperbolic tangent of the input argument.
- `__device__ float tgammaf (float x)`
Calculate the gamma function of the input argument.
- `__device__ float truncf (float x)`
Truncate input argument to the integral part.
- `__device__ float y0f (float x)`
Calculate the value of the Bessel function of the second kind of order 0 for the input argument.
- `__device__ float y1f (float x)`
Calculate the value of the Bessel function of the second kind of order 1 for the input argument.
- `__device__ float ynf (int n, float x)`
Calculate the value of the Bessel function of the second kind of order n for the input argument.

4.56.1 Detailed Description

This section describes single precision mathematical functions.

4.56.2 Function Documentation

4.56.2.1 `__device__ float acosf (float x)`

Calculate the principal value of the arc cosine of the input argument x .

Returns:

Result will be in the interval $[0, \pi]$ for x inside $[-1, +1]$.

- `acosf(1)` returns $+0$.
- `acosf(x)` returns NaN for x outside $[-1, +1]$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.2 __device__ float acoshf (float x)

Calculate the nonnegative arc hyperbolic cosine of the input argument x (measured in radians).

Returns:

Result will be in the interval $[0, +\infty]$.

- `acoshf(1)` returns 0.
- `acoshf(x)` returns NaN for x in the interval $[-\infty, 1)$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.3 __device__ float asinf (float x)

Calculate the principal value of the arc sine of the input argument x .

Returns:

Result will be in the interval $[-\pi/2, +\pi/2]$ for x inside $[-1, +1]$.

- `asinf(0)` returns +0.
- `asinf(x)` returns NaN for x outside $[-1, +1]$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.4 __device__ float asinhf (float x)

Calculate the arc hyperbolic sine of the input argument x (measured in radians).

Returns:

- `asinhf(0)` returns 1.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.5 __device__ float atan2f (float x, float y)

Calculate the principal value of the arc tangent of the ratio of first and second input arguments x / y . The quadrant of the result is determined by the signs of inputs x and y .

Returns:

Result will be in radians, in the interval $[-\pi, +\pi]$.

- `atan2f(0, 1)` returns +0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.6 `__device__ float atanhf (float x)`

Calculate the principal value of the arc tangent of the input argument x .

Returns:

Result will be in radians, in the interval $[-\pi/2, +\pi/2]$.

- `atanhf(0)` returns $+0$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.7 `__device__ float atanhf (float x)`

Calculate the arc hyperbolic tangent of the input argument x (measured in radians).

Returns:

- `atanhf(± 0)` returns ± 0 .
- `atanhf(± 1)` returns $\pm \infty$.
- `atanhf(x)` returns NaN for x outside interval $[-1, 1]$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.8 `__device__ float cbrtf (float x)`

Calculate the cube root of x , $x^{1/3}$.

Returns:

Returns $x^{1/3}$.

- `cbrtf(± 0)` returns ± 0 .
- `cbrtf($\pm \infty$)` returns $\pm \infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.9 `__device__ float ceilf (float x)`

Compute the smallest integer value not less than x .

Returns:

Returns $\lceil x \rceil$ expressed as a floating-point number.

- `ceilf(± 0)` returns ± 0 .
- `ceilf($\pm \infty$)` returns $\pm \infty$.

4.56.2.10 `__device__ float copysignf (float x, float y)`

Create a floating-point value with the magnitude x and the sign of y .

Returns:

Returns a value with the magnitude of x and the sign of y .

4.56.2.11 `__device__ float cosf (float x)`

Calculate the cosine of the input argument x (measured in radians).

Returns:

- `cosf(0)` returns 1.
- `cosf($\pm\infty$)` returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1. This function is affected by the `-use_fast_math` compiler flag. See the CUDA C Programming Guide, Appendix C, Table C-3 for a complete list of functions affected.

4.56.2.12 `__device__ float coshf (float x)`

Calculate the hyperbolic cosine of the input argument x (measured in radians).

Returns:

- `coshf(0)` returns 1.
- `coshf($\pm\infty$)` returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.13 `__device__ float cospif (float x)`

Calculate the cosine of $x \times \pi$ (measured in radians), where x is the input argument.

Returns:

- `cospif(± 0)` returns 1.
- `cospif($\pm\infty$)` returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.14 `__device__ float erfcf (float x)`

Calculate the complementary error function of the input argument x , $1 - \text{erf}(x)$.

Returns:

- $\text{erfcf}(-\infty)$ returns 2.
- $\text{erfcf}(+\infty)$ returns +0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.15 `__device__ float erfcinvf (float y)`

Calculate the inverse complementary error function of the input argument y , for y in the interval $[0, 2]$. The inverse complementary error function find the value x that satisfies the equation $y = \text{erfc}(x)$, for $0 \leq y \leq 2$, and $-\infty \leq x \leq \infty$.

Returns:

- $\text{erfcinvf}(0)$ returns ∞ .
- $\text{erfcinvf}(2)$ returns $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.16 `__device__ float erfcxf (float x)`

Calculate the scaled complementary error function of the input argument x , $e^{x^2} \cdot \text{erfc}(x)$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.17 `__device__ float erff (float x)`

Calculate the value of the error function for the input argument x , $\frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt$.

Returns:

- $\text{erff}(\pm 0)$ returns ± 0 .
- $\text{erff}(\pm \infty)$ returns ± 1 .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.18 `__device__ float erfinvf (float y)`

Calculate the inverse error function of the input argument y , for y in the interval $[-1, 1]$. The inverse error function finds the value x that satisfies the equation $y = \text{erf}(x)$, for $-1 \leq y \leq 1$, and $-\infty \leq x \leq \infty$.

Returns:

- `erfinvf(1)` returns ∞ .
- `erfinvf(-1)` returns $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.19 `__device__ float exp10f (float x)`

Calculate the base 10 exponential of the input argument x .

Returns:

Returns 10^x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1. This function is affected by the `-use_fast_math` compiler flag. See the CUDA C Programming Guide, Appendix C, Table C-3 for a complete list of functions affected.

4.56.2.20 `__device__ float exp2f (float x)`

Calculate the base 2 exponential of the input argument x .

Returns:

Returns 2^x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.21 `__device__ float expf (float x)`

Calculate the base e exponential of the input argument x , e^x .

Returns:

Returns e^x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1. This function is affected by the `-use_fast_math` compiler flag. See the CUDA C Programming Guide, Appendix C, Table C-3 for a complete list of functions affected.

4.56.2.22 __device__ float expm1f (float x)

Calculate the base e exponential of the input argument x , minus 1.

Returns:

Returns $e^x - 1$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.23 __device__ float fabsf (float x)

Calculate the absolute value of the input argument x .

Returns:

Returns the absolute value of its argument.

- $\text{fabs}(\pm\infty)$ returns $+\infty$.
- $\text{fabs}(\pm 0)$ returns 0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.24 __device__ float fdimf (float x, float y)

Compute the positive difference between x and y . The positive difference is $x - y$ when $x > y$ and $+0$ otherwise.

Returns:

Returns the positive difference between x and y .

- $\text{fdimf}(x, y)$ returns $x - y$ if $x > y$.
- $\text{fdimf}(x, y)$ returns $+0$ if $x \leq y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.25 __device__ float fdividef (float x, float y)

Compute x divided by y . If `-use_fast_math` is specified, use `__fdividef()` for higher performance, otherwise use normal division.

Returns:

Returns x / y .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1. This function is affected by the `-use_fast_math` compiler flag. See the CUDA C Programming Guide, Appendix C, Table C-3 for a complete list of functions affected.

4.56.2.26 `__device__ float floorf (float x)`

Calculate the largest integer value which is less than or equal to x .

Returns:

Returns $\lfloor x \rfloor$ expressed as a floating-point number.

- `floorf($\pm\infty$)` returns $\pm\infty$.
- `floorf(± 0)` returns ± 0 .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.27 `__device__ float fmaf (float x, float y, float z)`

Compute the value of $x \times y + z$ as a single ternary operation. After computing the value to infinite precision, the value is rounded once.

Returns:

Returns the rounded value of $x \times y + z$ as a single operation.

- `fmaf($\pm\infty$, ± 0 , z)` returns NaN.
- `fmaf(± 0 , $\pm\infty$, z)` returns NaN.
- `fmaf(x , y , $-\infty$)` returns NaN if $x \times y$ is an exact $+\infty$.
- `fmaf(x , y , $+\infty$)` returns NaN if $x \times y$ is an exact $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.28 `__device__ float fmaxf (float x, float y)`

Determines the maximum numeric value of the arguments x and y . Treats NaN arguments as missing data. If one argument is a NaN and the other is legitimate numeric value, the numeric value is chosen.

Returns:

Returns the maximum numeric values of the arguments x and y .

- If both arguments are NaN, returns NaN.
- If one argument is NaN, returns the numeric argument.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.29 `__device__ float fminf (float x, float y)`

Determines the minimum numeric value of the arguments x and y . Treats NaN arguments as missing data. If one argument is a NaN and the other is legitimate numeric value, the numeric value is chosen.

Returns:

Returns the minimum numeric values of the arguments x and y .

- If both arguments are NaN, returns NaN.
- If one argument is NaN, returns the numeric argument.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.30 `__device__ float fmodf (float x, float y)`

Calculate the floating-point remainder of x / y . The absolute value of the computed value is always less than y 's absolute value and will have the same sign as x .

Returns:

- Returns the floating point remainder of x / y .
- `fmodf(± 0 , y)` returns ± 0 if y is not zero.
- `fmodf(x , y)` returns NaN and raised an invalid floating point exception if x is ∞ or y is zero.
- `fmodf(x , y)` returns zero if y is zero or the result would overflow.
- `fmodf(x , $\pm\infty$)` returns x if x is finite.
- `fmodf(x , 0)` returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.31 `__device__ float frexpf (float x, int * nptr)`

Decomposes the floating-point value x into a component m for the normalized fraction element and another term n for the exponent. The absolute value of m will be greater than or equal to 0.5 and less than 1.0 or it will be equal to 0; $x = m \cdot 2^n$. The integer exponent n will be stored in the location to which `nptr` points.

Returns:

Returns the fractional component m .

- `frexp(0, nptr)` returns 0 for the fractional component and zero for the integer component.
- `frexp(± 0 , nptr)` returns ± 0 and stores zero in the location pointed to by `nptr`.
- `frexp($\pm\infty$, nptr)` returns $\pm\infty$ and stores an unspecified value in the location to which `nptr` points.
- `frexp(NaN, y)` returns a NaN and stores an unspecified value in the location to which `nptr` points.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.32 __device__ float hypotf (float x, float y)

Calculates the length of the hypotenuse of a right triangle whose two sides have lengths x and y without undue overflow or underflow.

Returns:

Returns the length of the hypotenuse $\sqrt{x^2 + y^2}$. If the correct value would overflow, returns ∞ . If the correct value would underflow, returns 0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.33 __device__ int ilogbf (float x)

Calculates the unbiased integer exponent of the input argument x .

Returns:

- If successful, returns the unbiased exponent of the argument.
- `ilogbf(0)` returns `INT_MIN`.
- `ilogbf(NaN)` returns `NaN`.
- `ilogbf(x)` returns `INT_MAX` if x is ∞ or the correct value is greater than `INT_MAX`.
- `ilogbf(x)` return `INT_MIN` if the correct value is less than `INT_MIN`.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.34 __device__ int isfinite (float a)

Determine whether the floating-point value a is a finite value (zero, subnormal, or normal and not infinity or NaN).

Returns:

Returns a nonzero value if and only if a is a finite value.

4.56.2.35 __device__ int isinf (float a)

Determine whether the floating-point value a is an infinite value (positive or negative).

Returns:

Returns a nonzero value if and only if a is a infinite value.

4.56.2.36 __device__ int isnan (float a)

Determine whether the floating-point value a is a NaN.

Returns:

Returns a nonzero value if and only if a is a NaN value.

4.56.2.37 `__device__ float j0f (float x)`

Calculate the value of the Bessel function of the first kind of order 0 for the input argument x , $J_0(x)$.

Returns:

Returns the value of the Bessel function of the first kind of order 0.

- $j0f(\pm\infty)$ returns +0.
- $j0f(\text{NaN})$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.38 `__device__ float j1f (float x)`

Calculate the value of the Bessel function of the first kind of order 1 for the input argument x , $J_1(x)$.

Returns:

Returns the value of the Bessel function of the first kind of order 1.

- $j1f(\pm 0)$ returns ± 0 .
- $j1f(\pm\infty)$ returns +0.
- $j1f(\text{NaN})$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.39 `__device__ float jnf (int n, float x)`

Calculate the value of the Bessel function of the first kind of order n for the input argument x , $J_n(x)$.

Returns:

Returns the value of the Bessel function of the first kind of order n .

- $jnf(n, \text{NaN})$ returns NaN.
- $jnf(n, x)$ returns NaN for $n < 0$.
- $jnf(n, +\infty)$ returns +0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.40 `__device__ float ldexpf (float x, int exp)`

Calculate the value of $x \cdot 2^{\text{exp}}$ of the input arguments x and exp .

Returns:

- $ldexpf(x)$ returns $\pm\infty$ if the correctly calculated value is outside the single floating point range.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.41 __device__ float lgammaf (float x)

Calculate the natural logarithm of the gamma function of the input argument x , namely the value of $\log_e |\int_0^\infty e^{-t} t^{x-1} dt|$.

Returns:

- `lgammaf(1)` returns $+0$.
- `lgammaf(2)` returns $+0$.
- `lgammaf(x)` returns $\pm\infty$ if the correctly calculated value is outside the single floating point range.
- `lgammaf(x)` returns $+\infty$ if $x \leq 0$.
- `lgammaf(-∞)` returns $-\infty$.
- `lgammaf(+∞)` returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.42 __device__ long long int llrintf (float x)

Round x to the nearest integer value, with halfway cases rounded towards zero. If the result is outside the range of the return type, the result is undefined.

Returns:

Returns rounded integer value.

4.56.2.43 __device__ long long int llroundf (float x)

Round x to the nearest integer value, with halfway cases rounded away from zero. If the result is outside the range of the return type, the result is undefined.

Returns:

Returns rounded integer value.

Note:

This function may be slower than alternate rounding methods. See [llrintf\(\)](#).

4.56.2.44 __device__ float log10f (float x)

Calculate the base 10 logarithm of the input argument x .

Returns:

- `log10f(±0)` returns $-\infty$.

- $\log_{10}f(1)$ returns $+0$.
- $\log_{10}f(x)$ returns NaN for $x < 0$.
- $\log_{10}f(+\infty)$ returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.45 __device__ float log1pf (float x)

Calculate the value of $\log_e(1 + x)$ of the input argument x .

Returns:

- $\log_{10}pf(\pm 0)$ returns $-\infty$.
- $\log_{10}pf(-1)$ returns $+0$.
- $\log_{10}pf(x)$ returns NaN for $x < -1$.
- $\log_{10}pf(+\infty)$ returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.46 __device__ float log2f (float x)

Calculate the base 2 logarithm of the input argument x .

Returns:

- $\log_{20}f(\pm 0)$ returns $-\infty$.
- $\log_{20}f(1)$ returns $+0$.
- $\log_{20}f(x)$ returns NaN for $x < 0$.
- $\log_{20}f(+\infty)$ returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.47 __device__ float logbf (float x)

Calculate the floating point representation of the exponent of the input argument x .

Returns:

- $\log_{b0}f(\pm 0)$ returns $-\infty$
- $\log_{b0}f(\pm \infty)$ returns $+\infty$

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.48 `__device__ float logf (float x)`

Calculate the natural logarithm of the input argument x .

Returns:

- $\text{logf}(\pm 0)$ returns $-\infty$.
- $\text{logf}(1)$ returns $+0$.
- $\text{logf}(x)$ returns NaN for $x < 0$.
- $\text{logf}(+\infty)$ returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.49 `__device__ long int lrintf (float x)`

Round x to the nearest integer value, with halfway cases rounded towards zero. If the result is outside the range of the return type, the result is undefined.

Returns:

Returns rounded integer value.

4.56.2.50 `__device__ long int lroundf (float x)`

Round x to the nearest integer value, with halfway cases rounded away from zero. If the result is outside the range of the return type, the result is undefined.

Returns:

Returns rounded integer value.

Note:

This function may be slower than alternate rounding methods. See [lrintf\(\)](#).

4.56.2.51 `__device__ float modff (float x, float * iptr)`

Break down the argument x into fractional and integral parts. The integral part is stored in the argument `iptr`. Fractional and integral parts are given the same sign as the argument x .

Returns:

- $\text{modff}(\pm x, \text{iptr})$ returns a result with the same sign as x .
- $\text{modff}(\pm\infty, \text{iptr})$ returns ± 0 and stores $\pm\infty$ in the object pointed to by `iptr`.
- $\text{modff}(\text{NaN}, \text{iptr})$ stores a NaN in the object pointed to by `iptr` and returns a NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.52 `__device__ float nanf (const char * tagp)`

Return a representation of a quiet NaN. Argument `tagp` selects one of the possible representations.

Returns:

- `nanf(tagp)` returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.53 `__device__ float nearbyintf (float x)`

Round argument `x` to an integer value in single precision floating-point format.

Returns:

- `nearbyintf(± 0)` returns ± 0 .
- `nearbyintf($\pm \infty$)` returns $\pm \infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.54 `__device__ float nextafterf (float x, float y)`

Calculate the next representable single-precision floating-point value following `x` in the direction of `y`. For example, if `y` is greater than `x`, `nextafterf()` returns the smallest representable number greater than `x`.

Returns:

- `nextafterf($\pm \infty$, y)` returns $\pm \infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.55 `__device__ float powf (float x, float y)`

Calculate the value of `x` to the power of `y`.

Returns:

- `powf(± 0 , y)` returns $\pm \infty$ for `y` an integer less than 0.
- `powf(± 0 , y)` returns ± 0 for `y` an odd integer greater than 0.
- `powf(± 0 , y)` returns +0 for `y` > 0 and not an odd integer.
- `powf(-1, $\pm \infty$)` returns 1.
- `powf(+1, y)` returns 1 for any `y`, even a NaN.
- `powf(x, ± 0)` returns 1 for any `x`, even a NaN.

- `powf(x, y)` returns a NaN for finite $x < 0$ and finite non-integer y .
- `powf(x, -∞)` returns $+\infty$ for $|x| < 1$.
- `powf(x, -∞)` returns $+0$ for $|x| > 1$.
- `powf(x, +∞)` returns $+0$ for $|x| < 1$.
- `powf(x, +∞)` returns $+\infty$ for $|x| > 1$.
- `powf(-∞, y)` returns -0 for y an odd integer less than 0.
- `powf(-∞, y)` returns $+0$ for $y < 0$ and not an odd integer.
- `powf(-∞, y)` returns $-\infty$ for y an odd integer greater than 0.
- `powf(-∞, y)` returns $+\infty$ for $y > 0$ and not an odd integer.
- `powf(+∞, y)` returns $+0$ for $y < 0$.
- `powf(+∞, y)` returns $+\infty$ for $y > 0$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.56 __device__ float rcbrtf (float x)

Calculate reciprocal cube root function of x

Returns:

- `rcbrt(±0)` returns $\pm\infty$.
- `rcbrt(±∞)` returns ± 0 .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.57 __device__ float remainderf (float x, float y)

Compute single-precision floating-point remainder r of dividing x by y for nonzero y . Thus $r = x - ny$. The value n is the integer value nearest $\frac{x}{y}$. In the case when $|n - \frac{x}{y}| = \frac{1}{2}$, the even n value is chosen.

Returns:

- `remainderf(x, 0)` returns NaN.
- `remainderf(±∞, y)` returns NaN.
- `remainderf(x, ±∞)` returns x for finite x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.58 `__device__ float remquof (float x, float y, int * quo)`

Compute a double-precision floating-point remainder in the same way as the [remainderf\(\)](#) function. Argument `quo` returns part of quotient upon division of x by y . Value `quo` has the same sign as $\frac{x}{y}$ and may not be the exact quotient but agrees with the exact quotient in the low order 3 bits.

Returns:

Returns the remainder.

- `remquof(x, 0, quo)` returns NaN.
- `remquof($\pm\infty$, y, quo)` returns NaN.
- `remquof(x, $\pm\infty$, quo)` returns x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.59 `__device__ float rintf (float x)`

Round x to the nearest integer value in floating-point format, with halfway cases rounded towards zero.

Returns:

Returns rounded integer value.

4.56.2.60 `__device__ float roundf (float x)`

Round x to the nearest integer value in floating-point format, with halfway cases rounded away from zero.

Returns:

Returns rounded integer value.

Note:

This function may be slower than alternate rounding methods. See [rintf\(\)](#).

4.56.2.61 `__device__ float rsqrtf (float x)`

Calculate the reciprocal of the nonnegative square root of x , $1/\sqrt{x}$.

Returns:

Returns $1/\sqrt{x}$.

- `rsqrtf(+ ∞)` returns +0.
- `rsqrtf(± 0)` returns $\pm\infty$.
- `rsqrtf(x)` returns NaN if x is less than 0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.62 `__device__ float scalblnf (float x, long int n)`

Scale x by 2^n by efficient manipulation of the floating-point exponent.

Returns:

Returns $x * 2^n$.

- `scalblnf(± 0 , n)` returns ± 0 .
- `scalblnf(x, 0)` returns *x*.
- `scalblnf($\pm\infty$, n)` returns $\pm\infty$.

4.56.2.63 `__device__ float scalbnf (float x, int n)`

Scale x by 2^n by efficient manipulation of the floating-point exponent.

Returns:

Returns $x * 2^n$.

- `scalbnf(± 0 , n)` returns ± 0 .
- `scalbnf(x, 0)` returns *x*.
- `scalbnf($\pm\infty$, n)` returns $\pm\infty$.

4.56.2.64 `__device__ int signbit (float a)`

Determine whether the floating-point value *a* is negative.

Returns:

Returns a nonzero value if and only if *a* is negative. Reports the sign bit of all values including infinities, zeros, and NaNs.

4.56.2.65 `__device__ void sincosf (float x, float * sptr, float * cptr)`

Calculate the sine and cosine of the first input argument *x* (measured in radians). The results for sine and cosine are written into the second argument, *sptr*, and, respectively, third argument, *cptr*.

Returns:

- none

See also:

[sinf\(\)](#) and [cosf\(\)](#).

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1. This function is affected by the `-use_fast_math` compiler flag. See the CUDA C Programming Guide, Appendix C, Table C-3 for a complete list of functions affected.

4.56.2.66 `__device__ float sinf (float x)`

Calculate the sine of the input argument x (measured in radians).

Returns:

- $\text{sinf}(\pm 0)$ returns ± 0 .
- $\text{sinf}(\pm \infty)$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1. This function is affected by the `-use_fast_math` compiler flag. See the CUDA C Programming Guide, Appendix C, Table C-3 for a complete list of functions affected.

4.56.2.67 `__device__ float sinhf (float x)`

Calculate the hyperbolic sine of the input argument x (measured in radians).

Returns:

- $\text{sinhf}(\pm 0)$ returns ± 0 .
- $\text{sinhf}(\pm \infty)$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.68 `__device__ float sinpif (float x)`

Calculate the sine of $x \times \pi$ (measured in radians), where x is the input argument.

Returns:

- $\text{sinpif}(\pm 0)$ returns ± 0 .
- $\text{sinpif}(\pm \infty)$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.69 `__device__ float sqrtf (float x)`

Calculate the nonnegative square root of x , \sqrt{x} .

Returns:

Returns \sqrt{x} .

- $\text{sqrtf}(\pm 0)$ returns ± 0 .
- $\text{sqrtf}(+\infty)$ returns $+\infty$.
- $\text{sqrtf}(x)$ returns NaN if x is less than 0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.70 `__device__ float tanf (float x)`

Calculate the tangent of the input argument x (measured in radians).

Returns:

- $\text{tanf}(\pm 0)$ returns ± 0 .
- $\text{tanf}(\pm \infty)$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1. This function is affected by the `-use_fast_math` compiler flag. See the CUDA C Programming Guide, Appendix C, Table C-3 for a complete list of functions affected.

4.56.2.71 `__device__ float tanhf (float x)`

Calculate the hyperbolic tangent of the input argument x (measured in radians).

Returns:

- $\text{tanhf}(\pm 0)$ returns ± 0 .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.72 `__device__ float tgammaf (float x)`

Calculate the gamma function of the input argument x , namely the value of $\int_0^\infty e^{-t} t^{x-1} dt$.

Returns:

- $\text{tgammaf}(\pm 0)$ returns $\pm \infty$.
- $\text{tgammaf}(2)$ returns $+0$.
- $\text{tgammaf}(x)$ returns $\pm \infty$ if the correctly calculated value is outside the single floating point range.
- $\text{tgammaf}(x)$ returns NaN if $x < 0$.
- $\text{tgammaf}(-\infty)$ returns NaN.
- $\text{tgammaf}(+\infty)$ returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.73 `__device__ float truncf (float x)`

Round x to the nearest integer value that does not exceed x in magnitude.

Returns:

Returns truncated integer value.

4.56.2.74 `__device__ float y0f(float x)`

Calculate the value of the Bessel function of the second kind of order 0 for the input argument x , $Y_0(x)$.

Returns:

Returns the value of the Bessel function of the second kind of order 0.

- `y0f(0)` returns $-\infty$.
- `y0f(x)` returns NaN for $x < 0$.
- `y0f(+\infty)` returns $+0$.
- `y0f(NaN)` returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.75 `__device__ float y1f(float x)`

Calculate the value of the Bessel function of the second kind of order 1 for the input argument x , $Y_1(x)$.

Returns:

Returns the value of the Bessel function of the second kind of order 1.

- `y1f(0)` returns $-\infty$.
- `y1f(x)` returns NaN for $x < 0$.
- `y1f(+\infty)` returns $+0$.
- `y1f(NaN)` returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.56.2.76 `__device__ float ynf(int n, float x)`

Calculate the value of the Bessel function of the second kind of order n for the input argument x , $Y_n(x)$.

Returns:

Returns the value of the Bessel function of the second kind of order n .

- `ynf(n, x)` returns NaN for $n < 0$.
- `ynf(n, 0)` returns $-\infty$.
- `ynf(n, x)` returns NaN for $x < 0$.
- `ynf(n, +\infty)` returns $+0$.
- `ynf(n, NaN)` returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.57 Double Precision Mathematical Functions

Functions

- `__device__ double acos (double x)`
Calculate the arc cosine of the input argument.
- `__device__ double acosh (double x)`
Calculate the nonnegative arc hyperbolic cosine of the input argument.
- `__device__ double asin (double x)`
Calculate the arc sine of the input argument.
- `__device__ double asinh (double x)`
Calculate the arc hyperbolic sine of the input argument.
- `__device__ double atan (double x)`
Calculate the arc tangent of the input argument.
- `__device__ double atan2 (double x, double y)`
Calculate the arc tangent of the ratio of first and second input arguments.
- `__device__ double atanh (double x)`
Calculate the arc hyperbolic tangent of the input argument.
- `__device__ double cbrt (double x)`
Calculate the cube root of the input argument.
- `__device__ double ceil (double x)`
Calculate ceiling of the input argument.
- `__device__ double copysign (double x, double y)`
Create value with given magnitude, copying sign of second value.
- `__device__ double cos (double x)`
Calculate the cosine of the input argument.
- `__device__ double cosh (double x)`
Calculate the hyperbolic cosine of the input argument.
- `__device__ double cospi (double x)`
Calculate the cosine of the input argument $\times \pi$.
- `__device__ double erf (double x)`
Calculate the error function of the input argument.
- `__device__ double erfc (double x)`
Calculate the complementary error function of the input argument.
- `__device__ double erfcinv (double y)`

Calculate the inverse complementary error function of the input argument.

- `__device__ double erfcx (double x)`

Calculate the scaled complementary error function of the input argument.

- `__device__ double erfinv (double y)`

Calculate the inverse error function of the input argument.

- `__device__ double exp (double x)`

Calculate the base e exponential of the input argument.

- `__device__ double exp10 (double x)`

Calculate the base 10 exponential of the input argument.

- `__device__ double exp2 (double x)`

Calculate the base 2 exponential of the input argument.

- `__device__ double expm1 (double x)`

Calculate the base e exponential of the input argument, minus 1.

- `__device__ double fabs (double x)`

Calculate the absolute value of the input argument.

- `__device__ double fdim (double x, double y)`

Compute the positive difference between x and y .

- `__device__ double floor (double x)`

Calculate the largest integer less than or equal to x .

- `__device__ double fma (double x, double y, double z)`

Compute $x \times y + z$ as a single operation.

- `__device__ double fmax (double, double)`

Determine the maximum numeric value of the arguments.

- `__device__ double fmin (double x, double y)`

Determine the minimum numeric value of the arguments.

- `__device__ double fmod (double x, double y)`

Calculate the floating-point remainder of x / y .

- `__device__ double frexp (double x, int *nptr)`

Extract mantissa and exponent of a floating-point value.

- `__device__ double hypot (double x, double y)`

Calculate the square root of the sum of squares of two arguments.

- `__device__ int ilogb (double x)`

Compute the unbiased integer exponent of the argument.

- `__device__ int isfinite` (double a)
Determine whether argument is finite.
- `__device__ int isinf` (double a)
Determine whether argument is infinite.
- `__device__ int isnan` (double a)
Determine whether argument is a NaN.
- `__device__ double j0` (double x)
Calculate the value of the Bessel function of the first kind of order 0 for the input argument.
- `__device__ double j1` (double x)
Calculate the value of the Bessel function of the first kind of order 1 for the input argument.
- `__device__ double jn` (int n, double x)
Calculate the value of the Bessel function of the first kind of order n for the input argument.
- `__device__ double ldexp` (double x, int exp)
Calculate the value of $x \cdot 2^{exp}$.
- `__device__ double lgamma` (double x)
Calculate the natural logarithm of the gamma function of the input argument.
- `__device__ long long int llrint` (double x)
Round input to nearest integer value.
- `__device__ long long int llround` (double x)
Round to nearest integer value.
- `__device__ double log` (double x)
Calculate the base e logarithm of the input argument.
- `__device__ double log10` (double x)
Calculate the base 10 logarithm of the input argument.
- `__device__ double log1p` (double x)
Calculate the value of $\log_e(1 + x)$.
- `__device__ double log2` (double x)
Calculate the base 2 logarithm of the input argument.
- `__device__ double logb` (double x)
Calculate the floating point representation of the exponent of the input argument.
- `__device__ long int lrint` (double x)
Round input to nearest integer value.
- `__device__ long int lround` (double x)
Round to nearest integer value.

- `__device__ double modf (double x, double *iptr)`
Break down the input argument into fractional and integral parts.
- `__device__ double nan (const char *tagp)`
Returns "Not a Number" value.
- `__device__ double nearbyint (double x)`
Round the input argument to the nearest integer.
- `__device__ double nextafter (double x, double y)`
Return next representable double-precision floating-point value after argument.
- `__device__ double pow (double x, double y)`
Calculate the value of first argument to the power of second argument.
- `__device__ double rcbrt (double x)`
Calculate reciprocal cube root function.
- `__device__ double remainder (double x, double y)`
Compute double-precision floating-point remainder.
- `__device__ double remquo (double x, double y, int *quo)`
Compute double-precision floating-point remainder and part of quotient.
- `__device__ double rint (double x)`
Round to nearest integer value in floating-point.
- `__device__ double round (double x)`
Round to nearest integer value in floating-point.
- `__device__ double rsqrt (double x)`
Calculate the reciprocal of the square root of the input argument.
- `__device__ double scalbln (double x, long int n)`
Scale floating-point input by integer power of two.
- `__device__ double scalbn (double x, int n)`
Scale floating-point input by integer power of two.
- `__device__ int signbit (double a)`
Return the sign bit of the input.
- `__device__ double sin (double x)`
Calculate the sine of the input argument.
- `__device__ void sincos (double x, double *sptr, double *cptr)`
Calculate the sine and cosine of the first input argument.
- `__device__ double sinh (double x)`

Calculate the hyperbolic sine of the input argument.

- `__device__ double sinpi (double x)`

Calculate the sine of the input argument $\times \pi$.

- `__device__ double sqrt (double x)`

Calculate the square root of the input argument.

- `__device__ double tan (double x)`

Calculate the tangent of the input argument.

- `__device__ double tanh (double x)`

Calculate the hyperbolic tangent of the input argument.

- `__device__ double tgamma (double x)`

Calculate the gamma function of the input argument.

- `__device__ double trunc (double x)`

Truncate input argument to the integral part.

- `__device__ double y0 (double x)`

Calculate the value of the Bessel function of the second kind of order 0 for the input argument.

- `__device__ double y1 (double x)`

Calculate the value of the Bessel function of the second kind of order 1 for the input argument.

- `__device__ double yn (int n, double x)`

Calculate the value of the Bessel function of the second kind of order n for the input argument.

4.57.1 Detailed Description

This section describes double precision mathematical functions.

4.57.2 Function Documentation

4.57.2.1 `__device__ double acos (double x)`

Calculate the principal value of the arc cosine of the input argument x .

Returns:

Result will be in the interval $[0, \pi]$ for x inside $[-1, +1]$.

- `acos(1)` returns $+0$.
- `acos(x)` returns NaN for x outside $[-1, +1]$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.2 `__device__ double acosh (double x)`

Calculate the nonnegative arc hyperbolic cosine of the input argument x (measured in radians).

Returns:

Result will be in the interval $[0, +\infty]$.

- `acosh(1)` returns 0.
- `acosh(x)` returns NaN for x in the interval $[-\infty, 1)$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.3 `__device__ double asin (double x)`

Calculate the principal value of the arc sine of the input argument x .

Returns:

Result will be in the interval $[-\pi/2, +\pi/2]$ for x inside $[-1, +1]$.

- `asin(0)` returns +0.
- `asin(x)` returns NaN for x outside $[-1, +1]$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.4 `__device__ double asinh (double x)`

Calculate the arc hyperbolic sine of the input argument x (measured in radians).

Returns:

- `asinh(0)` returns 0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.5 `__device__ double atan (double x)`

Calculate the principal value of the arc tangent of the input argument x .

Returns:

Result will be in radians, in the interval $[-\pi/2, +\pi/2]$.

- `atan(0)` returns +0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.6 __device__ double atan2 (double x, double y)

Calculate the principal value of the arc tangent of the ratio of first and second input arguments x / y . The quadrant of the result is determined by the signs of inputs x and y .

Returns:

Result will be in radians, in the interval $[-\pi/, +\pi]$.

- `atan2(0, 1)` returns `+0`.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.7 __device__ double atanh (double x)

Calculate the arc hyperbolic tangent of the input argument x (measured in radians).

Returns:

- `atanh(± 0)` returns ± 0 .
- `atanh(± 1)` returns $\pm \infty$.
- `atanh(x)` returns NaN for x outside interval $[-1, 1]$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.8 __device__ double cbrt (double x)

Calculate the cube root of x , $x^{1/3}$.

Returns:

Returns $x^{1/3}$.

- `cbrt(± 0)` returns ± 0 .
- `cbrt($\pm \infty$)` returns $\pm \infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.9 __device__ double ceil (double x)

Compute the smallest integer value not less than x .

Returns:

Returns $\lceil x \rceil$ expressed as a floating-point number.

- `ceil(± 0)` returns ± 0 .
- `ceil($\pm \infty$)` returns $\pm \infty$.

4.57.2.10 __device__ double copysign (double x, double y)

Create a floating-point value with the magnitude x and the sign of y .

Returns:

Returns a value with the magnitude of x and the sign of y .

4.57.2.11 __device__ double cos (double x)

Calculate the cosine of the input argument x (measured in radians).

Returns:

- $\cos(\pm 0)$ returns 1.
- $\cos(\pm \infty)$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.12 __device__ double cosh (double x)

Calculate the hyperbolic cosine of the input argument x (measured in radians).

Returns:

- $\cosh(0)$ returns 1.
- $\cosh(\pm \infty)$ returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.13 __device__ double cospi (double x)

Calculate the cosine of $x \times \pi$ (measured in radians), where x is the input argument.

Returns:

- $\cospi(\pm 0)$ returns 1.
- $\cospi(\pm \infty)$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.14 `__device__ double erf (double x)`

Calculate the value of the error function for the input argument x , $\frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt$.

Returns:

- $\text{erf}(\pm 0)$ returns ± 0 .
- $\text{erf}(\pm \infty)$ returns ± 1 .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.15 `__device__ double erfc (double x)`

Calculate the complementary error function of the input argument x , $1 - \text{erf}(x)$.

Returns:

- $\text{erfc}(-\infty)$ returns 2.
- $\text{erfc}(+\infty)$ returns +0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.16 `__device__ double erfcinv (double y)`

Calculate the inverse complementary error function of the input argument y , for y in the interval $[0, 2]$. The inverse complementary error function find the value x that satisfies the equation $y = \text{erfc}(x)$, for $0 \leq y \leq 2$, and $-\infty \leq x \leq \infty$.

Returns:

- $\text{erfcinv}(0)$ returns ∞ .
- $\text{erfcinv}(2)$ returns $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.17 `__device__ double erfcx (double x)`

Calculate the scaled complementary error function of the input argument x , $e^{x^2} \cdot \text{erfc}(x)$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.18 __device__ double erfinv (double y)

Calculate the inverse error function of the input argument y , for y in the interval $[-1, 1]$. The inverse error function finds the value x that satisfies the equation $y = \text{erf}(x)$, for $-1 \leq y \leq 1$, and $-\infty \leq x \leq \infty$.

Returns:

- $\text{erfinv}(1)$ returns ∞ .
- $\text{erfinv}(-1)$ returns $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.19 __device__ double exp (double x)

Calculate the base e exponential of the input argument x .

Returns:

Returns e^x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.20 __device__ double exp10 (double x)

Calculate the base 10 exponential of the input argument x .

Returns:

Returns 10^x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.21 __device__ double exp2 (double x)

Calculate the base 2 exponential of the input argument x .

Returns:

Returns 2^x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.22 __device__ double expm1 (double x)

Calculate the base e exponential of the input argument x , minus 1.

Returns:

Returns $e^x - 1$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.23 __device__ double fabs (double x)

Calculate the absolute value of the input argument x .

Returns:

Returns the absolute value of the input argument.

- $\text{fabs}(\pm\infty)$ returns $+\infty$.
- $\text{fabs}(\pm 0)$ returns 0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.24 __device__ double fdim (double x, double y)

Compute the positive difference between x and y . The positive difference is $x - y$ when $x > y$ and +0 otherwise.

Returns:

Returns the positive difference between x and y .

- $\text{fdim}(x, y)$ returns $x - y$ if $x > y$.
- $\text{fdim}(x, y)$ returns +0 if $x \leq y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.57.2.25 __device__ double floor (double x)

Calculates the largest integer value which is less than or equal to x .

Returns:

Returns $\lfloor x \rfloor$ expressed as a floating-point number.

- $\text{floor}(\pm\infty)$ returns $\pm\infty$.
- $\text{floor}(\pm 0)$ returns ± 0 .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.26 __device__ double fma (double x, double y, double z)

Compute the value of $x \times y + z$ as a single ternary operation. After computing the value to infinite precision, the value is rounded once.

Returns:

Returns the rounded value of $x \times y + z$ as a single operation.

- $\text{fma}(\pm\infty, \pm 0, z)$ returns NaN.
- $\text{fma}(\pm 0, \pm\infty, z)$ returns NaN.
- $\text{fma}(x, y, -\infty)$ returns NaN if $x \times y$ is an exact $+\infty$.
- $\text{fma}(x, y, +\infty)$ returns NaN if $x \times y$ is an exact $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.27 __device__ double fmax (double, double)

Determines the maximum numeric value of the arguments x and y . Treats NaN arguments as missing data. If one argument is a NaN and the other is legitimate numeric value, the numeric value is chosen.

Returns:

Returns the maximum numeric values of the arguments x and y .

- If both arguments are NaN, returns NaN.
- If one argument is NaN, returns the numeric argument.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.28 __device__ double fmin (double x, double y)

Determines the minimum numeric value of the arguments x and y . Treats NaN arguments as missing data. If one argument is a NaN and the other is legitimate numeric value, the numeric value is chosen.

Returns:

Returns the minimum numeric values of the arguments x and y .

- If both arguments are NaN, returns NaN.
- If one argument is NaN, returns the numeric argument.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.29 `__device__ double fmod (double x, double y)`

Calculate the floating-point remainder of x / y . The absolute value of the computed value is always less than y 's absolute value and will have the same sign as x .

Returns:

- Returns the floating point remainder of x / y .
- `fmod(± 0 , y)` returns ± 0 if y is not zero.
- `fmod(x , y)` returns NaN and raised an invalid floating point exception if x is ∞ or y is zero.
- `fmod(x , y)` returns zero if y is zero or the result would overflow.
- `fmod(x , $\pm\infty$)` returns x if x is finite.
- `fmod(x , 0)` returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.30 `__device__ double frexp (double x, int *nptr)`

Decompose the floating-point value x into a component m for the normalized fraction element and another term n for the exponent. The absolute value of m will be greater than or equal to 0.5 and less than 1.0 or it will be equal to 0; $x = m \cdot 2^n$. The integer exponent n will be stored in the location to which `nptr` points.

Returns:

Returns the fractional component m .

- `frexp(0, nptr)` returns 0 for the fractional component and zero for the integer component.
- `frexp(± 0 , nptr)` returns ± 0 and stores zero in the location pointed to by `nptr`.
- `frexp($\pm\infty$, nptr)` returns $\pm\infty$ and stores an unspecified value in the location to which `nptr` points.
- `frexp(NaN, y)` returns a NaN and stores an unspecified value in the location to which `nptr` points.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.31 `__device__ double hypot (double x, double y)`

Calculate the length of the hypotenuse of a right triangle whose two sides have lengths x and y without undue overflow or underflow.

Returns:

Returns the length of the hypotenuse $\sqrt{x^2 + y^2}$. If the correct value would overflow, returns ∞ . If the correct value would underflow, returns 0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.32 __device__ int ilogb (double x)

Calculates the unbiased integer exponent of the input argument x .

Returns:

- If successful, returns the unbiased exponent of the argument.
- `ilogb(0)` returns `INT_MIN`.
- `ilogb(NaN)` returns `NaN`.
- `ilogb(x)` returns `INT_MAX` if x is ∞ or the correct value is greater than `INT_MAX`.
- `ilogb(x)` return `INT_MIN` if the correct value is less than `INT_MIN`.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.33 __device__ int isfinite (double a)

Determine whether the floating-point value a is a finite value (zero, subnormal, or normal and not infinity or NaN).

Returns:

Returns a nonzero value if and only if a is a finite value.

4.57.2.34 __device__ int isinf (double a)

Determine whether the floating-point value a is an infinite value (positive or negative).

Returns:

Returns a nonzero value if and only if a is a infinite value.

4.57.2.35 __device__ int isnan (double a)

Determine whether the floating-point value a is a NaN.

Returns:

Returns a nonzero value if and only if a is a NaN value.

4.57.2.36 __device__ double j0 (double x)

Calculate the value of the Bessel function of the first kind of order 0 for the input argument x , $J_0(x)$.

Returns:

Returns the value of the Bessel function of the first kind of order 0.

- `j0($\pm\infty$)` returns +0.
- `j0(NaN)` returns `NaN`.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.37 __device__ double j1 (double x)

Calculate the value of the Bessel function of the first kind of order 1 for the input argument x , $J_1(x)$.

Returns:

Returns the value of the Bessel function of the first kind of order 1.

- $j1(\pm 0)$ returns ± 0 .
- $j1(\pm \infty)$ returns $+0$.
- $j1(\text{NaN})$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.38 __device__ double jn (int n, double x)

Calculate the value of the Bessel function of the first kind of order n for the input argument x , $J_n(x)$.

Returns:

Returns the value of the Bessel function of the first kind of order n .

- $jn(n, \text{NaN})$ returns NaN.
- $jn(n, x)$ returns NaN for $n < 0$.
- $jn(n, +\infty)$ returns $+0$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.39 __device__ double ldexp (double x, int exp)

Calculate the value of $x \cdot 2^{\text{exp}}$ of the input arguments x and exp .

Returns:

- $\text{ldexp}(x)$ returns $\pm \infty$ if the correctly calculated value is outside the double floating point range.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.40 __device__ double lgamma (double x)

Calculate the natural logarithm of the gamma function of the input argument x , namely the value of $\log_e \left| \int_0^\infty e^{-t} t^{x-1} dt \right|$

Returns:

- $\text{lgamma}(1)$ returns $+0$.

- `lgamma(2)` returns `+0`.
- `lgamma(x)` returns $\pm\infty$ if the correctly calculated value is outside the double floating point range.
- `lgamma(x)` returns $+\infty$ if $x \leq 0$.
- `lgamma($-\infty$)` returns $-\infty$.
- `lgamma($+\infty$)` returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.41 `__device__ long long int llrint (double x)`

Round x to the nearest integer value, with halfway cases rounded towards zero. If the result is outside the range of the return type, the result is undefined.

Returns:

Returns rounded integer value.

4.57.2.42 `__device__ long long int llround (double x)`

Round x to the nearest integer value, with halfway cases rounded away from zero. If the result is outside the range of the return type, the result is undefined.

Returns:

Returns rounded integer value.

Note:

This function may be slower than alternate rounding methods. See [llrint\(\)](#).

4.57.2.43 `__device__ double log (double x)`

Calculate the base e logarithm of the input argument x .

Returns:

- `log(± 0)` returns $-\infty$.
- `log(1)` returns `+0`.
- `log(x)` returns NaN for $x < 0$.
- `log($+\infty$)` returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.44 __device__ double log10 (double x)

Calculate the base 10 logarithm of the input argument x .

Returns:

- $\log_{10}(\pm 0)$ returns $-\infty$.
- $\log_{10}(1)$ returns $+0$.
- $\log_{10}(x)$ returns NaN for $x < 0$.
- $\log_{10}(+\infty)$ returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.45 __device__ double log1p (double x)

Calculate the value of $\log_e(1 + x)$ of the input argument x .

Returns:

- $\log_{1p}(\pm 0)$ returns $-\infty$.
- $\log_{1p}(-1)$ returns $+0$.
- $\log_{1p}(x)$ returns NaN for $x < -1$.
- $\log_{1p}(+\infty)$ returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.46 __device__ double log2 (double x)

Calculate the base 2 logarithm of the input argument x .

Returns:

- $\log_2(\pm 0)$ returns $-\infty$.
- $\log_2(1)$ returns $+0$.
- $\log_2(x)$ returns NaN for $x < 0$.
- $\log_2(+\infty)$ returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.47 __device__ double logb (double x)

Calculate the floating point representation of the exponent of the input argument x .

Returns:

- $\text{logb}(\pm 0)$ returns $-\infty$
- $\text{logb}(\pm \infty)$ returns $+\infty$

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.48 __device__ long int lrint (double x)

Round x to the nearest integer value, with halfway cases rounded towards zero. If the result is outside the range of the return type, the result is undefined.

Returns:

Returns rounded integer value.

4.57.2.49 __device__ long int lround (double x)

Round x to the nearest integer value, with halfway cases rounded away from zero. If the result is outside the range of the return type, the result is undefined.

Returns:

Returns rounded integer value.

Note:

This function may be slower than alternate rounding methods. See [lrint\(\)](#).

4.57.2.50 __device__ double modf (double x, double * iptr)

Break down the argument x into fractional and integral parts. The integral part is stored in the argument `iptr`. Fractional and integral parts are given the same sign as the argument x .

Returns:

- $\text{modf}(\pm x, \text{iptr})$ returns a result with the same sign as x .
- $\text{modf}(\pm \infty, \text{iptr})$ returns ± 0 and stores $\pm \infty$ in the object pointed to by `iptr`.
- $\text{modf}(\text{NaN}, \text{iptr})$ stores a NaN in the object pointed to by `iptr` and returns a NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.51 __device__ double nan (const char * tagp)

Return a representation of a quiet NaN. Argument `tagp` selects one of the possible representations.

Returns:

- `nan(tagp)` returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.52 __device__ double nearbyint (double x)

Round argument `x` to an integer value in double precision floating-point format.

Returns:

- `nearbyint(± 0)` returns ± 0 .
- `nearbyint($\pm \infty$)` returns $\pm \infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.53 __device__ double nextafter (double x, double y)

Calculate the next representable double-precision floating-point value following `x` in the direction of `y`. For example, if `y` is greater than `x`, `nextafter()` returns the smallest representable number greater than `x`.

Returns:

- `nextafter($\pm \infty$, y)` returns $\pm \infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.54 __device__ double pow (double x, double y)

Calculate the value of `x` to the power of `y`.

Returns:

- `pow(± 0 , y)` returns $\pm \infty$ for `y` an integer less than 0.
- `pow(± 0 , y)` returns ± 0 for `y` an odd integer greater than 0.
- `pow(± 0 , y)` returns +0 for `y` > 0 and not an odd integer.
- `pow(-1, $\pm \infty$)` returns 1.
- `pow(+1, y)` returns 1 for any `y`, even a NaN.
- `pow(x, ± 0)` returns 1 for any `x`, even a NaN.

- `pow(x, y)` returns a NaN for finite $x < 0$ and finite non-integer y .
- `pow(x, $-\infty$)` returns $+\infty$ for $|x| < 1$.
- `pow(x, $-\infty$)` returns $+0$ for $|x| > 1$.
- `pow(x, $+\infty$)` returns $+0$ for $|x| < 1$.
- `pow(x, $+\infty$)` returns $+\infty$ for $|x| > 1$.
- `pow($-\infty$, y)` returns -0 for y an odd integer less than 0.
- `pow($-\infty$, y)` returns $+0$ for $y < 0$ and not an odd integer.
- `pow($-\infty$, y)` returns $-\infty$ for y an odd integer greater than 0.
- `pow($-\infty$, y)` returns $+\infty$ for $y > 0$ and not an odd integer.
- `pow($+\infty$, y)` returns $+0$ for $y < 0$.
- `pow($+\infty$, y)` returns $+\infty$ for $y > 0$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.55 __device__ double rcbrt (double x)

Calculate reciprocal cube root function of x

Returns:

- `rcbrt(± 0)` returns $\pm\infty$.
- `rcbrt($\pm\infty$)` returns ± 0 .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.56 __device__ double remainder (double x, double y)

Compute double-precision floating-point remainder r of dividing x by y for nonzero y . Thus $r = x - ny$. The value n is the integer value nearest $\frac{x}{y}$. In the case when $|n - \frac{x}{y}| = \frac{1}{2}$, the even n value is chosen.

Returns:

- `remainder(x, 0)` returns NaN.
- `remainder($\pm\infty$, y)` returns NaN.
- `remainder(x, $\pm\infty$)` returns x for finite x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.57 __device__ double remquo (double x, double y, int * quo)

Compute a double-precision floating-point remainder in the same way as the [remainder\(\)](#) function. Argument `quo` returns part of quotient upon division of x by y . Value `quo` has the same sign as $\frac{x}{y}$ and may not be the exact quotient but agrees with the exact quotient in the low order 3 bits.

Returns:

Returns the remainder.

- `remquo(x, 0, quo)` returns NaN.
- `remquo($\pm\infty$, y, quo)` returns NaN.
- `remquo(x, $\pm\infty$, quo)` returns x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.58 __device__ double rint (double x)

Round x to the nearest integer value in floating-point format, with halfway cases rounded towards zero.

Returns:

Returns rounded integer value.

4.57.2.59 __device__ double round (double x)

Round x to the nearest integer value in floating-point format, with halfway cases rounded away from zero.

Returns:

Returns rounded integer value.

Note:

This function may be slower than alternate rounding methods. See [rint\(\)](#).

4.57.2.60 __device__ double rsqrt (double x)

Calculate the reciprocal of the nonnegative square root of x , $1/\sqrt{x}$.

Returns:

Returns $1/\sqrt{x}$.

- `rsqrt(+ ∞)` returns +0.
- `rsqrt(± 0)` returns $\pm\infty$.
- `rsqrt(x)` returns NaN if x is less than 0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.61 __device__ double scalbln (double x , long int n)

Scale x by 2^n by efficient manipulation of the floating-point exponent.

Returns:

Returns $x * 2^n$.

- `scalbln(± 0 , n)` returns ± 0 .
- `scalbln(x , 0)` returns x .
- `scalbln($\pm\infty$, n)` returns $\pm\infty$.

4.57.2.62 __device__ double scalbn (double x , int n)

Scale x by 2^n by efficient manipulation of the floating-point exponent.

Returns:

Returns $x * 2^n$.

- `scalbn(± 0 , n)` returns ± 0 .
- `scalbn(x , 0)` returns x .
- `scalbn($\pm\infty$, n)` returns $\pm\infty$.

4.57.2.63 __device__ int signbit (double a)

Determine whether the floating-point value a is negative.

Returns:

Returns a nonzero value if and only if a is negative. Reports the sign bit of all values including infinities, zeros, and NaNs.

4.57.2.64 __device__ double sin (double x)

Calculate the sine of the input argument x (measured in radians).

Returns:

- `sin(± 0)` returns ± 0 .
- `sin($\pm\infty$)` returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.65 `__device__ void sincos (double x, double * sptr, double * cptr)`

Calculate the sine and cosine of the first input argument x (measured in radians). The results for sine and cosine are written into the second argument, *sptr*, and, respectively, third argument, *cptr*.

Returns:

- none

See also:

[sin\(\)](#) and [cos\(\)](#).

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.66 `__device__ double sinh (double x)`

Calculate the hyperbolic sine of the input argument x (measured in radians).

Returns:

- $\sinh(\pm 0)$ returns ± 0 .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.67 `__device__ double sinpi (double x)`

Calculate the sine of $x \times \pi$ (measured in radians), where x is the input argument.

Returns:

- $\sinpi(\pm 0)$ returns ± 0 .
- $\sinpi(\pm \infty)$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.68 `__device__ double sqrt (double x)`

Calculate the nonnegative square root of x , \sqrt{x} .

Returns:

Returns \sqrt{x} .

- $\text{sqrt}(\pm 0)$ returns ± 0 .
- $\text{sqrt}(+\infty)$ returns $+\infty$.
- $\text{sqrt}(x)$ returns NaN if x is less than 0.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.69 __device__ double tan (double x)

Calculate the tangent of the input argument x (measured in radians).

Returns:

- $\tan(\pm 0)$ returns ± 0 .
- $\tan(\pm \infty)$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.70 __device__ double tanh (double x)

Calculate the hyperbolic tangent of the input argument x (measured in radians).

Returns:

- $\tanh(\pm 0)$ returns ± 0 .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.71 __device__ double tgamma (double x)

Calculate the gamma function of the input argument x , namely the value of $\int_0^\infty e^{-t} t^{x-1} dt$.

Returns:

- $\text{tgamma}(\pm 0)$ returns $\pm \infty$.
- $\text{tgamma}(2)$ returns $+0$.
- $\text{tgamma}(x)$ returns $\pm \infty$ if the correctly calculated value is outside the double floating point range.
- $\text{tgamma}(x)$ returns NaN if $x < 0$.
- $\text{tgamma}(-\infty)$ returns NaN.
- $\text{tgamma}(+\infty)$ returns $+\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.72 __device__ double trunc (double x)

Round x to the nearest integer value that does not exceed x in magnitude.

Returns:

Returns truncated integer value.

4.57.2.73 `__device__ double y0 (double x)`

Calculate the value of the Bessel function of the second kind of order 0 for the input argument x , $Y_0(x)$.

Returns:

Returns the value of the Bessel function of the second kind of order 0.

- $y0(0)$ returns $-\infty$.
- $y0(x)$ returns NaN for $x < 0$.
- $y0(+\infty)$ returns $+0$.
- $y0(\text{NaN})$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.74 `__device__ double y1 (double x)`

Calculate the value of the Bessel function of the second kind of order 1 for the input argument x , $Y_1(x)$.

Returns:

Returns the value of the Bessel function of the second kind of order 1.

- $y1(0)$ returns $-\infty$.
- $y1(x)$ returns NaN for $x < 0$.
- $y1(+\infty)$ returns $+0$.
- $y1(\text{NaN})$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.57.2.75 `__device__ double yn (int n, double x)`

Calculate the value of the Bessel function of the second kind of order n for the input argument x , $Y_n(x)$.

Returns:

Returns the value of the Bessel function of the second kind of order n .

- $yn(n, x)$ returns NaN for $n < 0$.
- $yn(n, 0)$ returns $-\infty$.
- $yn(n, x)$ returns NaN for $x < 0$.
- $yn(n, +\infty)$ returns $+0$.
- $yn(n, \text{NaN})$ returns NaN.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.58 Single Precision Ininsics

Functions

- `__device__ float __cosf (float x)`
Calculate the fast approximate cosine of the input argument.
- `__device__ float __exp10f (float x)`
Calculate the fast approximate base 10 exponential of the input argument.
- `__device__ float __expf (float x)`
Calculate the fast approximate base e exponential of the input argument.
- `__device__ float __fadd_rd (float x, float y)`
Add two floating point values in round-down mode.
- `__device__ float __fadd_rn (float x, float y)`
Add two floating point values in round-to-nearest-even mode.
- `__device__ float __fadd_ru (float x, float y)`
Add two floating point values in round-up mode.
- `__device__ float __fadd_rz (float x, float y)`
Add two floating point values in round-towards-zero mode.
- `__device__ float __fdiv_rd (float x, float y)`
Divide two floating point values in round-down mode.
- `__device__ float __fdiv_rn (float x, float y)`
Divide two floating point values in round-to-nearest-even mode.
- `__device__ float __fdiv_ru (float x, float y)`
Divide two floating point values in round-up mode.
- `__device__ float __fdiv_rz (float x, float y)`
Divide two floating point values in round-towards-zero mode.
- `__device__ float __fdividef (float x, float y)`
Calculate the fast approximate division of the input arguments.
- `__device__ float __fmaf_rd (float x, float y, float z)`
Compute $x \times y + z$ as a single operation, in round-down mode.
- `__device__ float __fmaf_rn (float x, float y, float z)`
Compute $x \times y + z$ as a single operation, in round-to-nearest-even mode.
- `__device__ float __fmaf_ru (float x, float y, float z)`
Compute $x \times y + z$ as a single operation, in round-up mode.
- `__device__ float __fmaf_rz (float x, float y, float z)`

Compute $x \times y + z$ as a single operation, in round-towards-zero mode.

- `__device__ float __fmul_rd (float x, float y)`
Multiply two floating point values in round-down mode.
- `__device__ float __fmul_rn (float x, float y)`
Multiply two floating point values in round-to-nearest-even mode.
- `__device__ float __fmul_ru (float x, float y)`
Multiply two floating point values in round-up mode.
- `__device__ float __fmul_rz (float x, float y)`
Multiply two floating point values in round-towards-zero mode.
- `__device__ float __frcp_rd (float x)`
Compute $\frac{1}{x}$ in round-down mode.
- `__device__ float __frcp_rn (float x)`
Compute $\frac{1}{x}$ in round-to-nearest-even mode.
- `__device__ float __frcp_ru (float x)`
Compute $\frac{1}{x}$ in round-up mode.
- `__device__ float __frcp_rz (float x)`
Compute $\frac{1}{x}$ in round-towards-zero mode.
- `__device__ float __fsqrt_rd (float x)`
Compute \sqrt{x} in round-down mode.
- `__device__ float __fsqrt_rn (float x)`
Compute \sqrt{x} in round-to-nearest-even mode.
- `__device__ float __fsqrt_ru (float x)`
Compute \sqrt{x} in round-up mode.
- `__device__ float __fsqrt_rz (float x)`
Compute \sqrt{x} in round-towards-zero mode.
- `__device__ float __log10f (float x)`
Calculate the fast approximate base 10 logarithm of the input argument.
- `__device__ float __log2f (float x)`
Calculate the fast approximate base 2 logarithm of the input argument.
- `__device__ float __logf (float x)`
Calculate the fast approximate base e logarithm of the input argument.
- `__device__ float __powf (float x, float y)`
Calculate the fast approximate of x^y .

- `__device__ float __saturatef (float x)`
Clamp the input argument to $[+0.0, 1.0]$.
- `__device__ void __sincosf (float x, float *sptr, float *cptr)`
Calculate the fast approximate of sine and cosine of the first input argument.
- `__device__ float __sinf (float x)`
Calculate the fast approximate sine of the input argument.
- `__device__ float __tanf (float x)`
Calculate the fast approximate tangent of the input argument.

4.58.1 Detailed Description

This section describes single precision intrinsic functions that are only supported in device code.

4.58.2 Function Documentation

4.58.2.1 `__device__ float __cosf (float x)`

Calculate the fast approximate cosine of the input argument x , measured in radians.

Returns:

Returns the approximate cosine of x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-4. Input and output in the denormal range is flushed to sign preserving 0.0.

4.58.2.2 `__device__ float __exp10f (float x)`

Calculate the fast approximate base 10 exponential of the input argument x , 10^x .

Returns:

Returns an approximation to 10^x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-4. Most input and output values around denormal range are flushed to sign preserving 0.0.

4.58.2.3 `__device__ float __expf (float x)`

Calculate the fast approximate base e exponential of the input argument x , e^x .

Returns:

Returns an approximation to e^x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-4. Most input and output values around denormal range are flushed to sign preserving 0.0.

4.58.2.4 __device__ float __fadd_rd (float x, float y)

Compute the sum of x and y in round-down (to negative infinity) mode.

Returns:

Returns $x + y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1. This operation will never be merged into a single multiply-add instruction.

4.58.2.5 __device__ float __fadd_rn (float x, float y)

Compute the sum of x and y in round-to-nearest-even rounding mode.

Returns:

Returns $x + y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1. This operation will never be merged into a single multiply-add instruction.

4.58.2.6 __device__ float __fadd_ru (float x, float y)

Compute the sum of x and y in round-up (to positive infinity) mode.

Returns:

Returns $x + y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1. This operation will never be merged into a single multiply-add instruction.

4.58.2.7 `__device__ float __fadd_rz (float x, float y)`

Compute the sum of x and y in round-towards-zero mode.

Returns:

Returns $x + y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.
This operation will never be merged into a single multiply-add instruction.

4.58.2.8 `__device__ float __fdiv_rd (float x, float y)`

Divide two floating point values x by y in round-down (to negative infinity) mode.

Returns:

Returns x / y .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.9 `__device__ float __fdiv_rn (float x, float y)`

Divide two floating point values x by y in round-to-nearest-even mode.

Returns:

Returns x / y .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.10 `__device__ float __fdiv_ru (float x, float y)`

Divide two floating point values x by y in round-up (to positive infinity) mode.

Returns:

Returns x / y .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.11 `__device__ float __fdiv_rz(float x, float y)`

Divide two floating point values x by y in round-towards-zero mode.

Returns:

Returns x / y .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.12 `__device__ float __fdivdef(float x, float y)`

Calculate the fast approximate division of x by y .

Returns:

Returns x / y .

- `__fdivdef(∞ , y)` returns NaN for $2^{126} < y < 2^{128}$.
- `__fdivdef(x , y)` returns 0 for $2^{126} < y < 2^{128}$ and $x \neq \infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-4.

4.58.2.13 `__device__ float __fmaf_rd(float x, float y, float z)`

Computes the value of $x \times y + z$ as a single ternary operation, rounding the result once in round-down (to negative infinity) mode.

Returns:

Returns the rounded value of $x \times y + z$ as a single operation.

- `fmaf($\pm\infty$, ± 0 , z)` returns NaN.
- `fmaf(± 0 , $\pm\infty$, z)` returns NaN.
- `fmaf(x , y , $-\infty$)` returns NaN if $x \times y$ is an exact $+\infty$.
- `fmaf(x , y , $+\infty$)` returns NaN if $x \times y$ is an exact $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.14 `__device__ float __fmaf_rn(float x, float y, float z)`

Computes the value of $x \times y + z$ as a single ternary operation, rounding the result once in round-to-nearest-even mode.

Returns:

Returns the rounded value of $x \times y + z$ as a single operation.

- `fmaf($\pm\infty$, ± 0 , z)` returns NaN.
- `fmaf(± 0 , $\pm\infty$, z)` returns NaN.
- `fmaf(x , y , $-\infty$)` returns NaN if $x \times y$ is an exact $+\infty$.
- `fmaf(x , y , $+\infty$)` returns NaN if $x \times y$ is an exact $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.15 `__device__ float __fmaf_ru (float x, float y, float z)`

Computes the value of $x \times y + z$ as a single ternary operation, rounding the result once in round-up (to positive infinity) mode.

Returns:

Returns the rounded value of $x \times y + z$ as a single operation.

- `fmaf($\pm\infty$, ± 0 , z)` returns NaN.
- `fmaf(± 0 , $\pm\infty$, z)` returns NaN.
- `fmaf(x , y , $-\infty$)` returns NaN if $x \times y$ is an exact $+\infty$.
- `fmaf(x , y , $+\infty$)` returns NaN if $x \times y$ is an exact $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.16 `__device__ float __fmaf_rz (float x, float y, float z)`

Computes the value of $x \times y + z$ as a single ternary operation, rounding the result once in round-towards-zero mode.

Returns:

Returns the rounded value of $x \times y + z$ as a single operation.

- `fmaf($\pm\infty$, ± 0 , z)` returns NaN.
- `fmaf(± 0 , $\pm\infty$, z)` returns NaN.
- `fmaf(x , y , $-\infty$)` returns NaN if $x \times y$ is an exact $+\infty$.
- `fmaf(x , y , $+\infty$)` returns NaN if $x \times y$ is an exact $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.17 `__device__ float __fmul_rd (float x, float y)`

Compute the product of x and y in round-down (to negative infinity) mode.

Returns:

Returns $x * y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.
This operation will never be merged into a single multiply-add instruction.

4.58.2.18 `__device__ float __fmul_rn (float x, float y)`

Compute the product of x and y in round-to-nearest-even mode.

Returns:

Returns $x * y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.
This operation will never be merged into a single multiply-add instruction.

4.58.2.19 `__device__ float __fmul_ru (float x, float y)`

Compute the product of x and y in round-up (to positive infinity) mode.

Returns:

Returns $x * y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.
This operation will never be merged into a single multiply-add instruction.

4.58.2.20 `__device__ float __fmul_rz (float x, float y)`

Compute the product of x and y in round-towards-zero mode.

Returns:

Returns $x * y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.
This operation will never be merged into a single multiply-add instruction.

4.58.2.21 `__device__ float __frec_rd (float x)`

Compute the reciprocal of x in round-down (to negative infinity) mode.

Returns:

Returns $\frac{1}{x}$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.22 __device__ float __frcp_rn (float x)

Compute the reciprocal of x in round-to-nearest-even mode.

Returns:

Returns $\frac{1}{x}$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.23 __device__ float __frcp_ru (float x)

Compute the reciprocal of x in round-up (to positive infinity) mode.

Returns:

Returns $\frac{1}{x}$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.24 __device__ float __frcp_rz (float x)

Compute the reciprocal of x in round-towards-zero mode.

Returns:

Returns $\frac{1}{x}$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.25 __device__ float __fsqrt_rd (float x)

Compute the square root of x in round-down (to negative infinity) mode.

Returns:

Returns \sqrt{x} .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.26 `__device__ float __fsqrt_rn (float x)`

Compute the square root of x in round-to-nearest-even mode.

Returns:

Returns \sqrt{x} .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.27 `__device__ float __fsqrt_ru (float x)`

Compute the square root of x in round-up (to positive infinity) mode.

Returns:

Returns \sqrt{x} .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.28 `__device__ float __fsqrt_rz (float x)`

Compute the square root of x in round-towards-zero mode.

Returns:

Returns \sqrt{x} .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-1.

4.58.2.29 `__device__ float __log10f (float x)`

Calculate the fast approximate base 10 logarithm of the input argument x .

Returns:

Returns an approximation to $\log_{10}(x)$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-4.
Most input and output values around denormal range are flushed to sign preserving 0.0.

4.58.2.30 __device__ float __log2f (float x)

Calculate the fast approximate base 2 logarithm of the input argument x .

Returns:

Returns an approximation to $\log_2(x)$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-4. Input and output in the denormal range is flushed to sign preserving 0.0.

4.58.2.31 __device__ float __logf (float x)

Calculate the fast approximate base e logarithm of the input argument x .

Returns:

Returns an approximation to $\log_e(x)$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-4. Most input and output values around denormal range are flushed to sign preserving 0.0.

4.58.2.32 __device__ float __powf (float x, float y)

Calculate the fast approximate of x , the first input argument, raised to the power of y , the second input argument, x^y .

Returns:

Returns an approximation to x^y .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-4. Most input and output values around denormal range are flushed to sign preserving 0.0.

4.58.2.33 __device__ float __saturatef (float x)

Clamp the input argument x to be within the interval $[+0.0, 1.0]$.

Returns:

- `__saturatef(x)` returns 0 if $x < 0$.
- `__saturatef(x)` returns 1 if $x > 1$.
- `__saturatef(x)` returns x if $0 \leq x \leq 1$.
- `__saturatef(NaN)` returns 0.

4.58.2.34 `__device__ void __sincosf (float x, float * sptr, float * cptr)`

Calculate the fast approximate of sine and cosine of the first input argument x (measured in radians). The results for sine and cosine are written into the second argument, `sptr`, and, respectively, third argument, `cptr`.

Returns:

- none

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-4. Denorm input/output is flushed to sign preserving 0.0.

4.58.2.35 `__device__ float __sinf (float x)`

Calculate the fast approximate sine of the input argument x , measured in radians.

Returns:

Returns the approximate sine of x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-4. Input and output in the denormal range is flushed to sign preserving 0.0.

4.58.2.36 `__device__ float __tanf (float x)`

Calculate the fast approximate tangent of the input argument x , measured in radians.

Returns:

Returns the approximate tangent of x .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-4. The result is computed as the fast divide of `__sinf()` by `__cosf()`. Denormal input and output are flushed to sign-preserving 0.0 at each step of the computation.

4.59 Double Precision Ininsics

Functions

- `__device__ double __dadd_rd (double x, double y)`
Add two floating point values in round-down mode.
- `__device__ double __dadd_rn (double x, double y)`
Add two floating point values in round-to-nearest-even mode.
- `__device__ double __dadd_ru (double x, double y)`
Add two floating point values in round-up mode.
- `__device__ double __dadd_rz (double x, double y)`
Add two floating point values in round-towards-zero mode.
- `__device__ double __ddiv_rd (double x, double y)`
Divide two floating point values in round-down mode.
- `__device__ double __ddiv_rn (double x, double y)`
Divide two floating point values in round-to-nearest-even mode.
- `__device__ double __ddiv_ru (double x, double y)`
Divide two floating point values in round-up mode.
- `__device__ double __ddiv_rz (double x, double y)`
Divide two floating point values in round-towards-zero mode.
- `__device__ double __dmul_rd (double x, double y)`
Multiply two floating point values in round-down mode.
- `__device__ double __dmul_rn (double x, double y)`
Multiply two floating point values in round-to-nearest-even mode.
- `__device__ double __dmul_ru (double x, double y)`
Multiply two floating point values in round-up mode.
- `__device__ double __dmul_rz (double x, double y)`
Multiply two floating point values in round-towards-zero mode.
- `__device__ double __drcp_rd (double x)`
Compute $\frac{1}{x}$ in round-down mode.
- `__device__ double __drcp_rn (double x)`
Compute $\frac{1}{x}$ in round-to-nearest-even mode.
- `__device__ double __drcp_ru (double x)`
Compute $\frac{1}{x}$ in round-up mode.
- `__device__ double __drcp_rz (double x)`

Compute $\frac{1}{x}$ in round-towards-zero mode.

- `__device__ double __dsqrt_rd (double x)`
Compute \sqrt{x} in round-down mode.
- `__device__ double __dsqrt_rn (double x)`
Compute \sqrt{x} in round-to-nearest-even mode.
- `__device__ double __dsqrt_ru (double x)`
Compute \sqrt{x} in round-up mode.
- `__device__ double __dsqrt_rz (double x)`
Compute \sqrt{x} in round-towards-zero mode.
- `__device__ double __fma_rd (double x, double y, double z)`
Compute $x \times y + z$ as a single operation in round-down mode.
- `__device__ double __fma_rn (double x, double y, double z)`
Compute $x \times y + z$ as a single operation in round-to-nearest-even mode.
- `__device__ double __fma_ru (double x, double y, double z)`
Compute $x \times y + z$ as a single operation in round-up mode.
- `__device__ double __fma_rz (double x, double y, double z)`
Compute $x \times y + z$ as a single operation in round-towards-zero mode.

4.59.1 Detailed Description

This section describes double precision intrinsic functions that are only supported in device code.

4.59.2 Function Documentation

4.59.2.1 `__device__ double __dadd_rd (double x, double y)`

Adds two floating point values x and y in round-down (to negative infinity) mode.

Returns:

Returns $x + y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2. This operation will never be merged into a single multiply-add instruction.

4.59.2.2 __device__ double __dadd_rn (double x, double y)

Adds two floating point values x and y in round-to-nearest-even mode.

Returns:

Returns $x + y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
This operation will never be merged into a single multiply-add instruction.

4.59.2.3 __device__ double __dadd_ru (double x, double y)

Adds two floating point values x and y in round-up (to positive infinity) mode.

Returns:

Returns $x + y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
This operation will never be merged into a single multiply-add instruction.

4.59.2.4 __device__ double __dadd_rz (double x, double y)

Adds two floating point values x and y in round-towards-zero mode.

Returns:

Returns $x + y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
This operation will never be merged into a single multiply-add instruction.

4.59.2.5 __device__ double __ddiv_rd (double x, double y)

Divides two floating point values x by y in round-down (to negative infinity) mode.

Returns:

Returns x / y .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.6 `__device__ double __ddiv_rn (double x, double y)`

Divides two floating point values x by y in round-to-nearest-even mode.

Returns:

Returns x / y .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.7 `__device__ double __ddiv_ru (double x, double y)`

Divides two floating point values x by y in round-up (to positive infinity) mode.

Returns:

Returns x / y .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.8 `__device__ double __ddiv_rz (double x, double y)`

Divides two floating point values x by y in round-towards-zero mode.

Returns:

Returns x / y .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.9 `__device__ double __dmul_rd (double x, double y)`

Multiplies two floating point values x and y in round-down (to negative infinity) mode.

Returns:

Returns $x * y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
This operation will never be merged into a single multiply-add instruction.

4.59.2.10 `__device__ double __dmul_rn (double x, double y)`

Multiplies two floating point values x and y in round-to-nearest-even mode.

Returns:

Returns $x * y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
This operation will never be merged into a single multiply-add instruction.

4.59.2.11 `__device__ double __dmul_ru (double x, double y)`

Multiplies two floating point values x and y in round-up (to positive infinity) mode.

Returns:

Returns $x * y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
This operation will never be merged into a single multiply-add instruction.

4.59.2.12 `__device__ double __dmul_rz (double x, double y)`

Multiplies two floating point values x and y in round-towards-zero mode.

Returns:

Returns $x * y$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
This operation will never be merged into a single multiply-add instruction.

4.59.2.13 `__device__ double __drcp_rd (double x)`

Compute the reciprocal of x in round-down (to negative infinity) mode.

Returns:

Returns $\frac{1}{x}$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.14 `__device__ double __drcp_rn (double x)`

Compute the reciprocal of x in round-to-nearest-even mode.

Returns:

Returns $\frac{1}{x}$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.15 `__device__ double __drcp_ru (double x)`

Compute the reciprocal of x in round-up (to positive infinity) mode.

Returns:

Returns $\frac{1}{x}$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.16 `__device__ double __drcp_rz (double x)`

Compute the reciprocal of x in round-towards-zero mode.

Returns:

Returns $\frac{1}{x}$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.17 `__device__ double __dsqrt_rd (double x)`

Compute the square root of x in round-down (to negative infinity) mode.

Returns:

Returns \sqrt{x} .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.18 `__device__ double __dsqrt_rn (double x)`

Compute the square root of x in round-to-nearest-even mode.

Returns:

Returns \sqrt{x} .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.19 `__device__ double __dsqrt_ru (double x)`

Compute the square root of x in round-up (to positive infinity) mode.

Returns:

Returns \sqrt{x} .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.20 `__device__ double __dsqrt_rz (double x)`

Compute the square root of x in round-towards-zero mode.

Returns:

Returns \sqrt{x} .

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.
Requires compute capability ≥ 2.0 .

4.59.2.21 `__device__ double __fma_rd (double x, double y, double z)`

Computes the value of $x \times y + z$ as a single ternary operation, rounding the result once in round-down (to negative infinity) mode.

Returns:

Returns the rounded value of $x \times y + z$ as a single operation.

- `fmaf($\pm\infty$, ± 0 , z)` returns NaN.
- `fmaf(± 0 , $\pm\infty$, z)` returns NaN.
- `fmaf(x , y , $-\infty$)` returns NaN if $x \times y$ is an exact $+\infty$.
- `fmaf(x , y , $+\infty$)` returns NaN if $x \times y$ is an exact $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.59.2.22 `__device__ double __fma_rn (double x, double y, double z)`

Computes the value of $x \times y + z$ as a single ternary operation, rounding the result once in round-to-nearest-even mode.

Returns:

Returns the rounded value of $x \times y + z$ as a single operation.

- `fmaf($\pm\infty$, ± 0 , z)` returns NaN.
- `fmaf(± 0 , $\pm\infty$, z)` returns NaN.
- `fmaf(x , y , $-\infty$)` returns NaN if $x \times y$ is an exact $+\infty$.
- `fmaf(x , y , $+\infty$)` returns NaN if $x \times y$ is an exact $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.59.2.23 `__device__ double __fma_ru (double x, double y, double z)`

Computes the value of $x \times y + z$ as a single ternary operation, rounding the result once in round-up (to positive infinity) mode.

Returns:

Returns the rounded value of $x \times y + z$ as a single operation.

- `fmaf($\pm\infty$, ± 0 , z)` returns NaN.
- `fmaf(± 0 , $\pm\infty$, z)` returns NaN.
- `fmaf(x , y , $-\infty$)` returns NaN if $x \times y$ is an exact $+\infty$.
- `fmaf(x , y , $+\infty$)` returns NaN if $x \times y$ is an exact $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.59.2.24 `__device__ double __fma_rz (double x, double y, double z)`

Computes the value of $x \times y + z$ as a single ternary operation, rounding the result once in round-towards-zero mode.

Returns:

Returns the rounded value of $x \times y + z$ as a single operation.

- `fmaf($\pm\infty$, ± 0 , z)` returns NaN.
- `fmaf(± 0 , $\pm\infty$, z)` returns NaN.
- `fmaf(x , y , $-\infty$)` returns NaN if $x \times y$ is an exact $+\infty$.
- `fmaf(x , y , $+\infty$)` returns NaN if $x \times y$ is an exact $-\infty$.

Note:

For accuracy information for this function see the CUDA C Programming Guide, Appendix C, Table C-2.

4.60 Integer Intrinsics

Functions

- `__device__ unsigned int __brev` (unsigned int x)
Reverse the bit order of a 32 bit unsigned integer.
- `__device__ unsigned long long int __brevll` (unsigned long long int x)
Reverse the bit order of a 64 bit unsigned integer.
- `__device__ unsigned int __byte_perm` (unsigned int x, unsigned int y, unsigned int s)
Return selected bytes from two 32 bit unsigned integers.
- `__device__ int __clz` (int x)
Return the number of consecutive high-order zero bits in a 32 bit integer.
- `__device__ int __clzll` (long long int x)
Count the number of consecutive high-order zero bits in a 64 bit integer.
- `__device__ int __ffs` (int x)
Find the position of the least significant bit set to 1 in a 32 bit integer.
- `__device__ int __ffsll` (long long int x)
Find the position of the least significant bit set to 1 in a 64 bit integer.
- `__device__ int __mul24` (int x, int y)
Calculate the least significant 32 bits of the product of the least significant 24 bits of two integers.
- `__device__ long long int __mul64hi` (long long int x, long long int y)
Calculate the most significant 64 bits of the product of the two 64 bit integers.
- `__device__ int __mulhi` (int x, int y)
Calculate the most significant 32 bits of the product of the two 32 bit integers.
- `__device__ int __popc` (unsigned int x)
Count the number of bits that are set to 1 in a 32 bit integer.
- `__device__ int __popc1l` (unsigned long long int x)
Count the number of bits that are set to 1 in a 64 bit integer.
- `__device__ unsigned int __sad` (int x, int y, unsigned int z)
Calculate $|x - y| + z$, the sum of absolute difference.
- `__device__ unsigned int __umul24` (unsigned int x, unsigned int y)
Calculate the least significant 32 bits of the product of the least significant 24 bits of two unsigned integers.
- `__device__ unsigned long long int __umul64hi` (unsigned long long int x, unsigned long long int y)
Calculate the most significant 64 bits of the product of the two 64 unsigned bit integers.
- `__device__ unsigned int __umulhi` (unsigned int x, unsigned int y)

Calculate the most significant 32 bits of the product of the two 32 bit unsigned integers.

- `__device__ unsigned int __usad (unsigned int x, unsigned int y, unsigned int z)`

Calculate $|x - y| + z$, the sum of absolute difference.

4.60.1 Detailed Description

This section describes integer intrinsic functions that are only supported in device code.

4.60.2 Function Documentation

4.60.2.1 `__device__ unsigned int __brev (unsigned int x)`

Reverses the bit order of the 32 bit unsigned integer `x`.

Returns:

Returns the bit-reversed value of `x`. i.e. bit `N` of the return value corresponds to bit `31-N` of `x`.

4.60.2.2 `__device__ unsigned long long int __brevll (unsigned long long int x)`

Reverses the bit order of the 64 bit unsigned integer `x`.

Returns:

Returns the bit-reversed value of `x`. i.e. bit `N` of the return value corresponds to bit `63-N` of `x`.

4.60.2.3 `__device__ unsigned int __byte_perm (unsigned int x, unsigned int y, unsigned int s)`

`byte_perm(x,y,s)` returns a 32-bit integer consisting of four bytes from eight input bytes provided in the two input integers `x` and `y`, as specified by a selector, `s`.

The input bytes are indexed as follows:

```
input[0] = x<0:7>   input[1] = x<8:15>
input[2] = x<16:23> input[3] = x<24:31>
input[4] = y<0:7>   input[5] = y<8:15>
input[6] = y<16:23> input[7] = y<24:31>
```

The selector indices are stored in 4-bit nibbles (with the upper 16-bits of the selector not being used):

```
selector[0] = s<0:3> selector[1] = s<4:7>
selector[2] = s<8:11> selector[3] = s<12:15>
```

Returns:

The returned value `r` is computed to be: `result[n] := input[selector[n]]` where `result[n]` is the `n`th byte of `r`.

4.60.2.4 __device__ int __clz (int x)

Count the number of consecutive leading zero bits, starting at the most significant bit (bit 31) of x .

Returns:

Returns a value between 0 and 32 inclusive representing the number of zero bits.

4.60.2.5 __device__ int __clzll (long long int x)

Count the number of consecutive leading zero bits, starting at the most significant bit (bit 63) of x .

Returns:

Returns a value between 0 and 64 inclusive representing the number of zero bits.

4.60.2.6 __device__ int __ffs (int x)

Find the position of the first (least significant) bit set to 1 in x , where the least significant bit position is 1.

Returns:

Returns a value between 0 and 32 inclusive representing the position of the first bit set.

- `__ffs(0)` returns 0.

4.60.2.7 __device__ int __ffsll (long long int x)

Find the position of the first (least significant) bit set to 1 in x , where the least significant bit position is 1.

Returns:

Returns a value between 0 and 64 inclusive representing the position of the first bit set.

- `__ffsll(0)` returns 0.

4.60.2.8 __device__ int __mul24 (int x, int y)

Calculate the least significant 32 bits of the product of the least significant 24 bits of x and y . The high order 8 bits of x and y are ignored.

Returns:

Returns the least significant 32 bits of the product $x * y$.

4.60.2.9 __device__ long long int __mul64hi (long long int x, long long int y)

Calculate the most significant 64 bits of the 128-bit product $x * y$, where x and y are 64-bit integers.

Returns:

Returns the most significant 64 bits of the product $x * y$.

4.60.2.10 `__device__ int __mulhi(int x, int y)`

Calculate the most significant 32 bits of the 64-bit product $x * y$, where x and y are 32-bit integers.

Returns:

Returns the most significant 32 bits of the product $x * y$.

4.60.2.11 `__device__ int __popc(unsigned int x)`

Count the number of bits that are set to 1 in x .

Returns:

Returns a value between 0 and 32 inclusive representing the number of set bits.

4.60.2.12 `__device__ int __popcll(unsigned long long int x)`

Count the number of bits that are set to 1 in x .

Returns:

Returns a value between 0 and 64 inclusive representing the number of set bits.

4.60.2.13 `__device__ unsigned int __sad(int x, int y, unsigned int z)`

Calculate $|x - y| + z$, the 32-bit sum of the third argument z plus and the absolute value of the difference between the first argument, x , and second argument, y .

Inputs x and y are signed 32-bit integers, input z is a 32-bit unsigned integer.

Returns:

Returns $|x - y| + z$.

4.60.2.14 `__device__ unsigned int __umul24(unsigned int x, unsigned int y)`

Calculate the least significant 32 bits of the product of the least significant 24 bits of x and y . The high order 8 bits of x and y are ignored.

Returns:

Returns the least significant 32 bits of the product $x * y$.

4.60.2.15 `__device__ unsigned long long int __umul64hi(unsigned long long int x, unsigned long long int y)`

Calculate the most significant 64 bits of the 128-bit product $x * y$, where x and y are 64-bit unsigned integers.

Returns:

Returns the most significant 64 bits of the product $x * y$.

4.60.2.16 `__device__ unsigned int __umulhi (unsigned int x, unsigned int y)`

Calculate the most significant 32 bits of the 64-bit product $x * y$, where x and y are 32-bit unsigned integers.

Returns:

Returns the most significant 32 bits of the product $x * y$.

4.60.2.17 `__device__ unsigned int __usad (unsigned int x, unsigned int y, unsigned int z)`

Calculate $|x - y| + z$, the 32-bit sum of the third argument z plus and the absolute value of the difference between the first argument, x , and second argument, y .

Inputs x , y , and z are unsigned 32-bit integers.

Returns:

Returns $|x - y| + z$.

4.61 Type Casting Ininsics

Functions

- `__device__ float __double2float_rd (double x)`
Convert a double to a float in round-down mode.
- `__device__ float __double2float_rn (double x)`
Convert a double to a float in round-to-nearest-even mode.
- `__device__ float __double2float_ru (double x)`
Convert a double to a float in round-up mode.
- `__device__ float __double2float_rz (double x)`
Convert a double to a float in round-towards-zero mode.
- `__device__ int __double2hiint (double x)`
Reinterpret high 32 bits in a double as a signed integer.
- `__device__ int __double2int_rd (double x)`
Convert a double to a signed int in round-down mode.
- `__device__ int __double2int_rn (double x)`
Convert a double to a signed int in round-to-nearest-even mode.
- `__device__ int __double2int_ru (double x)`
Convert a double to a signed int in round-up mode.
- `__device__ int __double2int_rz (double)`
Convert a double to a signed int in round-towards-zero mode.
- `__device__ long long int __double2ll_rd (double x)`
Convert a double to a signed 64-bit int in round-down mode.
- `__device__ long long int __double2ll_rn (double x)`
Convert a double to a signed 64-bit int in round-to-nearest-even mode.
- `__device__ long long int __double2ll_ru (double x)`
Convert a double to a signed 64-bit int in round-up mode.
- `__device__ long long int __double2ll_rz (double)`
Convert a double to a signed 64-bit int in round-towards-zero mode.
- `__device__ int __double2loint (double x)`
Reinterpret low 32 bits in a double as a signed integer.
- `__device__ unsigned int __double2uint_rd (double x)`
Convert a double to an unsigned int in round-down mode.
- `__device__ unsigned int __double2uint_rn (double x)`

Convert a double to an unsigned int in round-to-nearest-even mode.

- `__device__ unsigned int __double2uint_ru (double x)`
Convert a double to an unsigned int in round-up mode.
- `__device__ unsigned int __double2uint_rz (double)`
Convert a double to an unsigned int in round-towards-zero mode.
- `__device__ unsigned long long int __double2ull_rd (double x)`
Convert a double to an unsigned 64-bit int in round-down mode.
- `__device__ unsigned long long int __double2ull_rn (double x)`
Convert a double to an unsigned 64-bit int in round-to-nearest-even mode.
- `__device__ unsigned long long int __double2ull_ru (double x)`
Convert a double to an unsigned 64-bit int in round-up mode.
- `__device__ unsigned long long int __double2ull_rz (double)`
Convert a double to an unsigned 64-bit int in round-towards-zero mode.
- `__device__ long long int __double_as_longlong (double x)`
Reinterpret bits in a double as a 64-bit signed integer.
- `__device__ unsigned short __float2half_rn (float x)`
Convert a single-precision float to a half-precision float in round-to-nearest-even mode.
- `__device__ int __float2int_rd (float x)`
Convert a float to a signed integer in round-down mode.
- `__device__ int __float2int_rn (float x)`
Convert a float to a signed integer in round-to-nearest-even mode.
- `__device__ int __float2int_ru (float)`
Convert a float to a signed integer in round-up mode.
- `__device__ int __float2int_rz (float x)`
Convert a float to a signed integer in round-towards-zero mode.
- `__device__ long long int __float2ll_rd (float x)`
Convert a float to a signed 64-bit integer in round-down mode.
- `__device__ long long int __float2ll_rn (float x)`
Convert a float to a signed 64-bit integer in round-to-nearest-even mode.
- `__device__ long long int __float2ll_ru (float x)`
Convert a float to a signed 64-bit integer in round-up mode.
- `__device__ long long int __float2ll_rz (float x)`
Convert a float to a signed 64-bit integer in round-towards-zero mode.

- `__device__ unsigned int __float2uint_rd (float x)`
Convert a float to an unsigned integer in round-down mode.
- `__device__ unsigned int __float2uint_rn (float x)`
Convert a float to an unsigned integer in round-to-nearest-even mode.
- `__device__ unsigned int __float2uint_ru (float x)`
Convert a float to an unsigned integer in round-up mode.
- `__device__ unsigned int __float2uint_rz (float x)`
Convert a float to an unsigned integer in round-towards-zero mode.
- `__device__ unsigned long long int __float2ull_rd (float x)`
Convert a float to an unsigned 64-bit integer in round-down mode.
- `__device__ unsigned long long int __float2ull_rn (float x)`
Convert a float to an unsigned 64-bit integer in round-to-nearest-even mode.
- `__device__ unsigned long long int __float2ull_ru (float x)`
Convert a float to an unsigned 64-bit integer in round-up mode.
- `__device__ unsigned long long int __float2ull_rz (float x)`
Convert a float to an unsigned 64-bit integer in round-towards-zero mode.
- `__device__ int __float_as_int (float x)`
Reinterpret bits in a float as a signed integer.
- `__device__ float __half2float (unsigned short x)`
Convert a half-precision float to a single-precision float in round-to-nearest-even mode.
- `__device__ double __hiloInt2double (int hi, int lo)`
Reinterpret high and low 32-bit integer values as a double.
- `__device__ double __int2double_rn (int x)`
Convert a signed int to a double.
- `__device__ float __int2float_rd (int x)`
Convert a signed integer to a float in round-down mode.
- `__device__ float __int2float_rn (int x)`
Convert a signed integer to a float in round-to-nearest-even mode.
- `__device__ float __int2float_ru (int x)`
Convert a signed integer to a float in round-up mode.
- `__device__ float __int2float_rz (int x)`
Convert a signed integer to a float in round-towards-zero mode.
- `__device__ float __int_as_float (int x)`
Reinterpret bits in an integer as a float.

- `__device__ double __ll2double_rd (long long int x)`
Convert a signed 64-bit int to a double in round-down mode.
- `__device__ double __ll2double_rn (long long int x)`
Convert a signed 64-bit int to a double in round-to-nearest-even mode.
- `__device__ double __ll2double_ru (long long int x)`
Convert a signed 64-bit int to a double in round-up mode.
- `__device__ double __ll2double_rz (long long int x)`
Convert a signed 64-bit int to a double in round-towards-zero mode.
- `__device__ float __ll2float_rd (long long int x)`
Convert a signed integer to a float in round-down mode.
- `__device__ float __ll2float_rn (long long int x)`
Convert a signed 64-bit integer to a float in round-to-nearest-even mode.
- `__device__ float __ll2float_ru (long long int x)`
Convert a signed integer to a float in round-up mode.
- `__device__ float __ll2float_rz (long long int x)`
Convert a signed integer to a float in round-towards-zero mode.
- `__device__ double __longlong_as_double (long long int x)`
Reinterpret bits in a 64-bit signed integer as a double.
- `__device__ double __uint2double_rn (unsigned int x)`
Convert an unsigned int to a double.
- `__device__ float __uint2float_rd (unsigned int x)`
Convert an unsigned integer to a float in round-down mode.
- `__device__ float __uint2float_rn (unsigned int x)`
Convert an unsigned integer to a float in round-to-nearest-even mode.
- `__device__ float __uint2float_ru (unsigned int x)`
Convert an unsigned integer to a float in round-up mode.
- `__device__ float __uint2float_rz (unsigned int x)`
Convert an unsigned integer to a float in round-towards-zero mode.
- `__device__ double __ull2double_rd (unsigned long long int x)`
Convert an unsigned 64-bit int to a double in round-down mode.
- `__device__ double __ull2double_rn (unsigned long long int x)`
Convert an unsigned 64-bit int to a double in round-to-nearest-even mode.
- `__device__ double __ull2double_ru (unsigned long long int x)`

Convert an unsigned 64-bit int to a double in round-up mode.

- `__device__ double __ull2double_rz` (unsigned long long int x)

Convert an unsigned 64-bit int to a double in round-towards-zero mode.

- `__device__ float __ull2float_rd` (unsigned long long int x)

Convert an unsigned integer to a float in round-down mode.

- `__device__ float __ull2float_rn` (unsigned long long int x)

Convert an unsigned integer to a float in round-to-nearest-even mode.

- `__device__ float __ull2float_ru` (unsigned long long int x)

Convert an unsigned integer to a float in round-up mode.

- `__device__ float __ull2float_rz` (unsigned long long int x)

Convert an unsigned integer to a float in round-towards-zero mode.

4.61.1 Detailed Description

This section describes type casting intrinsic functions that are only supported in device code.

4.61.2 Function Documentation

4.61.2.1 `__device__ float __double2float_rd` (double x)

Convert the double-precision floating point value x to a single-precision floating point value in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.2 `__device__ float __double2float_rn` (double x)

Convert the double-precision floating point value x to a single-precision floating point value in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.3 `__device__ float __double2float_ru` (double x)

Convert the double-precision floating point value x to a single-precision floating point value in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.4 `__device__ float __double2float_rz (double x)`

Convert the double-precision floating point value x to a single-precision floating point value in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.5 `__device__ int __double2hiint (double x)`

Reinterpret the high 32 bits in the double-precision floating point value x as a signed integer.

Returns:

Returns reinterpreted value.

4.61.2.6 `__device__ int __double2int_rd (double x)`

Convert the double-precision floating point value x to a signed integer value in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.7 `__device__ int __double2int_rn (double x)`

Convert the double-precision floating point value x to a signed integer value in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.8 `__device__ int __double2int_ru (double x)`

Convert the double-precision floating point value x to a signed integer value in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.9 `__device__ int __double2int_rz (double)`

Convert the double-precision floating point value x to a signed integer value in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.10 `__device__ long long int __double2ll_rd (double x)`

Convert the double-precision floating point value x to a signed 64-bit integer value in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.11 `__device__ long long int __double2ll_rn (double x)`

Convert the double-precision floating point value x to a signed 64-bit integer value in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.12 `__device__ long long int __double2ll_ru (double x)`

Convert the double-precision floating point value x to a signed 64-bit integer value in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.13 `__device__ long long int __double2ll_rz (double)`

Convert the double-precision floating point value x to a signed 64-bit integer value in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.14 `__device__ int __double2loint (double x)`

Reinterpret the low 32 bits in the double-precision floating point value x as a signed integer.

Returns:

Returns reinterpreted value.

4.61.2.15 `__device__ unsigned int __double2uint_rd (double x)`

Convert the double-precision floating point value x to an unsigned integer value in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.16 `__device__ unsigned int __double2uint_rn (double x)`

Convert the double-precision floating point value x to an unsigned integer value in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.17 `__device__ unsigned int __double2uint_ru (double x)`

Convert the double-precision floating point value x to an unsigned integer value in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.18 `__device__ unsigned int __double2uint_rz (double)`

Convert the double-precision floating point value x to an unsigned integer value in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.19 `__device__ unsigned long long int __double2ull_rd (double x)`

Convert the double-precision floating point value x to an unsigned 64-bit integer value in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.20 `__device__ unsigned long long int __double2ull_rn (double x)`

Convert the double-precision floating point value x to an unsigned 64-bit integer value in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.21 `__device__ unsigned long long int __double2ull_ru (double x)`

Convert the double-precision floating point value x to an unsigned 64-bit integer value in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.22 `__device__ unsigned long long int __double2ull_rz (double)`

Convert the double-precision floating point value x to an unsigned 64-bit integer value in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.23 `__device__ long long int __double_as_longlong (double x)`

Reinterpret the bits in the double-precision floating point value x as a signed 64-bit integer.

Returns:

Returns reinterpreted value.

4.61.2.24 `__device__ unsigned short __float2half_rn (float x)`

Convert the single-precision float value x to a half-precision floating point value represented in `unsigned short` format, in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.25 `__device__ int __float2int_rd (float x)`

Convert the single-precision floating point value x to a signed integer in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.26 `__device__ int __float2int_rn (float x)`

Convert the single-precision floating point value x to a signed integer in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.27 `__device__ int __float2int_ru (float)`

Convert the single-precision floating point value x to a signed integer in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.28 `__device__ int __float2int_rz (float x)`

Convert the single-precision floating point value x to a signed integer in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.29 `__device__ long long int __float2ll_rd (float x)`

Convert the single-precision floating point value x to a signed 64-bit integer in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.30 `__device__ long long int __float2ll_rn (float x)`

Convert the single-precision floating point value x to a signed 64-bit integer in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.31 `__device__ long long int __float2ll_ru (float x)`

Convert the single-precision floating point value x to a signed 64-bit integer in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.32 `__device__ long long int __float2ll_rz (float x)`

Convert the single-precision floating point value x to a signed 64-bit integer in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.33 `__device__ unsigned int __float2uint_rd (float x)`

Convert the single-precision floating point value x to an unsigned integer in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.34 `__device__ unsigned int __float2uint_rn (float x)`

Convert the single-precision floating point value x to an unsigned integer in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.35 `__device__ unsigned int __float2uint_ru (float x)`

Convert the single-precision floating point value x to an unsigned integer in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.36 `__device__ unsigned int __float2uint_rz (float x)`

Convert the single-precision floating point value x to an unsigned integer in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.37 `__device__ unsigned long long int __float2ull_rd (float x)`

Convert the single-precision floating point value x to an unsigned 64-bit integer in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.38 `__device__ unsigned long long int __float2ull_rn (float x)`

Convert the single-precision floating point value x to an unsigned 64-bit integer in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.39 `__device__ unsigned long long int __float2ull_ru (float x)`

Convert the single-precision floating point value x to an unsigned 64-bit integer in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.40 `__device__ unsigned long long int __float2ull_rz (float x)`

Convert the single-precision floating point value `x` to an unsigned 64-bit integer in round-towards_zero mode.

Returns:

Returns converted value.

4.61.2.41 `__device__ int __float_as_int (float x)`

Reinterpret the bits in the single-precision floating point value `x` as a signed integer.

Returns:

Returns reinterpreted value.

4.61.2.42 `__device__ float __half2float (unsigned short x)`

Convert the half-precision floating point value `x` represented in `unsigned short` format to a single-precision floating point value.

Returns:

Returns converted value.

4.61.2.43 `__device__ double __hiloint2double (int hi, int lo)`

Reinterpret the integer value of `hi` as the high 32 bits of a double-precision floating point value and the integer value of `lo` as the low 32 bits of the same double-precision floating point value.

Returns:

Returns reinterpreted value.

4.61.2.44 `__device__ double __int2double_rn (int x)`

Convert the signed integer value `x` to a double-precision floating point value.

Returns:

Returns converted value.

4.61.2.45 `__device__ float __int2float_rd (int x)`

Convert the signed integer value `x` to a single-precision floating point value in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.46 `__device__ float __int2float_rn (int x)`

Convert the signed integer value x to a single-precision floating point value in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.47 `__device__ float __int2float_ru (int x)`

Convert the signed integer value x to a single-precision floating point value in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.48 `__device__ float __int2float_rz (int x)`

Convert the signed integer value x to a single-precision floating point value in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.49 `__device__ float __int_as_float (int x)`

Reinterpret the bits in the signed integer value x as a single-precision floating point value.

Returns:

Returns reinterpreted value.

4.61.2.50 `__device__ double __ll2double_rd (long long int x)`

Convert the signed 64-bit integer value x to a double-precision floating point value in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.51 `__device__ double __ll2double_rn (long long int x)`

Convert the signed 64-bit integer value x to a double-precision floating point value in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.52 `__device__ double __ll2double_ru (long long int x)`

Convert the signed 64-bit integer value x to a double-precision floating point value in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.53 `__device__ double __ll2double_rz (long long int x)`

Convert the signed 64-bit integer value x to a double-precision floating point value in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.54 `__device__ float __ll2float_rd (long long int x)`

Convert the signed integer value x to a single-precision floating point value in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.55 `__device__ float __ll2float_rn (long long int x)`

Convert the signed 64-bit integer value x to a single-precision floating point value in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.56 `__device__ float __ll2float_ru (long long int x)`

Convert the signed integer value x to a single-precision floating point value in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.57 `__device__ float __ll2float_rz (long long int x)`

Convert the signed integer value x to a single-precision floating point value in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.58 `__device__ double __longlong_as_double (long long int x)`

Reinterpret the bits in the 64-bit signed integer value x as a double-precision floating point value.

Returns:

Returns reinterpreted value.

4.61.2.59 `__device__ double __uint2double_rn (unsigned int x)`

Convert the unsigned integer value x to a double-precision floating point value.

Returns:

Returns converted value.

4.61.2.60 `__device__ float __uint2float_rd (unsigned int x)`

Convert the unsigned integer value x to a single-precision floating point value in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.61 `__device__ float __uint2float_rn (unsigned int x)`

Convert the unsigned integer value x to a single-precision floating point value in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.62 `__device__ float __uint2float_ru (unsigned int x)`

Convert the unsigned integer value x to a single-precision floating point value in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.63 `__device__ float __uint2float_rz (unsigned int x)`

Convert the unsigned integer value x to a single-precision floating point value in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.64 `__device__ double __ull2double_rd (unsigned long long int x)`

Convert the unsigned 64-bit integer value x to a double-precision floating point value in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.65 `__device__ double __ull2double_rn (unsigned long long int x)`

Convert the unsigned 64-bit integer value x to a double-precision floating point value in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.66 `__device__ double __ull2double_ru (unsigned long long int x)`

Convert the unsigned 64-bit integer value x to a double-precision floating point value in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.67 `__device__ double __ull2double_rz (unsigned long long int x)`

Convert the unsigned 64-bit integer value x to a double-precision floating point value in round-towards-zero mode.

Returns:

Returns converted value.

4.61.2.68 `__device__ float __ull2float_rd (unsigned long long int x)`

Convert the unsigned integer value x to a single-precision floating point value in round-down (to negative infinity) mode.

Returns:

Returns converted value.

4.61.2.69 `__device__ float __ull2float_rn (unsigned long long int x)`

Convert the unsigned integer value x to a single-precision floating point value in round-to-nearest-even mode.

Returns:

Returns converted value.

4.61.2.70 `__device__ float __ull2float_ru (unsigned long long int x)`

Convert the unsigned integer value x to a single-precision floating point value in round-up (to positive infinity) mode.

Returns:

Returns converted value.

4.61.2.71 `__device__ float __ull2float_rz (unsigned long long int x)`

Convert the unsigned integer value x to a single-precision floating point value in round-towards-zero mode.

Returns:

Returns converted value.

Chapter 5

Data Structure Documentation

5.1 CUDA_ARRAY3D_DESCRIPTOR_st Struct Reference

Data Fields

- `size_t` [Depth](#)
- `unsigned int` [Flags](#)
- `CUarray_format` [Format](#)
- `size_t` [Height](#)
- `unsigned int` [NumChannels](#)
- `size_t` [Width](#)

5.1.1 Detailed Description

3D array descriptor

5.1.2 Field Documentation

5.1.2.1 `size_t` `CUDA_ARRAY3D_DESCRIPTOR_st::Depth`

Depth of 3D array

5.1.2.2 `unsigned int` `CUDA_ARRAY3D_DESCRIPTOR_st::Flags`

Flags

5.1.2.3 `CUarray_format` `CUDA_ARRAY3D_DESCRIPTOR_st::Format`

Array format

5.1.2.4 `size_t` `CUDA_ARRAY3D_DESCRIPTOR_st::Height`

Height of 3D array

5.1.2.5 unsigned int CUDA_ARRAY3D_DESCRIPTOR_st::NumChannels

Channels per array element

5.1.2.6 size_t CUDA_ARRAY3D_DESCRIPTOR_st::Width

Width of 3D array

5.2 CUDA_ARRAY_DESCRIPTOR_st Struct Reference

Data Fields

- [CUarray_format](#) Format
- [size_t](#) Height
- [unsigned int](#) NumChannels
- [size_t](#) Width

5.2.1 Detailed Description

Array descriptor

5.2.2 Field Documentation

5.2.2.1 [CUarray_format](#) CUDA_ARRAY_DESCRIPTOR_st::Format

Array format

5.2.2.2 [size_t](#) CUDA_ARRAY_DESCRIPTOR_st::Height

Height of array

5.2.2.3 [unsigned int](#) CUDA_ARRAY_DESCRIPTOR_st::NumChannels

Channels per array element

5.2.2.4 [size_t](#) CUDA_ARRAY_DESCRIPTOR_st::Width

Width of array

5.3 CUDA_MEMCPY2D_st Struct Reference

Data Fields

- [CUarray dstArray](#)
- [CUdeviceptr dstDevice](#)
- `void * dstHost`
- [CUMemorytype dstMemoryType](#)
- `size_t dstPitch`
- `size_t dstXInBytes`
- `size_t dstY`
- `size_t Height`
- [CUarray srcArray](#)
- [CUdeviceptr srcDevice](#)
- `const void * srcHost`
- [CUMemorytype srcMemoryType](#)
- `size_t srcPitch`
- `size_t srcXInBytes`
- `size_t srcY`
- `size_t WidthInBytes`

5.3.1 Detailed Description

2D memory copy parameters

5.3.2 Field Documentation

5.3.2.1 CUarray CUDA_MEMCPY2D_st::dstArray

Destination array reference

5.3.2.2 CUdeviceptr CUDA_MEMCPY2D_st::dstDevice

Destination device pointer

5.3.2.3 void* CUDA_MEMCPY2D_st::dstHost

Destination host pointer

5.3.2.4 CUMemorytype CUDA_MEMCPY2D_st::dstMemoryType

Destination memory type (host, device, array)

5.3.2.5 size_t CUDA_MEMCPY2D_st::dstPitch

Destination pitch (ignored when dst is array)

5.3.2.6 size_t CUDA_MEMCPY2D_st::dstXInBytes

Destination X in bytes

5.3.2.7 size_t CUDA_MEMCPY2D_st::dstY

Destination Y

5.3.2.8 size_t CUDA_MEMCPY2D_st::Height

Height of 2D memory copy

5.3.2.9 CUarray CUDA_MEMCPY2D_st::srcArray

Source array reference

5.3.2.10 CUdeviceptr CUDA_MEMCPY2D_st::srcDevice

Source device pointer

5.3.2.11 const void* CUDA_MEMCPY2D_st::srcHost

Source host pointer

5.3.2.12 CUmemorytype CUDA_MEMCPY2D_st::srcMemoryType

Source memory type (host, device, array)

5.3.2.13 size_t CUDA_MEMCPY2D_st::srcPitch

Source pitch (ignored when src is array)

5.3.2.14 size_t CUDA_MEMCPY2D_st::srcXInBytes

Source X in bytes

5.3.2.15 size_t CUDA_MEMCPY2D_st::srcY

Source Y

5.3.2.16 size_t CUDA_MEMCPY2D_st::WidthInBytes

Width of 2D memory copy in bytes

5.4 CUDA_MEMCPY3D_PEER_st Struct Reference

Data Fields

- [size_t Depth](#)
- [CUarray dstArray](#)
- [CUcontext dstContext](#)
- [CUdeviceptr dstDevice](#)
- [size_t dstHeight](#)
- [void * dstHost](#)
- [size_t dstLOD](#)
- [CUmemorytype dstMemoryType](#)
- [size_t dstPitch](#)
- [size_t dstXInBytes](#)
- [size_t dstY](#)
- [size_t dstZ](#)
- [size_t Height](#)
- [CUarray srcArray](#)
- [CUcontext srcContext](#)
- [CUdeviceptr srcDevice](#)
- [size_t srcHeight](#)
- [const void * srcHost](#)
- [size_t srcLOD](#)
- [CUmemorytype srcMemoryType](#)
- [size_t srcPitch](#)
- [size_t srcXInBytes](#)
- [size_t srcY](#)
- [size_t srcZ](#)
- [size_t WidthInBytes](#)

5.4.1 Detailed Description

3D memory cross-context copy parameters

5.4.2 Field Documentation

5.4.2.1 [size_t CUDA_MEMCPY3D_PEER_st::Depth](#)

Depth of 3D memory copy

5.4.2.2 [CUarray CUDA_MEMCPY3D_PEER_st::dstArray](#)

Destination array reference

5.4.2.3 [CUcontext CUDA_MEMCPY3D_PEER_st::dstContext](#)

Destination context (ignored with [dstMemoryType](#) is [CU_MEMORYTYPE_ARRAY](#))

5.4.2.4 CUdeviceptr CUDA_MEMCPY3D_PEER_st::dstDevice

Destination device pointer

5.4.2.5 size_t CUDA_MEMCPY3D_PEER_st::dstHeight

Destination height (ignored when dst is array; may be 0 if Depth==1)

5.4.2.6 void* CUDA_MEMCPY3D_PEER_st::dstHost

Destination host pointer

5.4.2.7 size_t CUDA_MEMCPY3D_PEER_st::dstLOD

Destination LOD

5.4.2.8 CUmemorytype CUDA_MEMCPY3D_PEER_st::dstMemoryType

Destination memory type (host, device, array)

5.4.2.9 size_t CUDA_MEMCPY3D_PEER_st::dstPitch

Destination pitch (ignored when dst is array)

5.4.2.10 size_t CUDA_MEMCPY3D_PEER_st::dstXInBytes

Destination X in bytes

5.4.2.11 size_t CUDA_MEMCPY3D_PEER_st::dstY

Destination Y

5.4.2.12 size_t CUDA_MEMCPY3D_PEER_st::dstZ

Destination Z

5.4.2.13 size_t CUDA_MEMCPY3D_PEER_st::Height

Height of 3D memory copy

5.4.2.14 CUarray CUDA_MEMCPY3D_PEER_st::srcArray

Source array reference

5.4.2.15 CUcontext CUDA_MEMCPY3D_PEER_st::srcContext

Source context (ignored with srcMemoryType is [CU_MEMORYTYPE_ARRAY](#))

5.4.2.16 CUdeviceptr CUDA_MEMCPY3D_PEER_st::srcDevice

Source device pointer

5.4.2.17 size_t CUDA_MEMCPY3D_PEER_st::srcHeight

Source height (ignored when src is array; may be 0 if Depth==1)

5.4.2.18 const void* CUDA_MEMCPY3D_PEER_st::srcHost

Source host pointer

5.4.2.19 size_t CUDA_MEMCPY3D_PEER_st::srcLOD

Source LOD

5.4.2.20 CUMemorytype CUDA_MEMCPY3D_PEER_st::srcMemoryType

Source memory type (host, device, array)

5.4.2.21 size_t CUDA_MEMCPY3D_PEER_st::srcPitch

Source pitch (ignored when src is array)

5.4.2.22 size_t CUDA_MEMCPY3D_PEER_st::srcXInBytes

Source X in bytes

5.4.2.23 size_t CUDA_MEMCPY3D_PEER_st::srcY

Source Y

5.4.2.24 size_t CUDA_MEMCPY3D_PEER_st::srcZ

Source Z

5.4.2.25 size_t CUDA_MEMCPY3D_PEER_st::WidthInBytes

Width of 3D memory copy in bytes

5.5 CUDA_MEMCPY3D_st Struct Reference

Data Fields

- `size_t` [Depth](#)
- `CUarray` [dstArray](#)
- `CUdeviceptr` [dstDevice](#)
- `size_t` [dstHeight](#)
- `void *` [dstHost](#)
- `size_t` [dstLOD](#)
- `CUMemorytype` [dstMemoryType](#)
- `size_t` [dstPitch](#)
- `size_t` [dstXInBytes](#)
- `size_t` [dstY](#)
- `size_t` [dstZ](#)
- `size_t` [Height](#)
- `void *` [reserved0](#)
- `void *` [reserved1](#)
- `CUarray` [srcArray](#)
- `CUdeviceptr` [srcDevice](#)
- `size_t` [srcHeight](#)
- `const void *` [srcHost](#)
- `size_t` [srcLOD](#)
- `CUMemorytype` [srcMemoryType](#)
- `size_t` [srcPitch](#)
- `size_t` [srcXInBytes](#)
- `size_t` [srcY](#)
- `size_t` [srcZ](#)
- `size_t` [WidthInBytes](#)

5.5.1 Detailed Description

3D memory copy parameters

5.5.2 Field Documentation

5.5.2.1 `size_t` `CUDA_MEMCPY3D_st::Depth`

Depth of 3D memory copy

5.5.2.2 `CUarray` `CUDA_MEMCPY3D_st::dstArray`

Destination array reference

5.5.2.3 `CUdeviceptr` `CUDA_MEMCPY3D_st::dstDevice`

Destination device pointer

5.5.2.4 size_t CUDA_MEMCPY3D_st::dstHeight

Destination height (ignored when dst is array; may be 0 if Depth==1)

5.5.2.5 void* CUDA_MEMCPY3D_st::dstHost

Destination host pointer

5.5.2.6 size_t CUDA_MEMCPY3D_st::dstLOD

Destination LOD

5.5.2.7 CUMemoryType CUDA_MEMCPY3D_st::dstMemoryType

Destination memory type (host, device, array)

5.5.2.8 size_t CUDA_MEMCPY3D_st::dstPitch

Destination pitch (ignored when dst is array)

5.5.2.9 size_t CUDA_MEMCPY3D_st::dstXInBytes

Destination X in bytes

5.5.2.10 size_t CUDA_MEMCPY3D_st::dstY

Destination Y

5.5.2.11 size_t CUDA_MEMCPY3D_st::dstZ

Destination Z

5.5.2.12 size_t CUDA_MEMCPY3D_st::Height

Height of 3D memory copy

5.5.2.13 void* CUDA_MEMCPY3D_st::reserved0

Must be NULL

5.5.2.14 void* CUDA_MEMCPY3D_st::reserved1

Must be NULL

5.5.2.15 CUarray CUDA_MEMCPY3D_st::srcArray

Source array reference

5.5.2.16 CUdeviceptr CUDA_MEMCPY3D_st::srcDevice

Source device pointer

5.5.2.17 size_t CUDA_MEMCPY3D_st::srcHeight

Source height (ignored when src is array; may be 0 if Depth==1)

5.5.2.18 const void* CUDA_MEMCPY3D_st::srcHost

Source host pointer

5.5.2.19 size_t CUDA_MEMCPY3D_st::srcLOD

Source LOD

5.5.2.20 CUMemorytype CUDA_MEMCPY3D_st::srcMemoryType

Source memory type (host, device, array)

5.5.2.21 size_t CUDA_MEMCPY3D_st::srcPitch

Source pitch (ignored when src is array)

5.5.2.22 size_t CUDA_MEMCPY3D_st::srcXInBytes

Source X in bytes

5.5.2.23 size_t CUDA_MEMCPY3D_st::srcY

Source Y

5.5.2.24 size_t CUDA_MEMCPY3D_st::srcZ

Source Z

5.5.2.25 size_t CUDA_MEMCPY3D_st::WidthInBytes

Width of 3D memory copy in bytes

5.6 cudaChannelFormatDesc Struct Reference

Data Fields

- enum [cudaChannelFormatKind](#) `f`
- int `w`
- int `x`
- int `y`
- int `z`

5.6.1 Detailed Description

CUDA Channel format descriptor

5.6.2 Field Documentation

5.6.2.1 enum `cudaChannelFormatKind` `cudaChannelFormatDesc::f`

Channel format kind

5.6.2.2 int `cudaChannelFormatDesc::w`

w

5.6.2.3 int `cudaChannelFormatDesc::x`

x

5.6.2.4 int `cudaChannelFormatDesc::y`

y

5.6.2.5 int `cudaChannelFormatDesc::z`

z

5.7 cudaDeviceProp Struct Reference

Data Fields

- int [asyncEngineCount](#)
- int [canMapHostMemory](#)
- int [clockRate](#)
- int [computeMode](#)
- int [concurrentKernels](#)
- int [deviceOverlap](#)
- int [ECCEnabled](#)
- int [integrated](#)
- int [kernelExecTimeoutEnabled](#)
- int [l2CacheSize](#)
- int [major](#)
- int [maxGridSize](#) [3]
- int [maxSurface1D](#)
- int [maxSurface1DLayered](#) [2]
- int [maxSurface2D](#) [2]
- int [maxSurface2DLayered](#) [3]
- int [maxSurface3D](#) [3]
- int [maxSurfaceCubemap](#)
- int [maxSurfaceCubemapLayered](#) [2]
- int [maxTexture1D](#)
- int [maxTexture1DLayered](#) [2]
- int [maxTexture1DLinear](#)
- int [maxTexture2D](#) [2]
- int [maxTexture2DGather](#) [2]
- int [maxTexture2DLayered](#) [3]
- int [maxTexture2DLinear](#) [3]
- int [maxTexture3D](#) [3]
- int [maxTextureCubemap](#)
- int [maxTextureCubemapLayered](#) [2]
- int [maxThreadsDim](#) [3]
- int [maxThreadsPerBlock](#)
- int [maxThreadsPerMultiProcessor](#)
- int [memoryBusWidth](#)
- int [memoryClockRate](#)
- size_t [memPitch](#)
- int [minor](#)
- int [multiProcessorCount](#)
- char [name](#) [256]
- int [pciBusID](#)
- int [pciDeviceID](#)
- int [pciDomainID](#)
- int [regsPerBlock](#)
- size_t [sharedMemPerBlock](#)
- size_t [surfaceAlignment](#)
- int [tccDriver](#)
- size_t [textureAlignment](#)

- `size_t` [texturePitchAlignment](#)
- `size_t` [totalConstMem](#)
- `size_t` [totalGlobalMem](#)
- `int` [unifiedAddressing](#)
- `int` [warpSize](#)

5.7.1 Detailed Description

CUDA device properties

5.7.2 Field Documentation

5.7.2.1 `int cudaDeviceProp::asyncEngineCount`

Number of asynchronous engines

5.7.2.2 `int cudaDeviceProp::canMapHostMemory`

Device can map host memory with `cudaHostAlloc/cudaHostGetDevicePointer`

5.7.2.3 `int cudaDeviceProp::clockRate`

Clock frequency in kilohertz

5.7.2.4 `int cudaDeviceProp::computeMode`

Compute mode (See [cudaComputeMode](#))

5.7.2.5 `int cudaDeviceProp::concurrentKernels`

Device can possibly execute multiple kernels concurrently

5.7.2.6 `int cudaDeviceProp::deviceOverlap`

Device can concurrently copy memory and execute a kernel. Deprecated. Use instead `asyncEngineCount`.

5.7.2.7 `int cudaDeviceProp::ECCEnabled`

Device has ECC support enabled

5.7.2.8 `int cudaDeviceProp::integrated`

Device is integrated as opposed to discrete

5.7.2.9 `int cudaDeviceProp::kernelExecTimeoutEnabled`

Specified whether there is a run time limit on kernels

5.7.2.10 int cudaDeviceProp::l2CacheSize

Size of L2 cache in bytes

5.7.2.11 int cudaDeviceProp::major

Major compute capability

5.7.2.12 int cudaDeviceProp::maxGridSize[3]

Maximum size of each dimension of a grid

5.7.2.13 int cudaDeviceProp::maxSurface1D

Maximum 1D surface size

5.7.2.14 int cudaDeviceProp::maxSurface1DLayered[2]

Maximum 1D layered surface dimensions

5.7.2.15 int cudaDeviceProp::maxSurface2D[2]

Maximum 2D surface dimensions

5.7.2.16 int cudaDeviceProp::maxSurface2DLayered[3]

Maximum 2D layered surface dimensions

5.7.2.17 int cudaDeviceProp::maxSurface3D[3]

Maximum 3D surface dimensions

5.7.2.18 int cudaDeviceProp::maxSurfaceCubemap

Maximum Cubemap surface dimensions

5.7.2.19 int cudaDeviceProp::maxSurfaceCubemapLayered[2]

Maximum Cubemap layered surface dimensions

5.7.2.20 int cudaDeviceProp::maxTexture1D

Maximum 1D texture size

5.7.2.21 int cudaDeviceProp::maxTexture1DLayered[2]

Maximum 1D layered texture dimensions

5.7.2.22 int cudaDeviceProp::maxTexture1DLinear

Maximum size for 1D textures bound to linear memory

5.7.2.23 int cudaDeviceProp::maxTexture2D[2]

Maximum 2D texture dimensions

5.7.2.24 int cudaDeviceProp::maxTexture2DGather[2]

Maximum 2D texture dimensions if texture gather operations have to be performed

5.7.2.25 int cudaDeviceProp::maxTexture2DLayered[3]

Maximum 2D layered texture dimensions

5.7.2.26 int cudaDeviceProp::maxTexture2DLinear[3]

Maximum dimensions (width, height, pitch) for 2D textures bound to pitched memory

5.7.2.27 int cudaDeviceProp::maxTexture3D[3]

Maximum 3D texture dimensions

5.7.2.28 int cudaDeviceProp::maxTextureCubemap

Maximum Cubemap texture dimensions

5.7.2.29 int cudaDeviceProp::maxTextureCubemapLayered[2]

Maximum Cubemap layered texture dimensions

5.7.2.30 int cudaDeviceProp::maxThreadsDim[3]

Maximum size of each dimension of a block

5.7.2.31 int cudaDeviceProp::maxThreadsPerBlock

Maximum number of threads per block

5.7.2.32 int cudaDeviceProp::maxThreadsPerMultiProcessor

Maximum resident threads per multiprocessor

5.7.2.33 int cudaDeviceProp::memoryBusWidth

Global memory bus width in bits

5.7.2.34 int cudaDeviceProp::memoryClockRate

Peak memory clock frequency in kilohertz

5.7.2.35 size_t cudaDeviceProp::memPitch

Maximum pitch in bytes allowed by memory copies

5.7.2.36 int cudaDeviceProp::minor

Minor compute capability

5.7.2.37 int cudaDeviceProp::multiProcessorCount

Number of multiprocessors on device

5.7.2.38 char cudaDeviceProp::name[256]

ASCII string identifying device

5.7.2.39 int cudaDeviceProp::pciBusID

PCI bus ID of the device

5.7.2.40 int cudaDeviceProp::pciDeviceID

PCI device ID of the device

5.7.2.41 int cudaDeviceProp::pciDomainID

PCI domain ID of the device

5.7.2.42 int cudaDeviceProp::regsPerBlock

32-bit registers available per block

5.7.2.43 size_t cudaDeviceProp::sharedMemPerBlock

Shared memory available per block in bytes

5.7.2.44 size_t cudaDeviceProp::surfaceAlignment

Alignment requirements for surfaces

5.7.2.45 int cudaDeviceProp::tccDriver

1 if device is a Tesla device using TCC driver, 0 otherwise

5.7.2.46 `size_t cudaDeviceProp::textureAlignment`

Alignment requirement for textures

5.7.2.47 `size_t cudaDeviceProp::texturePitchAlignment`

Pitch alignment requirement for texture references bound to pitched memory

5.7.2.48 `size_t cudaDeviceProp::totalConstMem`

Constant memory available on device in bytes

5.7.2.49 `size_t cudaDeviceProp::totalGlobalMem`

Global memory available on device in bytes

5.7.2.50 `int cudaDeviceProp::unifiedAddressing`

Device shares a unified address space with the host

5.7.2.51 `int cudaDeviceProp::warpSize`

Warp size in threads

5.8 cudaExtent Struct Reference

Data Fields

- [size_t depth](#)
- [size_t height](#)
- [size_t width](#)

5.8.1 Detailed Description

CUDA extent

See also:

[make_cudaExtent](#)

5.8.2 Field Documentation

5.8.2.1 `size_t cudaExtent::depth`

Depth in elements

5.8.2.2 `size_t cudaExtent::height`

Height in elements

5.8.2.3 `size_t cudaExtent::width`

Width in elements when referring to array memory, in bytes when referring to linear memory

5.9 cudaFuncAttributes Struct Reference

Data Fields

- int [binaryVersion](#)
- size_t [constSizeBytes](#)
- size_t [localSizeBytes](#)
- int [maxThreadsPerBlock](#)
- int [numRegs](#)
- int [ptxVersion](#)
- size_t [sharedSizeBytes](#)

5.9.1 Detailed Description

CUDA function attributes

5.9.2 Field Documentation

5.9.2.1 int cudaFuncAttributes::binaryVersion

The binary architecture version for which the function was compiled. This value is the major binary version * 10 + the minor binary version, so a binary version 1.3 function would return the value 13.

5.9.2.2 size_t cudaFuncAttributes::constSizeBytes

The size in bytes of user-allocated constant memory required by this function.

5.9.2.3 size_t cudaFuncAttributes::localSizeBytes

The size in bytes of local memory used by each thread of this function.

5.9.2.4 int cudaFuncAttributes::maxThreadsPerBlock

The maximum number of threads per block, beyond which a launch of the function would fail. This number depends on both the function and the device on which the function is currently loaded.

5.9.2.5 int cudaFuncAttributes::numRegs

The number of registers used by each thread of this function.

5.9.2.6 int cudaFuncAttributes::ptxVersion

The PTX virtual architecture version for which the function was compiled. This value is the major PTX version * 10 + the minor PTX version, so a PTX version 1.3 function would return the value 13.

5.9.2.7 `size_t cudaFuncAttributes::sharedSizeBytes`

The size in bytes of statically-allocated shared memory per block required by this function. This does not include dynamically-allocated shared memory requested by the user at runtime.

5.10 cudaMemcpy3DParms Struct Reference

Data Fields

- struct cudaArray * [dstArray](#)
- struct [cudaPos](#) [dstPos](#)
- struct [cudaPitchedPtr](#) [dstPtr](#)
- struct [cudaExtent](#) [extent](#)
- enum [cudaMemcpyKind](#) [kind](#)
- struct cudaArray * [srcArray](#)
- struct [cudaPos](#) [srcPos](#)
- struct [cudaPitchedPtr](#) [srcPtr](#)

5.10.1 Detailed Description

CUDA 3D memory copying parameters

5.10.2 Field Documentation

5.10.2.1 struct cudaArray* cudaMemcpy3DParms::dstArray [read]

Destination memory address

5.10.2.2 struct cudaPos cudaMemcpy3DParms::dstPos [read]

Destination position offset

5.10.2.3 struct cudaPitchedPtr cudaMemcpy3DParms::dstPtr [read]

Pitched destination memory address

5.10.2.4 struct cudaExtent cudaMemcpy3DParms::extent [read]

Requested memory copy size

5.10.2.5 enum cudaMemcpyKind cudaMemcpy3DParms::kind

Type of transfer

5.10.2.6 struct cudaArray* cudaMemcpy3DParms::srcArray [read]

Source memory address

5.10.2.7 struct cudaPos cudaMemcpy3DParms::srcPos [read]

Source position offset

5.10.2.8 struct cudaPitchedPtr cudaMemcpy3DParms::srcPtr [read]

Pitched source memory address

5.11 cudaMemcpy3DPeerParms Struct Reference

Data Fields

- struct cudaArray * [dstArray](#)
- int [dstDevice](#)
- struct [cudaPos](#) [dstPos](#)
- struct [cudaPitchedPtr](#) [dstPtr](#)
- struct [cudaExtent](#) [extent](#)
- struct cudaArray * [srcArray](#)
- int [srcDevice](#)
- struct [cudaPos](#) [srcPos](#)
- struct [cudaPitchedPtr](#) [srcPtr](#)

5.11.1 Detailed Description

CUDA 3D cross-device memory copying parameters

5.11.2 Field Documentation

5.11.2.1 struct cudaArray* cudaMemcpy3DPeerParms::dstArray [read]

Destination memory address

5.11.2.2 int cudaMemcpy3DPeerParms::dstDevice

Destination device

5.11.2.3 struct cudaPos cudaMemcpy3DPeerParms::dstPos [read]

Destination position offset

5.11.2.4 struct cudaPitchedPtr cudaMemcpy3DPeerParms::dstPtr [read]

Pitched destination memory address

5.11.2.5 struct cudaExtent cudaMemcpy3DPeerParms::extent [read]

Requested memory copy size

5.11.2.6 struct cudaArray* cudaMemcpy3DPeerParms::srcArray [read]

Source memory address

5.11.2.7 int cudaMemcpy3DPeerParms::srcDevice

Source device

5.11.2.8 struct cudaPos cudaMemcpy3DPeerParms::srcPos [read]

Source position offset

5.11.2.9 struct cudaPitchedPtr cudaMemcpy3DPeerParms::srcPtr [read]

Pitched source memory address

5.12 cudaPitchedPtr Struct Reference

Data Fields

- `size_t` [pitch](#)
- `void *` [ptr](#)
- `size_t` [xsize](#)
- `size_t` [ysize](#)

5.12.1 Detailed Description

CUDA Pitched memory pointer

See also:

[make_cudaPitchedPtr](#)

5.12.2 Field Documentation

5.12.2.1 `size_t` `cudaPitchedPtr::pitch`

Pitch of allocated memory in bytes

5.12.2.2 `void*` `cudaPitchedPtr::ptr`

Pointer to allocated memory

5.12.2.3 `size_t` `cudaPitchedPtr::xsize`

Logical width of allocation in elements

5.12.2.4 `size_t` `cudaPitchedPtr::ysize`

Logical height of allocation in elements

5.13 cudaPointerAttributes Struct Reference

Data Fields

- int [device](#)
- void * [devicePointer](#)
- void * [hostPointer](#)
- enum [cudaMemoryType](#) [memoryType](#)

5.13.1 Detailed Description

CUDA pointer attributes

5.13.2 Field Documentation

5.13.2.1 int cudaPointerAttributes::device

The device against which the memory was allocated or registered. If the memory type is [cudaMemoryTypeDevice](#) then this identifies the device on which the memory referred physically resides. If the memory type is [cudaMemoryTypeHost](#) then this identifies the device which was current when the memory was allocated or registered (and if that device is deinitialized then this allocation will vanish with that device's state).

5.13.2.2 void* cudaPointerAttributes::devicePointer

The address which may be dereferenced on the current device to access the memory or NULL if no such address exists.

5.13.2.3 void* cudaPointerAttributes::hostPointer

The address which may be dereferenced on the host to access the memory or NULL if no such address exists.

5.13.2.4 enum cudaMemoryType cudaPointerAttributes::memoryType

The physical location of the memory, [cudaMemoryTypeHost](#) or [cudaMemoryTypeDevice](#).

5.14 cudaPos Struct Reference

Data Fields

- `size_t x`
- `size_t y`
- `size_t z`

5.14.1 Detailed Description

CUDA 3D position

See also:

[make_cudaPos](#)

5.14.2 Field Documentation

5.14.2.1 `size_t cudaPos::x`

x

5.14.2.2 `size_t cudaPos::y`

y

5.14.2.3 `size_t cudaPos::z`

z

5.15 CUdevprop_st Struct Reference

Data Fields

- int [clockRate](#)
- int [maxGridSize](#) [3]
- int [maxThreadsDim](#) [3]
- int [maxThreadsPerBlock](#)
- int [memPitch](#)
- int [regsPerBlock](#)
- int [sharedMemPerBlock](#)
- int [SIMDWidth](#)
- int [textureAlign](#)
- int [totalConstantMemory](#)

5.15.1 Detailed Description

Legacy device properties

5.15.2 Field Documentation

5.15.2.1 int CUdevprop_st::clockRate

Clock frequency in kilohertz

5.15.2.2 int CUdevprop_st::maxGridSize[3]

Maximum size of each dimension of a grid

5.15.2.3 int CUdevprop_st::maxThreadsDim[3]

Maximum size of each dimension of a block

5.15.2.4 int CUdevprop_st::maxThreadsPerBlock

Maximum number of threads per block

5.15.2.5 int CUdevprop_st::memPitch

Maximum pitch in bytes allowed by memory copies

5.15.2.6 int CUdevprop_st::regsPerBlock

32-bit registers available per block

5.15.2.7 int CUdevprop_st::sharedMemPerBlock

Shared memory available per block in bytes

5.15.2.8 int CUdevprop_st::SIMDWidth

Warp size in threads

5.15.2.9 int CUdevprop_st::textureAlign

Alignment requirement for textures

5.15.2.10 int CUdevprop_st::totalConstantMemory

Constant memory available on device in bytes

5.16 surfaceReference Struct Reference

Data Fields

- struct [cudaChannelFormatDesc](#) `channelDesc`

5.16.1 Detailed Description

CUDA Surface reference

5.16.2 Field Documentation

5.16.2.1 struct `cudaChannelFormatDesc` `surfaceReference::channelDesc` [read]

Channel descriptor for surface reference

5.17 textureReference Struct Reference

Data Fields

- enum [cudaTextureAddressMode](#) `addressMode` [3]
- struct [cudaChannelFormatDesc](#) `channelDesc`
- enum [cudaTextureFilterMode](#) `filterMode`
- int [normalized](#)
- int [sRGB](#)

5.17.1 Detailed Description

CUDA texture reference

5.17.2 Field Documentation

5.17.2.1 enum `cudaTextureAddressMode textureReference::addressMode[3]`

Texture address mode for up to 3 dimensions

5.17.2.2 struct `cudaChannelFormatDesc textureReference::channelDesc` [read]

Channel descriptor for the texture reference

5.17.2.3 enum `cudaTextureFilterMode textureReference::filterMode`

Texture filter mode

5.17.2.4 int `textureReference::normalized`

Indicates whether texture reads are normalized or not

5.17.2.5 int `textureReference::sRGB`

Perform sRGB->linear conversion during texture read

Index

__brev
 CUDA_MATH_INTRINSIC_INT, 447
__brevll
 CUDA_MATH_INTRINSIC_INT, 447
__byte_perm
 CUDA_MATH_INTRINSIC_INT, 447
__clz
 CUDA_MATH_INTRINSIC_INT, 447
__clzll
 CUDA_MATH_INTRINSIC_INT, 448
__cosf
 CUDA_MATH_INTRINSIC_SINGLE, 428
__dadd_rd
 CUDA_MATH_INTRINSIC_DOUBLE, 439
__dadd_rn
 CUDA_MATH_INTRINSIC_DOUBLE, 439
__dadd_ru
 CUDA_MATH_INTRINSIC_DOUBLE, 440
__dadd_rz
 CUDA_MATH_INTRINSIC_DOUBLE, 440
__ddiv_rd
 CUDA_MATH_INTRINSIC_DOUBLE, 440
__ddiv_rn
 CUDA_MATH_INTRINSIC_DOUBLE, 440
__ddiv_ru
 CUDA_MATH_INTRINSIC_DOUBLE, 441
__ddiv_rz
 CUDA_MATH_INTRINSIC_DOUBLE, 441
__dmul_rd
 CUDA_MATH_INTRINSIC_DOUBLE, 441
__dmul_rn
 CUDA_MATH_INTRINSIC_DOUBLE, 441
__dmul_ru
 CUDA_MATH_INTRINSIC_DOUBLE, 442
__dmul_rz
 CUDA_MATH_INTRINSIC_DOUBLE, 442
__double2float_rd
 CUDA_MATH_INTRINSIC_CAST, 455
__double2float_rn
 CUDA_MATH_INTRINSIC_CAST, 455
__double2float_ru
 CUDA_MATH_INTRINSIC_CAST, 455
__double2float_rz
 CUDA_MATH_INTRINSIC_CAST, 455
__double2hiint
 CUDA_MATH_INTRINSIC_CAST, 456
__double2int_rd
 CUDA_MATH_INTRINSIC_CAST, 456
__double2int_rn
 CUDA_MATH_INTRINSIC_CAST, 456
__double2int_ru
 CUDA_MATH_INTRINSIC_CAST, 456
__double2int_rz
 CUDA_MATH_INTRINSIC_CAST, 456
__double2ll_rd
 CUDA_MATH_INTRINSIC_CAST, 456
__double2ll_rn
 CUDA_MATH_INTRINSIC_CAST, 457
__double2ll_ru
 CUDA_MATH_INTRINSIC_CAST, 457
__double2ll_rz
 CUDA_MATH_INTRINSIC_CAST, 457
__double2loint
 CUDA_MATH_INTRINSIC_CAST, 457
__double2uint_rd
 CUDA_MATH_INTRINSIC_CAST, 457
__double2uint_rn
 CUDA_MATH_INTRINSIC_CAST, 457
__double2uint_ru
 CUDA_MATH_INTRINSIC_CAST, 458
__double2uint_rz
 CUDA_MATH_INTRINSIC_CAST, 458
__double2ull_rd
 CUDA_MATH_INTRINSIC_CAST, 458
__double2ull_rn
 CUDA_MATH_INTRINSIC_CAST, 458
__double2ull_ru
 CUDA_MATH_INTRINSIC_CAST, 458
__double2ull_rz
 CUDA_MATH_INTRINSIC_CAST, 458
__double_as_longlong
 CUDA_MATH_INTRINSIC_CAST, 459
__drcp_rd
 CUDA_MATH_INTRINSIC_DOUBLE, 442
__drcp_rn
 CUDA_MATH_INTRINSIC_DOUBLE, 442
__drcp_ru
 CUDA_MATH_INTRINSIC_DOUBLE, 443
__drcp_rz
 CUDA_MATH_INTRINSIC_DOUBLE, 443

- __dsqrt_rd
 - CUDA_MATH_INTRINSIC_DOUBLE, [443](#)
- __dsqrt_rn
 - CUDA_MATH_INTRINSIC_DOUBLE, [443](#)
- __dsqrt_ru
 - CUDA_MATH_INTRINSIC_DOUBLE, [444](#)
- __dsqrt_rz
 - CUDA_MATH_INTRINSIC_DOUBLE, [444](#)
- __exp10f
 - CUDA_MATH_INTRINSIC_SINGLE, [428](#)
- __expf
 - CUDA_MATH_INTRINSIC_SINGLE, [428](#)
- __fadd_rd
 - CUDA_MATH_INTRINSIC_SINGLE, [429](#)
- __fadd_rn
 - CUDA_MATH_INTRINSIC_SINGLE, [429](#)
- __fadd_ru
 - CUDA_MATH_INTRINSIC_SINGLE, [429](#)
- __fadd_rz
 - CUDA_MATH_INTRINSIC_SINGLE, [429](#)
- __fdiv_rd
 - CUDA_MATH_INTRINSIC_SINGLE, [430](#)
- __fdiv_rn
 - CUDA_MATH_INTRINSIC_SINGLE, [430](#)
- __fdiv_ru
 - CUDA_MATH_INTRINSIC_SINGLE, [430](#)
- __fdiv_rz
 - CUDA_MATH_INTRINSIC_SINGLE, [430](#)
- __fdividef
 - CUDA_MATH_INTRINSIC_SINGLE, [431](#)
- __ffs
 - CUDA_MATH_INTRINSIC_INT, [448](#)
- __ffsll
 - CUDA_MATH_INTRINSIC_INT, [448](#)
- __float2half_rn
 - CUDA_MATH_INTRINSIC_CAST, [459](#)
- __float2int_rd
 - CUDA_MATH_INTRINSIC_CAST, [459](#)
- __float2int_rn
 - CUDA_MATH_INTRINSIC_CAST, [459](#)
- __float2int_ru
 - CUDA_MATH_INTRINSIC_CAST, [459](#)
- __float2int_rz
 - CUDA_MATH_INTRINSIC_CAST, [459](#)
- __float2ll_rd
 - CUDA_MATH_INTRINSIC_CAST, [460](#)
- __float2ll_rn
 - CUDA_MATH_INTRINSIC_CAST, [460](#)
- __float2ll_ru
 - CUDA_MATH_INTRINSIC_CAST, [460](#)
- __float2ll_rz
 - CUDA_MATH_INTRINSIC_CAST, [460](#)
- __float2uint_rd
 - CUDA_MATH_INTRINSIC_CAST, [460](#)
- __float2uint_rn
 - CUDA_MATH_INTRINSIC_CAST, [460](#)
- __float2uint_ru
 - CUDA_MATH_INTRINSIC_CAST, [461](#)
- __float2uint_rz
 - CUDA_MATH_INTRINSIC_CAST, [461](#)
- __float2ull_rd
 - CUDA_MATH_INTRINSIC_CAST, [461](#)
- __float2ull_rn
 - CUDA_MATH_INTRINSIC_CAST, [461](#)
- __float2ull_ru
 - CUDA_MATH_INTRINSIC_CAST, [461](#)
- __float2ull_rz
 - CUDA_MATH_INTRINSIC_CAST, [461](#)
- __float_as_int
 - CUDA_MATH_INTRINSIC_CAST, [462](#)
- __fma_rd
 - CUDA_MATH_INTRINSIC_DOUBLE, [444](#)
- __fma_rn
 - CUDA_MATH_INTRINSIC_DOUBLE, [444](#)
- __fma_ru
 - CUDA_MATH_INTRINSIC_DOUBLE, [445](#)
- __fma_rz
 - CUDA_MATH_INTRINSIC_DOUBLE, [445](#)
- __fmaf_rd
 - CUDA_MATH_INTRINSIC_SINGLE, [431](#)
- __fmaf_rn
 - CUDA_MATH_INTRINSIC_SINGLE, [431](#)
- __fmaf_ru
 - CUDA_MATH_INTRINSIC_SINGLE, [432](#)
- __fmaf_rz
 - CUDA_MATH_INTRINSIC_SINGLE, [432](#)
- __fmul_rd
 - CUDA_MATH_INTRINSIC_SINGLE, [432](#)
- __fmul_rn
 - CUDA_MATH_INTRINSIC_SINGLE, [432](#)
- __fmul_ru
 - CUDA_MATH_INTRINSIC_SINGLE, [433](#)
- __fmul_rz
 - CUDA_MATH_INTRINSIC_SINGLE, [433](#)
- __frcp_rd
 - CUDA_MATH_INTRINSIC_SINGLE, [433](#)
- __frcp_rn
 - CUDA_MATH_INTRINSIC_SINGLE, [433](#)
- __frcp_ru
 - CUDA_MATH_INTRINSIC_SINGLE, [434](#)
- __frcp_rz
 - CUDA_MATH_INTRINSIC_SINGLE, [434](#)
- __fsqrt_rd
 - CUDA_MATH_INTRINSIC_SINGLE, [434](#)
- __fsqrt_rn
 - CUDA_MATH_INTRINSIC_SINGLE, [434](#)
- __fsqrt_ru
 - CUDA_MATH_INTRINSIC_SINGLE, [435](#)

- __fsqrt_rz
 - CUDA_MATH_INTRINSIC_SINGLE, 435
- __half2float
 - CUDA_MATH_INTRINSIC_CAST, 462
- __hiloint2double
 - CUDA_MATH_INTRINSIC_CAST, 462
- __int2double_rn
 - CUDA_MATH_INTRINSIC_CAST, 462
- __int2float_rd
 - CUDA_MATH_INTRINSIC_CAST, 462
- __int2float_rn
 - CUDA_MATH_INTRINSIC_CAST, 462
- __int2float_ru
 - CUDA_MATH_INTRINSIC_CAST, 463
- __int2float_rz
 - CUDA_MATH_INTRINSIC_CAST, 463
- __int_as_float
 - CUDA_MATH_INTRINSIC_CAST, 463
- __ll2double_rd
 - CUDA_MATH_INTRINSIC_CAST, 463
- __ll2double_rn
 - CUDA_MATH_INTRINSIC_CAST, 463
- __ll2double_ru
 - CUDA_MATH_INTRINSIC_CAST, 463
- __ll2double_rz
 - CUDA_MATH_INTRINSIC_CAST, 464
- __ll2float_rd
 - CUDA_MATH_INTRINSIC_CAST, 464
- __ll2float_rn
 - CUDA_MATH_INTRINSIC_CAST, 464
- __ll2float_ru
 - CUDA_MATH_INTRINSIC_CAST, 464
- __ll2float_rz
 - CUDA_MATH_INTRINSIC_CAST, 464
- __log10f
 - CUDA_MATH_INTRINSIC_SINGLE, 435
- __log2f
 - CUDA_MATH_INTRINSIC_SINGLE, 435
- __logf
 - CUDA_MATH_INTRINSIC_SINGLE, 436
- __longlong_as_double
 - CUDA_MATH_INTRINSIC_CAST, 464
- __mul24
 - CUDA_MATH_INTRINSIC_INT, 448
- __mul64hi
 - CUDA_MATH_INTRINSIC_INT, 448
- __mulhi
 - CUDA_MATH_INTRINSIC_INT, 448
- __popc
 - CUDA_MATH_INTRINSIC_INT, 449
- __popcll
 - CUDA_MATH_INTRINSIC_INT, 449
- __powf
 - CUDA_MATH_INTRINSIC_SINGLE, 436
- __sad
 - CUDA_MATH_INTRINSIC_INT, 449
- __saturatef
 - CUDA_MATH_INTRINSIC_SINGLE, 436
- __sincosf
 - CUDA_MATH_INTRINSIC_SINGLE, 436
- __sinf
 - CUDA_MATH_INTRINSIC_SINGLE, 437
- __tanf
 - CUDA_MATH_INTRINSIC_SINGLE, 437
- __uint2double_rn
 - CUDA_MATH_INTRINSIC_CAST, 465
- __uint2float_rd
 - CUDA_MATH_INTRINSIC_CAST, 465
- __uint2float_rn
 - CUDA_MATH_INTRINSIC_CAST, 465
- __uint2float_ru
 - CUDA_MATH_INTRINSIC_CAST, 465
- __uint2float_rz
 - CUDA_MATH_INTRINSIC_CAST, 465
- __ull2double_rd
 - CUDA_MATH_INTRINSIC_CAST, 465
- __ull2double_rn
 - CUDA_MATH_INTRINSIC_CAST, 466
- __ull2double_ru
 - CUDA_MATH_INTRINSIC_CAST, 466
- __ull2double_rz
 - CUDA_MATH_INTRINSIC_CAST, 466
- __ull2float_rd
 - CUDA_MATH_INTRINSIC_CAST, 466
- __ull2float_rn
 - CUDA_MATH_INTRINSIC_CAST, 466
- __ull2float_ru
 - CUDA_MATH_INTRINSIC_CAST, 466
- __ull2float_rz
 - CUDA_MATH_INTRINSIC_CAST, 467
- __umul24
 - CUDA_MATH_INTRINSIC_INT, 449
- __umul64hi
 - CUDA_MATH_INTRINSIC_INT, 449
- __umulhi
 - CUDA_MATH_INTRINSIC_INT, 449
- __usad
 - CUDA_MATH_INTRINSIC_INT, 450
- acos
 - CUDA_MATH_DOUBLE, 405
- acosh
 - CUDA_MATH_SINGLE, 380
- acoshf
 - CUDA_MATH_DOUBLE, 405
- acoshf
 - CUDA_MATH_SINGLE, 380
- addressMode

- textureReference, 500
- asin
 - CUDA_MATH_DOUBLE, 406
- asinf
 - CUDA_MATH_SINGLE, 381
- asinh
 - CUDA_MATH_DOUBLE, 406
- asinhf
 - CUDA_MATH_SINGLE, 381
- asyncEngineCount
 - cudaDeviceProp, 482
- atan
 - CUDA_MATH_DOUBLE, 406
- atan2
 - CUDA_MATH_DOUBLE, 406
- atan2f
 - CUDA_MATH_SINGLE, 381
- atanf
 - CUDA_MATH_SINGLE, 381
- atanh
 - CUDA_MATH_DOUBLE, 407
- atanhf
 - CUDA_MATH_SINGLE, 382
- binaryVersion
 - cudaFuncAttributes, 488
- C++ API Routines, 121
- canMapHostMemory
 - cudaDeviceProp, 482
- cbrt
 - CUDA_MATH_DOUBLE, 407
- cbrtf
 - CUDA_MATH_SINGLE, 382
- ceil
 - CUDA_MATH_DOUBLE, 407
- ceilf
 - CUDA_MATH_SINGLE, 382
- channelDesc
 - surfaceReference, 499
 - textureReference, 500
- clockRate
 - cudaDeviceProp, 482
 - CUdevprop_st, 497
- computeMode
 - cudaDeviceProp, 482
- concurrentKernels
 - cudaDeviceProp, 482
- constSizeBytes
 - cudaFuncAttributes, 488
- Context Management, 210
- copysign
 - CUDA_MATH_DOUBLE, 407
- copysignf
 - CUDA_MATH_SINGLE, 382
- cos
 - CUDA_MATH_DOUBLE, 408
- cosf
 - CUDA_MATH_SINGLE, 383
- cosh
 - CUDA_MATH_DOUBLE, 408
- coshf
 - CUDA_MATH_SINGLE, 383
- cospi
 - CUDA_MATH_DOUBLE, 408
- cospif
 - CUDA_MATH_SINGLE, 383
- CU_AD_FORMAT_FLOAT
 - CUDA_TYPES, 189
- CU_AD_FORMAT_HALF
 - CUDA_TYPES, 189
- CU_AD_FORMAT_SIGNED_INT16
 - CUDA_TYPES, 189
- CU_AD_FORMAT_SIGNED_INT32
 - CUDA_TYPES, 189
- CU_AD_FORMAT_SIGNED_INT8
 - CUDA_TYPES, 189
- CU_AD_FORMAT_UNSIGNED_INT16
 - CUDA_TYPES, 189
- CU_AD_FORMAT_UNSIGNED_INT32
 - CUDA_TYPES, 189
- CU_AD_FORMAT_UNSIGNED_INT8
 - CUDA_TYPES, 189
- CU_COMPUTEMODE_DEFAULT
 - CUDA_TYPES, 189
- CU_COMPUTEMODE_EXCLUSIVE
 - CUDA_TYPES, 189
- CU_COMPUTEMODE_EXCLUSIVE_PROCESS
 - CUDA_TYPES, 190
- CU_COMPUTEMODE_PROHIBITED
 - CUDA_TYPES, 190
- CU_CTX_BLOCKING_SYNC
 - CUDA_TYPES, 190
- CU_CTX_LMEM_RESIZE_TO_MAX
 - CUDA_TYPES, 190
- CU_CTX_MAP_HOST
 - CUDA_TYPES, 190
- CU_CTX_SCHED_AUTO
 - CUDA_TYPES, 190
- CU_CTX_SCHED_BLOCKING_SYNC
 - CUDA_TYPES, 190
- CU_CTX_SCHED_SPIN
 - CUDA_TYPES, 190
- CU_CTX_SCHED_YIELD
 - CUDA_TYPES, 190
- CU_CUBEMAP_FACE_NEGATIVE_X
 - CUDA_TYPES, 189
- CU_CUBEMAP_FACE_NEGATIVE_Y

- CUDA_TYPES, [189](#)
- CU_CUBEMAP_FACE_NEGATIVE_Z
 - CUDA_TYPES, [189](#)
- CU_CUBEMAP_FACE_POSITIVE_X
 - CUDA_TYPES, [189](#)
- CU_CUBEMAP_FACE_POSITIVE_Y
 - CUDA_TYPES, [189](#)
- CU_CUBEMAP_FACE_POSITIVE_Z
 - CUDA_TYPES, [189](#)
- CU_D3D10_DEVICE_LIST_ALL
 - CUDA_D3D10, [351](#)
- CU_D3D10_DEVICE_LIST_CURRENT_FRAME
 - CUDA_D3D10, [351](#)
- CU_D3D10_DEVICE_LIST_NEXT_FRAME
 - CUDA_D3D10, [351](#)
- CU_D3D11_DEVICE_LIST_ALL
 - CUDA_D3D11, [366](#)
- CU_D3D11_DEVICE_LIST_CURRENT_FRAME
 - CUDA_D3D11, [366](#)
- CU_D3D11_DEVICE_LIST_NEXT_FRAME
 - CUDA_D3D11, [366](#)
- CU_D3D9_DEVICE_LIST_ALL
 - CUDA_D3D9, [336](#)
- CU_D3D9_DEVICE_LIST_CURRENT_FRAME
 - CUDA_D3D9, [336](#)
- CU_D3D9_DEVICE_LIST_NEXT_FRAME
 - CUDA_D3D9, [336](#)
- CU_DEVICE_ATTRIBUTE_ASYNC_ENGINE_COUNT
 - CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_CAN_MAP_HOST_MEMORY
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_CAN_TEX2D_GATHER
 - CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_CLOCK_RATE
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_COMPUTE_MODE
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_CONCURRENT_KERNELS
 - CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_ECC_ENABLED
 - CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_GLOBAL_MEMORY_BUS_WIDTH
 - CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_GPU_OVERLAP
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_INTEGRATED
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_KERNEL_EXEC_TIMEOUT
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_L2_CACHE_SIZE
 - CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_X
 - CUDA_TYPES, [192](#)
- CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_Y
 - CUDA_TYPES, [192](#)
- CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_Z
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_X
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_Y
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_Z
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAX_PITCH
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAX_REGISTERS_PER_BLOCK
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAX_SHARED_MEMORY_PER_BLOCK
 - CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAX_THREADS_PER_BLOCK
 - CUDA_TYPES, [192](#)
- CU_DEVICE_ATTRIBUTE_MAX_THREADS_PER_MULTIPROCESSOR
 - CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_LAYERED_LAYERS
 - CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_LAYERED_WIDTH
 - CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_WIDTH
 - CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_HEIGHT
 - CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_HEIGHT
 - CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_LAYERS
 - CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_WIDTH
 - CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_WIDTH
 - CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_DEPTH

- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
SURFACE3D_HEIGHT
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
SURFACE3D_WIDTH
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
SURFACECUBEMAP_LAYERED_LAYERS
- CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
SURFACECUBEMAP_LAYERED_WIDTH
- CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
SURFACECUBEMAP_WIDTH
- CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE1D_LAYERED_LAYERS
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE1D_LAYERED_WIDTH
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE1D_LINEAR_WIDTH
- CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE1D_WIDTH
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_ARRAY_HEIGHT
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_ARRAY_NUMSLICES
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_ARRAY_WIDTH
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_GATHER_HEIGHT
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_GATHER_WIDTH
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_HEIGHT
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_LAYERED_HEIGHT
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_LAYERED_LAYERS
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_LAYERED_WIDTH
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_LINEAR_HEIGHT
- CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_LINEAR_PITCH
- CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_LINEAR_WIDTH
- CUDA_TYPES, [195](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE2D_WIDTH
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE3D_DEPTH
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE3D_DEPTH_ALTERNATE
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE3D_HEIGHT
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE3D_HEIGHT_ALTERNATE
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE3D_WIDTH
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURE3D_WIDTH_ALTERNATE
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURECUBEMAP_LAYERED_LAYERS
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURECUBEMAP_LAYERED_WIDTH
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-
TEXTURECUBEMAP_WIDTH
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MEMORY_CLOCK_-
RATE
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_MULTIPROCESSOR_-
COUNT
- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_PCI_BUS_ID
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_PCI_DEVICE_ID
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_PCI_DOMAIN_ID
- CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_REGISTERS_PER_-
BLOCK

- CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_SHARED_MEMORY_-
PER_BLOCK
CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_SURFACE_ALIGNMENT
CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_TCC_DRIVER
CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_TEXTURE_ALIGNMENT
CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_TEXTURE_PITCH_-
ALIGNMENT
CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_TOTAL_CONSTANT_-
MEMORY
CUDA_TYPES, [193](#)
- CU_DEVICE_ATTRIBUTE_UNIFIED_ADDRESSING
CUDA_TYPES, [194](#)
- CU_DEVICE_ATTRIBUTE_WARP_SIZE
CUDA_TYPES, [193](#)
- CU_EVENT_BLOCKING_SYNC
CUDA_TYPES, [195](#)
- CU_EVENT_DEFAULT
CUDA_TYPES, [195](#)
- CU_EVENT_DISABLE_TIMING
CUDA_TYPES, [195](#)
- CU_EVENT_INTERPROCESS
CUDA_TYPES, [195](#)
- CU_FUNC_ATTRIBUTE_BINARY_VERSION
CUDA_TYPES, [196](#)
- CU_FUNC_ATTRIBUTE_CONST_SIZE_BYTES
CUDA_TYPES, [196](#)
- CU_FUNC_ATTRIBUTE_LOCAL_SIZE_BYTES
CUDA_TYPES, [196](#)
- CU_FUNC_ATTRIBUTE_MAX_THREADS_PER_-
BLOCK
CUDA_TYPES, [196](#)
- CU_FUNC_ATTRIBUTE_NUM_REGS
CUDA_TYPES, [196](#)
- CU_FUNC_ATTRIBUTE_PTX_VERSION
CUDA_TYPES, [196](#)
- CU_FUNC_ATTRIBUTE_SHARED_SIZE_BYTES
CUDA_TYPES, [196](#)
- CU_FUNC_CACHE_PREFER_EQUAL
CUDA_TYPES, [196](#)
- CU_FUNC_CACHE_PREFER_L1
CUDA_TYPES, [196](#)
- CU_FUNC_CACHE_PREFER_NONE
CUDA_TYPES, [196](#)
- CU_FUNC_CACHE_PREFER_SHARED
CUDA_TYPES, [196](#)
- CU_GL_DEVICE_LIST_ALL
CUDA_GL, [325](#)
- CU_GL_DEVICE_LIST_CURRENT_FRAME
CUDA_GL, [325](#)
- CU_GL_DEVICE_LIST_NEXT_FRAME
CUDA_GL, [325](#)
- CU_JIT_ERROR_LOG_BUFFER
CUDA_TYPES, [197](#)
- CU_JIT_ERROR_LOG_BUFFER_SIZE_BYTES
CUDA_TYPES, [197](#)
- CU_JIT_FALLBACK_STRATEGY
CUDA_TYPES, [198](#)
- CU_JIT_INFO_LOG_BUFFER
CUDA_TYPES, [197](#)
- CU_JIT_INFO_LOG_BUFFER_SIZE_BYTES
CUDA_TYPES, [197](#)
- CU_JIT_MAX_REGISTERS
CUDA_TYPES, [197](#)
- CU_JIT_OPTIMIZATION_LEVEL
CUDA_TYPES, [197](#)
- CU_JIT_TARGET
CUDA_TYPES, [197](#)
- CU_JIT_TARGET_FROM_CUCONTEXT
CUDA_TYPES, [197](#)
- CU_JIT_THREADS_PER_BLOCK
CUDA_TYPES, [197](#)
- CU_JIT_WALL_TIME
CUDA_TYPES, [197](#)
- CU_LIMIT_MALLOC_HEAP_SIZE
CUDA_TYPES, [198](#)
- CU_LIMIT_PRINTF_FIFO_SIZE
CUDA_TYPES, [198](#)
- CU_LIMIT_STACK_SIZE
CUDA_TYPES, [198](#)
- CU_MEMORYTYPE_ARRAY
CUDA_TYPES, [198](#)
- CU_MEMORYTYPE_DEVICE
CUDA_TYPES, [198](#)
- CU_MEMORYTYPE_HOST
CUDA_TYPES, [198](#)
- CU_MEMORYTYPE_UNIFIED
CUDA_TYPES, [198](#)
- CU_POINTER_ATTRIBUTE_CONTEXT
CUDA_TYPES, [198](#)
- CU_POINTER_ATTRIBUTE_DEVICE_POINTER
CUDA_TYPES, [199](#)
- CU_POINTER_ATTRIBUTE_HOST_POINTER
CUDA_TYPES, [199](#)
- CU_POINTER_ATTRIBUTE_MEMORY_TYPE
CUDA_TYPES, [198](#)
- CU_PREFER_BINARY
CUDA_TYPES, [197](#)
- CU_PREFER_PTX
CUDA_TYPES, [197](#)
- CU_TARGET_COMPUTE_10
CUDA_TYPES, [198](#)
- CU_TARGET_COMPUTE_11

- CUDA_TYPES, [198](#)
- CU_TARGET_COMPUTE_12
 - CUDA_TYPES, [198](#)
- CU_TARGET_COMPUTE_13
 - CUDA_TYPES, [198](#)
- CU_TARGET_COMPUTE_20
 - CUDA_TYPES, [198](#)
- CU_TARGET_COMPUTE_21
 - CUDA_TYPES, [198](#)
- CU_TR_ADDRESS_MODE_BORDER
 - CUDA_TYPES, [189](#)
- CU_TR_ADDRESS_MODE_CLAMP
 - CUDA_TYPES, [189](#)
- CU_TR_ADDRESS_MODE_MIRROR
 - CUDA_TYPES, [189](#)
- CU_TR_ADDRESS_MODE_WRAP
 - CUDA_TYPES, [189](#)
- CU_TR_FILTER_MODE_LINEAR
 - CUDA_TYPES, [195](#)
- CU_TR_FILTER_MODE_POINT
 - CUDA_TYPES, [195](#)
- CU_IPC_HANDLE_SIZE
 - CUDA_TYPES, [183](#)
- CU_LAUNCH_PARAM_BUFFER_POINTER
 - CUDA_TYPES, [183](#)
- CU_LAUNCH_PARAM_BUFFER_SIZE
 - CUDA_TYPES, [184](#)
- CU_LAUNCH_PARAM_END
 - CUDA_TYPES, [184](#)
- CU_MEMHOSTALLOC_DEVICEMAP
 - CUDA_TYPES, [184](#)
- CU_MEMHOSTALLOC_PORTABLE
 - CUDA_TYPES, [184](#)
- CU_MEMHOSTALLOC_WRITECOMBINED
 - CUDA_TYPES, [184](#)
- CU_MEMHOSTREGISTER_DEVICEMAP
 - CUDA_TYPES, [184](#)
- CU_MEMHOSTREGISTER_PORTABLE
 - CUDA_TYPES, [184](#)
- CU_PARAM_TR_DEFAULT
 - CUDA_TYPES, [184](#)
- CU_TRSA_OVERRIDE_FORMAT
 - CUDA_TYPES, [184](#)
- CU_TRSF_NORMALIZED_COORDINATES
 - CUDA_TYPES, [184](#)
- CU_TRSF_READ_AS_INTEGER
 - CUDA_TYPES, [185](#)
- CU_TRSF_SRGB
 - CUDA_TYPES, [185](#)
- CUaddress_mode
 - CUDA_TYPES, [185](#)
- CUaddress_mode_enum
 - CUDA_TYPES, [189](#)
- CUarray
 - CUDA_TYPES, [185](#)
- cuArray3DCreate
 - CUDA_MEM, [232](#)
- cuArray3DGetDescriptor
 - CUDA_MEM, [234](#)
- CUarray_cubemap_face
 - CUDA_TYPES, [186](#)
- CUarray_cubemap_face_enum
 - CUDA_TYPES, [189](#)
- CUarray_format
 - CUDA_TYPES, [186](#)
- CUarray_format_enum
 - CUDA_TYPES, [189](#)
- cuArrayCreate
 - CUDA_MEM, [235](#)
- cuArrayDestroy
 - CUDA_MEM, [236](#)
- cuArrayGetDescriptor
 - CUDA_MEM, [237](#)
- CUcomputemode
 - CUDA_TYPES, [186](#)
- CUcomputemode_enum
 - CUDA_TYPES, [189](#)
- CUcontext
 - CUDA_TYPES, [186](#)
- CUctx_flags
 - CUDA_TYPES, [186](#)
- CUctx_flags_enum
 - CUDA_TYPES, [190](#)
- cuCtxAttach
 - CUDA_CTX_DEPRECATED, [219](#)
- cuCtxCreate
 - CUDA_CTX, [211](#)
- cuCtxDestroy
 - CUDA_CTX, [212](#)
- cuCtxDetach
 - CUDA_CTX_DEPRECATED, [219](#)
- cuCtxDisablePeerAccess
 - CUDA_PEER_ACCESS, [315](#)
- cuCtxEnablePeerAccess
 - CUDA_PEER_ACCESS, [315](#)
- cuCtxGetApiVersion
 - CUDA_CTX, [212](#)
- cuCtxGetCacheConfig
 - CUDA_CTX, [213](#)
- cuCtxGetCurrent
 - CUDA_CTX, [213](#)
- cuCtxGetDevice
 - CUDA_CTX, [214](#)
- cuCtxGetLimit
 - CUDA_CTX, [214](#)
- cuCtxPopCurrent
 - CUDA_CTX, [215](#)
- cuCtxPushCurrent

- CUDA_CTX, 215
- cuCtxSetCacheConfig
 - CUDA_CTX, 216
- cuCtxSetCurrent
 - CUDA_CTX, 216
- cuCtxSetLimit
 - CUDA_CTX, 217
- cuCtxSynchronize
 - CUDA_CTX, 218
- cuD3D10CtxCreate
 - CUDA_D3D10, 351
- cuD3D10CtxCreateOnDevice
 - CUDA_D3D10, 351
- CuD3d10DeviceList
 - CUDA_D3D10, 351
- CuD3d10DeviceList_enum
 - CUDA_D3D10, 351
- cuD3D10GetDevice
 - CUDA_D3D10, 352
- cuD3D10GetDevices
 - CUDA_D3D10, 352
- cuD3D10GetDirect3DDevice
 - CUDA_D3D10, 353
- CuD3D10map_flags
 - CUDA_D3D10_DEPRECATED, 357
- CuD3D10map_flags_enum
 - CUDA_D3D10_DEPRECATED, 357
- cuD3D10MapResources
 - CUDA_D3D10_DEPRECATED, 357
- CuD3D10register_flags
 - CUDA_D3D10_DEPRECATED, 357
- CuD3D10register_flags_enum
 - CUDA_D3D10_DEPRECATED, 357
- cuD3D10RegisterResource
 - CUDA_D3D10_DEPRECATED, 358
- cuD3D10ResourceGetMappedArray
 - CUDA_D3D10_DEPRECATED, 359
- cuD3D10ResourceGetMappedPitch
 - CUDA_D3D10_DEPRECATED, 360
- cuD3D10ResourceGetMappedPointer
 - CUDA_D3D10_DEPRECATED, 360
- cuD3D10ResourceGetMappedSize
 - CUDA_D3D10_DEPRECATED, 361
- cuD3D10ResourceGetSurfaceDimensions
 - CUDA_D3D10_DEPRECATED, 362
- cuD3D10ResourceSetMapFlags
 - CUDA_D3D10_DEPRECATED, 362
- cuD3D10UnmapResources
 - CUDA_D3D10_DEPRECATED, 363
- cuD3D10UnregisterResource
 - CUDA_D3D10_DEPRECATED, 364
- cuD3D11CtxCreate
 - CUDA_D3D11, 366
- cuD3D11CtxCreateOnDevice
 - CUDA_D3D11, 366
- CuD3d11DeviceList
 - CUDA_D3D11, 365
- CuD3d11DeviceList_enum
 - CUDA_D3D11, 366
- cuD3D11GetDevice
 - CUDA_D3D11, 367
- cuD3D11GetDevices
 - CUDA_D3D11, 367
- cuD3D11GetDirect3DDevice
 - CUDA_D3D11, 368
- cuD3D9CtxCreate
 - CUDA_D3D9, 336
- cuD3D9CtxCreateOnDevice
 - CUDA_D3D9, 336
- CuD3d9DeviceList
 - CUDA_D3D9, 336
- CuD3d9DeviceList_enum
 - CUDA_D3D9, 336
- cuD3D9GetDevice
 - CUDA_D3D9, 337
- cuD3D9GetDevices
 - CUDA_D3D9, 337
- cuD3D9GetDirect3DDevice
 - CUDA_D3D9, 338
- CuD3d9map_flags
 - CUDA_D3D9_DEPRECATED, 342
- CuD3d9map_flags_enum
 - CUDA_D3D9_DEPRECATED, 342
- cuD3D9MapResources
 - CUDA_D3D9_DEPRECATED, 342
- CuD3d9register_flags
 - CUDA_D3D9_DEPRECATED, 342
- CuD3d9register_flags_enum
 - CUDA_D3D9_DEPRECATED, 342
- cuD3D9RegisterResource
 - CUDA_D3D9_DEPRECATED, 343
- cuD3D9ResourceGetMappedArray
 - CUDA_D3D9_DEPRECATED, 344
- cuD3D9ResourceGetMappedPitch
 - CUDA_D3D9_DEPRECATED, 345
- cuD3D9ResourceGetMappedPointer
 - CUDA_D3D9_DEPRECATED, 346
- cuD3D9ResourceGetMappedSize
 - CUDA_D3D9_DEPRECATED, 346
- cuD3D9ResourceGetSurfaceDimensions
 - CUDA_D3D9_DEPRECATED, 347
- cuD3D9ResourceSetMapFlags
 - CUDA_D3D9_DEPRECATED, 348
- cuD3D9UnmapResources
 - CUDA_D3D9_DEPRECATED, 348
- cuD3D9UnregisterResource
 - CUDA_D3D9_DEPRECATED, 349
- CUDA Driver API, 176

- CUDA Runtime API, [11](#)
- CUDA_D3D10
 - CU_D3D10_DEVICE_LIST_ALL, [351](#)
 - CU_D3D10_DEVICE_LIST_CURRENT_FRAME, [351](#)
 - CU_D3D10_DEVICE_LIST_NEXT_FRAME, [351](#)
- CUDA_D3D11
 - CU_D3D11_DEVICE_LIST_ALL, [366](#)
 - CU_D3D11_DEVICE_LIST_CURRENT_FRAME, [366](#)
 - CU_D3D11_DEVICE_LIST_NEXT_FRAME, [366](#)
- CUDA_D3D9
 - CU_D3D9_DEVICE_LIST_ALL, [336](#)
 - CU_D3D9_DEVICE_LIST_CURRENT_FRAME, [336](#)
 - CU_D3D9_DEVICE_LIST_NEXT_FRAME, [336](#)
- CUDA_ERROR_ALREADY_ACQUIRED
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_ALREADY_MAPPED
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_ARRAY_IS_MAPPED
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_ASSERT
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_CONTEXT_ALREADY_CURRENT
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_CONTEXT_ALREADY_IN_USE
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_CONTEXT_IS_DESTROYED
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_DEINITIALIZED
 - CUDA_TYPES, [190](#)
- CUDA_ERROR_ECC_UNCORRECTABLE
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_FILE_NOT_FOUND
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_HOST_MEMORY_ALREADY_REGISTERED
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_HOST_MEMORY_NOT_REGISTERED
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_INVALID_CONTEXT
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_INVALID_DEVICE
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_INVALID_HANDLE
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_INVALID_IMAGE
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_INVALID_SOURCE
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_INVALID_VALUE
 - CUDA_TYPES, [190](#)
- CUDA_ERROR_LAUNCH_FAILED
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_LAUNCH_INCOMPATIBLE_TEXTURING
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_LAUNCH_OUT_OF_RESOURCES
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_LAUNCH_TIMEOUT
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_MAP_FAILED
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_NO_BINARY_FOR_GPU
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_NO_DEVICE
 - CUDA_TYPES, [190](#)
- CUDA_ERROR_NOT_FOUND
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_NOT_INITIALIZED
 - CUDA_TYPES, [190](#)
- CUDA_ERROR_NOT_MAPPED
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_NOT_MAPPED_AS_ARRAY
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_NOT_MAPPED_AS_POINTER
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_NOT_READY
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_OPERATING_SYSTEM
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_OUT_OF_MEMORY
 - CUDA_TYPES, [190](#)
- CUDA_ERROR_PEER_ACCESS_ALREADY_ENABLED
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_PEER_ACCESS_NOT_ENABLED
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_PRIMARY_CONTEXT_ACTIVE
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_PROFILER_ALREADY_STARTED
 - CUDA_TYPES, [190](#)
- CUDA_ERROR_PROFILER_ALREADY_STOPPED
 - CUDA_TYPES, [190](#)
- CUDA_ERROR_PROFILER_DISABLED
 - CUDA_TYPES, [190](#)
- CUDA_ERROR_PROFILER_NOT_INITIALIZED
 - CUDA_TYPES, [190](#)
- CUDA_ERROR_SHARED_OBJECT_INIT_FAILED
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_SHARED_OBJECT_SYMBOL_NOT_FOUND
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_TOO_MANY_PEERS
 - CUDA_TYPES, [192](#)
- CUDA_ERROR_UNKNOWN

- CUDA_TYPES, [192](#)
- CUDA_ERROR_UNMAP_FAILED
 - CUDA_TYPES, [191](#)
- CUDA_ERROR_UNSUPPORTED_LIMIT
 - CUDA_TYPES, [191](#)
- CUDA_GL
 - CU_GL_DEVICE_LIST_ALL, [325](#)
 - CU_GL_DEVICE_LIST_CURRENT_FRAME, [325](#)
 - CU_GL_DEVICE_LIST_NEXT_FRAME, [325](#)
- CUDA_SUCCESS
 - CUDA_TYPES, [190](#)
- CUDA_TYPES
 - CU_AD_FORMAT_FLOAT, [189](#)
 - CU_AD_FORMAT_HALF, [189](#)
 - CU_AD_FORMAT_SIGNED_INT16, [189](#)
 - CU_AD_FORMAT_SIGNED_INT32, [189](#)
 - CU_AD_FORMAT_SIGNED_INT8, [189](#)
 - CU_AD_FORMAT_UNSIGNED_INT16, [189](#)
 - CU_AD_FORMAT_UNSIGNED_INT32, [189](#)
 - CU_AD_FORMAT_UNSIGNED_INT8, [189](#)
 - CU_COMPUTEMODE_DEFAULT, [189](#)
 - CU_COMPUTEMODE_EXCLUSIVE, [189](#)
 - CU_COMPUTEMODE_EXCLUSIVE_PROCESS, [190](#)
 - CU_COMPUTEMODE_PROHIBITED, [190](#)
 - CU_CTX_BLOCKING_SYNC, [190](#)
 - CU_CTX_LMEM_RESIZE_TO_MAX, [190](#)
 - CU_CTX_MAP_HOST, [190](#)
 - CU_CTX_SCHED_AUTO, [190](#)
 - CU_CTX_SCHED_BLOCKING_SYNC, [190](#)
 - CU_CTX_SCHED_SPIN, [190](#)
 - CU_CTX_SCHED_YIELD, [190](#)
 - CU_CUBEMAP_FACE_NEGATIVE_X, [189](#)
 - CU_CUBEMAP_FACE_NEGATIVE_Y, [189](#)
 - CU_CUBEMAP_FACE_NEGATIVE_Z, [189](#)
 - CU_CUBEMAP_FACE_POSITIVE_X, [189](#)
 - CU_CUBEMAP_FACE_POSITIVE_Y, [189](#)
 - CU_CUBEMAP_FACE_POSITIVE_Z, [189](#)
 - CU_DEVICE_ATTRIBUTE_ASYNC_ENGINE_COUNT, [194](#)
 - CU_DEVICE_ATTRIBUTE_CAN_MAP_HOST_MEMORY, [193](#)
 - CU_DEVICE_ATTRIBUTE_CAN_TEX2D_GATHER, [194](#)
 - CU_DEVICE_ATTRIBUTE_CLOCK_RATE, [193](#)
 - CU_DEVICE_ATTRIBUTE_COMPUTE_MODE, [193](#)
 - CU_DEVICE_ATTRIBUTE_CONCURRENT_KERNELS, [194](#)
 - CU_DEVICE_ATTRIBUTE_ECC_ENABLED, [194](#)
 - CU_DEVICE_ATTRIBUTE_GLOBAL_MEMORY_BUS_WIDTH, [194](#)
 - CU_DEVICE_ATTRIBUTE_GPU_OVERLAP, [193](#)
 - CU_DEVICE_ATTRIBUTE_INTEGRATED, [193](#)
 - CU_DEVICE_ATTRIBUTE_KERNEL_EXEC_TIMEOUT, [193](#)
 - CU_DEVICE_ATTRIBUTE_L2_CACHE_SIZE, [194](#)
 - CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_X, [192](#)
 - CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_Y, [192](#)
 - CU_DEVICE_ATTRIBUTE_MAX_BLOCK_DIM_Z, [193](#)
 - CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_X, [193](#)
 - CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_Y, [193](#)
 - CU_DEVICE_ATTRIBUTE_MAX_GRID_DIM_Z, [193](#)
 - CU_DEVICE_ATTRIBUTE_MAX_PITCH, [193](#)
 - CU_DEVICE_ATTRIBUTE_MAX_REGISTERS_PER_BLOCK, [193](#)
 - CU_DEVICE_ATTRIBUTE_MAX_SHARED_MEMORY_PER_BLOCK, [193](#)
 - CU_DEVICE_ATTRIBUTE_MAX_THREADS_PER_BLOCK, [192](#)
 - CU_DEVICE_ATTRIBUTE_MAX_THREADS_PER_MULTIPROCESSOR, [194](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_LAYERED_LAYERS, [195](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_LAYERED_WIDTH, [195](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE1D_WIDTH, [194](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_HEIGHT, [194](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_HEIGHT, [195](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_LAYERS, [195](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_LAYERED_WIDTH, [195](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE2D_WIDTH, [194](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_DEPTH, [194](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_HEIGHT, [194](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACE3D_WIDTH, [194](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACECUBEMAP_LAYERED_LAYERS, [195](#)
 - CU_DEVICE_ATTRIBUTE_MAXIMUM_SURFACECUBEMAP_LAYERED_WIDTH, [195](#)

- SURFACECUBEMAP_LAYERED_WIDTH, 195
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-SURFACECUBEMAP_WIDTH, 195
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE1D_LAYERED_LAYERS, 194
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE1D_LAYERED_WIDTH, 194
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE1D_LINEAR_WIDTH, 195
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE1D_WIDTH, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_ARRAY_HEIGHT, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_ARRAY_NUMSLICES, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_ARRAY_WIDTH, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_GATHER_HEIGHT, 194
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_GATHER_WIDTH, 194
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_HEIGHT, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_LAYERED_HEIGHT, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_LAYERED_LAYERS, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_LAYERED_WIDTH, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_LINEAR_HEIGHT, 195
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_LINEAR_PITCH, 195
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_LINEAR_WIDTH, 195
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE2D_WIDTH, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE3D_DEPTH, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE3D_DEPTH_ALTERNATE, 194
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE3D_HEIGHT, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE3D_HEIGHT_ALTERNATE, 194
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE3D_WIDTH, 193
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURE3D_WIDTH_ALTERNATE, 194
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURECUBEMAP_LAYERED_LAYERS, 194
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURECUBEMAP_LAYERED_WIDTH, 194
- CU_DEVICE_ATTRIBUTE_MAXIMUM_-TEXTURECUBEMAP_WIDTH, 194
- CU_DEVICE_ATTRIBUTE_MEMORY_-CLOCK_RATE, 194
- CU_DEVICE_ATTRIBUTE_-MULTIPROCESSOR_COUNT, 193
- CU_DEVICE_ATTRIBUTE_PCI_BUS_ID, 194
- CU_DEVICE_ATTRIBUTE_PCI_DEVICE_ID, 194
- CU_DEVICE_ATTRIBUTE_PCI_DOMAIN_ID, 194
- CU_DEVICE_ATTRIBUTE_REGISTERS_PER_BLOCK, 193
- CU_DEVICE_ATTRIBUTE_SHARED_-MEMORY_PER_BLOCK, 193
- CU_DEVICE_ATTRIBUTE_SURFACE_-ALIGNMENT, 194
- CU_DEVICE_ATTRIBUTE_TCC_DRIVER, 194
- CU_DEVICE_ATTRIBUTE_TEXTURE_-ALIGNMENT, 193
- CU_DEVICE_ATTRIBUTE_TEXTURE_PITCH_-ALIGNMENT, 194
- CU_DEVICE_ATTRIBUTE_TOTAL_-CONSTANT_MEMORY, 193
- CU_DEVICE_ATTRIBUTE_UNIFIED_-ADDRESSING, 194
- CU_DEVICE_ATTRIBUTE_WARP_SIZE, 193
- CU_EVENT_BLOCKING_SYNC, 195
- CU_EVENT_DEFAULT, 195
- CU_EVENT_DISABLE_TIMING, 195
- CU_EVENT_INTERPROCESS, 195
- CU_FUNC_ATTRIBUTE_BINARY_VERSION, 196
- CU_FUNC_ATTRIBUTE_CONST_SIZE_BYTES, 196
- CU_FUNC_ATTRIBUTE_LOCAL_SIZE_BYTES, 196
- CU_FUNC_ATTRIBUTE_MAX_THREADS_-PER_BLOCK, 196
- CU_FUNC_ATTRIBUTE_NUM_REGS, 196
- CU_FUNC_ATTRIBUTE_PTX_VERSION, 196
- CU_FUNC_ATTRIBUTE_SHARED_SIZE_-BYTES, 196
- CU_FUNC_CACHE_PREFER_EQUAL, 196
- CU_FUNC_CACHE_PREFER_L1, 196
- CU_FUNC_CACHE_PREFER_NONE, 196
- CU_FUNC_CACHE_PREFER_SHARED, 196
- CU_JIT_ERROR_LOG_BUFFER, 197
- CU_JIT_ERROR_LOG_BUFFER_SIZE_BYTES, 197
- CU_JIT_FALLBACK_STRATEGY, 198
- CU_JIT_INFO_LOG_BUFFER, 197

- CU_JIT_INFO_LOG_BUFFER_SIZE_BYTES, [197](#)
- CU_JIT_MAX_REGISTERS, [197](#)
- CU_JIT_OPTIMIZATION_LEVEL, [197](#)
- CU_JIT_TARGET, [197](#)
- CU_JIT_TARGET_FROM_CUCONTEXT, [197](#)
- CU_JIT_THREADS_PER_BLOCK, [197](#)
- CU_JIT_WALL_TIME, [197](#)
- CU_LIMIT_MALLOC_HEAP_SIZE, [198](#)
- CU_LIMIT_PRINTF_FIFO_SIZE, [198](#)
- CU_LIMIT_STACK_SIZE, [198](#)
- CU_MEMORYTYPE_ARRAY, [198](#)
- CU_MEMORYTYPE_DEVICE, [198](#)
- CU_MEMORYTYPE_HOST, [198](#)
- CU_MEMORYTYPE_UNIFIED, [198](#)
- CU_POINTER_ATTRIBUTE_CONTEXT, [198](#)
- CU_POINTER_ATTRIBUTE_DEVICE_POINTER, [199](#)
- CU_POINTER_ATTRIBUTE_HOST_POINTER, [199](#)
- CU_POINTER_ATTRIBUTE_MEMORY_TYPE, [198](#)
- CU_PREFER_BINARY, [197](#)
- CU_PREFER_PTX, [197](#)
- CU_TARGET_COMPUTE_10, [198](#)
- CU_TARGET_COMPUTE_11, [198](#)
- CU_TARGET_COMPUTE_12, [198](#)
- CU_TARGET_COMPUTE_13, [198](#)
- CU_TARGET_COMPUTE_20, [198](#)
- CU_TARGET_COMPUTE_21, [198](#)
- CU_TR_ADDRESS_MODE_BORDER, [189](#)
- CU_TR_ADDRESS_MODE_CLAMP, [189](#)
- CU_TR_ADDRESS_MODE_MIRROR, [189](#)
- CU_TR_ADDRESS_MODE_WRAP, [189](#)
- CU_TR_FILTER_MODE_LINEAR, [195](#)
- CU_TR_FILTER_MODE_POINT, [195](#)
- CUDA_ERROR_ALREADY_ACQUIRED, [191](#)
- CUDA_ERROR_ALREADY_MAPPED, [191](#)
- CUDA_ERROR_ARRAY_IS_MAPPED, [191](#)
- CUDA_ERROR_ASSERT, [192](#)
- CUDA_ERROR_CONTEXT_ALREADY_CURRENT, [191](#)
- CUDA_ERROR_CONTEXT_ALREADY_IN_USE, [191](#)
- CUDA_ERROR_CONTEXT_IS_DESTROYED, [192](#)
- CUDA_ERROR_DEINITIALIZED, [190](#)
- CUDA_ERROR_ECC_UNCORRECTABLE, [191](#)
- CUDA_ERROR_FILE_NOT_FOUND, [191](#)
- CUDA_ERROR_HOST_MEMORY_ALREADY_REGISTERED, [192](#)
- CUDA_ERROR_HOST_MEMORY_NOT_REGISTERED, [192](#)
- CUDA_ERROR_INVALID_CONTEXT, [191](#)
- CUDA_ERROR_INVALID_DEVICE, [191](#)
- CUDA_ERROR_INVALID_HANDLE, [191](#)
- CUDA_ERROR_INVALID_IMAGE, [191](#)
- CUDA_ERROR_INVALID_SOURCE, [191](#)
- CUDA_ERROR_INVALID_VALUE, [190](#)
- CUDA_ERROR_LAUNCH_FAILED, [192](#)
- CUDA_ERROR_LAUNCH_INCOMPATIBLE_TEXTURING, [192](#)
- CUDA_ERROR_LAUNCH_OUT_OF_RESOURCES, [192](#)
- CUDA_ERROR_LAUNCH_TIMEOUT, [192](#)
- CUDA_ERROR_MAP_FAILED, [191](#)
- CUDA_ERROR_NO_BINARY_FOR_GPU, [191](#)
- CUDA_ERROR_NO_DEVICE, [190](#)
- CUDA_ERROR_NOT_FOUND, [191](#)
- CUDA_ERROR_NOT_INITIALIZED, [190](#)
- CUDA_ERROR_NOT_MAPPED, [191](#)
- CUDA_ERROR_NOT_MAPPED_AS_ARRAY, [191](#)
- CUDA_ERROR_NOT_MAPPED_AS_POINTER, [191](#)
- CUDA_ERROR_NOT_READY, [191](#)
- CUDA_ERROR_OPERATING_SYSTEM, [191](#)
- CUDA_ERROR_OUT_OF_MEMORY, [190](#)
- CUDA_ERROR_PEER_ACCESS_ALREADY_ENABLED, [192](#)
- CUDA_ERROR_PEER_ACCESS_NOT_ENABLED, [192](#)
- CUDA_ERROR_PRIMARY_CONTEXT_ACTIVE, [192](#)
- CUDA_ERROR_PROFILER_ALREADY_STARTED, [190](#)
- CUDA_ERROR_PROFILER_ALREADY_STOPPED, [190](#)
- CUDA_ERROR_PROFILER_DISABLED, [190](#)
- CUDA_ERROR_PROFILER_NOT_INITIALIZED, [190](#)
- CUDA_ERROR_SHARED_OBJECT_INIT_FAILED, [191](#)
- CUDA_ERROR_SHARED_OBJECT_SYMBOL_NOT_FOUND, [191](#)
- CUDA_ERROR_TOO_MANY_PEERS, [192](#)
- CUDA_ERROR_UNKNOWN, [192](#)
- CUDA_ERROR_UNMAP_FAILED, [191](#)
- CUDA_ERROR_UNSUPPORTED_LIMIT, [191](#)
- CUDA_SUCCESS, [190](#)
- CUDA_ARRAY3D_2DARRAY
 - CUDA_TYPES, [185](#)
- CUDA_ARRAY3D_CUBEMAP
 - CUDA_TYPES, [185](#)
- CUDA_ARRAY3D_DESCRIPTOR
 - CUDA_TYPES, [186](#)
- CUDA_ARRAY3D_DESCRIPTOR_st, [469](#)
- Depth, [469](#)

- Flags, [469](#)
- Format, [469](#)
- Height, [469](#)
- NumChannels, [469](#)
- Width, [470](#)
- CUDA_ARRAY3D_LAYERED
 - CUDA_TYPES, [185](#)
- CUDA_ARRAY3D_SURFACE_LDST
 - CUDA_TYPES, [185](#)
- CUDA_ARRAY3D_TEXTURE_GATHER
 - CUDA_TYPES, [185](#)
- CUDA_ARRAY_DESCRIPTOR
 - CUDA_TYPES, [186](#)
- CUDA_ARRAY_DESCRIPTOR_st, [471](#)
 - Format, [471](#)
 - Height, [471](#)
 - NumChannels, [471](#)
 - Width, [471](#)
- CUDA_CTX
 - cuCtxCreate, [211](#)
 - cuCtxDestroy, [212](#)
 - cuCtxGetApiVersion, [212](#)
 - cuCtxGetCacheConfig, [213](#)
 - cuCtxGetCurrent, [213](#)
 - cuCtxGetDevice, [214](#)
 - cuCtxGetLimit, [214](#)
 - cuCtxPopCurrent, [215](#)
 - cuCtxPushCurrent, [215](#)
 - cuCtxSetCacheConfig, [216](#)
 - cuCtxSetCurrent, [216](#)
 - cuCtxSetLimit, [217](#)
 - cuCtxSynchronize, [218](#)
- CUDA_CTX_DEPRECATED
 - cuCtxAttach, [219](#)
 - cuCtxDetach, [219](#)
- CUDA_D3D10
 - cuD3D10CtxCreate, [351](#)
 - cuD3D10CtxCreateOnDevice, [351](#)
 - CUd3d10DeviceList, [351](#)
 - CUd3d10DeviceList_enum, [351](#)
 - cuD3D10GetDevice, [352](#)
 - cuD3D10GetDevices, [352](#)
 - cuD3D10GetDirect3DDevice, [353](#)
 - cuGraphicsD3D10RegisterResource, [353](#)
- CUDA_D3D10_DEPRECATED
 - CUD3D10map_flags, [357](#)
 - CUD3D10map_flags_enum, [357](#)
 - cuD3D10MapResources, [357](#)
 - CUD3D10register_flags, [357](#)
 - CUD3D10register_flags_enum, [357](#)
 - cuD3D10RegisterResource, [358](#)
 - cuD3D10ResourceGetMappedArray, [359](#)
 - cuD3D10ResourceGetMappedPitch, [360](#)
 - cuD3D10ResourceGetMappedPointer, [360](#)
 - cuD3D10ResourceGetMappedSize, [361](#)
 - cuD3D10ResourceGetSurfaceDimensions, [362](#)
 - cuD3D10ResourceSetMapFlags, [362](#)
 - cuD3D10UnmapResources, [363](#)
 - cuD3D10UnregisterResource, [364](#)
- CUDA_D3D11
 - cuD3D11CtxCreate, [366](#)
 - cuD3D11CtxCreateOnDevice, [366](#)
 - CUd3d11DeviceList, [365](#)
 - CUd3d11DeviceList_enum, [366](#)
 - cuD3D11GetDevice, [367](#)
 - cuD3D11GetDevices, [367](#)
 - cuD3D11GetDirect3DDevice, [368](#)
 - cuGraphicsD3D11RegisterResource, [368](#)
- CUDA_D3D9
 - cuD3D9CtxCreate, [336](#)
 - cuD3D9CtxCreateOnDevice, [336](#)
 - CUd3d9DeviceList, [336](#)
 - CUd3d9DeviceList_enum, [336](#)
 - cuD3D9GetDevice, [337](#)
 - cuD3D9GetDevices, [337](#)
 - cuD3D9GetDirect3DDevice, [338](#)
 - cuGraphicsD3D9RegisterResource, [338](#)
- CUDA_D3D9_DEPRECATED
 - CUd3d9map_flags, [342](#)
 - CUd3d9map_flags_enum, [342](#)
 - cuD3D9MapResources, [342](#)
 - CUd3d9register_flags, [342](#)
 - CUd3d9register_flags_enum, [342](#)
 - cuD3D9RegisterResource, [343](#)
 - cuD3D9ResourceGetMappedArray, [344](#)
 - cuD3D9ResourceGetMappedPitch, [345](#)
 - cuD3D9ResourceGetMappedPointer, [346](#)
 - cuD3D9ResourceGetMappedSize, [346](#)
 - cuD3D9ResourceGetSurfaceDimensions, [347](#)
 - cuD3D9ResourceSetMapFlags, [348](#)
 - cuD3D9UnmapResources, [348](#)
 - cuD3D9UnregisterResource, [349](#)
- CUDA_DEVICE
 - cuDeviceComputeCapability, [202](#)
 - cuDeviceGet, [203](#)
 - cuDeviceGetAttribute, [203](#)
 - cuDeviceGetCount, [206](#)
 - cuDeviceGetName, [207](#)
 - cuDeviceGetProperties, [207](#)
 - cuDeviceTotalMem, [208](#)
- CUDA_EVENT
 - cuEventCreate, [288](#)
 - cuEventDestroy, [289](#)
 - cuEventElapsedTime, [289](#)
 - cuEventQuery, [290](#)
 - cuEventRecord, [290](#)
 - cuEventSynchronize, [291](#)
- CUDA_EXEC

- cuFuncGetAttribute, 292
- cuFuncSetCacheConfig, 293
- cuLaunchKernel, 294
- CUDA_EXEC_DEPRECATED
 - cuFuncSetBlockShape, 296
 - cuFuncSetSharedSize, 297
 - cuLaunch, 297
 - cuLaunchGrid, 298
 - cuLaunchGridAsync, 298
 - cuParamSetf, 299
 - cuParamSeti, 300
 - cuParamSetSize, 300
 - cuParamSetTexRef, 301
 - cuParamSetv, 301
- CUDA_GL
 - cuGLCtxCreate, 325
 - CUGLDeviceList, 324
 - CUGLDeviceList_enum, 325
 - cuGLGetDevices, 325
 - cuGraphicsGLRegisterBuffer, 326
 - cuGraphicsGLRegisterImage, 326
 - cuWGLGetDevice, 328
- CUDA_GL_DEPRECATED
 - cuGLInit, 330
 - CUGLmap_flags, 329
 - CUGLmap_flags_enum, 330
 - cuGLMapBufferObject, 330
 - cuGLMapBufferObjectAsync, 331
 - cuGLRegisterBufferObject, 331
 - cuGLSetBufferObjectMapFlags, 332
 - cuGLUnmapBufferObject, 332
 - cuGLUnmapBufferObjectAsync, 333
 - cuGLUnregisterBufferObject, 333
- CUDA_GRAPHICS
 - cuGraphicsMapResources, 317
 - cuGraphicsResourceGetMappedPointer, 318
 - cuGraphicsResourceSetMapFlags, 318
 - cuGraphicsSubResourceGetMappedArray, 319
 - cuGraphicsUnmapResources, 320
 - cuGraphicsUnregisterResource, 320
- CUDA_INITIALIZE
 - cuInit, 200
- CUDA_IPC_HANDLE_SIZE
 - CUDART_TYPES, 165
- CUDA_MATH_DOUBLE
 - acos, 405
 - acosh, 405
 - asin, 406
 - asinh, 406
 - atan, 406
 - atan2, 406
 - atanh, 407
 - cbirt, 407
 - ceil, 407
 - copysign, 407
 - cos, 408
 - cosh, 408
 - cospi, 408
 - erf, 408
 - erfc, 409
 - erfcinv, 409
 - erfcx, 409
 - erfinv, 409
 - exp, 410
 - exp10, 410
 - exp2, 410
 - expm1, 410
 - fabs, 411
 - fdim, 411
 - floor, 411
 - fma, 411
 - fmax, 412
 - fmin, 412
 - fmod, 412
 - frexp, 413
 - hypot, 413
 - ilogb, 413
 - isfinite, 414
 - isinf, 414
 - isnan, 414
 - j0, 414
 - j1, 414
 - jn, 415
 - ldexp, 415
 - lgamma, 415
 - llrint, 416
 - llround, 416
 - log, 416
 - log10, 416
 - log1p, 417
 - log2, 417
 - logb, 417
 - lrint, 418
 - lround, 418
 - modf, 418
 - nan, 418
 - nearbyint, 419
 - nextafter, 419
 - pow, 419
 - rcbrt, 420
 - remainder, 420
 - remquo, 420
 - rint, 421
 - round, 421
 - rsqrt, 421
 - scalbln, 421
 - scalbn, 422
 - signbit, 422

- sin, [422](#)
- sincos, [422](#)
- sinh, [423](#)
- sinpi, [423](#)
- sqrt, [423](#)
- tan, [423](#)
- tanh, [424](#)
- tgamma, [424](#)
- trunc, [424](#)
- y0, [424](#)
- y1, [425](#)
- yn, [425](#)
- CUDA_MATH_INTRINSIC_CAST
 - __double2float_rd, [455](#)
 - __double2float_rn, [455](#)
 - __double2float_ru, [455](#)
 - __double2float_rz, [455](#)
 - __double2hiint, [456](#)
 - __double2int_rd, [456](#)
 - __double2int_rn, [456](#)
 - __double2int_ru, [456](#)
 - __double2int_rz, [456](#)
 - __double2ll_rd, [456](#)
 - __double2ll_rn, [457](#)
 - __double2ll_ru, [457](#)
 - __double2ll_rz, [457](#)
 - __double2loint, [457](#)
 - __double2uint_rd, [457](#)
 - __double2uint_rn, [457](#)
 - __double2uint_ru, [458](#)
 - __double2uint_rz, [458](#)
 - __double2ull_rd, [458](#)
 - __double2ull_rn, [458](#)
 - __double2ull_ru, [458](#)
 - __double2ull_rz, [458](#)
 - __double_as_longlong, [459](#)
 - __float2half_rn, [459](#)
 - __float2int_rd, [459](#)
 - __float2int_rn, [459](#)
 - __float2int_ru, [459](#)
 - __float2int_rz, [459](#)
 - __float2ll_rd, [460](#)
 - __float2ll_rn, [460](#)
 - __float2ll_ru, [460](#)
 - __float2ll_rz, [460](#)
 - __float2uint_rd, [460](#)
 - __float2uint_rn, [460](#)
 - __float2uint_ru, [461](#)
 - __float2uint_rz, [461](#)
 - __float2ull_rd, [461](#)
 - __float2ull_rn, [461](#)
 - __float2ull_ru, [461](#)
 - __float2ull_rz, [461](#)
 - __float_as_int, [462](#)
 - __half2float, [462](#)
 - __hiloint2double, [462](#)
 - __int2double_rn, [462](#)
 - __int2float_rd, [462](#)
 - __int2float_rn, [462](#)
 - __int2float_ru, [463](#)
 - __int2float_rz, [463](#)
 - __int_as_float, [463](#)
 - __ll2double_rd, [463](#)
 - __ll2double_rn, [463](#)
 - __ll2double_ru, [463](#)
 - __ll2double_rz, [464](#)
 - __ll2float_rd, [464](#)
 - __ll2float_rn, [464](#)
 - __ll2float_ru, [464](#)
 - __ll2float_rz, [464](#)
 - __longlong_as_double, [464](#)
 - __uint2double_rn, [465](#)
 - __uint2float_rd, [465](#)
 - __uint2float_rn, [465](#)
 - __uint2float_ru, [465](#)
 - __uint2float_rz, [465](#)
 - __ull2double_rd, [465](#)
 - __ull2double_rn, [466](#)
 - __ull2double_ru, [466](#)
 - __ull2double_rz, [466](#)
 - __ull2float_rd, [466](#)
 - __ull2float_rn, [466](#)
 - __ull2float_ru, [466](#)
 - __ull2float_rz, [467](#)
- CUDA_MATH_INTRINSIC_DOUBLE
 - __dadd_rd, [439](#)
 - __dadd_rn, [439](#)
 - __dadd_ru, [440](#)
 - __dadd_rz, [440](#)
 - __ddiv_rd, [440](#)
 - __ddiv_rn, [440](#)
 - __ddiv_ru, [441](#)
 - __ddiv_rz, [441](#)
 - __dmul_rd, [441](#)
 - __dmul_rn, [441](#)
 - __dmul_ru, [442](#)
 - __dmul_rz, [442](#)
 - __drcp_rd, [442](#)
 - __drcp_rn, [442](#)
 - __drcp_ru, [443](#)
 - __drcp_rz, [443](#)
 - __dsqrt_rd, [443](#)
 - __dsqrt_rn, [443](#)
 - __dsqrt_ru, [444](#)
 - __dsqrt_rz, [444](#)
 - __fma_rd, [444](#)
 - __fma_rn, [444](#)
 - __fma_ru, [445](#)

- __fma_rz, 445
- CUDA_MATH_INTRINSIC_INT
 - __brev, 447
 - __brevll, 447
 - __byte_perm, 447
 - __clz, 447
 - __clzll, 448
 - __ffs, 448
 - __ffsll, 448
 - __mul24, 448
 - __mul64hi, 448
 - __mulhi, 448
 - __popc, 449
 - __popc1l, 449
 - __sad, 449
 - __umul24, 449
 - __umul64hi, 449
 - __umulhi, 449
 - __usad, 450
- CUDA_MATH_INTRINSIC_SINGLE
 - __cosf, 428
 - __exp10f, 428
 - __expf, 428
 - __fadd_rd, 429
 - __fadd_rn, 429
 - __fadd_ru, 429
 - __fadd_rz, 429
 - __fdiv_rd, 430
 - __fdiv_rn, 430
 - __fdiv_ru, 430
 - __fdiv_rz, 430
 - __fdividef, 431
 - __fmaf_rd, 431
 - __fmaf_rn, 431
 - __fmaf_ru, 432
 - __fmaf_rz, 432
 - __fmul_rd, 432
 - __fmul_rn, 432
 - __fmul_ru, 433
 - __fmul_rz, 433
 - __frcp_rd, 433
 - __frcp_rn, 433
 - __frcp_ru, 434
 - __frcp_rz, 434
 - __fsqrt_rd, 434
 - __fsqrt_rn, 434
 - __fsqrt_ru, 435
 - __fsqrt_rz, 435
 - __log10f, 435
 - __log2f, 435
 - __logf, 436
 - __powf, 436
 - __saturatef, 436
 - __sincosf, 436
 - __sinf, 437
 - __tanf, 437
- CUDA_MATH_SINGLE
 - acosf, 380
 - acoshf, 380
 - asinf, 381
 - asinhf, 381
 - atan2f, 381
 - atanf, 381
 - atanhf, 382
 - cbrtf, 382
 - ceilf, 382
 - copysignf, 382
 - cosf, 383
 - coshf, 383
 - cospif, 383
 - erfcf, 383
 - erfcinvf, 384
 - erfcxf, 384
 - erff, 384
 - erfinvf, 384
 - exp10f, 385
 - exp2f, 385
 - expf, 385
 - expm1f, 385
 - fabsf, 386
 - fdimf, 386
 - fdividef, 386
 - floorf, 386
 - fmaf, 387
 - fmaxf, 387
 - fminf, 387
 - fmodf, 388
 - frexpf, 388
 - hypotf, 388
 - ilogbf, 389
 - isfinite, 389
 - isinf, 389
 - isnan, 389
 - j0f, 389
 - j1f, 390
 - jnf, 390
 - ldexpf, 390
 - lgammaf, 391
 - llrintf, 391
 - llroundf, 391
 - log10f, 391
 - log1pf, 392
 - log2f, 392
 - logbf, 392
 - logf, 392
 - lrintf, 393
 - lroundf, 393
 - modff, 393

- nanf, 393
- nearbyintf, 394
- nextafterf, 394
- powf, 394
- rcbrtf, 395
- remainderf, 395
- remquof, 395
- rintf, 396
- roundf, 396
- rsqrtf, 396
- scalblnf, 396
- scalbnf, 397
- signbit, 397
- sincosf, 397
- sinf, 397
- sinhf, 398
- sinpif, 398
- sqrtf, 398
- tanf, 398
- tanhf, 399
- tgammaf, 399
- truncf, 399
- y0f, 399
- y1f, 400
- ynf, 400
- CUDA_MEM
 - cuArray3DCreate, 232
 - cuArray3DGetDescriptor, 234
 - cuArrayCreate, 235
 - cuArrayDestroy, 236
 - cuArrayGetDescriptor, 237
 - cuDeviceGetByPCIBusId, 237
 - cuDeviceGetPCIBusId, 238
 - cuIpcCloseMemHandle, 238
 - cuIpcGetEventHandle, 239
 - cuIpcGetMemHandle, 239
 - cuIpcOpenEventHandle, 240
 - cuIpcOpenMemHandle, 240
 - cuMemAlloc, 241
 - cuMemAllocHost, 241
 - cuMemAllocPitch, 242
 - cuMemcpy, 243
 - cuMemcpy2D, 243
 - cuMemcpy2DAsync, 246
 - cuMemcpy2DUnaligned, 248
 - cuMemcpy3D, 250
 - cuMemcpy3DAsync, 253
 - cuMemcpy3DPeer, 255
 - cuMemcpy3DPeerAsync, 256
 - cuMemcpyAsync, 256
 - cuMemcpyAtoA, 257
 - cuMemcpyAtoD, 258
 - cuMemcpyAtoH, 258
 - cuMemcpyAtoHAsync, 259
 - cuMemcpyDtoA, 260
 - cuMemcpyDtoD, 260
 - cuMemcpyDtoDAsync, 261
 - cuMemcpyDtoH, 261
 - cuMemcpyDtoHAsync, 262
 - cuMemcpyHtoA, 263
 - cuMemcpyHtoAAsync, 263
 - cuMemcpyHtoD, 264
 - cuMemcpyHtoDAsync, 264
 - cuMemcpyPeer, 265
 - cuMemcpyPeerAsync, 266
 - cuMemFree, 266
 - cuMemFreeHost, 267
 - cuMemGetAddressRange, 267
 - cuMemGetInfo, 268
 - cuMemHostAlloc, 268
 - cuMemHostGetDevicePointer, 270
 - cuMemHostGetFlags, 270
 - cuMemHostRegister, 271
 - cuMemHostUnregister, 272
 - cuMemsetD16, 272
 - cuMemsetD16Async, 273
 - cuMemsetD2D16, 273
 - cuMemsetD2D16Async, 274
 - cuMemsetD2D32, 275
 - cuMemsetD2D32Async, 275
 - cuMemsetD2D8, 276
 - cuMemsetD2D8Async, 277
 - cuMemsetD32, 277
 - cuMemsetD32Async, 278
 - cuMemsetD8, 279
 - cuMemsetD8Async, 279
- CUDA_MEMCPY2D
 - CUDA_TYPES, 186
- CUDA_MEMCPY2D_st, 472
 - dstArray, 472
 - dstDevice, 472
 - dstHost, 472
 - dstMemoryType, 472
 - dstPitch, 472
 - dstXInBytes, 472
 - dstY, 473
 - Height, 473
 - srcArray, 473
 - srcDevice, 473
 - srcHost, 473
 - srcMemoryType, 473
 - srcPitch, 473
 - srcXInBytes, 473
 - srcY, 473
 - WidthInBytes, 473
- CUDA_MEMCPY3D
 - CUDA_TYPES, 186
- CUDA_MEMCPY3D_PEER

- CUDA_TYPES, 186
- CUDA_MEMCPY3D_PEER_st, 474
 - Depth, 474
 - dstArray, 474
 - dstContext, 474
 - dstDevice, 474
 - dstHeight, 475
 - dstHost, 475
 - dstLOD, 475
 - dstMemoryType, 475
 - dstPitch, 475
 - dstXInBytes, 475
 - dstY, 475
 - dstZ, 475
 - Height, 475
 - srcArray, 475
 - srcContext, 475
 - srcDevice, 475
 - srcHeight, 476
 - srcHost, 476
 - srcLOD, 476
 - srcMemoryType, 476
 - srcPitch, 476
 - srcXInBytes, 476
 - srcY, 476
 - srcZ, 476
 - WidthInBytes, 476
- CUDA_MEMCPY3D_st, 477
 - Depth, 477
 - dstArray, 477
 - dstDevice, 477
 - dstHeight, 477
 - dstHost, 478
 - dstLOD, 478
 - dstMemoryType, 478
 - dstPitch, 478
 - dstXInBytes, 478
 - dstY, 478
 - dstZ, 478
 - Height, 478
 - reserved0, 478
 - reserved1, 478
 - srcArray, 478
 - srcDevice, 478
 - srcHeight, 479
 - srcHost, 479
 - srcLOD, 479
 - srcMemoryType, 479
 - srcPitch, 479
 - srcXInBytes, 479
 - srcY, 479
 - srcZ, 479
 - WidthInBytes, 479
- CUDA_MODULE
 - cuModuleGetFunction, 221
 - cuModuleGetGlobal, 222
 - cuModuleGetSurfRef, 222
 - cuModuleGetTexRef, 223
 - cuModuleLoad, 223
 - cuModuleLoadData, 224
 - cuModuleLoadDataEx, 224
 - cuModuleLoadFatBinary, 226
 - cuModuleUnload, 226
- CUDA_PEER_ACCESS
 - cuCtxDisablePeerAccess, 315
 - cuCtxEnablePeerAccess, 315
 - cuDeviceCanAccessPeer, 316
- CUDA_PROFILER
 - cuProfilerInitialize, 322
 - cuProfilerStart, 323
 - cuProfilerStop, 323
- CUDA_STREAM
 - cuStreamCreate, 285
 - cuStreamDestroy, 285
 - cuStreamQuery, 286
 - cuStreamSynchronize, 286
 - cuStreamWaitEvent, 287
- CUDA_SURFREF
 - cuSurfRefGetArray, 313
 - cuSurfRefSetArray, 313
- CUDA_TEXREF
 - cuTexRefGetAddress, 304
 - cuTexRefGetAddressMode, 304
 - cuTexRefGetArray, 304
 - cuTexRefGetFilterMode, 305
 - cuTexRefGetFlags, 305
 - cuTexRefGetFormat, 306
 - cuTexRefSetAddress, 306
 - cuTexRefSetAddress2D, 307
 - cuTexRefSetAddressMode, 307
 - cuTexRefSetArray, 308
 - cuTexRefSetFilterMode, 308
 - cuTexRefSetFlags, 309
 - cuTexRefSetFormat, 309
- CUDA_TEXREF_DEPRECATED
 - cuTexRefCreate, 311
 - cuTexRefDestroy, 311
- CUDA_TYPES
 - CU_IPC_HANDLE_SIZE, 183
 - CU_LAUNCH_PARAM_BUFFER_POINTER, 183
 - CU_LAUNCH_PARAM_BUFFER_SIZE, 184
 - CU_LAUNCH_PARAM_END, 184
 - CU_MEMHOSTALLOC_DEVICEMAP, 184
 - CU_MEMHOSTALLOC_PORTABLE, 184
 - CU_MEMHOSTALLOC_WRITECOMBINED, 184
 - CU_MEMHOSTREGISTER_DEVICEMAP, 184
 - CU_MEMHOSTREGISTER_PORTABLE, 184

- CU_PARAM_TR_DEFAULT, 184
- CU_TRSA_OVERRIDE_FORMAT, 184
- CU_TRSF_NORMALIZED_COORDINATES, 184
- CU_TRSF_READ_AS_INTEGER, 185
- CU_TRSF_SRGB, 185
- CUaddress_mode, 185
- CUaddress_mode_enum, 189
- CUarray, 185
- CUarray_cubemap_face, 186
- CUarray_cubemap_face_enum, 189
- CUarray_format, 186
- CUarray_format_enum, 189
- CUcomputemode, 186
- CUcomputemode_enum, 189
- CUcontext, 186
- CUctx_flags, 186
- CUctx_flags_enum, 190
- CUDA_ARRAY3D_2DARRAY, 185
- CUDA_ARRAY3D_CUBEMAP, 185
- CUDA_ARRAY3D_DESCRIPTOR, 186
- CUDA_ARRAY3D_LAYERED, 185
- CUDA_ARRAY3D_SURFACE_LDST, 185
- CUDA_ARRAY3D_TEXTURE_GATHER, 185
- CUDA_ARRAY_DESCRIPTOR, 186
- CUDA_MEMCPY2D, 186
- CUDA_MEMCPY3D, 186
- CUDA_MEMCPY3D_PEER, 186
- CUDA_VERSION, 185
- cudaError_enum, 190
- CUdevice, 186
- CUdevice_attribute, 186
- CUdevice_attribute_enum, 192
- CUdeviceptr, 187
- CUdevprop, 187
- CUEvent, 187
- CUEvent_flags, 187
- CUEvent_flags_enum, 195
- CUfilter_mode, 187
- CUfilter_mode_enum, 195
- CUfunc_cache, 187
- CUfunc_cache_enum, 195
- CUfunction, 187
- CUfunction_attribute, 187
- CUfunction_attribute_enum, 196
- CUgraphicsMapResourceFlags, 187
- CUgraphicsMapResourceFlags_enum, 196
- CUgraphicsRegisterFlags, 187
- CUgraphicsRegisterFlags_enum, 196
- CUgraphicsResource, 187
- CUjit_fallback, 187
- CUjit_fallback_enum, 196
- CUjit_option, 188
- CUjit_option_enum, 197
- CUjit_target, 188
- CUjit_target_enum, 198
- CULimit, 188
- CULimit_enum, 198
- CUmemorytype, 188
- CUmemorytype_enum, 198
- CUmodule, 188
- CUpointer_attribute, 188
- CUpointer_attribute_enum, 198
- CUresult, 188
- CUstream, 188
- CUsurfref, 188
- CUtexref, 188
- CUDA_UNIFIED
 - cuPointerGetAttribute, 282
- CUDA_VDPAU
 - cuGraphicsVDPAURegisterOutputSurface, 371
 - cuGraphicsVDPAURegisterVideoSurface, 372
 - cuVDPAUCtxCreate, 373
 - cuVDPAUGetDevice, 373
- CUDA_VERSION
 - CUDA_TYPES, 185
 - cuDriverGetVersion, 201
- cudaAddressModeBorder
 - CUDART_TYPES, 175
- cudaAddressModeClamp
 - CUDART_TYPES, 175
- cudaAddressModeMirror
 - CUDART_TYPES, 175
- cudaAddressModeWrap
 - CUDART_TYPES, 175
- cudaArrayCubemap
 - CUDART_TYPES, 165
- cudaArrayDefault
 - CUDART_TYPES, 165
- cudaArrayLayered
 - CUDART_TYPES, 165
- cudaArraySurfaceLoadStore
 - CUDART_TYPES, 165
- cudaArrayTextureGather
 - CUDART_TYPES, 165
- cudaBindSurfaceToArray
 - CUDART_HIGHLEVEL, 122, 123
 - CUDART_SURFACE, 118
- cudaBindTexture
 - CUDART_HIGHLEVEL, 123, 124
 - CUDART_TEXTURE, 113
- cudaBindTexture2D
 - CUDART_HIGHLEVEL, 124, 125
 - CUDART_TEXTURE, 114
- cudaBindTextureToArray
 - CUDART_HIGHLEVEL, 126
 - CUDART_TEXTURE, 115
- cudaBoundaryModeClamp
 - CUDART_TYPES, 174

- cudaBoundaryModeTrap
 - CUDART_TYPES, [174](#)
- cudaBoundaryModeZero
 - CUDART_TYPES, [174](#)
- cudaChannelFormatDesc, [480](#)
 - f, [480](#)
 - w, [480](#)
 - x, [480](#)
 - y, [480](#)
 - z, [480](#)
- cudaChannelFormatKind
 - CUDART_TYPES, [168](#)
- cudaChannelFormatKindFloat
 - CUDART_TYPES, [168](#)
- cudaChannelFormatKindNone
 - CUDART_TYPES, [168](#)
- cudaChannelFormatKindSigned
 - CUDART_TYPES, [168](#)
- cudaChannelFormatKindUnsigned
 - CUDART_TYPES, [168](#)
- cudaChooseDevice
 - CUDART_DEVICE, [14](#)
- cudaComputeMode
 - CUDART_TYPES, [168](#)
- cudaComputeModeDefault
 - CUDART_TYPES, [169](#)
- cudaComputeModeExclusive
 - CUDART_TYPES, [169](#)
- cudaComputeModeExclusiveProcess
 - CUDART_TYPES, [169](#)
- cudaComputeModeProhibited
 - CUDART_TYPES, [169](#)
- cudaConfigureCall
 - CUDART_EXECUTION, [41](#)
- cudaCreateChannelDesc
 - CUDART_HIGHLEVEL, [127](#)
 - CUDART_TEXTURE, [115](#)
- cudaCSV
 - CUDART_TYPES, [174](#)
- cudaD3D10DeviceList
 - CUDART_D3D10, [96](#)
- cudaD3D10DeviceListAll
 - CUDART_D3D10, [96](#)
- cudaD3D10DeviceListCurrentFrame
 - CUDART_D3D10, [96](#)
- cudaD3D10DeviceListNextFrame
 - CUDART_D3D10, [97](#)
- cudaD3D10GetDevice
 - CUDART_D3D10, [97](#)
- cudaD3D10GetDevices
 - CUDART_D3D10, [97](#)
- cudaD3D10GetDirect3DDevice
 - CUDART_D3D10, [98](#)
- cudaD3D10MapFlags
 - CUDART_D3D10_DEPRECATED, [148](#)
- cudaD3D10MapFlagsNone
 - CUDART_D3D10_DEPRECATED, [148](#)
- cudaD3D10MapFlagsReadOnly
 - CUDART_D3D10_DEPRECATED, [148](#)
- cudaD3D10MapFlagsWriteDiscard
 - CUDART_D3D10_DEPRECATED, [148](#)
- cudaD3D10MapResources
 - CUDART_D3D10_DEPRECATED, [148](#)
- cudaD3D10RegisterFlags
 - CUDART_D3D10_DEPRECATED, [148](#)
- cudaD3D10RegisterFlagsArray
 - CUDART_D3D10_DEPRECATED, [148](#)
- cudaD3D10RegisterFlagsNone
 - CUDART_D3D10_DEPRECATED, [148](#)
- cudaD3D10RegisterResource
 - CUDART_D3D10_DEPRECATED, [149](#)
- cudaD3D10ResourceGetMappedArray
 - CUDART_D3D10_DEPRECATED, [150](#)
- cudaD3D10ResourceGetMappedPitch
 - CUDART_D3D10_DEPRECATED, [150](#)
- cudaD3D10ResourceGetMappedPointer
 - CUDART_D3D10_DEPRECATED, [151](#)
- cudaD3D10ResourceGetMappedSize
 - CUDART_D3D10_DEPRECATED, [152](#)
- cudaD3D10ResourceGetSurfaceDimensions
 - CUDART_D3D10_DEPRECATED, [152](#)
- cudaD3D10ResourceSetMapFlags
 - CUDART_D3D10_DEPRECATED, [153](#)
- cudaD3D10SetDirect3DDevice
 - CUDART_D3D10, [98](#)
- cudaD3D10UnmapResources
 - CUDART_D3D10_DEPRECATED, [154](#)
- cudaD3D10UnregisterResource
 - CUDART_D3D10_DEPRECATED, [154](#)
- cudaD3D11DeviceList
 - CUDART_D3D11, [101](#)
- cudaD3D11DeviceListAll
 - CUDART_D3D11, [101](#)
- cudaD3D11DeviceListCurrentFrame
 - CUDART_D3D11, [101](#)
- cudaD3D11DeviceListNextFrame
 - CUDART_D3D11, [101](#)
- cudaD3D11GetDevice
 - CUDART_D3D11, [102](#)
- cudaD3D11GetDevices
 - CUDART_D3D11, [102](#)
- cudaD3D11GetDirect3DDevice
 - CUDART_D3D11, [102](#)
- cudaD3D11SetDirect3DDevice
 - CUDART_D3D11, [103](#)
- cudaD3D9DeviceList
 - CUDART_D3D9, [91](#)
- cudaD3D9DeviceListAll

- CUDART_D3D9, 91
- cudaD3D9DeviceListCurrentFrame
 - CUDART_D3D9, 91
- cudaD3D9DeviceListNextFrame
 - CUDART_D3D9, 92
- cudaD3D9GetDevice
 - CUDART_D3D9, 92
- cudaD3D9GetDevices
 - CUDART_D3D9, 92
- cudaD3D9GetDirect3DDevice
 - CUDART_D3D9, 93
- cudaD3D9MapFlags
 - CUDART_D3D9_DEPRECATED, 139
- cudaD3D9MapFlagsNone
 - CUDART_D3D9_DEPRECATED, 139
- cudaD3D9MapFlagsReadOnly
 - CUDART_D3D9_DEPRECATED, 139
- cudaD3D9MapFlagsWriteDiscard
 - CUDART_D3D9_DEPRECATED, 139
- cudaD3D9MapResources
 - CUDART_D3D9_DEPRECATED, 139
- cudaD3D9RegisterFlags
 - CUDART_D3D9_DEPRECATED, 139
- cudaD3D9RegisterFlagsArray
 - CUDART_D3D9_DEPRECATED, 139
- cudaD3D9RegisterFlagsNone
 - CUDART_D3D9_DEPRECATED, 139
- cudaD3D9RegisterResource
 - CUDART_D3D9_DEPRECATED, 140
- cudaD3D9ResourceGetMappedArray
 - CUDART_D3D9_DEPRECATED, 141
- cudaD3D9ResourceGetMappedPitch
 - CUDART_D3D9_DEPRECATED, 141
- cudaD3D9ResourceGetMappedPointer
 - CUDART_D3D9_DEPRECATED, 142
- cudaD3D9ResourceGetMappedSize
 - CUDART_D3D9_DEPRECATED, 143
- cudaD3D9ResourceGetSurfaceDimensions
 - CUDART_D3D9_DEPRECATED, 144
- cudaD3D9ResourceSetMapFlags
 - CUDART_D3D9_DEPRECATED, 144
- cudaD3D9SetDirect3DDevice
 - CUDART_D3D9, 93
- cudaD3D9UnmapResources
 - CUDART_D3D9_DEPRECATED, 145
- cudaD3D9UnregisterResource
 - CUDART_D3D9_DEPRECATED, 146
- cudaDeviceBlockingSync
 - CUDART_TYPES, 166
- cudaDeviceCanAccessPeer
 - CUDART_PEER, 84
- cudaDeviceDisablePeerAccess
 - CUDART_PEER, 84
- cudaDeviceEnablePeerAccess
 - CUDART_PEER, 85
- cudaDeviceGetByPCIBusId
 - CUDART_DEVICE, 14
- cudaDeviceGetCacheConfig
 - CUDART_DEVICE, 15
- cudaDeviceGetLimit
 - CUDART_DEVICE, 15
- cudaDeviceGetPCIBusId
 - CUDART_DEVICE, 16
- cudaDeviceLmemResizeToMax
 - CUDART_TYPES, 166
- cudaDeviceMapHost
 - CUDART_TYPES, 166
- cudaDeviceMask
 - CUDART_TYPES, 166
- cudaDeviceProp, 481
 - asyncEngineCount, 482
 - canMapHostMemory, 482
 - clockRate, 482
 - computeMode, 482
 - concurrentKernels, 482
 - deviceOverlap, 482
 - ECCEnabled, 482
 - integrated, 482
 - kernelExecTimeoutEnabled, 482
 - l2CacheSize, 482
 - major, 483
 - maxGridSize, 483
 - maxSurface1D, 483
 - maxSurface1DLayered, 483
 - maxSurface2D, 483
 - maxSurface2DLayered, 483
 - maxSurface3D, 483
 - maxSurfaceCubemap, 483
 - maxSurfaceCubemapLayered, 483
 - maxTexture1D, 483
 - maxTexture1DLayered, 483
 - maxTexture1DLinear, 483
 - maxTexture2D, 484
 - maxTexture2DGather, 484
 - maxTexture2DLayered, 484
 - maxTexture2DLinear, 484
 - maxTexture3D, 484
 - maxTextureCubemap, 484
 - maxTextureCubemapLayered, 484
 - maxThreadsDim, 484
 - maxThreadsPerBlock, 484
 - maxThreadsPerMultiProcessor, 484
 - memoryBusWidth, 484
 - memoryClockRate, 484
 - memPitch, 485
 - minor, 485
 - multiProcessorCount, 485
 - name, 485

- pciBusID, [485](#)
- pciDeviceID, [485](#)
- pciDomainID, [485](#)
- regsPerBlock, [485](#)
- sharedMemPerBlock, [485](#)
- surfaceAlignment, [485](#)
- tccDriver, [485](#)
- textureAlignment, [485](#)
- texturePitchAlignment, [486](#)
- totalConstMem, [486](#)
- totalGlobalMem, [486](#)
- unifiedAddressing, [486](#)
- warpSize, [486](#)
- cudaDevicePropDontCare
 - CUDART_TYPES, [166](#)
- cudaDeviceReset
 - CUDART_DEVICE, [16](#)
- cudaDeviceScheduleAuto
 - CUDART_TYPES, [166](#)
- cudaDeviceScheduleBlockingSync
 - CUDART_TYPES, [166](#)
- cudaDeviceScheduleMask
 - CUDART_TYPES, [166](#)
- cudaDeviceScheduleSpin
 - CUDART_TYPES, [166](#)
- cudaDeviceScheduleYield
 - CUDART_TYPES, [166](#)
- cudaDeviceSetCacheConfig
 - CUDART_DEVICE, [16](#)
- cudaDeviceSetLimit
 - CUDART_DEVICE, [17](#)
- cudaDeviceSynchronize
 - CUDART_DEVICE, [18](#)
- cudaDriverGetVersion
 - CUDART__VERSION, [120](#)
- cudaError
 - CUDART_TYPES, [169](#)
- cudaError_enum
 - CUDA_TYPES, [190](#)
- cudaError_t
 - CUDART_TYPES, [168](#)
- cudaErrorAddressOfConstant
 - CUDART_TYPES, [170](#)
- cudaErrorApiFailureBase
 - CUDART_TYPES, [172](#)
- cudaErrorAssert
 - CUDART_TYPES, [172](#)
- cudaErrorCudartUnloading
 - CUDART_TYPES, [171](#)
- cudaErrorDeviceAlreadyInUse
 - CUDART_TYPES, [172](#)
- cudaErrorDevicesUnavailable
 - CUDART_TYPES, [172](#)
- cudaErrorDuplicateSurfaceName
 - CUDART_TYPES, [171](#)
- cudaErrorDuplicateTextureName
 - CUDART_TYPES, [171](#)
- cudaErrorDuplicateVariableName
 - CUDART_TYPES, [171](#)
- cudaErrorECCUncorrectable
 - CUDART_TYPES, [171](#)
- cudaErrorHostMemoryAlreadyRegistered
 - CUDART_TYPES, [172](#)
- cudaErrorHostMemoryNotRegistered
 - CUDART_TYPES, [172](#)
- cudaErrorIncompatibleDriverContext
 - CUDART_TYPES, [172](#)
- cudaErrorInitializationError
 - CUDART_TYPES, [169](#)
- cudaErrorInsufficientDriver
 - CUDART_TYPES, [171](#)
- cudaErrorInvalidChannelDescriptor
 - CUDART_TYPES, [170](#)
- cudaErrorInvalidConfiguration
 - CUDART_TYPES, [169](#)
- cudaErrorInvalidDevice
 - CUDART_TYPES, [170](#)
- cudaErrorInvalidDeviceFunction
 - CUDART_TYPES, [169](#)
- cudaErrorInvalidDevicePointer
 - CUDART_TYPES, [170](#)
- cudaErrorInvalidFilterSetting
 - CUDART_TYPES, [171](#)
- cudaErrorInvalidHostPointer
 - CUDART_TYPES, [170](#)
- cudaErrorInvalidKernelImage
 - CUDART_TYPES, [172](#)
- cudaErrorInvalidMemcpyDirection
 - CUDART_TYPES, [170](#)
- cudaErrorInvalidNormSetting
 - CUDART_TYPES, [171](#)
- cudaErrorInvalidPitchValue
 - CUDART_TYPES, [170](#)
- cudaErrorInvalidResourceHandle
 - CUDART_TYPES, [171](#)
- cudaErrorInvalidSurface
 - CUDART_TYPES, [171](#)
- cudaErrorInvalidSymbol
 - CUDART_TYPES, [170](#)
- cudaErrorInvalidTexture
 - CUDART_TYPES, [170](#)
- cudaErrorInvalidTextureBinding
 - CUDART_TYPES, [170](#)
- cudaErrorInvalidValue
 - CUDART_TYPES, [170](#)
- cudaErrorLaunchFailure
 - CUDART_TYPES, [169](#)
- cudaErrorLaunchOutOfResources

CUDART_TYPES, 169
 cudaErrorLaunchTimeout
 CUDART_TYPES, 169
 cudaErrorMapBufferObjectFailed
 CUDART_TYPES, 170
 cudaErrorMemoryAllocation
 CUDART_TYPES, 169
 cudaErrorMemoryValueTooLarge
 CUDART_TYPES, 171
 cudaErrorMissingConfiguration
 CUDART_TYPES, 169
 cudaErrorMixedDeviceExecution
 CUDART_TYPES, 171
 cudaErrorNoDevice
 CUDART_TYPES, 171
 cudaErrorNoKernelImageForDevice
 CUDART_TYPES, 172
 cudaErrorNotReady
 CUDART_TYPES, 171
 cudaErrorNotYetImplemented
 CUDART_TYPES, 171
 cudaErrorPeerAccessAlreadyEnabled
 CUDART_TYPES, 172
 cudaErrorPeerAccessNotEnabled
 CUDART_TYPES, 172
 cudaErrorPriorLaunchFailure
 CUDART_TYPES, 169
 cudaErrorProfilerAlreadyStarted
 CUDART_TYPES, 172
 cudaErrorProfilerAlreadyStopped
 CUDART_TYPES, 172
 cudaErrorProfilerDisabled
 CUDART_TYPES, 172
 cudaErrorProfilerNotInitialized
 CUDART_TYPES, 172
 cudaErrorSetOnActiveProcess
 CUDART_TYPES, 171
 cudaErrorSharedObjectInitFailed
 CUDART_TYPES, 171
 cudaErrorSharedObjectSymbolNotFound
 CUDART_TYPES, 171
 cudaErrorStartupFailure
 CUDART_TYPES, 172
 cudaErrorSynchronizationError
 CUDART_TYPES, 170
 cudaErrorTextureFetchFailed
 CUDART_TYPES, 170
 cudaErrorTextureNotBound
 CUDART_TYPES, 170
 cudaErrorTooManyPeers
 CUDART_TYPES, 172
 cudaErrorUnknown
 CUDART_TYPES, 171
 cudaErrorUnmapBufferObjectFailed

CUDART_TYPES, 170
 cudaErrorUnsupportedLimit
 CUDART_TYPES, 171
 cudaEvent_t
 CUDART_TYPES, 168
 cudaEventBlockingSync
 CUDART_TYPES, 167
 cudaEventCreate
 CUDART_EVENT, 37
 CUDART_HIGHLEVEL, 127
 cudaEventCreateWithFlags
 CUDART_EVENT, 37
 cudaEventDefault
 CUDART_TYPES, 167
 cudaEventDestroy
 CUDART_EVENT, 38
 cudaEventDisableTiming
 CUDART_TYPES, 167
 cudaEventElapsedTime
 CUDART_EVENT, 38
 cudaEventInterprocess
 CUDART_TYPES, 167
 cudaEventQuery
 CUDART_EVENT, 39
 cudaEventRecord
 CUDART_EVENT, 39
 cudaEventSynchronize
 CUDART_EVENT, 40
 cudaExtent, 487
 depth, 487
 height, 487
 width, 487
 cudaFilterModeLinear
 CUDART_TYPES, 175
 cudaFilterModePoint
 CUDART_TYPES, 175
 cudaFormatModeAuto
 CUDART_TYPES, 175
 cudaFormatModeForced
 CUDART_TYPES, 175
 cudaFree
 CUDART_MEMORY, 48
 cudaFreeArray
 CUDART_MEMORY, 49
 cudaFreeHost
 CUDART_MEMORY, 49
 cudaFuncAttributes, 488
 binaryVersion, 488
 constSizeBytes, 488
 localSizeBytes, 488
 maxThreadsPerBlock, 488
 numRegs, 488
 ptxVersion, 488
 sharedSizeBytes, 488

- cudaFuncCache
 - CUDART_TYPES, [172](#)
- cudaFuncCachePreferEqual
 - CUDART_TYPES, [173](#)
- cudaFuncCachePreferL1
 - CUDART_TYPES, [173](#)
- cudaFuncCachePreferNone
 - CUDART_TYPES, [173](#)
- cudaFuncCachePreferShared
 - CUDART_TYPES, [173](#)
- cudaFuncGetAttributes
 - CUDART_EXECUTION, [42](#)
 - CUDART_HIGHLEVEL, [128](#)
- cudaFuncSetCacheConfig
 - CUDART_EXECUTION, [42](#)
 - CUDART_HIGHLEVEL, [129](#)
- cudaGetChannelDesc
 - CUDART_TEXTURE, [116](#)
- cudaGetDevice
 - CUDART_DEVICE, [18](#)
- cudaGetDeviceCount
 - CUDART_DEVICE, [18](#)
- cudaGetDeviceProperties
 - CUDART_DEVICE, [19](#)
- cudaGetErrorString
 - CUDART_ERROR, [32](#)
- cudaGetLastError
 - CUDART_ERROR, [32](#)
- cudaGetSurfaceReference
 - CUDART_SURFACE, [118](#)
- cudaGetSymbolAddress
 - CUDART_HIGHLEVEL, [129](#)
 - CUDART_MEMORY, [49](#)
- cudaGetSymbolSize
 - CUDART_HIGHLEVEL, [130](#)
 - CUDART_MEMORY, [50](#)
- cudaGetTextureAlignmentOffset
 - CUDART_HIGHLEVEL, [130](#)
 - CUDART_TEXTURE, [116](#)
- cudaGetTextureReference
 - CUDART_TEXTURE, [117](#)
- cudaGLDeviceList
 - CUDART_OPENGL, [86](#)
- cudaGLDeviceListAll
 - CUDART_OPENGL, [86](#)
- cudaGLDeviceListCurrentFrame
 - CUDART_OPENGL, [86](#)
- cudaGLDeviceListNextFrame
 - CUDART_OPENGL, [87](#)
- cudaGLGetDevices
 - CUDART_OPENGL, [87](#)
- cudaGLMapBufferObject
 - CUDART_OPENGL_DEPRECATED, [157](#)
- cudaGLMapBufferObjectAsync
 - CUDART_OPENGL_DEPRECATED, [157](#)
- cudaGLMapFlags
 - CUDART_OPENGL_DEPRECATED, [156](#)
- cudaGLMapFlagsNone
 - CUDART_OPENGL_DEPRECATED, [156](#)
- cudaGLMapFlagsReadOnly
 - CUDART_OPENGL_DEPRECATED, [156](#)
- cudaGLMapFlagsWriteDiscard
 - CUDART_OPENGL_DEPRECATED, [156](#)
- cudaGLRegisterBufferObject
 - CUDART_OPENGL_DEPRECATED, [158](#)
- cudaGLSetBufferObjectMapFlags
 - CUDART_OPENGL_DEPRECATED, [158](#)
- cudaGLSetGLDevice
 - CUDART_OPENGL, [87](#)
- cudaGLUnmapBufferObject
 - CUDART_OPENGL_DEPRECATED, [159](#)
- cudaGLUnmapBufferObjectAsync
 - CUDART_OPENGL_DEPRECATED, [159](#)
- cudaGLUnregisterBufferObject
 - CUDART_OPENGL_DEPRECATED, [160](#)
- cudaGraphicsCubeFace
 - CUDART_TYPES, [173](#)
- cudaGraphicsCubeFaceNegativeX
 - CUDART_TYPES, [173](#)
- cudaGraphicsCubeFaceNegativeY
 - CUDART_TYPES, [173](#)
- cudaGraphicsCubeFaceNegativeZ
 - CUDART_TYPES, [173](#)
- cudaGraphicsCubeFacePositiveX
 - CUDART_TYPES, [173](#)
- cudaGraphicsCubeFacePositiveY
 - CUDART_TYPES, [173](#)
- cudaGraphicsCubeFacePositiveZ
 - CUDART_TYPES, [173](#)
- cudaGraphicsD3D10RegisterResource
 - CUDART_D3D10, [98](#)
- cudaGraphicsD3D11RegisterResource
 - CUDART_D3D11, [103](#)
- cudaGraphicsD3D9RegisterResource
 - CUDART_D3D9, [93](#)
- cudaGraphicsGLRegisterBuffer
 - CUDART_OPENGL, [88](#)
- cudaGraphicsGLRegisterImage
 - CUDART_OPENGL, [88](#)
- cudaGraphicsMapFlags
 - CUDART_TYPES, [173](#)
- cudaGraphicsMapFlagsNone
 - CUDART_TYPES, [173](#)
- cudaGraphicsMapFlagsReadOnly
 - CUDART_TYPES, [173](#)
- cudaGraphicsMapFlagsWriteDiscard
 - CUDART_TYPES, [173](#)
- cudaGraphicsMapResources

- CUDART_INTEROP, 109
- cudaGraphicsRegisterFlags
 - CUDART_TYPES, 173
- cudaGraphicsRegisterFlagsNone
 - CUDART_TYPES, 173
- cudaGraphicsRegisterFlagsReadOnly
 - CUDART_TYPES, 173
- cudaGraphicsRegisterFlagsSurfaceLoadStore
 - CUDART_TYPES, 173
- cudaGraphicsRegisterFlagsTextureGather
 - CUDART_TYPES, 173
- cudaGraphicsRegisterFlagsWriteDiscard
 - CUDART_TYPES, 173
- cudaGraphicsResource_t
 - CUDART_TYPES, 168
- cudaGraphicsResourceGetMappedPointer
 - CUDART_INTEROP, 110
- cudaGraphicsResourceSetMapFlags
 - CUDART_INTEROP, 110
- cudaGraphicsSubResourceGetMappedArray
 - CUDART_INTEROP, 111
- cudaGraphicsUnmapResources
 - CUDART_INTEROP, 111
- cudaGraphicsUnregisterResource
 - CUDART_INTEROP, 112
- cudaGraphicsVDPAURegisterOutputSurface
 - CUDART_VDPAU, 106
- cudaGraphicsVDPAURegisterVideoSurface
 - CUDART_VDPAU, 107
- cudaHostAlloc
 - CUDART_MEMORY, 50
- cudaHostAllocDefault
 - CUDART_TYPES, 167
- cudaHostAllocMapped
 - CUDART_TYPES, 167
- cudaHostAllocPortable
 - CUDART_TYPES, 167
- cudaHostAllocWriteCombined
 - CUDART_TYPES, 167
- cudaHostGetDevicePointer
 - CUDART_MEMORY, 51
- cudaHostGetFlags
 - CUDART_MEMORY, 52
- cudaHostRegister
 - CUDART_MEMORY, 52
- cudaHostRegisterDefault
 - CUDART_TYPES, 167
- cudaHostRegisterMapped
 - CUDART_TYPES, 167
- cudaHostRegisterPortable
 - CUDART_TYPES, 167
- cudaHostUnregister
 - CUDART_MEMORY, 53
- cudaIpcCloseMemHandle
 - CUDART_DEVICE, 22
- cudaIpcEventHandle_t
 - CUDART_TYPES, 168
- cudaIpcGetEventHandle
 - CUDART_DEVICE, 22
- cudaIpcGetMemHandle
 - CUDART_DEVICE, 23
- cudaIpcOpenEventHandle
 - CUDART_DEVICE, 23
- cudaIpcOpenMemHandle
 - CUDART_DEVICE, 24
- cudaKeyValuePair
 - CUDART_TYPES, 174
- cudaLaunch
 - CUDART_EXECUTION, 43
 - CUDART_HIGHLEVEL, 131
- cudaLimit
 - CUDART_TYPES, 173
- cudaLimitMallocHeapSize
 - CUDART_TYPES, 174
- cudaLimitPrintfFifoSize
 - CUDART_TYPES, 174
- cudaLimitStackSize
 - CUDART_TYPES, 174
- cudaMalloc
 - CUDART_MEMORY, 53
- cudaMalloc3D
 - CUDART_MEMORY, 54
- cudaMalloc3DArray
 - CUDART_MEMORY, 54
- cudaMallocArray
 - CUDART_MEMORY, 56
- cudaMallocHost
 - CUDART_HIGHLEVEL, 131
 - CUDART_MEMORY, 57
- cudaMallocPitch
 - CUDART_MEMORY, 58
- cudaMemcpy
 - CUDART_MEMORY, 58
- cudaMemcpy2D
 - CUDART_MEMORY, 59
- cudaMemcpy2DArrayToArray
 - CUDART_MEMORY, 59
- cudaMemcpy2DAsync
 - CUDART_MEMORY, 60
- cudaMemcpy2DFromArray
 - CUDART_MEMORY, 61
- cudaMemcpy2DFromArrayAsync
 - CUDART_MEMORY, 62
- cudaMemcpy2DToArray
 - CUDART_MEMORY, 63
- cudaMemcpy2DToArrayAsync
 - CUDART_MEMORY, 63
- cudaMemcpy3D

- CUDART_MEMORY, 64
- cudaMemcpy3DAsync
 - CUDART_MEMORY, 66
- cudaMemcpy3DParms, 490
 - dstArray, 490
 - dstPos, 490
 - dstPtr, 490
 - extent, 490
 - kind, 490
 - srcArray, 490
 - srcPos, 490
 - srcPtr, 490
- cudaMemcpy3DPeer
 - CUDART_MEMORY, 67
- cudaMemcpy3DPeerAsync
 - CUDART_MEMORY, 68
- cudaMemcpy3DPeerParms, 492
 - dstArray, 492
 - dstDevice, 492
 - dstPos, 492
 - dstPtr, 492
 - extent, 492
 - srcArray, 492
 - srcDevice, 492
 - srcPos, 492
 - srcPtr, 493
- cudaMemcpyArrayToArray
 - CUDART_MEMORY, 68
- cudaMemcpyAsync
 - CUDART_MEMORY, 69
- cudaMemcpyDefault
 - CUDART_TYPES, 174
- cudaMemcpyDeviceToDevice
 - CUDART_TYPES, 174
- cudaMemcpyDeviceToHost
 - CUDART_TYPES, 174
- cudaMemcpyFromArray
 - CUDART_MEMORY, 69
- cudaMemcpyFromArrayAsync
 - CUDART_MEMORY, 70
- cudaMemcpyFromSymbol
 - CUDART_MEMORY, 71
- cudaMemcpyFromSymbolAsync
 - CUDART_MEMORY, 71
- cudaMemcpyHostToDevice
 - CUDART_TYPES, 174
- cudaMemcpyHostToHost
 - CUDART_TYPES, 174
- cudaMemcpyKind
 - CUDART_TYPES, 174
- cudaMemcpyPeer
 - CUDART_MEMORY, 72
- cudaMemcpyPeerAsync
 - CUDART_MEMORY, 73
- cudaMemcpyToArray
 - CUDART_MEMORY, 73
- cudaMemcpyToArrayAsync
 - CUDART_MEMORY, 74
- cudaMemcpyToSymbol
 - CUDART_MEMORY, 74
- cudaMemcpyToSymbolAsync
 - CUDART_MEMORY, 75
- cudaMemGetInfo
 - CUDART_MEMORY, 76
- cudaMemoryType
 - CUDART_TYPES, 174
- cudaMemoryTypeDevice
 - CUDART_TYPES, 174
- cudaMemoryTypeHost
 - CUDART_TYPES, 174
- cudaMemset
 - CUDART_MEMORY, 76
- cudaMemset2D
 - CUDART_MEMORY, 76
- cudaMemset2DAsync
 - CUDART_MEMORY, 77
- cudaMemset3D
 - CUDART_MEMORY, 77
- cudaMemset3DAsync
 - CUDART_MEMORY, 78
- cudaMemsetAsync
 - CUDART_MEMORY, 79
- cudaOutputMode
 - CUDART_TYPES, 174
- cudaOutputMode_t
 - CUDART_TYPES, 168
- cudaPeekAtLastError
 - CUDART_ERROR, 33
- cudaPeerAccessDefault
 - CUDART_TYPES, 167
- cudaPitchedPtr, 494
 - pitch, 494
 - ptr, 494
 - xsize, 494
 - ysize, 494
- cudaPointerAttributes, 495
 - device, 495
 - devicePointer, 495
 - hostPointer, 495
 - memoryType, 495
- cudaPointerGetAttributes
 - CUDART_UNIFIED, 82
- cudaPos, 496
 - x, 496
 - y, 496
 - z, 496
- cudaProfilerInitialize
 - CUDART_PROFILER, 136

- cudaProfilerStart
 - CUDART_PROFILER, 137
- cudaProfilerStop
 - CUDART_PROFILER, 137
- cudaReadModeElementType
 - CUDART_TYPES, 175
- cudaReadModeNormalizedFloat
 - CUDART_TYPES, 175
- CUDART
 - CUDART_VERSION, 12
- CUDART_D3D10
 - cudaD3D10DeviceListAll, 96
 - cudaD3D10DeviceListCurrentFrame, 96
 - cudaD3D10DeviceListNextFrame, 97
- CUDART_D3D10_DEPRECATED
 - cudaD3D10MapFlagsNone, 148
 - cudaD3D10MapFlagsReadOnly, 148
 - cudaD3D10MapFlagsWriteDiscard, 148
 - cudaD3D10RegisterFlagsArray, 148
 - cudaD3D10RegisterFlagsNone, 148
- CUDART_D3D11
 - cudaD3D11DeviceListAll, 101
 - cudaD3D11DeviceListCurrentFrame, 101
 - cudaD3D11DeviceListNextFrame, 101
- CUDART_D3D9
 - cudaD3D9DeviceListAll, 91
 - cudaD3D9DeviceListCurrentFrame, 91
 - cudaD3D9DeviceListNextFrame, 92
- CUDART_D3D9_DEPRECATED
 - cudaD3D9MapFlagsNone, 139
 - cudaD3D9MapFlagsReadOnly, 139
 - cudaD3D9MapFlagsWriteDiscard, 139
 - cudaD3D9RegisterFlagsArray, 139
 - cudaD3D9RegisterFlagsNone, 139
- CUDART_OPENGL
 - cudaGLDeviceListAll, 86
 - cudaGLDeviceListCurrentFrame, 86
 - cudaGLDeviceListNextFrame, 87
- CUDART_OPENGL_DEPRECATED
 - cudaGLMapFlagsNone, 156
 - cudaGLMapFlagsReadOnly, 156
 - cudaGLMapFlagsWriteDiscard, 156
- CUDART_TYPES
 - cudaAddressModeBorder, 175
 - cudaAddressModeClamp, 175
 - cudaAddressModeMirror, 175
 - cudaAddressModeWrap, 175
 - cudaBoundaryModeClamp, 174
 - cudaBoundaryModeTrap, 174
 - cudaBoundaryModeZero, 174
 - cudaChannelFormatKindFloat, 168
 - cudaChannelFormatKindNone, 168
 - cudaChannelFormatKindSigned, 168
 - cudaChannelFormatKindUnsigned, 168
 - cudaComputeModeDefault, 169
 - cudaComputeModeExclusive, 169
 - cudaComputeModeExclusiveProcess, 169
 - cudaComputeModeProhibited, 169
 - cudaCSV, 174
 - cudaErrorAddressOfConstant, 170
 - cudaErrorApiFailureBase, 172
 - cudaErrorAssert, 172
 - cudaErrorCudartUnloading, 171
 - cudaErrorDeviceAlreadyInUse, 172
 - cudaErrorDevicesUnavailable, 172
 - cudaErrorDuplicateSurfaceName, 171
 - cudaErrorDuplicateTextureName, 171
 - cudaErrorDuplicateVariableName, 171
 - cudaErrorECCUncorrectable, 171
 - cudaErrorHostMemoryAlreadyRegistered, 172
 - cudaErrorHostMemoryNotRegistered, 172
 - cudaErrorIncompatibleDriverContext, 172
 - cudaErrorInitializationError, 169
 - cudaErrorInsufficientDriver, 171
 - cudaErrorInvalidChannelDescriptor, 170
 - cudaErrorInvalidConfiguration, 169
 - cudaErrorInvalidDevice, 170
 - cudaErrorInvalidDeviceFunction, 169
 - cudaErrorInvalidDevicePointer, 170
 - cudaErrorInvalidFilterSetting, 171
 - cudaErrorInvalidHostPointer, 170
 - cudaErrorInvalidKernelImage, 172
 - cudaErrorInvalidMemcpyDirection, 170
 - cudaErrorInvalidNormSetting, 171
 - cudaErrorInvalidPitchValue, 170
 - cudaErrorInvalidResourceHandle, 171
 - cudaErrorInvalidSurface, 171
 - cudaErrorInvalidSymbol, 170
 - cudaErrorInvalidTexture, 170
 - cudaErrorInvalidTextureBinding, 170
 - cudaErrorInvalidValue, 170
 - cudaErrorLaunchFailure, 169
 - cudaErrorLaunchOutOfResources, 169
 - cudaErrorLaunchTimeout, 169
 - cudaErrorMapBufferObjectFailed, 170
 - cudaErrorMemoryAllocation, 169
 - cudaErrorMemoryValueTooLarge, 171
 - cudaErrorMissingConfiguration, 169
 - cudaErrorMixedDeviceExecution, 171
 - cudaErrorNoDevice, 171
 - cudaErrorNoKernelImageForDevice, 172
 - cudaErrorNotReady, 171
 - cudaErrorNotYetImplemented, 171
 - cudaErrorPeerAccessAlreadyEnabled, 172
 - cudaErrorPeerAccessNotEnabled, 172
 - cudaErrorPriorLaunchFailure, 169
 - cudaErrorProfilerAlreadyStarted, 172
 - cudaErrorProfilerAlreadyStopped, 172

- cudaErrorProfilerDisabled, 172
- cudaErrorProfilerNotInitialized, 172
- cudaErrorSetOnActiveProcess, 171
- cudaErrorSharedObjectInitFailed, 171
- cudaErrorSharedObjectSymbolNotFound, 171
- cudaErrorStartupFailure, 172
- cudaErrorSynchronizationError, 170
- cudaErrorTextureFetchFailed, 170
- cudaErrorTextureNotBound, 170
- cudaErrorTooManyPeers, 172
- cudaErrorUnknown, 171
- cudaErrorUnmapBufferObjectFailed, 170
- cudaErrorUnsupportedLimit, 171
- cudaFilterModeLinear, 175
- cudaFilterModePoint, 175
- cudaFormatModeAuto, 175
- cudaFormatModeForced, 175
- cudaFuncCachePreferEqual, 173
- cudaFuncCachePreferL1, 173
- cudaFuncCachePreferNone, 173
- cudaFuncCachePreferShared, 173
- cudaGraphicsCubeFaceNegativeX, 173
- cudaGraphicsCubeFaceNegativeY, 173
- cudaGraphicsCubeFaceNegativeZ, 173
- cudaGraphicsCubeFacePositiveX, 173
- cudaGraphicsCubeFacePositiveY, 173
- cudaGraphicsCubeFacePositiveZ, 173
- cudaGraphicsMapFlagsNone, 173
- cudaGraphicsMapFlagsReadOnly, 173
- cudaGraphicsMapFlagsWriteDiscard, 173
- cudaGraphicsRegisterFlagsNone, 173
- cudaGraphicsRegisterFlagsReadOnly, 173
- cudaGraphicsRegisterFlagsSurfaceLoadStore, 173
- cudaGraphicsRegisterFlagsTextureGather, 173
- cudaGraphicsRegisterFlagsWriteDiscard, 173
- cudaKeyValuePair, 174
- cudaLimitMallocHeapSize, 174
- cudaLimitPrintfFifoSize, 174
- cudaLimitStackSize, 174
- cudaMemcpyDefault, 174
- cudaMemcpyDeviceToDevice, 174
- cudaMemcpyDeviceToHost, 174
- cudaMemcpyHostToDevice, 174
- cudaMemcpyHostToHost, 174
- cudaMemoryTypeDevice, 174
- cudaMemoryTypeHost, 174
- cudaReadModeElementType, 175
- cudaReadModeNormalizedFloat, 175
- cudaSuccess, 169
- CUDART__VERSION
 - cudaDriverGetVersion, 120
 - cudaRuntimeGetVersion, 120
- CUDART_D3D10
 - cudaD3D10DeviceList, 96
 - cudaD3D10GetDevice, 97
 - cudaD3D10GetDevices, 97
 - cudaD3D10GetDirect3DDevice, 98
 - cudaD3D10SetDirect3DDevice, 98
 - cudaGraphicsD3D10RegisterResource, 98
- CUDART_D3D10_DEPRECATED
 - cudaD3D10MapFlags, 148
 - cudaD3D10MapResources, 148
 - cudaD3D10RegisterFlags, 148
 - cudaD3D10RegisterResource, 149
 - cudaD3D10ResourceGetMappedArray, 150
 - cudaD3D10ResourceGetMappedPitch, 150
 - cudaD3D10ResourceGetMappedPointer, 151
 - cudaD3D10ResourceGetMappedSize, 152
 - cudaD3D10ResourceGetSurfaceDimensions, 152
 - cudaD3D10ResourceSetMapFlags, 153
 - cudaD3D10UnmapResources, 154
 - cudaD3D10UnregisterResource, 154
- CUDART_D3D11
 - cudaD3D11DeviceList, 101
 - cudaD3D11GetDevice, 102
 - cudaD3D11GetDevices, 102
 - cudaD3D11GetDirect3DDevice, 102
 - cudaD3D11SetDirect3DDevice, 103
 - cudaGraphicsD3D11RegisterResource, 103
- CUDART_D3D9
 - cudaD3D9DeviceList, 91
 - cudaD3D9GetDevice, 92
 - cudaD3D9GetDevices, 92
 - cudaD3D9GetDirect3DDevice, 93
 - cudaD3D9SetDirect3DDevice, 93
 - cudaGraphicsD3D9RegisterResource, 93
- CUDART_D3D9_DEPRECATED
 - cudaD3D9MapFlags, 139
 - cudaD3D9MapResources, 139
 - cudaD3D9RegisterFlags, 139
 - cudaD3D9RegisterResource, 140
 - cudaD3D9ResourceGetMappedArray, 141
 - cudaD3D9ResourceGetMappedPitch, 141
 - cudaD3D9ResourceGetMappedPointer, 142
 - cudaD3D9ResourceGetMappedSize, 143
 - cudaD3D9ResourceGetSurfaceDimensions, 144
 - cudaD3D9ResourceSetMapFlags, 144
 - cudaD3D9UnmapResources, 145
 - cudaD3D9UnregisterResource, 146
- CUDART_DEVICE
 - cudaChooseDevice, 14
 - cudaDeviceGetByPCIBusId, 14
 - cudaDeviceGetCacheConfig, 15
 - cudaDeviceGetLimit, 15
 - cudaDeviceGetPCIBusId, 16
 - cudaDeviceReset, 16
 - cudaDeviceSetCacheConfig, 16
 - cudaDeviceSetLimit, 17

- cudaDeviceSynchronize, 18
- cudaGetDevice, 18
- cudaGetDeviceCount, 18
- cudaGetDeviceProperties, 19
- cudaIpcCloseMemHandle, 22
- cudaIpcGetEventHandle, 22
- cudaIpcGetMemHandle, 23
- cudaIpcOpenEventHandle, 23
- cudaIpcOpenMemHandle, 24
- cudaSetDevice, 24
- cudaSetDeviceFlags, 25
- cudaSetValidDevices, 26
- CUDART_ERROR
 - cudaGetErrorString, 32
 - cudaGetLastError, 32
 - cudaPeekAtLastError, 33
- CUDART_EVENT
 - cudaEventCreate, 37
 - cudaEventCreateWithFlags, 37
 - cudaEventDestroy, 38
 - cudaEventElapsedTime, 38
 - cudaEventQuery, 39
 - cudaEventRecord, 39
 - cudaEventSynchronize, 40
- CUDART_EXECUTION
 - cudaConfigureCall, 41
 - cudaFuncGetAttributes, 42
 - cudaFuncSetCacheConfig, 42
 - cudaLaunch, 43
 - cudaSetDoubleForDevice, 43
 - cudaSetDoubleForHost, 44
 - cudaSetupArgument, 44
- CUDART_HIGHLEVEL
 - cudaBindSurfaceToArray, 122, 123
 - cudaBindTexture, 123, 124
 - cudaBindTexture2D, 124, 125
 - cudaBindTextureToArray, 126
 - cudaCreateChannelDesc, 127
 - cudaEventCreate, 127
 - cudaFuncGetAttributes, 128
 - cudaFuncSetCacheConfig, 129
 - cudaGetSymbolAddress, 129
 - cudaGetSymbolSize, 130
 - cudaGetTextureAlignmentOffset, 130
 - cudaLaunch, 131
 - cudaMallocHost, 131
 - cudaSetupArgument, 132
 - cudaUnbindTexture, 133
- CUDART_INTEROP
 - cudaGraphicsMapResources, 109
 - cudaGraphicsResourceGetMappedPointer, 110
 - cudaGraphicsResourceSetMapFlags, 110
 - cudaGraphicsSubResourceGetMappedArray, 111
 - cudaGraphicsUnmapResources, 111
 - cudaGraphicsUnregisterResource, 112
- CUDART_MEMORY
 - cudaFree, 48
 - cudaFreeArray, 49
 - cudaFreeHost, 49
 - cudaGetSymbolAddress, 49
 - cudaGetSymbolSize, 50
 - cudaHostAlloc, 50
 - cudaHostGetDevicePointer, 51
 - cudaHostGetFlags, 52
 - cudaHostRegister, 52
 - cudaHostUnregister, 53
 - cudaMalloc, 53
 - cudaMalloc3D, 54
 - cudaMalloc3DArray, 54
 - cudaMallocArray, 56
 - cudaMallocHost, 57
 - cudaMallocPitch, 58
 - cudaMemcpy, 58
 - cudaMemcpy2D, 59
 - cudaMemcpy2DArrayToArray, 59
 - cudaMemcpy2DAsync, 60
 - cudaMemcpy2DFromArray, 61
 - cudaMemcpy2DFromArrayAsync, 62
 - cudaMemcpy2DToArray, 63
 - cudaMemcpy2DToArrayAsync, 63
 - cudaMemcpy3D, 64
 - cudaMemcpy3DAsync, 66
 - cudaMemcpy3DPeer, 67
 - cudaMemcpy3DPeerAsync, 68
 - cudaMemcpyArrayToArray, 68
 - cudaMemcpyAsync, 69
 - cudaMemcpyFromArray, 69
 - cudaMemcpyFromArrayAsync, 70
 - cudaMemcpyFromSymbol, 71
 - cudaMemcpyFromSymbolAsync, 71
 - cudaMemcpyPeer, 72
 - cudaMemcpyPeerAsync, 73
 - cudaMemcpyToArray, 73
 - cudaMemcpyToArrayAsync, 74
 - cudaMemcpyToSymbol, 74
 - cudaMemcpyToSymbolAsync, 75
 - cudaMemGetInfo, 76
 - cudaMemset, 76
 - cudaMemset2D, 76
 - cudaMemset2DAsync, 77
 - cudaMemset3D, 77
 - cudaMemset3DAsync, 78
 - cudaMemsetAsync, 79
 - make_cudaExtent, 79
 - make_cudaPitchedPtr, 80
 - make_cudaPos, 80
- CUDART_OPENGL
 - cudaGLDeviceList, 86

- cudaGLGetDevices, 87
- cudaGLSetGLDevice, 87
- cudaGraphicsGLRegisterBuffer, 88
- cudaGraphicsGLRegisterImage, 88
- cudaWGLGetDevice, 89
- CUDART_OPENGL_DEPRECATED
 - cudaGLMapBufferObject, 157
 - cudaGLMapBufferObjectAsync, 157
 - cudaGLMapFlags, 156
 - cudaGLRegisterBufferObject, 158
 - cudaGLSetBufferObjectMapFlags, 158
 - cudaGLUnmapBufferObject, 159
 - cudaGLUnmapBufferObjectAsync, 159
 - cudaGLUnregisterBufferObject, 160
- CUDART_PEER
 - cudaDeviceCanAccessPeer, 84
 - cudaDeviceDisablePeerAccess, 84
 - cudaDeviceEnablePeerAccess, 85
- CUDART_PROFILER
 - cudaProfilerInitialize, 136
 - cudaProfilerStart, 137
 - cudaProfilerStop, 137
- CUDART_STREAM
 - cudaStreamCreate, 34
 - cudaStreamDestroy, 34
 - cudaStreamQuery, 35
 - cudaStreamSynchronize, 35
 - cudaStreamWaitEvent, 35
- CUDART_SURFACE
 - cudaBindSurfaceToArray, 118
 - cudaGetSurfaceReference, 118
- CUDART_TEXTURE
 - cudaBindTexture, 113
 - cudaBindTexture2D, 114
 - cudaBindTextureToArray, 115
 - cudaCreateChannelDesc, 115
 - cudaGetChannelDesc, 116
 - cudaGetTextureAlignmentOffset, 116
 - cudaGetTextureReference, 117
 - cudaUnbindTexture, 117
- CUDART_THREAD_DEPRECATED
 - cudaThreadExit, 27
 - cudaThreadGetCacheConfig, 28
 - cudaThreadGetLimit, 28
 - cudaThreadSetCacheConfig, 29
 - cudaThreadSetLimit, 30
 - cudaThreadSynchronize, 30
- CUDART_TYPES
 - CUDA_IPC_HANDLE_SIZE, 165
 - cudaArrayCubemap, 165
 - cudaArrayDefault, 165
 - cudaArrayLayered, 165
 - cudaArraySurfaceLoadStore, 165
 - cudaArrayTextureGather, 165
 - cudaChannelFormatKind, 168
 - cudaComputeMode, 168
 - cudaDeviceBlockingSync, 166
 - cudaDeviceLmemResizeToMax, 166
 - cudaDeviceMapHost, 166
 - cudaDeviceMask, 166
 - cudaDevicePropDontCare, 166
 - cudaDeviceScheduleAuto, 166
 - cudaDeviceScheduleBlockingSync, 166
 - cudaDeviceScheduleMask, 166
 - cudaDeviceScheduleSpin, 166
 - cudaDeviceScheduleYield, 166
 - cudaError, 169
 - cudaError_t, 168
 - cudaEvent_t, 168
 - cudaEventBlockingSync, 167
 - cudaEventDefault, 167
 - cudaEventDisableTiming, 167
 - cudaEventInterprocess, 167
 - cudaFuncCache, 172
 - cudaGraphicsCubeFace, 173
 - cudaGraphicsMapFlags, 173
 - cudaGraphicsRegisterFlags, 173
 - cudaGraphicsResource_t, 168
 - cudaHostAllocDefault, 167
 - cudaHostAllocMapped, 167
 - cudaHostAllocPortable, 167
 - cudaHostAllocWriteCombined, 167
 - cudaHostRegisterDefault, 167
 - cudaHostRegisterMapped, 167
 - cudaHostRegisterPortable, 167
 - cudaIpcEventHandle_t, 168
 - cudaLimit, 173
 - cudaMemcpyKind, 174
 - cudaMemoryType, 174
 - cudaOutputMode, 174
 - cudaOutputMode_t, 168
 - cudaPeerAccessDefault, 167
 - cudaStream_t, 168
 - cudaSurfaceBoundaryMode, 174
 - cudaSurfaceFormatMode, 174
 - cudaTextureAddressMode, 175
 - cudaTextureFilterMode, 175
 - cudaTextureReadMode, 175
 - cudaUUID_t, 168
- CUDART_UNIFIED
 - cudaPointerGetAttributes, 82
- CUDART_VDPAU
 - cudaGraphicsVDPAURegisterOutputSurface, 106
 - cudaGraphicsVDPAURegisterVideoSurface, 107
 - cudaVDPAUGetDevice, 107
 - cudaVDPAUSetVDPAUDevice, 108
- CUDART_VERSION
 - CUDART, 12

- cudaRuntimeGetVersion
 - CUDART__VERSION, [120](#)
- cudaSetDevice
 - CUDART_DEVICE, [24](#)
- cudaSetDeviceFlags
 - CUDART_DEVICE, [25](#)
- cudaSetDoubleForDevice
 - CUDART_EXECUTION, [43](#)
- cudaSetDoubleForHost
 - CUDART_EXECUTION, [44](#)
- cudaSetupArgument
 - CUDART_EXECUTION, [44](#)
 - CUDART_HIGHLEVEL, [132](#)
- cudaSetValidDevices
 - CUDART_DEVICE, [26](#)
- cudaStream_t
 - CUDART_TYPES, [168](#)
- cudaStreamCreate
 - CUDART_STREAM, [34](#)
- cudaStreamDestroy
 - CUDART_STREAM, [34](#)
- cudaStreamQuery
 - CUDART_STREAM, [35](#)
- cudaStreamSynchronize
 - CUDART_STREAM, [35](#)
- cudaStreamWaitEvent
 - CUDART_STREAM, [35](#)
- cudaSuccess
 - CUDART_TYPES, [169](#)
- cudaSurfaceBoundaryMode
 - CUDART_TYPES, [174](#)
- cudaSurfaceFormatMode
 - CUDART_TYPES, [174](#)
- cudaTextureAddressMode
 - CUDART_TYPES, [175](#)
- cudaTextureFilterMode
 - CUDART_TYPES, [175](#)
- cudaTextureReadMode
 - CUDART_TYPES, [175](#)
- cudaThreadExit
 - CUDART_THREAD_DEPRECATED, [27](#)
- cudaThreadGetCacheConfig
 - CUDART_THREAD_DEPRECATED, [28](#)
- cudaThreadGetLimit
 - CUDART_THREAD_DEPRECATED, [28](#)
- cudaThreadSetCacheConfig
 - CUDART_THREAD_DEPRECATED, [29](#)
- cudaThreadSetLimit
 - CUDART_THREAD_DEPRECATED, [30](#)
- cudaThreadSynchronize
 - CUDART_THREAD_DEPRECATED, [30](#)
- cudaUnbindTexture
 - CUDART_HIGHLEVEL, [133](#)
 - CUDART_TEXTURE, [117](#)
- cudaUUID_t
 - CUDART_TYPES, [168](#)
- cudaVDPAUGetDevice
 - CUDART_VDPAU, [107](#)
- cudaVDPAUSetVDPAUDevice
 - CUDART_VDPAU, [108](#)
- cudaWGLGetDevice
 - CUDART_OPENGL, [89](#)
- CUdevice
 - CUDA_TYPES, [186](#)
- CUdevice_attribute
 - CUDA_TYPES, [186](#)
- CUdevice_attribute_enum
 - CUDA_TYPES, [192](#)
- cuDeviceCanAccessPeer
 - CUDA_PEER_ACCESS, [316](#)
- cuDeviceComputeCapability
 - CUDA_DEVICE, [202](#)
- cuDeviceGet
 - CUDA_DEVICE, [203](#)
- cuDeviceGetAttribute
 - CUDA_DEVICE, [203](#)
- cuDeviceGetByPCIBusId
 - CUDA_MEM, [237](#)
- cuDeviceGetCount
 - CUDA_DEVICE, [206](#)
- cuDeviceGetName
 - CUDA_DEVICE, [207](#)
- cuDeviceGetPCIBusId
 - CUDA_MEM, [238](#)
- cuDeviceGetProperties
 - CUDA_DEVICE, [207](#)
- CUdeviceptr
 - CUDA_TYPES, [187](#)
- cuDeviceTotalMem
 - CUDA_DEVICE, [208](#)
- CUdevprop
 - CUDA_TYPES, [187](#)
- CUdevprop_st, [497](#)
 - clockRate, [497](#)
 - maxGridSize, [497](#)
 - maxThreadsDim, [497](#)
 - maxThreadsPerBlock, [497](#)
 - memPitch, [497](#)
 - regsPerBlock, [497](#)
 - sharedMemPerBlock, [497](#)
 - SIMDWidth, [497](#)
 - textureAlign, [498](#)
 - totalConstantMemory, [498](#)
- cuDriverGetVersion
 - CUDA_VERSION, [201](#)
- CUevent
 - CUDA_TYPES, [187](#)
- CUevent_flags

- CUDA_TYPES, [187](#)
- CUevent_flags_enum
 - CUDA_TYPES, [195](#)
- cuEventCreate
 - CUDA_EVENT, [288](#)
- cuEventDestroy
 - CUDA_EVENT, [289](#)
- cuEventElapsedTime
 - CUDA_EVENT, [289](#)
- cuEventQuery
 - CUDA_EVENT, [290](#)
- cuEventRecord
 - CUDA_EVENT, [290](#)
- cuEventSynchronize
 - CUDA_EVENT, [291](#)
- CUfilter_mode
 - CUDA_TYPES, [187](#)
- CUfilter_mode_enum
 - CUDA_TYPES, [195](#)
- CUfunc_cache
 - CUDA_TYPES, [187](#)
- CUfunc_cache_enum
 - CUDA_TYPES, [195](#)
- cuFuncGetAttribute
 - CUDA_EXEC, [292](#)
- cuFuncSetBlockShape
 - CUDA_EXEC_DEPRECATED, [296](#)
- cuFuncSetCacheConfig
 - CUDA_EXEC, [293](#)
- cuFuncSetSharedSize
 - CUDA_EXEC_DEPRECATED, [297](#)
- CUfunction
 - CUDA_TYPES, [187](#)
- CUfunction_attribute
 - CUDA_TYPES, [187](#)
- CUfunction_attribute_enum
 - CUDA_TYPES, [196](#)
- cuGLCtxCreate
 - CUDA_GL, [325](#)
- CUGLDeviceList
 - CUDA_GL, [324](#)
- CUGLDeviceList_enum
 - CUDA_GL, [325](#)
- cuGLGetDevices
 - CUDA_GL, [325](#)
- cuGLInit
 - CUDA_GL_DEPRECATED, [330](#)
- CUGLmap_flags
 - CUDA_GL_DEPRECATED, [329](#)
- CUGLmap_flags_enum
 - CUDA_GL_DEPRECATED, [330](#)
- cuGLMapBufferObject
 - CUDA_GL_DEPRECATED, [330](#)
- cuGLMapBufferObjectAsync
 - CUDA_GL_DEPRECATED, [331](#)
- cuGLRegisterBufferObject
 - CUDA_GL_DEPRECATED, [331](#)
- cuGLSetBufferObjectMapFlags
 - CUDA_GL_DEPRECATED, [332](#)
- cuGLUnmapBufferObject
 - CUDA_GL_DEPRECATED, [332](#)
- cuGLUnmapBufferObjectAsync
 - CUDA_GL_DEPRECATED, [333](#)
- cuGLUnregisterBufferObject
 - CUDA_GL_DEPRECATED, [333](#)
- cuGraphicsD3D10RegisterResource
 - CUDA_D3D10, [353](#)
- cuGraphicsD3D11RegisterResource
 - CUDA_D3D11, [368](#)
- cuGraphicsD3D9RegisterResource
 - CUDA_D3D9, [338](#)
- cuGraphicsGLRegisterBuffer
 - CUDA_GL, [326](#)
- cuGraphicsGLRegisterImage
 - CUDA_GL, [326](#)
- CUgraphicsMapResourceFlags
 - CUDA_TYPES, [187](#)
- CUgraphicsMapResourceFlags_enum
 - CUDA_TYPES, [196](#)
- cuGraphicsMapResources
 - CUDA_GRAPHICS, [317](#)
- CUgraphicsRegisterFlags
 - CUDA_TYPES, [187](#)
- CUgraphicsRegisterFlags_enum
 - CUDA_TYPES, [196](#)
- CUgraphicsResource
 - CUDA_TYPES, [187](#)
- cuGraphicsResourceGetMappedPointer
 - CUDA_GRAPHICS, [318](#)
- cuGraphicsResourceSetMapFlags
 - CUDA_GRAPHICS, [318](#)
- cuGraphicsSubResourceGetMappedArray
 - CUDA_GRAPHICS, [319](#)
- cuGraphicsUnmapResources
 - CUDA_GRAPHICS, [320](#)
- cuGraphicsUnregisterResource
 - CUDA_GRAPHICS, [320](#)
- cuGraphicsVDPAURegisterOutputSurface
 - CUDA_VDPAU, [371](#)
- cuGraphicsVDPAURegisterVideoSurface
 - CUDA_VDPAU, [372](#)
- cuInit
 - CUDA_INITIALIZE, [200](#)
- cuIpcCloseMemHandle
 - CUDA_MEM, [238](#)
- cuIpcGetEventHandle
 - CUDA_MEM, [239](#)
- cuIpcGetMemHandle

- CUDA_MEM, 239
- cuIpcOpenEventHandle
 - CUDA_MEM, 240
- cuIpcOpenMemHandle
 - CUDA_MEM, 240
- CUjit_fallback
 - CUDA_TYPES, 187
- CUjit_fallback_enum
 - CUDA_TYPES, 196
- CUjit_option
 - CUDA_TYPES, 188
- CUjit_option_enum
 - CUDA_TYPES, 197
- CUjit_target
 - CUDA_TYPES, 188
- CUjit_target_enum
 - CUDA_TYPES, 198
- cuLaunch
 - CUDA_EXEC_DEPRECATED, 297
- cuLaunchGrid
 - CUDA_EXEC_DEPRECATED, 298
- cuLaunchGridAsync
 - CUDA_EXEC_DEPRECATED, 298
- cuLaunchKernel
 - CUDA_EXEC, 294
- CULimit
 - CUDA_TYPES, 188
- CULimit_enum
 - CUDA_TYPES, 198
- cuMemAlloc
 - CUDA_MEM, 241
- cuMemAllocHost
 - CUDA_MEM, 241
- cuMemAllocPitch
 - CUDA_MEM, 242
- cuMemcpy
 - CUDA_MEM, 243
- cuMemcpy2D
 - CUDA_MEM, 243
- cuMemcpy2DAsync
 - CUDA_MEM, 246
- cuMemcpy2DUnaligned
 - CUDA_MEM, 248
- cuMemcpy3D
 - CUDA_MEM, 250
- cuMemcpy3DAsync
 - CUDA_MEM, 253
- cuMemcpy3DPeer
 - CUDA_MEM, 255
- cuMemcpy3DPeerAsync
 - CUDA_MEM, 256
- cuMemcpyAsync
 - CUDA_MEM, 256
- cuMemcpyAtoA
 - CUDA_MEM, 257
- cuMemcpyAtoD
 - CUDA_MEM, 258
- cuMemcpyAtoH
 - CUDA_MEM, 258
- cuMemcpyAtoHAsync
 - CUDA_MEM, 259
- cuMemcpyDtoA
 - CUDA_MEM, 260
- cuMemcpyDtoD
 - CUDA_MEM, 260
- cuMemcpyDtoDAsync
 - CUDA_MEM, 261
- cuMemcpyDtoH
 - CUDA_MEM, 261
- cuMemcpyDtoHAsync
 - CUDA_MEM, 262
- cuMemcpyHtoA
 - CUDA_MEM, 263
- cuMemcpyHtoAAsync
 - CUDA_MEM, 263
- cuMemcpyHtoD
 - CUDA_MEM, 264
- cuMemcpyHtoDAsync
 - CUDA_MEM, 264
- cuMemcpyPeer
 - CUDA_MEM, 265
- cuMemcpyPeerAsync
 - CUDA_MEM, 266
- cuMemFree
 - CUDA_MEM, 266
- cuMemFreeHost
 - CUDA_MEM, 267
- cuMemGetAddressRange
 - CUDA_MEM, 267
- cuMemGetInfo
 - CUDA_MEM, 268
- cuMemHostAlloc
 - CUDA_MEM, 268
- cuMemHostGetDevicePointer
 - CUDA_MEM, 270
- cuMemHostGetFlags
 - CUDA_MEM, 270
- cuMemHostRegister
 - CUDA_MEM, 271
- cuMemHostUnregister
 - CUDA_MEM, 272
- CUmemorytype
 - CUDA_TYPES, 188
- CUmemorytype_enum
 - CUDA_TYPES, 198
- cuMemsetD16
 - CUDA_MEM, 272
- cuMemsetD16Async

- CUDA_MEM, 273
- cuMemsetD2D16
 - CUDA_MEM, 273
- cuMemsetD2D16Async
 - CUDA_MEM, 274
- cuMemsetD2D32
 - CUDA_MEM, 275
- cuMemsetD2D32Async
 - CUDA_MEM, 275
- cuMemsetD2D8
 - CUDA_MEM, 276
- cuMemsetD2D8Async
 - CUDA_MEM, 277
- cuMemsetD32
 - CUDA_MEM, 277
- cuMemsetD32Async
 - CUDA_MEM, 278
- cuMemsetD8
 - CUDA_MEM, 279
- cuMemsetD8Async
 - CUDA_MEM, 279
- CUmodule
 - CUDA_TYPES, 188
- cuModuleGetFunction
 - CUDA_MODULE, 221
- cuModuleGetGlobal
 - CUDA_MODULE, 222
- cuModuleGetSurfRef
 - CUDA_MODULE, 222
- cuModuleGetTexRef
 - CUDA_MODULE, 223
- cuModuleLoad
 - CUDA_MODULE, 223
- cuModuleLoadData
 - CUDA_MODULE, 224
- cuModuleLoadDataEx
 - CUDA_MODULE, 224
- cuModuleLoadFatBinary
 - CUDA_MODULE, 226
- cuModuleUnload
 - CUDA_MODULE, 226
- cuParamSetf
 - CUDA_EXEC_DEPRECATED, 299
- cuParamSeti
 - CUDA_EXEC_DEPRECATED, 300
- cuParamSetSize
 - CUDA_EXEC_DEPRECATED, 300
- cuParamSetTexRef
 - CUDA_EXEC_DEPRECATED, 301
- cuParamSetv
 - CUDA_EXEC_DEPRECATED, 301
- CUpointer_attribute
 - CUDA_TYPES, 188
- CUpointer_attribute_enum
 - CUDA_TYPES, 198
- cuPointerGetAttribute
 - CUDA_UNIFIED, 282
- cuProfilerInitialize
 - CUDA_PROFILER, 322
- cuProfilerStart
 - CUDA_PROFILER, 323
- cuProfilerStop
 - CUDA_PROFILER, 323
- CUresult
 - CUDA_TYPES, 188
- CUstream
 - CUDA_TYPES, 188
- cuStreamCreate
 - CUDA_STREAM, 285
- cuStreamDestroy
 - CUDA_STREAM, 285
- cuStreamQuery
 - CUDA_STREAM, 286
- cuStreamSynchronize
 - CUDA_STREAM, 286
- cuStreamWaitEvent
 - CUDA_STREAM, 287
- CUsurfref
 - CUDA_TYPES, 188
- cuSurfRefGetArray
 - CUDA_SURFREF, 313
- cuSurfRefSetArray
 - CUDA_SURFREF, 313
- CUtexref
 - CUDA_TYPES, 188
- cuTexRefCreate
 - CUDA_TEXREF_DEPRECATED, 311
- cuTexRefDestroy
 - CUDA_TEXREF_DEPRECATED, 311
- cuTexRefGetAddress
 - CUDA_TEXREF, 304
- cuTexRefGetAddressMode
 - CUDA_TEXREF, 304
- cuTexRefGetArray
 - CUDA_TEXREF, 304
- cuTexRefGetFilterMode
 - CUDA_TEXREF, 305
- cuTexRefGetFlags
 - CUDA_TEXREF, 305
- cuTexRefGetFormat
 - CUDA_TEXREF, 306
- cuTexRefSetAddress
 - CUDA_TEXREF, 306
- cuTexRefSetAddress2D
 - CUDA_TEXREF, 307
- cuTexRefSetAddressMode
 - CUDA_TEXREF, 307
- cuTexRefSetArray

- CUDA_TEXREF, 308
- cuTexRefSetFilterMode
 - CUDA_TEXREF, 308
- cuTexRefSetFlags
 - CUDA_TEXREF, 309
- cuTexRefSetFormat
 - CUDA_TEXREF, 309
- cuVDPACtxCreate
 - CUDA_VDPAU, 373
- cuVDPAGetDevice
 - CUDA_VDPAU, 373
- cuWGLGetDevice
 - CUDA_GL, 328
- Data types used by CUDA driver, 177
- Data types used by CUDA Runtime, 161
- Depth
 - CUDA_ARRAY3D_DESCRIPTOR_st, 469
 - CUDA_MEMCPY3D_PEER_st, 474
 - CUDA_MEMCPY3D_st, 477
- depth
 - cudaExtent, 487
- device
 - cudaPointerAttributes, 495
- Device Management, 13, 202
- deviceOverlap
 - cudaDeviceProp, 482
- devicePointer
 - cudaPointerAttributes, 495
- Direct3D 10 Interoperability, 96, 350
- Direct3D 11 Interoperability, 101, 365
- Direct3D 9 Interoperability, 91, 335
- Double Precision Intrinsics, 438
- Double Precision Mathematical Functions, 401
- dstArray
 - CUDA_MEMCPY2D_st, 472
 - CUDA_MEMCPY3D_PEER_st, 474
 - CUDA_MEMCPY3D_st, 477
 - cudaMemcpy3DParms, 490
 - cudaMemcpy3DPeerParms, 492
- dstContext
 - CUDA_MEMCPY3D_PEER_st, 474
- dstDevice
 - CUDA_MEMCPY2D_st, 472
 - CUDA_MEMCPY3D_PEER_st, 474
 - CUDA_MEMCPY3D_st, 477
 - cudaMemcpy3DPeerParms, 492
- dstHeight
 - CUDA_MEMCPY3D_PEER_st, 475
 - CUDA_MEMCPY3D_st, 477
- dstHost
 - CUDA_MEMCPY2D_st, 472
 - CUDA_MEMCPY3D_PEER_st, 475
 - CUDA_MEMCPY3D_st, 478
- dstLOD
 - CUDA_MEMCPY3D_PEER_st, 475
 - CUDA_MEMCPY3D_st, 478
- dstMemoryType
 - CUDA_MEMCPY2D_st, 472
 - CUDA_MEMCPY3D_PEER_st, 475
 - CUDA_MEMCPY3D_st, 478
- dstPitch
 - CUDA_MEMCPY2D_st, 472
 - CUDA_MEMCPY3D_PEER_st, 475
 - CUDA_MEMCPY3D_st, 478
- dstPos
 - cudaMemcpy3DParms, 490
 - cudaMemcpy3DPeerParms, 492
- dstPtr
 - cudaMemcpy3DParms, 490
 - cudaMemcpy3DPeerParms, 492
- dstXInBytes
 - CUDA_MEMCPY2D_st, 472
 - CUDA_MEMCPY3D_PEER_st, 475
 - CUDA_MEMCPY3D_st, 478
- dstY
 - CUDA_MEMCPY2D_st, 473
 - CUDA_MEMCPY3D_PEER_st, 475
 - CUDA_MEMCPY3D_st, 478
- dstZ
 - CUDA_MEMCPY3D_PEER_st, 475
 - CUDA_MEMCPY3D_st, 478
- ECCEEnabled
 - cudaDeviceProp, 482
- erf
 - CUDA_MATH_DOUBLE, 408
- erfc
 - CUDA_MATH_DOUBLE, 409
- erfcf
 - CUDA_MATH_SINGLE, 383
- erfcinv
 - CUDA_MATH_DOUBLE, 409
- erfcinvf
 - CUDA_MATH_SINGLE, 384
- erfcx
 - CUDA_MATH_DOUBLE, 409
- erfcxf
 - CUDA_MATH_SINGLE, 384
- erff
 - CUDA_MATH_SINGLE, 384
- erfinv
 - CUDA_MATH_DOUBLE, 409
- erfinvf
 - CUDA_MATH_SINGLE, 384
- Error Handling, 32
- Event Management, 37, 288
- Execution Control, 41, 292

- exp
 - CUDA_MATH_DOUBLE, [410](#)
- exp10
 - CUDA_MATH_DOUBLE, [410](#)
- exp10f
 - CUDA_MATH_SINGLE, [385](#)
- exp2
 - CUDA_MATH_DOUBLE, [410](#)
- exp2f
 - CUDA_MATH_SINGLE, [385](#)
- expf
 - CUDA_MATH_SINGLE, [385](#)
- expm1
 - CUDA_MATH_DOUBLE, [410](#)
- expm1f
 - CUDA_MATH_SINGLE, [385](#)
- extent
 - cudaMemcpy3DParms, [490](#)
 - cudaMemcpy3DPeerParms, [492](#)
- f
 - cudaChannelFormatDesc, [480](#)
- fabs
 - CUDA_MATH_DOUBLE, [411](#)
- fabsf
 - CUDA_MATH_SINGLE, [386](#)
- fdim
 - CUDA_MATH_DOUBLE, [411](#)
- fdimf
 - CUDA_MATH_SINGLE, [386](#)
- fdividef
 - CUDA_MATH_SINGLE, [386](#)
- filterMode
 - textureReference, [500](#)
- Flags
 - CUDA_ARRAY3D_DESCRIPTOR_st, [469](#)
- floor
 - CUDA_MATH_DOUBLE, [411](#)
- floorf
 - CUDA_MATH_SINGLE, [386](#)
- fma
 - CUDA_MATH_DOUBLE, [411](#)
- fmaf
 - CUDA_MATH_SINGLE, [387](#)
- fmax
 - CUDA_MATH_DOUBLE, [412](#)
- fmaxf
 - CUDA_MATH_SINGLE, [387](#)
- fmin
 - CUDA_MATH_DOUBLE, [412](#)
- fminf
 - CUDA_MATH_SINGLE, [387](#)
- fmod
 - CUDA_MATH_DOUBLE, [412](#)
- fmodf
 - CUDA_MATH_SINGLE, [388](#)
- Format
 - CUDA_ARRAY3D_DESCRIPTOR_st, [469](#)
 - CUDA_ARRAY_DESCRIPTOR_st, [471](#)
- frexp
 - CUDA_MATH_DOUBLE, [413](#)
- frexpf
 - CUDA_MATH_SINGLE, [388](#)
- Graphics Interoperability, [109, 317](#)
- Height
 - CUDA_ARRAY3D_DESCRIPTOR_st, [469](#)
 - CUDA_ARRAY_DESCRIPTOR_st, [471](#)
 - CUDA_MEMCPY2D_st, [473](#)
 - CUDA_MEMCPY3D_PEER_st, [475](#)
 - CUDA_MEMCPY3D_st, [478](#)
- height
 - cudaExtent, [487](#)
- hostPointer
 - cudaPointerAttributes, [495](#)
- hypot
 - CUDA_MATH_DOUBLE, [413](#)
- hypotf
 - CUDA_MATH_SINGLE, [388](#)
- ilogb
 - CUDA_MATH_DOUBLE, [413](#)
- ilogbf
 - CUDA_MATH_SINGLE, [389](#)
- Initialization, [200](#)
- Integer Intrinsics, [446](#)
- integrated
 - cudaDeviceProp, [482](#)
- Interactions with the CUDA Driver API, [134](#)
- isfinite
 - CUDA_MATH_DOUBLE, [414](#)
 - CUDA_MATH_SINGLE, [389](#)
- isinf
 - CUDA_MATH_DOUBLE, [414](#)
 - CUDA_MATH_SINGLE, [389](#)
- isnan
 - CUDA_MATH_DOUBLE, [414](#)
 - CUDA_MATH_SINGLE, [389](#)
- j0
 - CUDA_MATH_DOUBLE, [414](#)
- j0f
 - CUDA_MATH_SINGLE, [389](#)
- j1
 - CUDA_MATH_DOUBLE, [414](#)
- j1f
 - CUDA_MATH_SINGLE, [390](#)
- jn

CUDA_MATH_DOUBLE, 415
 jnf
 CUDA_MATH_SINGLE, 390
 kernelExecTimeoutEnabled
 cudaDeviceProp, 482
 kind
 cudaMemcpy3DParms, 490
 l2CacheSize
 cudaDeviceProp, 482
 ldexp
 CUDA_MATH_DOUBLE, 415
 ldexpf
 CUDA_MATH_SINGLE, 390
 lgamma
 CUDA_MATH_DOUBLE, 415
 lgammaf
 CUDA_MATH_SINGLE, 391
 llrint
 CUDA_MATH_DOUBLE, 416
 llrintf
 CUDA_MATH_SINGLE, 391
 llround
 CUDA_MATH_DOUBLE, 416
 llroundf
 CUDA_MATH_SINGLE, 391
 localSizeBytes
 cudaFuncAttributes, 488
 log
 CUDA_MATH_DOUBLE, 416
 log10
 CUDA_MATH_DOUBLE, 416
 log10f
 CUDA_MATH_SINGLE, 391
 log1p
 CUDA_MATH_DOUBLE, 417
 log1pf
 CUDA_MATH_SINGLE, 392
 log2
 CUDA_MATH_DOUBLE, 417
 log2f
 CUDA_MATH_SINGLE, 392
 logb
 CUDA_MATH_DOUBLE, 417
 logbf
 CUDA_MATH_SINGLE, 392
 logf
 CUDA_MATH_SINGLE, 392
 lrint
 CUDA_MATH_DOUBLE, 418
 lrintf
 CUDA_MATH_SINGLE, 393
 lround

CUDA_MATH_DOUBLE, 418
 lroundf
 CUDA_MATH_SINGLE, 393
 major
 cudaDeviceProp, 483
 make_cudaExtent
 CUDART_MEMORY, 79
 make_cudaPitchedPtr
 CUDART_MEMORY, 80
 make_cudaPos
 CUDART_MEMORY, 80
 Mathematical Functions, 375
 maxGridSize
 cudaDeviceProp, 483
 CUdevprop_st, 497
 maxSurface1D
 cudaDeviceProp, 483
 maxSurface1DLayered
 cudaDeviceProp, 483
 maxSurface2D
 cudaDeviceProp, 483
 maxSurface2DLayered
 cudaDeviceProp, 483
 maxSurface3D
 cudaDeviceProp, 483
 maxSurfaceCubemap
 cudaDeviceProp, 483
 maxSurfaceCubemapLayered
 cudaDeviceProp, 483
 maxTexture1D
 cudaDeviceProp, 483
 maxTexture1DLayered
 cudaDeviceProp, 483
 maxTexture1DLinear
 cudaDeviceProp, 483
 maxTexture2D
 cudaDeviceProp, 484
 maxTexture2DGather
 cudaDeviceProp, 484
 maxTexture2DLayered
 cudaDeviceProp, 484
 maxTexture2DLinear
 cudaDeviceProp, 484
 maxTexture3D
 cudaDeviceProp, 484
 maxTextureCubemap
 cudaDeviceProp, 484
 maxTextureCubemapLayered
 cudaDeviceProp, 484
 maxThreadsDim
 cudaDeviceProp, 484
 CUdevprop_st, 497
 maxThreadsPerBlock

- cudaDeviceProp, 484
- cudaFuncAttributes, 488
- CUdevprop_st, 497
- maxThreadsPerMultiProcessor
 - cudaDeviceProp, 484
- Memory Management, 45, 228
- memoryBusWidth
 - cudaDeviceProp, 484
- memoryClockRate
 - cudaDeviceProp, 484
- memoryType
 - cudaPointerAttributes, 495
- memPitch
 - cudaDeviceProp, 485
 - CUdevprop_st, 497
- minor
 - cudaDeviceProp, 485
- modf
 - CUDA_MATH_DOUBLE, 418
- modff
 - CUDA_MATH_SINGLE, 393
- Module Management, 221
- multiProcessorCount
 - cudaDeviceProp, 485
- name
 - cudaDeviceProp, 485
- nan
 - CUDA_MATH_DOUBLE, 418
- nanf
 - CUDA_MATH_SINGLE, 393
- nearbyint
 - CUDA_MATH_DOUBLE, 419
- nearbyintf
 - CUDA_MATH_SINGLE, 394
- nextafter
 - CUDA_MATH_DOUBLE, 419
- nextafterf
 - CUDA_MATH_SINGLE, 394
- normalized
 - textureReference, 500
- NumChannels
 - CUDA_ARRAY3D_DESCRIPTOR_st, 469
 - CUDA_ARRAY_DESCRIPTOR_st, 471
- numRegs
 - cudaFuncAttributes, 488
- OpenGL Interoperability, 86, 324
- pciBusID
 - cudaDeviceProp, 485
- pciDeviceID
 - cudaDeviceProp, 485
- pciDomainID
 - cudaDeviceProp, 485
- Peer Context Memory Access, 315
- Peer Device Memory Access, 84
- pitch
 - cudaPitchedPtr, 494
- pow
 - CUDA_MATH_DOUBLE, 419
- powf
 - CUDA_MATH_SINGLE, 394
- Profiler Control, 136, 322
- ptr
 - cudaPitchedPtr, 494
- ptxVersion
 - cudaFuncAttributes, 488
- rcbrt
 - CUDA_MATH_DOUBLE, 420
- rcbrtf
 - CUDA_MATH_SINGLE, 395
- regsPerBlock
 - cudaDeviceProp, 485
 - CUdevprop_st, 497
- remainder
 - CUDA_MATH_DOUBLE, 420
- remainderf
 - CUDA_MATH_SINGLE, 395
- remquo
 - CUDA_MATH_DOUBLE, 420
- remquof
 - CUDA_MATH_SINGLE, 395
- reserved0
 - CUDA_MEMCPY3D_st, 478
- reserved1
 - CUDA_MEMCPY3D_st, 478
- rint
 - CUDA_MATH_DOUBLE, 421
- rintf
 - CUDA_MATH_SINGLE, 396
- round
 - CUDA_MATH_DOUBLE, 421
- roundf
 - CUDA_MATH_SINGLE, 396
- rsqrt
 - CUDA_MATH_DOUBLE, 421
- rsqrtf
 - CUDA_MATH_SINGLE, 396
- scalbln
 - CUDA_MATH_DOUBLE, 421
- scalblnf
 - CUDA_MATH_SINGLE, 396
- scalbn
 - CUDA_MATH_DOUBLE, 422
- scalbnf
 - CUDA_MATH_SINGLE, 397

- sharedMemPerBlock
 - cudaDeviceProp, [485](#)
 - CUdevprop_st, [497](#)
- sharedSizeBytes
 - cudaFuncAttributes, [488](#)
- signbit
 - CUDA_MATH_DOUBLE, [422](#)
 - CUDA_MATH_SINGLE, [397](#)
- SIMDWidth
 - CUdevprop_st, [497](#)
- sin
 - CUDA_MATH_DOUBLE, [422](#)
- sincos
 - CUDA_MATH_DOUBLE, [422](#)
- sincosf
 - CUDA_MATH_SINGLE, [397](#)
- sinf
 - CUDA_MATH_SINGLE, [397](#)
- Single Precision Ininsics, [426](#)
- Single Precision Mathematical Functions, [376](#)
- sinh
 - CUDA_MATH_DOUBLE, [423](#)
- sinhf
 - CUDA_MATH_SINGLE, [398](#)
- sinpi
 - CUDA_MATH_DOUBLE, [423](#)
- sinpif
 - CUDA_MATH_SINGLE, [398](#)
- sqrt
 - CUDA_MATH_DOUBLE, [423](#)
- sqrtf
 - CUDA_MATH_SINGLE, [398](#)
- srcArray
 - CUDA_MEMCPY2D_st, [473](#)
 - CUDA_MEMCPY3D_PEER_st, [475](#)
 - CUDA_MEMCPY3D_st, [478](#)
 - cudaMemcpy3DParms, [490](#)
 - cudaMemcpy3DPeerParms, [492](#)
- srcContext
 - CUDA_MEMCPY3D_PEER_st, [475](#)
- srcDevice
 - CUDA_MEMCPY2D_st, [473](#)
 - CUDA_MEMCPY3D_PEER_st, [475](#)
 - CUDA_MEMCPY3D_st, [478](#)
 - cudaMemcpy3DPeerParms, [492](#)
- srcHeight
 - CUDA_MEMCPY3D_PEER_st, [476](#)
 - CUDA_MEMCPY3D_st, [479](#)
- srcHost
 - CUDA_MEMCPY2D_st, [473](#)
 - CUDA_MEMCPY3D_PEER_st, [476](#)
 - CUDA_MEMCPY3D_st, [479](#)
- srcLOD
 - CUDA_MEMCPY3D_PEER_st, [476](#)
 - CUDA_MEMCPY3D_st, [479](#)
- srcMemoryType
 - CUDA_MEMCPY2D_st, [473](#)
 - CUDA_MEMCPY3D_PEER_st, [476](#)
 - CUDA_MEMCPY3D_st, [479](#)
- srcPitch
 - CUDA_MEMCPY2D_st, [473](#)
 - CUDA_MEMCPY3D_PEER_st, [476](#)
 - CUDA_MEMCPY3D_st, [479](#)
- srcPos
 - cudaMemcpy3DParms, [490](#)
 - cudaMemcpy3DPeerParms, [492](#)
- srcPtr
 - cudaMemcpy3DParms, [490](#)
 - cudaMemcpy3DPeerParms, [493](#)
- srcXInBytes
 - CUDA_MEMCPY2D_st, [473](#)
 - CUDA_MEMCPY3D_PEER_st, [476](#)
 - CUDA_MEMCPY3D_st, [479](#)
- srcY
 - CUDA_MEMCPY2D_st, [473](#)
 - CUDA_MEMCPY3D_PEER_st, [476](#)
 - CUDA_MEMCPY3D_st, [479](#)
- srcZ
 - CUDA_MEMCPY3D_PEER_st, [476](#)
 - CUDA_MEMCPY3D_st, [479](#)
- sRGB
 - textureReference, [500](#)
- Stream Management, [34](#), [285](#)
- Surface Reference Management, [118](#), [313](#)
- surfaceAlignment
 - cudaDeviceProp, [485](#)
- surfaceReference, [499](#)
 - channelDesc, [499](#)
- tan
 - CUDA_MATH_DOUBLE, [423](#)
- tanf
 - CUDA_MATH_SINGLE, [398](#)
- tanh
 - CUDA_MATH_DOUBLE, [424](#)
- tanhf
 - CUDA_MATH_SINGLE, [399](#)
- tccDriver
 - cudaDeviceProp, [485](#)
- Texture Reference Management, [113](#), [303](#)
- textureAlign
 - CUdevprop_st, [498](#)
- textureAlignment
 - cudaDeviceProp, [485](#)
- texturePitchAlignment
 - cudaDeviceProp, [486](#)
- textureReference, [500](#)
 - addressMode, [500](#)

- channelDesc, [500](#)
 - filterMode, [500](#)
 - normalized, [500](#)
 - sRGB, [500](#)
- tgamma
 - CUDA_MATH_DOUBLE, [424](#)
- tgammaf
 - CUDA_MATH_SINGLE, [399](#)
- totalConstantMemory
 - CUdevprop_st, [498](#)
- totalConstMem
 - cudaDeviceProp, [486](#)
- totalGlobalMem
 - cudaDeviceProp, [486](#)
- trunc
 - CUDA_MATH_DOUBLE, [424](#)
- truncf
 - CUDA_MATH_SINGLE, [399](#)
- Type Casting Intrinsics, [451](#)
- Unified Addressing, [81](#), [281](#)
- unifiedAddressing
 - cudaDeviceProp, [486](#)
- VDPAU Interoperability, [106](#), [371](#)
- Version Management, [120](#), [201](#)
- w
 - cudaChannelFormatDesc, [480](#)
- warpSize
 - cudaDeviceProp, [486](#)
- Width
 - CUDA_ARRAY3D_DESCRIPTOR_st, [470](#)
 - CUDA_ARRAY_DESCRIPTOR_st, [471](#)
- width
 - cudaExtent, [487](#)
- WidthInBytes
 - CUDA_MEMCPY2D_st, [473](#)
 - CUDA_MEMCPY3D_PEER_st, [476](#)
 - CUDA_MEMCPY3D_st, [479](#)
- x
 - cudaChannelFormatDesc, [480](#)
 - cudaPos, [496](#)
- xsize
 - cudaPitchedPtr, [494](#)
- y
 - cudaChannelFormatDesc, [480](#)
 - cudaPos, [496](#)
- y0
 - CUDA_MATH_DOUBLE, [424](#)
- y0f
 - CUDA_MATH_SINGLE, [399](#)
- y1
 - CUDA_MATH_DOUBLE, [425](#)
- y1f
 - CUDA_MATH_SINGLE, [400](#)
- yn
 - CUDA_MATH_DOUBLE, [425](#)
- ynf
 - CUDA_MATH_SINGLE, [400](#)
- ysize
 - cudaPitchedPtr, [494](#)
- z
 - cudaChannelFormatDesc, [480](#)
 - cudaPos, [496](#)

Notice

ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NONINFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE.

Information furnished is believed to be accurate and reliable. However, NVIDIA Corporation assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use. No license is granted by implication of otherwise under any patent rights of NVIDIA Corporation. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all other information previously supplied. NVIDIA Corporation products are not authorized as critical components in life support devices or systems without express written approval of NVIDIA Corporation.

Trademarks

NVIDIA, the NVIDIA logo, GeForce, Tesla, and Quadro are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated.

Copyright

© 2007-2011 NVIDIA Corporation. All rights reserved.